



US 20100194336A1

(19) **United States**

(12) **Patent Application Publication**  
**Azancot et al.**

(10) **Pub. No.: US 2010/0194336 A1**

(43) **Pub. Date: Aug. 5, 2010**

(54) **INDUCTIVELY CHARGEABLE AUDIO DEVICES**

(75) Inventors: **Yossi Azancot**, Jerusalem (IL);  
**Amir Ben-Shalom**, Modiin (IL);  
**Oola Greenwald**, Mevasseret Zion (IL); **Arik Rofe**, Jerusalem (IL)

Correspondence Address:  
**BROOKS KUSHMAN P.C.**  
**1000 TOWN CENTER, TWENTY-SECOND FLOOR**  
**SOUTHFIELD, MI 48075 (US)**

(73) Assignee: **POWERMAT LTD.**, Neve Ilan (IL)

(21) Appl. No.: **12/693,001**

(22) Filed: **Jan. 25, 2010**

**Related U.S. Application Data**

(63) Continuation of application No. PCT/IL2008/001348, filed on Oct. 12, 2008.

(60) Provisional application No. 60/960,878, filed on Oct. 18, 2007, provisional application No. 61/006,131, filed on Dec. 26, 2007, provisional application No. 61/064,403, filed on Mar. 4, 2008.


**Publication Classification**




(51) **Int. Cl.**  
**H02J 7/00** (2006.01)  
**H04R 1/10** (2006.01)


(52) **U.S. Cl.** ..... **320/108; 381/74**

(57) **ABSTRACT**


An inductively enabled audio speaker is disclosed configured to receive power inductively from an inductive power outlet. The audio speaker device has a voice coil which, as well as being able to produce an audible output, is further configured to function as a secondary inductor to inductively couple with a primary inductor. The inductively enabled audio speaker may be used to power an electrical device such as a Bluetooth earpiece, a telephone or the like.











**Fig. 4**





**Fig. 5**






**Fig. 6**






**Fig. 11b**







**Fig. 13**




**Fig. 14a**




**Fig. 14b**




**Fig. 14c**




**Fig. 15**




**Fig. 16**



**Fig. 17**




**Fig. 18a**




**Fig. 18b**







**Fig.19a**




**Fig.19b**




**Fig.19c**





**Fig. 20**



**Fig. 21a**



**Fig. 21b**



## INDUCTIVELY CHARGEABLE AUDIO DEVICES

### CROSS-REFERENCE TO RELATED APPLICATIONS

**[0001]** This application is a continuation of PCT application Serial No. PCT/IL2008/001348 filed Oct. 12, 2008, which claims the benefit of U.S. provisional application Ser. Nos. 60/960,635 filed Oct. 9, 2007; 60/960,878 filed Oct. 18, 2007; 61/006,131 filed Dec. 26, 2007 and 61/064,403 filed Mar. 4, 2008, which are hereby incorporated by reference in their entirety.

### FIELD OF THE INVENTION

**[0002]** The present invention is directed to providing power to electrical devices. In particular the present invention relates to portable electrical devices adapted to receive power inductively.

### BACKGROUND

**[0003]** Mobile communication devices, such as computers, cellular telephones and the like, are typically powered by power cells, i.e. rechargeable electrochemical cells often also referred to as batteries. In order to recharge the power cells such devices are generally provided with a charger unit for connecting to a power jack socket on the device which is wired to contacts with the terminals of the cells. The charger itself usually consists of a plug box containing a step-down transformer and an AC-DC converter or rectifier which is wired to a connecting plug. When in use, the plug box is plugged into a 120V or 240V mains socket and the connecting plug is coupled to the device. The wire trailing between the device and the plug box can be unsightly. Moreover, if the trailing wire is snagged or jerked the wire and connectors may be damaged, as indeed could be the socket or the wall. Furthermore, the device may be pulled to the ground.

**[0004]** Chargers are bulky items to carry around. Therefore most users of compact portable equipment such as cell phones and the like do not carry chargers with them, but prefer to rely upon periodic charging, perhaps over night. Often users rely on even more infrequent charging. As a result cells often run down at inconvenient times when no charger is available.

**[0005]** Inductive battery charger systems are known such as the system described in U.S. Pat. No. 7,164,255 to Hui incorporated herein by reference. In Hui's system a planar inductive battery charging system is designed to enable electronic devices to be recharged. The system includes a planar charging module having a charging surface on which a device to be recharged is placed. Within the charging module, and parallel to the charging surface, is at least one, and preferably an array of primary windings that couple energy inductively to a secondary winding within the device to be recharged. The invention also provides secondary modules that allow the system to be used with conventional electronic devices not formed with secondary windings.

**[0006]** Hui's system provides an inductive charging platform for mobile telephones. However, unless the device to be charged has an integral secondary winding coil, it is necessary to carry a bulky secondary module with which to use the platform. Hui's system does not describe any convenient means for providing secondary windings for conventional devices.

**[0007]** There is therefore a need for a convenient power supply for a mobile communication device and particularly for a charger, which may be conveniently retrofitted to conventional devices.

### SUMMARY OF THE INVENTION

**[0008]** It is an aim of the invention to provide an inductive power providing system for an electrical device.

**[0009]** In accordance with a first embodiment, the present invention is directed to providing a power providing system for an electrical device comprising: a secondary inductor, wired to the electrical device, for inductively coupling with a primary inductor hardwired to a power supply, wherein the secondary inductor is incorporated into an accessory of the electrical device.

**[0010]** In various embodiments the electrical device may be selected from the group comprising: computers, mobile telephones, media players, PDAs, Walkman®s, portable CD players, dictaphones, portable DVD players and mobile communications devices. The accessory may be selected from the group comprising: removable casings of the electrical device, carrying cases for transporting the electrical device, straps for carrying the electrical device, carrying handles, fashion-tags, ornamental pendants, mobile dangles, skins for encasing the electrical device, stickers for adhering to the electrical device, belt-clips, neck support straps and earphone units.

**[0011]** Optionally, the secondary inductor comprises an electrical connector for coupling to a power jack socket such that the secondary inductor is retrofittable to the electrical device. Preferably, the electrical connector comprises a hermaphrodite connector comprising: a male plug portion, for coupling with the power jack socket and a female socket portion for coupling to an external power source.

**[0012]** In some embodiments the electrical device comprises a removable power pack; the power pack being connectable to the electrical device via contacts, the secondary inductor comprising an electrical connector for coupling to the contacts. Preferably, the electrical device further comprises an electrochemical cell, and the secondary inductor is connected to the electrochemical cell via a rectifier for charging the electrochemical cell.

**[0013]** Optionally, the accessory comprises a USB plug for coupling to a computer such that the electrochemical cell is selectively chargeable by power drawn from the computer. Typically, the USB plug is wired to a data jack socket of the electrical device such that data is exchangeable between the computer and the mobile communication device.

**[0014]** In preferred embodiments, the power providing system further comprises an audio device having an external earphone unit, wherein the secondary inductor is incorporated into the earphone unit. Typically, the external earphone unit, comprises at least one inductive element for inductively coupling the primary inductor to the secondary inductor. Optionally, the inductive element comprising the secondary inductor. The secondary inductor may comprise a voice coil of at least one speaker of the earphone unit. Alternatively, the secondary inductor comprises at least one loop of wire. The loop of wire may be incorporated into a neck support strap for supporting the audio device. Alternatively, the ends of at least one wire are connected together to produce the at least one loop of wire. In other embodiments of the invention the earphone unit includes an inductive element which comprises a

ferromagnetic core extending through the secondary inductor and into the earphone unit for selectively coupling with the primary inductor.

**[0015]** In still another embodiment of the invention, the power providing system comprises at least one inductive coil, the inductive coil being selectively connectable to: at least one charging circuit for connecting the inductive coil to a power pack via a rectifier for charging the power pack when the secondary inductor is inductively coupled to the primary inductor; and at least one driving circuit connectable to the power pack for providing a varying electrical potential to the inductive coil such that the inductive coil transfers power to an external inductor wired to an external electrical load. Preferably, the power pack is selected from the group comprising: nickel-cadmium cells, nickel metal hydride cells, alkaline cells, flow batteries, rechargeable electrochemical cells and capacitors. Optionally, the power providing system comprising a ferromagnetic core for guiding magnetic flux through the inductive coil when inductively coupled. Typically, the driver comprises at least one switching unit for intermittently connecting the power pack to the inductive coil at high frequency.

**[0016]** Optionally, the power providing system additionally comprises a jack for conductively connecting the power pack to an external power source for charging purposes. The power providing system may additionally comprise a jack for conductively connecting the power pack to the external electrical load.

**[0017]** It is a further aim of the invention to provide a computer comprising an inductive coil which is selectively connectable to: at least one charging circuit for connecting the inductive coil to a power pack via a rectifier for charging the power pack when the secondary inductor is inductively coupled to the primary inductor; and at least one driving circuit connectable to the power pack for providing a varying electrical potential to the inductive coil such that the inductive coil transfers power to an external inductor wired to an external electrical load. Preferably, the power pack is configured to power the computer.

**[0018]** It is a further aim of the invention to provide an inductive charger comprising at least one inductive coil and at least one chargeable power pack, the charger additionally comprising: at least one charging circuit for connecting the inductive coil to the power pack when the inductive coil is inductively coupled to a primary coil wired to a power supply for charging the power pack; and at least one driving circuit connectable to the power pack for providing a varying electrical potential to the inductive coil such that the inductive coil is inductively coupleable to a secondary coil wired to an electrical load.

#### BRIEF DESCRIPTION OF THE FIGURES

**[0019]** For a better understanding of the invention and to show how it may be carried into effect, reference will now be made, purely by way of example, to the accompanying drawings.

**[0020]** With specific reference now to the drawings in detail, it is stressed that the particulars shown are by way of example and for purposes of illustrative discussion of the preferred embodiments of the present invention only, and are presented in the cause of providing what is believed to be the most useful and readily understood description of the principles and conceptual aspects of the invention. In this regard, no attempt is made to show structural details of the invention

in more detail than is necessary for a fundamental understanding of the invention; the description taken with the drawings making apparent to those skilled in the art how the several forms of the invention may be embodied in practice. In the accompanying drawings:

**[0021]** FIG. 1 is a schematic illustration of an inductive power providing means for powering a computer, in accordance with one embodiment of the present invention;

**[0022]** FIG. 2 is a schematic illustration of a computer provided with a secondary inductive coil incorporated within the base thereof, for inductively powering the computer by bringing into proximity with a power supplying inductive coil, according to another embodiment of the invention;

**[0023]** FIG. 3 shows the jack sockets of a portable computer according to a further embodiment of the invention for coupling to an electricity mains power source via an inductive couple or via a conventional power supply;

**[0024]** FIG. 4 is a schematic illustration of a computer carrying case according to another embodiment of the invention with an inductive power coil built into the base thereof;

**[0025]** FIG. 5 is a schematic illustration of another embodiment of the computer carrying case having an inductive power coil built into the handle thereof;

**[0026]** FIG. 6 is a schematic illustration of still another embodiment of the computer carrying case having an inductive power coil built into the shoulder strap thereof;

**[0027]** FIGS. 7a and 7b are schematic illustrations of a retrofittable carrying handle for a portable computer with a built-in inductive power coil according to further embodiments of the invention;

**[0028]** FIG. 8 is a schematic illustration of a fashion-tag attachment with a built-in inductive power coil in accordance with still another embodiment of the invention;

**[0029]** FIGS. 9a and 9b are schematic illustrations of a computer provided with another embodiment of the invention including a retractable secondary inductive coil attachment;

**[0030]** FIG. 10 is a schematic illustration of an inductive charger for a mobile communication device of a further embodiment of the invention;

**[0031]** FIGS. 11a and 11b are schematic illustrations of a mobile communication device with an inductive charger built into the skin thereof according to another embodiment of the invention;

**[0032]** FIG. 12a is a schematic illustration of a self-adhesive inductive charger for a mobile communication device adhered to a power cell according to another embodiment of the invention;

**[0033]** FIG. 12b is a schematic illustration of how the self-adhesive inductive charger of FIG. 12a may be used to charge cells;

**[0034]** FIG. 13 is a schematic illustration of an inductive charger of another embodiment of the invention having a hermaphrodite power connector;

**[0035]** FIGS. 14a-c are schematic illustrations of a protective case according to a further embodiment of the invention with a built-in an inductive charger for a mobile communication device;

**[0036]** FIG. 15 is a schematic illustration of a mobile communication device with an inductive charger built into a fashion tag;

**[0037]** FIG. 16 is a schematic illustration of an inductive charger for a mobile communication device with a combined data connector;

[0038] FIG. 17 is a block diagram showing the main elements of a charger for an audio device incorporated into an earphone unit in accordance with another embodiment of the invention;

[0039] FIG. 18a is a schematic diagram of a charger for an audio device according to another embodiment of the invention, wherein the voice coil of a speaker is wired to the power cell of the audio device and is inductively coupleable to a primary inductor;

[0040] FIG. 18b is a block diagram showing the main elements of a switching unit for connecting the charger of FIG. 18a to an audio device;

[0041] FIG. 19a is a schematic diagram of another embodiment of the charger for an audio device wherein an induction loop is incorporated into a neck support of the earphone unit;

[0042] FIG. 19b is a schematic diagram of still another embodiment of the charger for an audio device wherein an induction loop is formed by connecting contact-terminals incorporated into the earphone cables;

[0043] FIG. 19c is a schematic representation of an embodiment of the charger for an audio device wherein an inductive core extends through an internal secondary coil and into the earphone unit for coupling with an external primary inductor;

[0044] FIG. 20 is a flowchart showing a possible method for charging the internal power cell of an audio device;

[0045] FIGS. 21a and 21b are block diagrams schematically representing an inductive charger according to a further embodiment of the invention in charging and driving modes respectively;

[0046] FIG. 22a is a schematic representation of another embodiment of the inductive charger being charged by a primary coil;

[0047] FIG. 22b is a schematic representation of the inductive charger of FIG. 22a being used to charge a mobile telephone wired to a secondary coil;

[0048] FIG. 23a is a schematic representation of a mobile computer being powered by a primary coil via an integral inductive coil according to another embodiment of the invention, and

[0049] FIG. 23b is a schematic representation of a mobile telephone being charged by the inductive coil of FIG. 23a.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0050] Reference is now made to FIG. 1, showing a power providing means 10 for a portable computer 12 consisting of a secondary inductor 14 wired to the portable computer by a connecting wire 15 that is typically a two stripe multi-fiber insulated wire, such as used for providing power to portable computers via a transformer.

[0051] The secondary inductor 14 is essentially a coil which can be brought into proximity with a primary inductor 16 which is essentially another coil hardwired to a mains power supply 18. The primary coil 16 and secondary coil 14 thus form an inductive power couple 20, allowing power to be provided to the portable computer 12. The primary coil 16 may be situated in the table top 18 of a conference table, for example. By supplying power inductively in this manner, trailing wires may be avoided, providing a neater, safer and more flexible work environment.

[0052] It will be appreciated that, although a system for providing power to a portable computer is described herein, the power providing means 10 may also be applicable to the

provision of power to other electrical devices such as a desk-top computer, handheld computer, vehicle mounted computer or the like. Power providing means 10 may also be used by other portable systems such as hand-held DVD players, projectors, hand-held televisions, digital picture frames or sound systems for example.

[0053] As shown in FIG. 2, in an embodiment of the invention, the secondary coil 14 may be integral to the portable computer 12, being built into the base thereof, under the keyboard. Positioning the computer 12 over a primary coil 16a in a work-surface 22, for example, enables power to be provided thereto, without trailing wires. The power may be used to recharge the electrochemical power pack (battery) 24 or to power the portable computer 12.

[0054] As shown in FIG. 3, in another embodiment of the invention, the secondary coil 14a may be coupled to a portable computer 12 designed for optional power provision in this manner, via a jack 26 that is plugged into a dedicated jack socket 28 designed for coupling the secondary coil 14a. The dedicated jack socket 28 is separate from the power supply jack socket 30 supplied for coupling to a power supply (not shown) of the type consisting of a transformer for plugging into a power mains socket that is typically provided. The dedicated jack plug 26 and jack socket 28 may usefully be physically different from power supply jack socket 30 and jack plug (not shown), to prevent misconnection. Similarly, the inductive and transformer sockets 28, 30 are preferably appropriately labeled, perhaps with letters I and T for inductive and transformer, to prevent confusion.

[0055] However, since the purpose of inductive coupling is to avoid and replace transformer coupling, in preferred embodiments, the secondary coil 14a is connected to the portable computer 12 via the power jack socket 30 designed for coupling to a mains via a power supply of the transformer type. In this manner, existing portable computers may be retrofitted with a secondary coil 14a for inductive powering.

[0056] Power may alternatively be provided to the portable computer 12 via connecting points designed for coupling to a rechargeable electrochemical power pack within the housing for the power pack.

[0057] The secondary coil 14a may be provided as a sort of puck on a wire that can be positioned over an access point in a surface where a primary coil 16 is provided.

[0058] Alternatively however, usefully, to provide a neat solution, to eliminate trailing wires, recoiling such wires and to make disconnecting simpler, as shown in FIG. 4 the secondary coil 14b is preferably incorporated into an accessory that has additional functionality. For example, it may be built into the side of a carrying case 40 or skin provided for carrying the portable computer 12. In one preferred embodiment as shown in FIG. 5 the secondary coil 14c is built into the handle 42 of a carrying case 44.

[0059] As shown in FIG. 6, in one embodiment, the secondary coil 14d is built into the shoulder strap 46 of a carrying case 48 which being flexible, gives more flexibility to the user, in that the computer 12 can be left in its case, and situated anywhere within a radius of about 80 cm from a "power-spot" where a primary coil 16 is situated.

[0060] With reference now to FIGS. 7a and 7b, a retrofitable carrying handle 52 for a computer 12 is shown. The handle 52 is attached to the computer by straps 54 and incorporates a built-in inductive power coil 14e electrically coupled to the computer via a power plug 56 which plugs into the power jack 30 of the computer 12.



[0061] While the computer 12 is being carried, the straps 54 surround and support the computer 12 as shown in FIG. 7b. However, as shown in FIG. 7a, when the computer 12 is laid down and in use, the support straps 54 are opened allowing the inductive power coil 14e to be coupled to a primary coil 16 situated anywhere within their radius.

[0062] Alternatively, with reference to FIG. 8, the inductive power coil 14 may be concealed inside a fashion-tag 62 attached to the computer 12 for example by a connecting chain 64 or the like. Thus, by aligning the fashion-tag 62 to a power spot, the computer may draw power from a primary coil 16.

[0063] In a further embodiment, a retractable secondary inductive coil attachment 70 may be retrofitted to a portable computer 12, as shown in FIGS. 9a and 9b. The secondary inductive coil 14f is held in a tongue 74 mounted upon the base of the computer 12 and when the computer 12 is in use as shown in FIG. 9a, the tongue 74 may be extended so that the secondary coil 14f may couple with a power spot 16 within its radius.

[0064] When the portable computer is stowed, as in FIG. 9b, tongue 74 may be retracted. Preferably, the thickness of the secondary inductive coil attachment 70 is less than the height of the feet 13 of the computer 12 so that the attachment 70 does not prevent the computer 12 lying flat along a table top.

[0065] Referring now to FIG. 10, an inductive charger 100 is shown for charging the power cells of a mobile communication device 200 such as mobile telephone, personal digital assistant (PDA), camera or the like, indeed many mobile devices include all of these functions. The charger 100 consists of a secondary coil 120 wired to the mobile communication device 200 typically via a power jack socket 220 of by a connecting wire 140—typically a two stripe multi-fiber insulating wire, such as used for electrically connecting a power source to a mobile communication device via a transformer.

[0066] The secondary coil 120 can be brought into proximity with a primary coil 10 hardwired to a mains power supply, to form an inductive power couple, allowing power to be provided to recharge the cells 240 (FIGS. 12a and 12b) of the mobile communication device 200. The primary coil 10 may be situated in the table top 20 of a conference table, for example, thereby allowing a phone 200 to be recharged thereby. By inductively recharging in this manner, trailing wires may be avoided or at least minimized. The secondary coil 120 may be provided for example as a sort of puck 122 on a wire that can be positioned over an access point in a surface where a primary coil 10 is provided. Alternatively the secondary coil 120 may be built into an accessory of the telephone 200.

[0067] Over the years, mobile telephones have become a fashion item and various fashionable accessories are often sold for use therewith. Such accessories include for example, replacement phone skins, protective cases, belt clips, small ornamental pendants, sometimes known as “mobile dangles” and the like. Some such accessories are merely decorative, others perform secondary functions such as providing added protection to the device, or more convenient ways to carry the device. The secondary coil 120 of the current invention may be incorporated into any of these.

[0068] As shown in FIG. 11a, according an embodiment of the invention the secondary coil 120 may be built into the skin or casing 260a, 260b of the mobile communication device.

Positioning the mobile communication device over a primary coil 10, as shown in FIG. 11b, at an access point in a work-surface 20, for example, enables power to be provided to the charger thereby charging the power cells 240 of the mobile communication device 200 without trailing wires.

[0069] The charger may be connected directly to the terminals of the power cells. Alternatively the charger may be connected to the power cells via the power jack socket 220 of the mobile communication device 200.

[0070] According to another embodiment, shown in FIG. 12a, the secondary coil 120 may be provided with an adhesive surface 122 so that the coil 120 may be adhered directly onto the power cells 240 of a mobile telecommunication device 200 in conductive contact with the terminals of the power cells. When power cells 240 are positioned such that the secondary coil 120 forms as inductive couple with a primary coil 10 the cells 240 may be recharged. As shown in FIG. 12b, it is noted that in this embodiment, the cells 240 are recharged directly from the secondary coil 120 so the cells 240 do not need to be connected to the device in order for them to be charged.

[0071] Referring now to FIG. 13, in further embodiment, the secondary coil 120 is wired to a hermaphrodite power connector 160 including both a male plug 162 and a female socket 164. The male plug 162 of the hermaphrodite power connector 160 may be coupled to the power jack socket 220 of the device while still providing a female socket 164 for accommodating the plug 40 of a conventional conductive charger. With this embodiment, a user may select between charging the power cells 240 of the mobile communication device 200 using the inductive charger 100 or the conductive type charger. The selection may be facilitated by means of a switch although, preferably, the power connector 160 is configured automatically to select the inductive charger whenever the secondary coil 120 is inductively coupled to a primary coil 10 and to select the conductive power supply whenever the female socket 164 is conductively coupled to a power source.

[0072] Alternatively, in the embodiment shown in FIGS. 14a-c, the secondary coil 120 may be built into a protective or fashionable case 300 which may be fitted to a mobile communication device 200. The secondary coil 120 is typically wired to a hermaphrodite power connector 160 within the case 300 which is configured to couple with the power jack socket 220 of the mobile communication device.

[0073] A further embodiment is illustrated in FIG. 15 showing a mobile communication device 200 having a secondary coil concealed within a fashionable tag 400, such as a so called “mobile dangle” or the like, which may be plugged directly into the power jack socket 220 with additional mechanical support 420 optionally provided when necessary. The inductive charger 100 of the invention may thus be incorporated within a fashion accessory for the mobile communication device. In a similar manner, the secondary coil 120 may be concealed in other accessories of the mobile telecommunication device such as a belt clip, neck cord, hand strap or the like.

[0074] According to still another embodiment, with reference to FIG. 16, an inductive charger 700 has a data channel coupled to the data jack socket 280 of the mobile communication device 200. A USB (Universal Serial Bus) cable 720 leading to a USB plug is wired to the inductive charger which may be connected to USB jack socket 820 of a computer 800,

for example, thereby providing a data link between the mobile communication device **200** and the computer **800**.

[0075] The USB connector **740** may, in addition, draw power from the computer **800** and may thus be used to provide power to charge the power cells **120** of the mobile communication device **200** directly. As described hereinabove with reference to the hermaphrodite connector, the charger **700** may be configured to select automatically between charging the power cells **120** from the USB connector **740** or the secondary coil **120** depending upon the availability of power.

[0076] U.S. Pat. No. 7,180,265 to Nokia Corporation, titled "Charging Device with an Induction Coil" describes an inductive charging device for charging portable electronic devices with small footprints. The charger described in '265 includes a battery; a first induction coil coupled to the battery; and an induction core extending through the first induction coil. The induction core has a portion which extends in an outward direction from the charging device and is adapted to removably couple with a second induction coil of a portable electronic device by extending into the second induction coil.

[0077] The charger described in '265 is essentially a charging hook upon which electronic devices may be suspended by support loops. The hook is coupled to the first inductive coil and is adapted to charge up the electronic devices via the secondary inductive coils which may be incorporated into the support loops. '265 claims to provide a convenient way to organize devices being charged. However, for some applications the support strap itself is undesirable, and as discussed hereinabove, there is a general desire to limit the number of wires, straps and cables.

[0078] By way of example, referring now to FIG. 17, a block diagram showing the main elements of an inductive charger **1100** for charging the internal power cells **1220** of an audio device **1200**, according to an embodiment of the invention.

[0079] The charger **1100** includes a secondary inductor **1140** wired to the power cells **1220** of the audio device **1200** via a rectifier **1240**. An inductive element **1180** is incorporated into the earphone unit **1120** for inductively coupling the secondary inductor **1140** to an external primary inductor **1320**.

[0080] The primary inductor **1320** is typically wired to a power supply **1300** via a driving unit **1310**. The driving unit **1310** provides the electronics necessary to drive the primary inductor **1320**, such as a switching unit providing a high frequency oscillating voltage supply, for example.

[0081] Charger **1100** is suitable for use with audio devices **1200** requiring earphones **1121** connected via earphone cables **1122** such as, telephones, media players, personal digital assistants (PDA), Walkman®s, portable CD players, portable DVD players, mobile communications devices and the like.

[0082] It is a particular feature of this embodiment, that at least a part of the inductive charger **1100** is incorporated in the earphone unit **1120** of the audio device **1200**. This represents an advantage over prior art devices such as the system described in U.S. Pat. No. 7,164,255 to Hui, which disadvantageously requires a secondary winding to be incorporated either within the device itself or in a dedicated adaptor, whereas the inductive charger **1100** of the present invention is suitable for use in charging audio devices with small footprints. Furthermore, because the inductive charger **1100** of the present invention is incorporated into the earphone unit **1120**, the dimensions of the audio device **1200** itself are not

compromised by the addition of peripheral elements such as the support strap described in U.S. Pat. No. 7,180,265 to Nokia Corporation, for example.

[0083] With reference to FIG. 18a, a schematic diagram of a charger **2100** for an audio device **2200** according to another embodiment is shown. In this embodiment, the earphone unit **2120** includes a moving coil speaker **2122** incorporated within an earpiece **2124** which is connected via a signal line **2125** to a plug **2126** for coupling to the audio device **2200** via an earphone jack **2202**. The voice coil **2140** of the moving coil speaker **2122** is a transducer that receives electrical signals from the signal lines **2125** and converts them to audio signals.

[0084] The voice coil **2140** is additionally configured to be coupleable to an external primary inductor **2320** which may be housed within a docking station **2322**. Thus the voice coil **2140** may serve as the secondary inductor **1140** (FIG. 17) of the inductive charger **2100**, providing power to the audio device via the signal lines **2125**. Alternatively, dedicated power lines within the earphone unit **2120** may provide a conductive connection between the voice coil **2140** and the internal power cell **220** of the audio device **200** via a rectifier **1240** (FIG. 17).

[0085] FIG. 18b is a block diagram of the main elements of a switching unit **2270** for connecting the charger **2100** of FIG. 18a to an audio device **2200**. The switching unit **2270** is provided to selectively connect the voice coil **2140** to the audio device **2200**. The switching unit **2270** may be a separate unit that is retrofittable both to the audio device **2200** and to the earphone unit **2120**. Alternatively, the switching unit **2270** may be incorporated into either the audio device **2200** or the earphone unit **2120**.

[0086] The switching unit **2270** may connect the voice coil terminal C to either an audio signal input A or to a charger output B of a switching circuit **2272**. The audio signal input A receives an audio signal **2250** from an amplifier **2260** which is communicated to the voice coil **2140**. The charger output B is connected to the power cell **2220** via a rectifier **2240** and may be used for charging the power cell **2220** when the voice coil **2140** is coupled to primary inductor **2320**.

[0087] Optionally the switching circuit **2272** may be controlled by a frequency detector **2274** which is configured and operable to detect high frequency voltage fluctuations along the signal line. High frequency voltage fluctuations are indicative that the voice coil **2140** is coupled to an active primary inductor **2320**. Therefore, when such high frequency fluctuations are detected, the switching circuit **2272** may be connected to the charger output B for charging the power cell **2220**.

[0088] FIGS. 19a-c are schematic diagrams showing various embodiments of charger **3100**, **4100**, **5100** for an audio device **3200**, **4200**, **5200**. With reference to FIG. 19a, the earphone unit **3120** includes a neck support **3122**. Within the neck support **3122** is an induction loop **3140** of conductive wire **3142** that is wound into a coil and connected to the internal power cell **1220** (FIG. 17) of the audio device **3200** via a rectifier **1240** (FIG. 17). The inductive loop **3140** is configured to inductively couple with an external primary inductor **320**. The audio device **3200** may be conveniently stored by suspending the neck support **3122** from a hook **3322**.

[0089] In preferred embodiments, the hook **3322** is fabricated from a ferromagnetic material which extends through a primary coil **3320**. When the neck support **3122** is suspended from the hook **3322**, the ferromagnetic material forms a com-

mon inductive core **3180** between the primary coil **3320** and the inductive loop **3140** within the neck support **3122**. The primary coil **3320** and inductive loop **3140** thus form an inductive couple such that power may be inductively transferred from the primary coil **3320** to the inductive loop **3140**, thereby charging the power cells **1220** (FIG. 17) of the audio device **3200**.

[0090] Optionally, the inductive couple may be improved by the inclusion of a ferromagnetic element (not shown) and may be incorporated into the neck support **3122** and configured so as to couple with the ferromagnetic inductive core **3180** of the hook **3322** so as to complete a magnetic circuit.

[0091] Although the example of an inductive loop **3140** within a neck support **3122** is described herein, it is noted that a secondary inductor may be housed in various other components of an earphone unit. For example a secondary induction coil may be housed in a dedicated unit within the earphone cable. Alternatively a secondary coil may be incorporated into a microphone housing such as is commonly included in the earphone cable of a cellular telephone. Alternatively again a secondary coil may be incorporated into a cable stowage unit such as a spring loaded winder as is sometimes included with earphone units for convenient storage.

[0092] An alternative embodiment of the induction loop is schematically represented in FIG. 19b, wherein a charger **4100** for an audio device **4200** according to another embodiment of the current invention is shown. The earphone unit **4120** of this embodiment includes two earpieces **4122a**, **4122b**, each connected to the audio device **4200** via its own earphone cable **4124a**, **4124b**. A bundle of induction wires **4140**, embedded in the earphone cables **4124**, is connected to the internal power cell **1220** (FIG. 17) of the audio device **4200** via the rectifier **1240** (FIG. 17). Contact-terminals **4142a** and **4142b** at each end of the bundle of induction wires **4140**, typically located near the earpieces **4122a**, **4122b**, are configured to conductively couple the ends of the bundle of induction wires **4140** thereby forming an induction loop. The induction loop may be coupled with an external primary coil (not shown) such that power may be inductively transferred from the primary coil to the inductive loop.

[0093] FIG. 19c is a schematic representation of a charger **5100** for an audio device **5200** according to still another embodiment of the invention. The audio device **5200** incorporates an internal secondary coil **5140** connected to the internal power cell **5220** via the rectifier **5240**. An inductive core **5180** extends through the internal secondary coil **5140** and into the earphone unit **5120** for coupling with a primary inductor **5320**. The primary inductor may, for example, be incorporated into a hook (not shown) for suspending the audio device **5200**.

[0094] FIG. 20 is a flowchart showing a method for inductively charging the internal power cell of an audio device in accordance with one embodiment of the invention. The method comprises the steps of:

[0095] step (a) providing an inductive charger incorporated within the earphone unit of the audio device, including a secondary inductor connected to the power cell via a rectifier;

[0096] step (b) providing an external primary inductor connected to a power source via a driver;

[0097] step (c) inductively coupling the secondary inductor of the charger to the external primary inductor, and

[0098] step (d) providing a variable voltage to the primary inductor.

[0099] Reference is now made to FIGS. 21a and 21b which are block diagrams schematically representing the inductive charger **6100** for use with another embodiment of the invention. The inductive charger **6100** consists of an inductive coil **6120** and a chargeable power pack **6140** which can be connected to each other via a charging circuit **6160** or alternatively via a driving circuit **6180**. It is a particular feature of the current invention that the inductive charger **6100** may be switched between two modes: (a) a charging mode as shown in FIG. 21a, and (b) a driving mode, as shown in FIG. 21b. A mode selector **6170** is used to select between the two modes.

[0100] With particular reference to FIG. 21a, representing the inductive charger **6100** in charging mode, the inductive coil **6120** is coupled to an external primary inductive coil **6220** which is connected to a power supply **6240** preferably via a driving unit **6260**. The mode selector **6170** is configured to connect the inductive coil **6120** to the power pack **6140** via the charging circuit **6160**.

[0101] In the charging mode, the external primary coil **6220** generates an oscillating magnetic field. The internal inductive coil **6120** is placed in the vicinity of the external primary coil **6220**, thereby creating a magnetic flux linkage between the primary coil **6220** and the internal inductive coil **6120**, by which power is transferred from the external primary coil **6220** to the internal inductive coil **6120**. Typically, direct current is required for reversing the electrochemical reactions that result in power supply from the power packs and the charging circuit **6160** rectifies the alternating current generated in the inductive coil **6120** thereby allowing the power pack **6140** to be recharged.

[0102] Referring now to FIG. 21b, representing the inductive charger **6100** in driving mode, where the inductive coil **6120** is inductively coupled to an external secondary inductive coil **6320** which is wired to an electric load **6340**. The mode selector **6170** is configured to connect the inductive coil **6120** to the power pack **6140** via the driving circuit **6180**. In the driving mode the power supply **6140** provides power to the driver circuit **6180** which provides a varying electrical potential to drive the inductive coil **6120**. The driver circuit **6180** typically includes a high frequency switching unit intermittently connecting the power pack **6140** to the inductive coil **6120**. The varying electrical potential across the inductive coil **6120** produces an oscillating magnetic field. Therefore, an external secondary coil **6320** which is brought into the vicinity of the inductive charger **6100** may inductively couple with the inductive coil **6120**. An electric load **6340** wired to the secondary coil **6320** may thereby draw power from the power pack **6140**.

[0103] Many examples of rechargeable power packs are known and may be suitable for use with various embodiments of the inductive charger **6100**. Examples of rechargeable electrochemical cells include nickel-cadmium cells, nickel metal hydride cells, alkaline cells, flow batteries and the like. Other power storage devices such as lead alkali accumulators, capacitors and supercapacitors may also be charged by the inductive charger **6100**.

[0104] Reference is now made to FIGS. 22a and 22b showing an exemplary inductive charger **7100** according to another embodiment of the invention. A housing **7110** contains an inductive coil **7120** which is wrapped around a ferromagnetic core **7122** and is connected to an internal power pack **7140** via a control box **7130**. The control box **7130** contains driving circuitry for the driving mode, charging circuitry for the charging mode and a mode selector (not shown). In alterna-

tive embodiments (not shown), additional circuitry may be provided for charging the power pack **7140** from the mains or other external power source, such as solar power or the like, via a dedicated jack. A dedicated jack may also be provided for conductively connecting with and the powering of an external electrical load.

[0105] FIG. **22a** shows the inductive charger **7100** being charged up by an inductive power outlet **7200** which consists of a primary coil **7220** concealed behind a facing layer, such as Formica or wood veneer, of a platform **7280** such as a desk-top, a kitchen work-top, a conference table or a work bench for example. The primary coil **7220** is wired to a power supply **7240** via a driving unit **7260** providing the electronics necessary to drive the primary coil **7120**. Driving electronics may include a switching unit providing a high frequency oscillating voltage supply, for example.

[0106] As inductive power outlets **7200** become more widespread, it is considered likely that devices may be hard-wired to secondary coils, to draw their power inductively therefrom. In particular, mobile phones, media players and the like which are generally connected to external chargers via connecting wires may be provided with internal charging circuitry that includes a secondary coil for inductively coupling to inductive power outlet **7200**.

[0107] FIG. **22b** shows a mobile phone **7300** which has an integral secondary inductive coil **7320** connected to its internal power source **7340** via a rectifier (not shown). The mobile phone **7300** may be charged by placing it over an inductive power outlet **7200** such as shown in FIG. **22a**, thereby inductively coupling the secondary coil **7320** of the device with the primary coil of the outlet **7200**.

[0108] Where no inductive power outlet **7200** is available, the mobile phone may be charged by placing it on top of the inductive charger **7100**, as shown in FIG. **7b**. With the inductive charger **7100** set to driving mode, the mobile phones secondary coil **7320** inductively couples with the internal inductive coil **7120** of the inductive charger **7100** and draws power therefrom.

[0109] According to another embodiment of the inductive charger, shown in FIGS. **23a** and **23b**, the inductive charger **8100** is incorporated into a mobile computer **8000**. The mobile computer **8000** has a built-in inductive coil **8120** for powering the computer from an inductive power outlet **8200**, as shown in FIG. **23a**. Once coupled to a primary coil **8220**, the inductive coil **8120** may power the computer and/or charge the internal power pack **8140** of the mobile computer.

[0110] The inductive coil **8120** of the computer **8000** may additionally be used to charge an external device such as a mobile phone **8300** with an in-built secondary coil **8320**, as shown in FIG. **8b**. A similar use is already made of computers **8000** to charge external devices such as media players, mobile phones, mice, Bluetooth devices and the like, generally using dedicated cables and via standard ports, such as their USB (universal serial bus) ports. One advantage of this is that no such dedicated cables are needed.

[0111] It is noted that, apart from the mobile computer **8000** described herein, inductive chargers may be incorporated into other hosts, such as electric cars, generators, emergency lights or the like for charging electrical devices thereby.

[0112] The scope of the present invention is defined by the appended claims and includes both combinations and sub combinations of the various features described hereinabove

as well as variations and modifications thereof, which would occur to persons skilled in the art upon reading the foregoing description.

[0113] In the claims, the word “comprise”, and variations thereof such as “comprises”, “comprising” and the like indicate that the components listed are included, but not generally to the exclusion of other components.

1. A speaker device configured to convert an electrical signal from an audio device into an audible output, comprising a voice coil wherein said voice coil is further configured to inductively couple with a primary inductor.

2. The speaker device of claim **1** incorporated into an earphone unit.

3. The speaker device of claim **2** wherein said earphone unit is configured to receive said electrical signals from at least one audio device.

4. The speaker device of claim **3** wherein said earphone unit comprises a signal line configured to conductively connect with said audio device.

5. The speaker device of claim **4** wherein said signal line is further configured to provide power to said audio device.

6. The speaker device of claim **3** wherein said earphone unit comprises a power line configured to provide power to said audio device.

7. The speaker device of claim **1** wherein said voice coil is conductively connected to a power cell via a rectification unit.

8. The speaker device of claim **1** wherein said voice coil is conductively connected to a switching unit, said switching unit configured to selectively connect the voice coil to at least one of:

an audio signal input, for transmitting said electrical signals to said voice coil via a signal line, and

and a charger output, for conductively connecting said voice coil to a power cell via a rectification unit.

9. The speaker device of claim **8** wherein said audio signal input is connected to an amplifier.

10. The speaker device of claim **8** wherein said switching unit further comprises a frequency detector configured to detect voltage fluctuations along said signal line.

11. The speaker device of claim **10** wherein said frequency detector is configured to connect said voice coil to said charger output when high frequency voltage fluctuations are detected.

12. The speaker device of claim **1** being configured to charge a power cell associated with an audio device selected from a group consisting of: telephones, media players, PDAs, portable CD players, dictaphones, portable DVD players, Bluetooth devices and mobile communications devices.

13. A power providing system for an electrical device comprising: a secondary inductor, wired to said electrical device, for inductively coupling with a primary inductor hardwired to a power supply, wherein said secondary inductor is incorporated into an earphone unit.

14. The power providing system of claim **13**, said earphone unit comprising at least one inductive element for inductively coupling said primary inductor to said secondary inductor.

15. The power providing system of claim **14**, said inductive element comprising said secondary inductor.

16. The power providing system of claim **13**, secondary inductor comprising a voice coil of at least one speaker of said earphone unit.

17. The power providing system of claim **13**, secondary inductor comprising at least one loop of wire.

**18.** The power providing system of claim **17** wherein said at least one loop of wire is incorporated into a support strap for supporting the electrical device.

**19.** The power providing system of claim **17** wherein the ends of at least one wire are connectable to produce said at least one loop of wire.

**20.** The power providing system of claim **13** wherein said inductive element comprises a ferromagnetic core extending through said secondary inductor and into said earphone unit for selectively coupling with said primary inductor.

\* \* \* \* \*