



US007080172B1

(12) **United States Patent**
Schmalz

(10) **Patent No.:** **US 7,080,172 B1**
(45) **Date of Patent:** **Jul. 18, 2006**

(54) **MANAGEMENT OF MEMORY, HARDWARE AND ASSOCIATED DEVICE DRIVERS USING STACKS**

(75) Inventor: **Joachim Schmalz**, Bischweier (DE)

(73) Assignee: **Marvell Luternational Ltd.** (BM)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 332 days.

(21) Appl. No.: **10/446,341**

(22) Filed: **May 27, 2003**

(51) **Int. Cl.**
G06F 13/00 (2006.01)

(52) **U.S. Cl.** **710/104**; 719/327; 719/321;
710/8; 710/10; 709/220; 709/226; 711/2;
711/170

(58) **Field of Classification Search** 710/2,
710/8, 10, 16, 300, 304, 104; 709/220, 221,
709/222, 226; 718/104; 719/321, 327; 711/1,
711/2, 170

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,675,793 A 10/1997 Crick et al.

5,701,476 A 12/1997 Fenger
5,757,386 A * 5/1998 Celi et al. 345/548
5,787,246 A * 7/1998 Lichtman et al. 709/220
5,794,035 A * 8/1998 Golub et al. 718/104
5,819,107 A 10/1998 Lichtman et al.
6,477,612 B1 11/2002 Wang
6,658,475 B1 * 12/2003 Ueno 709/229
6,785,888 B1 * 8/2004 McKenney et al. 718/104
2002/0032719 A1 3/2002 Thomas et al.

FOREIGN PATENT DOCUMENTS

JP 2003143175 A * 5/2003


* cited by examiner

Primary Examiner—B. James Peikari

(57) **ABSTRACT**

Managing memory allocations and de-allocations with a stack, and managing hardware initializations and de-initializations with another stack. A stack may store de-allocate information. Another stack may store de-initialization information. The techniques may be applied to allocating/de-allocating memory for parts of a device driver, initializing/de-initializing parts of hardware, and initializing/de-initializing parts of software.

102 Claims, 4 Drawing Sheets






FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 5




FIG. 6




FIG. 4




FIG. 7




FIG. 8

**MANAGEMENT OF MEMORY, HARDWARE
AND ASSOCIATED DEVICE DRIVERS
USING STACKS**

BACKGROUND

A system may have device driver software, which provides instructions on how to control or interface with a device within the system. The driver software may be allocated to different types of memories and subsequently de-allocated. Driver memory allocation may be dynamic.

The device driver may have a plurality of portions or instances. A conventional memory management technique may load each portion or instance of the device driver into an addressed location of a memory. Multiple portions or instances of the device driver may be loaded into various locations of multiple types of memory.

There may be no concerted effort to keep track of (a) the allocated memory location of each driver portion and (b) the order of allocations to multiple types of memory. As a result, when a system closes or shuts down and memory is de-allocated (or "freed"), such de-allocation may not necessarily be complete. This may leave the system in a state where some of the memory is effectively wasted. Incomplete de-allocation may cause memory leakage and/or system crashes and other undesired effects.

SUMMARY

The application relates to techniques for improving memory management for software, such as a device driver, particularly for software written under the Microsoft Windows® operating system. One technique may allocate a plurality of memory locations in a plurality of memory types to store a plurality of device driver portions and use a stack to store de-allocate information. Another technique may allocate a plurality of memory locations in a memory (typically one type of memory) to store a plurality of software parts of a user software application (not related to a device driver) and use a stack to store de-allocate information. The stacks may advantageously help a memory management technique reduce or avoid memory leaks.

Another technique may initialize a plurality of hardware parts in a peripheral device and use a stack to store de-initialize information for the hardware parts.

A system may use one or more of the following stacks: (a) a stack for device driver memory de-allocation, (b) a stack for software memory de-allocation, and (c) a stack for hardware de-initialization. These stacks may be used independently of each other.

An aspect of the application relates to a method comprising: first allocating a first portion of a device driver to a first location of a first memory; if said first allocating is successful, storing first de-allocate information of the first location of the first memory to a stack; second allocating a second portion of the device driver to a first location of a second memory different than the first memory; if said second allocating is successful, storing second de-allocate information of the first location of the second memory to the stack; and if said second allocating is not successful, de-allocating the first location of the first memory using the first de-allocate information in the stack.

Another aspect relates to a method comprising: allocating locations in a plurality of memory types to store portions of a device driver; storing de-allocate information for each successfully-allocated memory location in a stack; and if an

allocation is not successful, de-allocating a previously-successful allocated memory location by using de-allocate information in the stack.

Another aspect relates to a method of de-allocating a plurality of memory locations. The method comprises retrieving a first de-allocate information block from a stack; de-allocating a location in a first memory specified by the first de-allocate information block; retrieving a second de-allocate information block from the stack; and de-allocating a location in a second memory specified by the second de-allocate information block.

Another aspect relates to a method comprising: initializing a plurality of hardware parts; storing de-initialize information for each successfully-initialized hardware part in a stack; and if an initialization is not successful, de-initializing a previously-successful initialized hardware part by using the de-initialize information in the stack.

Another aspect relates to a method comprising: allocating a plurality of locations in a memory for a plurality of software parts; storing de-allocate information for each successfully-allocated memory location for a software part in a stack; and if an allocation is not successful, de-allocating a previously-successful allocated memory location for a software part by using de-allocate information in the stack.

Another aspect relates to method comprising: allocating a location in a memory for a free buffer; storing first de-allocate information for the allocated memory location of the free buffer in a first stack; storing data in the free buffer and using the first de-allocate information to de-allocate the memory location of the free buffer; and storing second de-allocate information for the memory location of a used buffer in a second stack.

Another aspect relates to a computer program comprising steps of: first allocating a first portion of a device driver to a first location of a first memory; if said first allocating is successful, storing first de-allocate information of the first location of the first memory to a stack; second allocating a second portion of the device driver to a first location of a second memory different than the first memory; if said second allocating is successful, storing second de-allocate information of the first location of the second memory to the stack; and if said second allocating is not successful, de-allocating the first location of the first memory using the first de-allocate information in the stack.

Another aspect relates to a computer program comprising steps of: allocating locations in a plurality of memory types to store portions of a device driver; storing de-allocate information for each successfully-allocated memory location in a stack; and if an allocation is not successful, de-allocating a previously-successful allocated memory location by using de-allocate information in the stack.

Another aspect relates to a computer program comprising steps of: retrieving a first de-allocate information block from a stack; de-allocating a location in a first memory specified by the first de-allocate information block; retrieving a second de-allocate information block from the stack; and de-allocating a location in a second memory specified by the second de-allocate information block.

Another aspect relates to a computer program comprising steps of: initializing a plurality of hardware parts; storing de-initialize information for each successfully-initialized hardware part in a stack; and if an initialization is not successful, de-initializing a previously-successful initialized hardware part by using the de-initialize information in the stack.

3

Another aspect relates to a computer program comprising steps of: allocating a plurality of locations in a memory for a plurality of software parts; storing de-allocate information for each successfully-allocated memory location for a software part in a stack; and if an allocation is not successful, de-allocation a previously-successful allocated memory location for a software part by using de-allocate information in the stack.

Another aspect relates to a computer program comprising steps of: allocating a location in a memory for a free buffer; storing first de-allocate information for the allocated memory location of the free buffer in a first stack; storing data in the free buffer and using the first de-allocate information to de-allocate the memory location of the free buffer; and storing second de-allocate information for the memory location of a used buffer in a second stack.

Another aspect relates to a system comprising a first memory, a second memory, a stack, and a controller. The controller is operable to first allocate a first portion of a device driver to a first location of the first memory. If the first allocating is successful, the controller stores first de-allocate information of the first location of the first memory to the stack. The controller second allocates a second portion of the device driver to a first location of the second memory different than the first memory. If the second allocating is successful, the controller stores second de-allocate information of the first location of the second memory to the stack. If the second allocating is not successful, the controller de-allocates the first location of the first memory using the first de-allocate information in the stack.

Another aspect relates to a system comprising a stack and a controller. The controller is operable to (a) allocate locations in a plurality of memory types to store portions of a device driver; (b) store de-allocate information for each successfully-allocated memory location in the stack; and (c) if an allocation is not successful, de-allocate a previously-successful allocated memory location by using de-allocate information in the stack.

Another aspect relates to a system comprising a stack and a controller. The controller is operable to (a) retrieve a first de-allocate information block from the stack; (b) de-allocate a location in a first memory specified by the first de-allocate information block; (c) retrieve a second de-allocate information block from the stack; and (d) de-allocate a location in a second memory specified by the second de-allocate information block.

Another aspect relates to a system comprising a first hardware part, a second hardware part, a stack, and a controller. The controller is operable to (a) initialize the first and second hardware parts, (b) store a first de-initialize information block and a second de-initialize information block in the stack, and (c) if an initialization of the second hardware part is not successful, de-initializing the previously-successful initialized first hardware part by using the first de-initialize information block in the stack.

Another aspect relates to a system comprising a memory, a first software part, a second software part, a stack, and a controller. The controller is operable to (a) allocate locations in the memory for the first and second software parts, (b) store a first de-allocate information block and a second de-allocate information block in the stack, and (c) if an allocation of the second software part is not successful, de-allocate the previously-successful allocated first software part by using the first de-allocate information block in the stack.

Another aspect relates to a system comprising a memory, a first stack, a second stack, and a controller. The controller

4

is operable to (a) allocate a location in the memory for a free buffer; (b) store first de-allocate information for the allocated memory location of the free buffer in the first stack; (c) store data in the free buffer and use the first de-allocate information to de-allocate the memory location of the free buffer; and (d) store second de-allocate information for the memory location of a used buffer in the second stack.

Another aspect relates to a system comprising a first memory means, a second memory means, a de-allocate information storing means, and a controlling means. The controlling means is operable to perform: first allocating a first portion of a device driver to a first location of the first memory means; if said first allocating is successful, storing first de-allocate information of the first location of the first memory means to the de-allocate information storing means; second allocating a second portion of the device driver to a first location of the second memory means different than the first memory means; if said second allocating is successful, storing second de-allocate information of the first location of the second memory means to the de-allocate information storing means; and if said second allocating is not successful, de-allocating the first location of the first memory means using the first de-allocate information in the de-allocate information storing means.

Another aspect relates to a system comprising a stacking means for storing de-allocate information and a controlling means. The controlling means is operable to (a) allocate locations in a plurality of memory means to store portions of a device driver; (b) store de-allocate information for each successfully-allocated memory location in the stacking means; and (c) if an allocation is not successful, de-allocate a previously-successful allocated memory location by using de-allocate information in the stacking means.

Another aspect relates to a system comprising a stacking means for storing de-allocate information blocks and a controlling means operable to (a) retrieve a first de-allocate information block from the stacking means; (b) de-allocate a location in a first memory means specified by the first de-allocate information block; (c) retrieve a second de-allocate information block from the stacking means; and (d) de-allocate a location in a second memory means specified by the second de-allocate information block.

Another aspect relates to a system comprising a first hardware means for performing a first peripheral function; a second hardware means for performing a second peripheral function; a stacking means for storing de-initialize information; and a controlling means operable to (a) initialize the first and second hardware means, (b) store a first de-initialize information block and a second de-initialize information block in the stacking means, and (c) if an initialization of the second hardware means is not successful, de-initializing the previously-successful initialized first hardware means by using the first de-initialize information block in the stacking means.

Another aspect relates to a system comprising a memory means; a first software means for performing a first function; a second software means for performing a second function; a stacking means for storing de-allocation information; and a controlling means operable to (a) allocate locations in the memory for the first and second software means, (b) store a first de-allocate information block and a second de-allocate information block in the stacking means, and (c) if an allocation of the second software means is not successful, de-allocate the previously-successful allocated first software means by using the first de-allocate information block in the stacking means.

Another aspect relates to a system comprising: a memory means; a first stack for storing de-allocate information; a second stack for storing de-allocate information; and a controlling means operable to (a) allocate a location in the memory means for a free buffer; (b) store first de-allocate information for the allocated memory location of the free buffer in the first stacking means; (c) store data in the free buffer and use the first de-allocate information to de-allocate the memory location of the free buffer; and (d) store second de-allocate information for the memory location of a used buffer in the second stacking means.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A illustrates a system including a CPU/controller, a bus, a peripheral device, a memory system, hardware, software, and a network interface.

FIG. 1B illustrates a typical technique of allocating and de-allocating a plurality of memory locations.

FIG. 2 illustrates a device driver, the CPU/controller and the memory system of FIG. 1A.

FIG. 3 illustrates a technique of de-allocating locations of a plurality of memories in FIG. 2.

FIG. 4 illustrates another technique of allocating and de-allocating a plurality of memory locations.

FIG. 5 illustrates a disable state and a de-allocate function.

FIG. 6 illustrates a technique for the de-allocate function of FIG. 4 and FIG. 5.

FIG. 7 illustrates a technique of initializing and de-initializing different parts of hardware of FIG. 1A.

FIG. 8 illustrates a technique of allocating and de-allocating memory locations for different parts of software of FIG. 1A.

DETAILED DESCRIPTION

FIG. 1A illustrates a system **151** with a central processing unit (CPU) and/or controller **150**, a bus **152**, a peripheral device **154**, a memory system **156**, software **160**, and a network interface **162** coupled to the peripheral device **154**. The bus **152** may be a peripheral component interconnect (PCI) bus. The system **151** may include other components.

Hardware **158** is shown in FIG. 1A inside the peripheral device **154** but there may be other hardware components apart from the peripheral device **154**. The hardware **158** may include a physical (PHY) layer chip or communications hardware **164**, a media access controller (MAC) **166**, an application specific integrated circuit (ASIC) **168**, and a PCI bus controller **170**.

The peripheral device **154** may be a network interface device, such as a network adapter or network interface card (NIC), a scanner, a disk drive or any other device that performs a function that is peripheral or external to the CPU **150**.

The memory system **156** may comprise a plurality of memory types, as described below with reference to FIG. 2.

The CPU/controller **150** is operable to execute a device driver software, which provides instructions on how to control or interface with the peripheral device **154** in the system **151**.

FIG. 1B illustrates a typical technique of allocating/loading multiple portions or instances of a device driver into multiple locations/sections of multiple types of memory in the memory system **156** of FIGS. 1A and 2 and de-allocating ("freeing") the memory locations.

For example, a startup phase of a driver initialization may need an operating system to allocate different types of memory for different portions of a device driver to work. A Microsoft Windows operating system may (a) allocate special memory for the peripheral device **154** (e.g., an adapter) in FIG. 1A, (b) allocate memory for several messages, (c) allocate memory for DMA descriptors etc., (d) allocate memory for statistic counters, and (e) allocate memory for message queuing. These driver portions may be stored in different locations of memory, but not all of them are stored in different types of memory. If the driver portions are not successfully allocated to all desired or intended memory locations/sections, the system **151** has to free all the allocated memory locations and leave a driver entry with an error code.

FIG. 2 illustrates a device driver **210**, the CPU/controller **150** and the memory system **156** of FIG. 1A. The memory system **156** includes a plurality of memory types, such as type A memory **200**, type B memory **202**, and type C memory **204**. Only three types of memory are shown in FIGS. 1 and 2, but there may be any number of memory types. For example, the memory types may include volatile and non-volatile memory, electrically-erasable programmable read-only memory (EEPROM), static random access memory (SRAM), dynamic RAM (DRAM), flash memory, memory for mapping direct memory accesses (DMAs), memory for registers (e.g., PCI configuration space registers), etc.

The operation of FIG. 1B begins with an Enable state **100**. The controller **150** or software/firmware executed by the controller **150** in FIG. 2 attempts to allocate a first portion or instance of the device driver **210** to a first location or section of the type A memory **200** at **102**. Block **104** determines whether the attempted allocation **102** has been successful. If the attempted allocation **102** is not successful, e.g., there is no available memory in type A memory **200**, an Error state **120** is entered.

If the attempted allocation **102** is successful, an attempt may be made to allocate a portion of the device driver **210** to a first location of the type B memory **202** at **106**. Block **108** determines whether the attempted allocation **106** was successful. If the attempted allocation **106** is not successful, block **122** may de-allocate the allocated first location of the type A memory **200**. The Error state **120** is entered.

If the attempted allocation **106** is successful, block **110** may attempt to allocate a portion of the device driver **210** to a second location of the type B memory **202**. Block **112** determines whether the attempted allocation **110** was successful. If the attempted allocation **110** is not successful, block **126** may de-allocate the allocated first location of the type B memory **202**, and block **124** may de-allocate the allocated first location of the type A memory **200**. The Error state **120** is entered.

If the attempted allocation **110** is successful, block **114** may attempt to allocate a portion of the device driver **210** to a first location of the type C memory **204**. Block **116** determines whether the attempted allocation **114** was successful. If the attempted allocation **114** is not successful, block **132** may de-allocate the allocated second location of the type B memory **202**, block **130** de-allocates the allocated first location of the type B memory **202**, and block **128** de-allocates the allocated first location of the type A memory **200**. The Error state **120** is entered.

If the attempted allocation **114** is successful, a Continue state **118** is entered.

Generally, if a particular allocation attempt (e.g., **110**) is not successful, the technique de-allocates ("frees up") all

previously successful allocations (e.g., **106**, **102**) of portions of the device driver in multiple locations of different memory types.

De-allocating multiple locations of multiple memory types A, B, C **200–204** in blocks **122–132** may be challenging for conventional memory management techniques. Code for de-allocation functions **122–132** should be written carefully and without errors or else memory leaks may occur. There may be no concerted effort to keep track of (a) the allocated memory location of each driver portion and (b) the order of allocations to multiple types of memory. As a result, when a system closes or shuts down and memory is de-allocated, such de-allocation may not necessarily be complete. Incomplete de-allocation may cause memory leakage, system crashes and other undesired effects.

FIG. 3 illustrates a technique of de-allocating locations of a plurality of memories **200–204** in FIG. 2. The technique of FIG. 3 starts at a Disable state **300**, e.g., when a device driver is disabled or the system **151** is shut down. The technique of FIG. 3 de-allocates a first location of type C memory **204** at **302**, a second location of type B memory **202** at **304**, a first location of type B memory **202** at **306**, and a first location of type A memory **200** at **308**.

Storing De-Allocation Information in a Stack

FIG. 4 illustrates another technique of allocating and de-allocating a plurality of memory locations. The technique may be implemented by software (e.g., an operating system) or firmware executed by hardware, such as the CPU/controller **150** in FIGS. 1A and 2. The technique of FIG. 4 uses a memory stack **400** to address the problem described above with conventional memory management techniques. The “stack” **400** may be a data structure where entries inserted first are the last ones removed, which may be referred to as FILO (first-in-last-out) or LIFO (last-in-first-out). Alternatively, the stack **400** may be arranged as a first-in-first-out (FIFO) structure. A standard stack enables software (or firmware) to track what the software was doing when the software branched or jumped to a procedure.

In general, after a portion of the device driver **210** is successfully allocated/loaded into a location of a memory **200**, **202** or **204**, a “de-allocate information” block is written/pushed into the memory stack **400**. Each “de-allocate information” block **428–432** in FIG. 4 may include (a) a first pointer or start address of a specific memory location allocated with a portion of the device driver, and (b) a second pointer to a specific de-allocate function or “free memory function” in a software layer above the device driver in an operating system, e.g., NDIS in Microsoft Windows, in program memory. This layer above the device driver may include a plurality of different de-allocate functions, where each de-allocate function corresponds to a particular type of memory **200–204**. For example, this layer may include first, second and third de-allocate functions for the type A, type B and type C memory types **200**, **202**, **204**, respectively. Each “de-allocate information” block **428–432** may include other “de-allocate information,” such as (c) a size of the allocated memory section, (d) a specific level of memory to which the technique should de-allocate, etc.

The operation of FIG. 4 starts in an Enable state **402**, e.g., when an operating system is activated and intends to initiate a device driver **210**. Block **404** attempts to allocate a first portion of the device driver **210** (FIG. 2) to a first location of the type A memory **200**. Block **406** determines whether the attempted allocation **404** was successful. If the attempted allocation **404** is not successful, block **426** may de-allocate any allocated memory locations (there are none at this point) and proceed to an Error state **424**.

If the attempted allocation **404** is successful, block **408** pushes de-allocate information **428** (e.g., (a) a pointer indicating the memory location of the successful allocation **404** and (b) a pointer to a type A memory de-allocate function in the operating system) to the stack **400**. Block **410** may attempt to allocate another portion of the device driver **210** to a first location in the type B memory **202**. Block **412** determines whether the attempted allocation **410** is successful.

If the attempted allocation **410** is not successful, block **426** may use the de-allocate information **428** in the stack **400** to de-allocate the previously-allocated first location in type A memory **200**. The technique proceeds to the Error state **424**.

If the attempted allocation **410** is successful, block **414** pushes de-allocate information **430** (e.g., (a) a pointer indicating the memory location of the successful allocation **410** and (b) a pointer to a type B memory de-allocate function in the operating system) to the stack **400**. Block **416** may attempt to allocate a portion of the device driver **210** to a second location of the type B memory **202**. Block **418** determines whether the attempted allocation **416** is successful.

If the attempted allocation **416** is not successful, block **426** may use the de-allocate information **430** and **428** in the stack **400** to de-allocate the previously-allocated first location of type B memory **202** and first location of type A memory **200**. The technique proceeds to the Error state **424**.

If the attempted allocation **416** is successful, block **420** pushes de-allocate information **432** (e.g., (a) a pointer indicating the memory location of the successful allocation **416** and (b) a pointer to the type B memory de-allocate function in the operating system) to the stack **400**.

FIG. 5 illustrates a disable driver state **500**, e.g., when the system **151** is shut down, and a de-allocate function **502**, which is the same as the de-allocate function **426** in FIG. 4. To de-allocate a portion of the device driver from memory, the operating system reads a memory location from the stack **400** and calls a de-allocate function (from a layer above the device driver). To de-allocate a plurality of device driver portions, the last portion of the device driver that was successfully allocated to a memory location may be de-allocated first, and the first portion of the device driver that was successfully allocated to a memory location may be de-allocated last. The technique of FIG. 4 may reduce or avoid memory leaks by de-allocating the driver in a reverse order to the order that the driver portions were loaded.

FIG. 6 illustrates a technique for the de-allocate functions **426**, **502** of FIGS. 4 and 5. The technique of FIG. 6 starts at a de-allocate state **600**. Block **602** retrieves or Gets a next de-allocate information block, e.g., information block **432**. Block **604** frees/de-allocates the location of a memory specified by the de-allocate information block, e.g., information block **432**, retrieved from the stack **400**. Block **606** pops (rewinds) the stack **400**. Block **608** determines if the stack **400** is empty. If the stack **400** is not empty, block **602** Gets a next de-allocate information, de-allocate information block **430**. If the stack **400** is empty, the technique Ends at **610**.

Flexibility to Track Additional Allocations

The CPU/controller **150** of FIG. 1A (e.g., using a Microsoft Windows operating system), may modify the sequence of FIG. 4 to add more allocation attempts to new memory locations in additional memory types. The technique and stack **400** of FIG. 4 is flexible to allow the CPU/controller **150** to dynamically allocate driver portions to additional memory locations. The CPU/controller **150**

will automatically push de-allocate information of additional memory allocations to the stack **400** in the order of the allocations. The stack **400** will advantageously track all additional memory allocations and ensure that all allocated memory locations will be de-allocated or freed in a desired order. The technique and stack **400** may reduce or avoid memory leaks, for example, when a system is closed. The stack **400** allows a de-allocate process to be more efficient, as shown by the single de-allocate function **426** in FIG. **4** versus the multiple de-allocate functions **122–132** (e.g., lines of code) in FIG. **1B**.

In contrast, if additional memory allocations are added to the technique of FIG. **1B**, lines of code for de-allocation functions (e.g., such as functions **122–132**) have to be written carefully and without errors or else memory leaks may occur. Memory leaks or other problems caused by improper de-allocation may be hard to detect.

In a Microsoft Windows operating system test, when there are no more memory locations or memory types to allocate the device driver portions, a system may remove/unload a driver from the system by “cleaning up” previously allocated memories **200**, **202**, **204**. The clean-up may occur at any one of a number of different times. Clean-up may automatically occur, e.g., when a system prepares to shut down or restart or after initialization. A user may access the control panel from Microsoft Windows and disable or uninstall a device. This will unload the driver, and the driver has to clean up its memory. Clean-up may also be manually called, e.g., to clean up memory (as an alternative to restarting). The system **151** calls the de-allocate information blocks **428**, **430**, **432** in the stack **400**. The system may use the stack **400** and avoid memory leaks associated with conventional memory management techniques.

Initialize And De-Initialize Hardware

A device driver or other software may initialize and de-initialize different parts of hardware **158** (FIG. **1A**) in a peripheral device **154**. For example, a driver may initialize a plurality of hardware parts of a Gigabit Ethernet network interface device, such as (a) initializing a physical (PHY) layer chip or communications hardware **164**, (b) initializing a media access controller (MAC) **166**, (c) initializing an application specific integrated circuit (ASIC) **168**, and (d) initializing a peripheral component interconnect (PCI) bus controller **170**. The hardware parts may be any component that performs a peripheral or external function apart from the CPU **150**.

The stack **400** in FIG. **4** and techniques described above with reference to FIGS. **4–6** may be modified to initialize and de-initialize different parts of hardware **158**. The order of hardware de-initialization may be more important than memory de-allocation because hardware parts (FIG. **1A**) may depend on each other.

FIG. **7** illustrates a technique of initializing and de-initializing different parts of hardware **158** of FIG. **1A**. The technique uses a stack **700** similar to stack **400** in FIG. **4** to store de-initialization information for de-initializing different parts of hardware **158**. Each block **718**, **720** of de-initialize information may include a first pointer, such as a hardware ID number or address, and a second pointer to a de-initialize command or function, even when the function is on the same layer as the device driver. This is because every part of hardware may need a specific de-initialize function. The de-initialize function may be in the device driver or the same layer as the device driver and may not need to be stored in the stack **700**. The technique of FIG. **7** may operate in substantially the same manner as the technique of FIG. **4**. If an attempted initialization **708** is not successful at **710**,

previously-initialized hardware are de-initialized at **716** using the stack **700** to “clean up” the hardware.

Allocate And De-Allocate Memory for Software Other Than Device Drivers

An operating system of the CPU **150** in FIG. **1A** may allocate and de-allocate portions of memory for different parts of a software application **160** of FIG. **1A**, e.g., a user application, which is not a device driver. For example, an operating system may allocate (a) memory for a communications software part, (b) memory for a database, (c) memory for a statistics software part, and (d) memory for a calculations software part. The allocated memory locations/sections may all be in one type of memory, e.g., virtual memory. The stack **400** and techniques described above with reference to FIGS. **4–6** may be modified to allocate and de-allocate memory for different parts of a software application.

FIG. **8** illustrates a technique of allocating and de-allocating memory locations for different parts of a software application **160** of FIG. **1A**. The technique uses a stack **800** similar to stack **400** in FIG. **4** to store de-allocate information for de-allocating different parts of software **160**. Each block **818**, **820** of de-allocate information may include (a) a first pointer or a logical memory address, and (b) a second pointer to a de-allocate function in a layer of the operating system. The stack **400** does not have to store the second pointers to de-allocate functions when only one type of memory is allocated because the operating system will use a common de-allocate function. The technique of FIG. **8** may operate in substantially the same manner as the technique of FIG. **4**. If an attempted allocation **808** is not successful at **810**, previously-allocated memory portions are de-allocated at **816** using the stack **800** to “clean up” the memory storing the software parts.

As an example, the system **151** may use a RAM memory (e.g., a memory in the memory system **156**) to buffer packets to be transmitted to or received from the bus **152** or network interface **162**. The operating system and/or driver run by the CPU **150** in the system **151** may use a first stack to store de-allocate information for memory locations in the RAM memory allocated to “free” buffers, which are available to store packets. The system **151** may use a second stack to store de-allocate information for memory locations in the RAM memory allocated to “used” buffers, which currently store packets.

Each de-allocate information block in the first stack or second stack may include a pointer indicating the memory location of a “free” or “used” buffer. The stack may not need to store pointers to a memory de-allocate function because only one type of memory is used. The operating system may use one de-allocate function in a layer (e.g., NDIS) above a driver. Each de-allocate information block may further include (b) a length of the “free” or “used” buffer, (c) a counter of how often the buffer has been used, (d) date and time when buffer was allocated.

The system **151** may use the first and second stacks to manage the RAM memory and determine when to allocate more memory locations in the RAM memory for “free” buffers. This may be called “load balancing.” When the system **151** has a heavy load, i.e., a large number of packets are to be transmitted or received, the system **151** may dynamically allocate more “free” buffers in the RAM memory to store packets. For example, when the number of de-allocate information blocks in the “free” stack drops below a pre-determined threshold number, e.g., 10, then the system **151** may allocate more memory locations for “free” buffers, and more entries are added to the first stack possibly

11

until a predetermined number is reached. The first stack (tracking “free” buffers) may be a FIFO or a FILO. The second stack (tracking “used” buffers) should be a FIFO.

As the system 151 sends packets from the “used” buffers of RAM memory across the bus 152 or network interface 162 or the system 151 processes the packets, the load decreases (number of “used” buffers decreases, and number of “free” buffers increases). The system 151 may de-allocate some of the “free” buffers in RAM memory using the de-allocate information in the first stack so the RAM memory can be used for other applications.

Another example may include two stacks with de-allocate information for “free” buffers. One stack has de-allocate information for large “free” buffers, and another stack has de-allocate information for small “free” buffers.

As mentioned above, the entries in each stack 400, 700, 800 (for driver memory de-allocation, for software de-allocation, for hardware de-initialization, for free buffer de-allocation, for used buffer de-allocation) may be modified to suit a user’s preferences. The user of a stack can add any number of parameters to the entries in a stack. The user can also specify the type of parameters. All parameters belong to one stack entry. For example, a memory stack may include:

- Parameter 1: Pointer to memory area.
- Type: Memory Pointer
- Parameter 2: Pointer to de-allocate function
- Type: Function Pointer
- Parameter 3: Time of allocation
- Type: Time format
- Parameter 4: Date of allocation
- Type: Date format
- Parameter 5: Software level
- Type: integer

A number of embodiments have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the application. For example, more than one stack 400 may be implemented and used. Any of the stacks described above may be a FIFO or FILO. In some situations, it is more practical to use a FIFO. In other situations, it is more practical to use a FILO. Each stack may store de-allocate information for one or more types of memories. Accordingly, other embodiments are within the scope of the following claims.

What is claimed is:

1. A method comprising:
 - first allocating a first portion of a device driver to a first location of a first memory;
 - if said first allocating is successful, storing first de-allocate information of the first location of the first memory to a stack;
 - second allocating a second portion of the device driver to a first location of a second memory different than the first memory;
 - if said second allocating is successful, storing second de-allocate information of the first location of the second memory to the stack; and
 - if said second allocating is not successful, de-allocating the first location of the first memory using the first de-allocate information in the stack.
2. The method of claim 1, wherein the first de-allocate information comprises:
 - a first pointer to the first location of the first memory; and
 - a second pointer to a first de-allocate function, which includes instructions for de-allocating a location of the first memory.

12

3. The method of claim 2, wherein the second pointer points to a de-allocate function in a layer of the operating system, the layer being above the device driver.

4. The method of claim 1, wherein the first de-allocate information comprises:

- a pointer to the first location of the first memory; and
- information indicative of a length of allocated memory.

5. The method of claim 1, further comprising:

- third allocating a third portion of the device driver to a second location of the second memory;

- if the third allocating is successful, storing third de-allocate information in the stack, the third de-allocate information block comprising (a) a pointer to the second memory location in the second memory and (b) a pointer to a second de-allocate function, which includes instructions for de-allocating a location of the second memory; and

- if said third allocating is not successful, de-allocating the first location of the second memory and de-allocating the first location of the first memory using first and second de-allocate information in the stack.

6. The method of claim 1, wherein the first and second portions of the device driver comprise separate instances of the device driver.

7. A method comprising:

- allocating locations in a plurality of memory types to store portions of a device driver;
- storing de-allocate information for each successfully-allocated memory location in a stack; and

- if an allocation is not successful, de-allocating a previously-successful allocated memory location by using de-allocate information in the stack.

8. The method of claim 7, wherein if an allocation is not successful, de-allocating all previously-successful allocated memory locations by using de-allocate information in the stack.

9. A method of de-allocating a plurality of memory locations, the method comprising:

- retrieving a first de-allocate information block from a stack;

- de-allocating a location in a first memory specified by the first de-allocate information block;

- retrieving a second de-allocate information block from the stack; and

- de-allocating a location in a second memory specified by the second de-allocate information block.

10. The method of claim 9, further comprising:

- retrieving a third de-allocate information block from the stack; and

- de-allocating a second location in the second memory specified by the third de-allocate information block.

11. A method comprising:

- initializing a plurality of hardware parts;

- storing de-initialize information for each successfully-initialized hardware part in a stack; and

- if an initialization is not successful, de-initializing a previously-successful initialized hardware part by using the de-initialize information in the stack.

12. The method of claim 11, wherein the hardware parts are within a peripheral device.

13. The method of claim 11, wherein the hardware parts are selected from a group consisting of a physical (PHY) layer chip, a media access controller (MAC), an application specific integrated circuit (ASIC), and a peripheral component interconnect (PCI) bus controller.

14. The method of claim 11, wherein the stack is a first-in-last-out structure.

13

15. The method of claim 11, wherein the de-initialize information comprises:

a first de-initialize information block comprising a first pointer to a first hardware part and a second pointer to a de-initialize function; and

a second de-initialize information block comprising a third pointer to a second hardware part and a fourth pointer to a de-initialize function.

16. A method comprising:

allocating a plurality of locations in a memory for a plurality of software parts;

storing de-allocate information for each successfully-allocated memory location for a software part in a stack; and

if an allocation is not successful, de-allocating a previously-successful allocated memory location for a software part by using de-allocate information in the stack.

17. The method of claim 16, wherein the plurality of software parts are selected from a group consisting of a communications software part, a database, a statistics software part, and a calculations software part.

18. The method of claim 16, wherein the de-allocate information comprises:

a first de-initialize allocate information block comprising a pointer to a first location in the memory allocated for a first software part; and

a second de-initialize allocate information block comprising a pointer to a second location in the memory allocated for a second software part.

19. A method comprising:

allocating a location in a memory for a free buffer; storing first de-allocate information for the allocated memory location of the free buffer in a first stack;

storing data in the free buffer and using the first de-allocate information to de-allocate the memory location of the free buffer; and

storing second de-allocate information for the memory location of a used buffer in a second stack.

20. The method of claim 19, wherein the first de-allocate information comprises a pointer to the memory location of the free buffer.

21. The method of claim 20, wherein the first de-allocate information further comprises a counter of how often the memory location has been used.

22. The method of claim 20, wherein the first de-allocate information further comprises a date and time when the memory location was allocated.

23. The method of claim 19, further comprising using the second de-allocate information to de-allocate the memory location of the used buffer; and storing first de-allocate information for the allocated memory location of the free buffer in the first stack again.

24. The method of claim 19, further comprising adding at least one de-allocate information to the first stack when a number of free buffers falls below a pre-determined threshold number.

25. A computer program encoded in a computer-readable medium, which when executed by a computer, performs steps of:

first allocating a first portion of a device driver to a first location of a first memory;

if said first allocating is successful, storing first de-allocate information of the first location of the first memory to a stack;

second allocating a second portion of the device driver to a first location of a second memory different than the first memory;

14

if said second allocating is successful, storing second de-allocate information of the first location of the second memory to the stack; and

if said second allocating is not successful, de-allocating the first location of the first memory using the first de-allocate information in the stack.

26. The computer program of claim 25, wherein the first de-allocate information comprises:

a first pointer to the first location of the first memory; and

a second pointer to a first de-allocate function, which includes instructions for de-allocating a location of the first memory.

27. The computer program of claim 26, wherein the second pointer points to a de-allocate function in a layer of the operating system, the layer being above the device driver.

28. The computer program of claim 25, wherein the first de-allocate information comprises:

a pointer to the first location of the first memory; and

information indicative of a length of allocated memory.

29. The computer program of claim 25, further comprising steps of:

third allocating a third portion of the device driver to a second location of the second memory;

if the third allocating is successful, storing third de-allocate information in the stack, the third de-allocate information block comprising (a) a pointer to the second memory location in the second memory and (b) a pointer to a second de-allocate function, which includes instructions for de-allocating a location of the second memory; and

if said third allocating is not successful, de-allocating the first location of the second memory and de-allocating the first location of the first memory using first and second de-allocate information in the stack.

30. The computer program of claim 25, wherein the first and second portions of the device driver comprise separate instances of the device driver.

31. A computer program encoded in a computer-readable medium, which when executed by a computer, performs steps of:

allocating locations in a plurality of memory types to store portions of a device driver;

storing de-allocate information for each successfully-allocated memory location in a stack; and

if an allocation is not successful, de-allocating a previously-successful allocated memory location by using de-allocate information in the stack.

32. The computer program of claim 31, wherein if an allocation is not successful, de-allocating all previously-successful allocated memory locations by using de-allocate information in the stack.

33. A computer program encoded in a computer-readable medium, which when executed by a computer, performs steps of:

retrieving a first de-allocate information block from a stack;

de-allocating a location in a first memory specified by the first de-allocate information block;

retrieving a second de-allocate information block from the stack; and

de-allocating a location in a second memory specified by the second de-allocate information block.

34. The computer program of claim 33, further comprising:

retrieving a third de-allocate information block from the stack; and

15

de-allocating a second location in the second memory specified by the third de-allocate information block.

35. A computer program encoded in a computer-readable medium, which when executed by a computer, performs steps of:

initializing a plurality of hardware parts;
storing de-initialize information for each successfully-initialized hardware part in a stack; and
if an initialization is not successful, de-initializing a previously-successful initialized hardware part by using the de-initialize information in the stack.

36. The computer program of claim 35, wherein the hardware parts are within a peripheral device.

37. The computer program of claim 35, wherein the hardware parts are selected from a group consisting of a physical (PHY) layer chip, a media access controller (MAC), an application specific integrated circuit (ASIC), and a peripheral component interconnect (PCI) bus controller.

38. The computer program of claim 35, wherein the stack is a first-in-last-out structure.

39. The computer program of claim 35, wherein the de-initialize information comprises:

a first de-initialize information block comprising a first pointer to a first hardware part and a second pointer to a de-initialize function; and
a second de-initialize information block comprising a third pointer to a second hardware part and a fourth pointer to a de-initialize function.

40. A computer program encoded in a computer-readable medium, which when executed by a computer, performs steps of:

allocating a plurality of locations in a memory for a plurality of software parts;
storing de-allocate information for each successfully-allocated memory location for a software part in a stack; and
if an allocation is not successful, de-allocation a previously-successful allocated memory location for a software part by using de-allocate information in the stack.

41. The computer program of claim 40, wherein the plurality of software parts are selected from a group consisting of a communications software part, a database, a statistics software part, and a calculations software part.

42. The computer program of claim 40, wherein the de-allocate information comprises:

a first de-initialize allocate information block comprising a pointer to a first location in the memory allocated for a first software part; and
a second de-initialize allocate information block comprising a pointer to a second location in the memory allocated for a second software part.

43. A computer program encoded in a computer-readable medium, which when executed by a computer, performs steps of:

allocating a location in a memory for a free buffer;
storing first de-allocate information for the allocated memory location of the free buffer in a first stack;
storing data in the free buffer and using the first de-allocate information to de-allocate the memory location of the free buffer; and
storing second de-allocate information for the memory location of a used buffer in a second stack.

44. The computer program of claim 43, wherein the first de-allocate information comprises a pointer to the memory location of the free buffer.

16

45. The computer program of claim 43, wherein the first de-allocate information further comprises a counter of how often the memory location has been used.

46. The computer program of claim 43, wherein the first de-allocate information further comprises a date and time when the memory location was allocated.

47. The computer program of claim 43, further comprising using the second de-allocate information to de-allocate the memory location of the used buffer; and

storing first de-allocate information for the allocated memory location of the free buffer in the first stack again.

48. The computer program of claim 43, further comprising adding at least one de-allocate information to the first stack when a number of free buffers falls below a predetermined threshold number.

49. A system comprising:

a first memory;
a second memory;
a stack; and

a controller operable to perform:

first allocating a first portion of a device driver to a first location of the first memory;

if said first allocating is successful, storing first de-allocate information of the first location of the first memory to the stack;

second allocating a second portion of the device driver to a first location of the second memory different than the first memory;

if said second allocating is successful, storing second de-allocate information of the first location of the second memory to the stack; and

if said second allocating is not successful, de-allocating the first location of the first memory using the first de-allocate information in the stack.

50. The system of claim 49, wherein the first de-allocate information comprises (a) a first pointer to the first location in the first memory, and (b) a second pointer to a first de-allocate function, which includes instructions for de-allocating a location of the first memory.

51. The system of claim 50, wherein the second pointer points to a de-allocate function in a layer of the operating system, the layer being above the device driver.

52. The system of claim 49, wherein the first de-allocate information comprises:

a pointer to the first location of the first memory; and
information indicative of a length of allocated memory.

53. The system of claim 49, wherein the controller is further operable to perform:

third allocating a third portion of the device driver to a second location of the second memory;

if the third allocating is successful, storing third de-allocate information in the stack, the third de-allocate information block comprising (a) a pointer to the second memory location in the second memory and (b) a pointer to a second de-allocate function, which includes instructions for de-allocating a location of the second memory; and

if said third allocating is not successful, de-allocating the first location of the second memory and de-allocating the first location of the first memory using first and second de-allocate information in the stack.

54. The system of claim 49, wherein the first and second portions of the device driver comprise separate instances of the device driver.

55. The system of claim 49, wherein the stack is a first-in-first-out structure.

17

56. The system of claim 49, wherein the stack is a first-in-last-out structure.

57. A system comprising:

a stack; and

a controller operable to (a) allocate locations in a plurality of memory types to store portions of a device driver; (b) store de-allocate information for each successfully-allocated memory location in the stack; and (c) if an allocation is not successful, de-allocate a previously-successful allocated memory location by using de-allocate information in the stack.

58. The system of claim 57, wherein if an allocation is not successful, the controller is operable to de-allocate all previously-successful allocated memory locations by using de-allocate information in the stack.

59. A system comprising:

a stack; and

a controller operable to (a) retrieve a first de-allocate information block from the stack; (b) de-allocate a location in a first memory specified by the first de-allocate information block; (c) retrieve a second de-allocate information block from the stack; and (d) de-allocate a location in a second memory specified by the second de-allocate information block.

60. The system of claim 59, wherein the controller is operable to retrieve a third de-allocate information block from the stack; and de-allocate a second location in the second memory specified by the third de-allocate information block.

61. A system comprising:

a first hardware part;

a second hardware part;

a stack; and

a controller operable to (a) initialize the first and second hardware parts, (b) store a first de-initialize information block and a second de-initialize information block in the stack, and (c) if an initialization of the second hardware part is not successful, de-initializing the previously-successful initialized first hardware part by using the first de-initialize information block in the stack.

62. The system of claim 61, wherein the hardware parts are selected from a group consisting of a physical (PHY) layer chip, a media access controller (MAC), an application specific integrated circuit (ASIC), and a peripheral component interconnect (PCI) bus controller.

63. The system of claim 61, wherein the stack is a first-in-last-out structure.

64. The system of claim 61, wherein the first de-initialize information block comprises a first pointer to a first hardware part and a second pointer to a de-initialize function; the second de-initialize information block comprising a third pointer to a second hardware part and a fourth pointer to a de-initialize function.

65. The system of claim 61, wherein the first and second hardware parts are within a peripheral device.

66. The system of claim 61, wherein the first and second hardware parts are within a network interface device.

67. A system comprising:

a memory;

a first software part;

a second software part;

a stack; and

a controller operable to (a) allocate locations in the memory for the first and second software parts, (b) store a first de-allocate information block and a second de-allocate information block in the stack, and (c) if an

18

allocation of the second software part is not successful, de-allocate the previously-successful allocated first software part by using the first de-allocate information block in the stack.

68. The system of claim 67, wherein the plurality of software parts are selected from a group consisting of a communications software part, a database, a statistics software part, and a calculations software part.

69. The system of claim 67, wherein the first de-allocate information block comprises a pointer to a first location in the memory allocated for the first software part; the second de-allocate information block comprising a pointer to a second location in the memory allocated for the second software part.

70. A system comprising:

a memory;

a first stack;

a second stack; and

a controller operable to (a) allocate a location in the memory for a free buffer; (b) store first de-allocate information for the allocated memory location of the free buffer in the first-stack; (c) store data in the free buffer and use the first de-allocate information to de-allocate the memory location of the free buffer; and (d) store second de-allocate information for the memory location of a used buffer in the second stack.

71. The system of claim 70, wherein the first de-allocate information comprises a pointer to the memory location of the free buffer.

72. The system of claim 70, wherein the first de-allocate information further comprises a counter of how often the memory location has been used.

73. The system of claim 70, wherein the first de-allocate information further comprises a date and time when the memory location was allocated.

74. The system of claim 70, wherein the controller is further operable to use the second de-allocate information to de-allocate the memory location of the used buffer; and store first de-allocate information for the allocated memory location of the free buffer in the first stack again.

75. The system of claim 70, wherein the controller is further operable to add at least one de-allocate information to the first stack when a number of free buffers falls below a pre-determined threshold number.

76. A system comprising:

a first memory means;

a second memory means;

a de-allocate information storing means; and

a controlling means operable to perform:

first allocating a first portion of a device driver to a first location of the first memory means;

if said first allocating is successful, storing first de-allocate information of the first location of the first memory means to the de-allocate information storing means;

second allocating a second portion of the device driver to a first location of the second memory means different than the first memory means;

if said second allocating is successful, storing second de-allocate information of the first location of the second memory means to the de-allocate information storing means; and

if said second allocating is not successful, de-allocating the first location of the first memory means using the first de-allocate information in the de-allocate information storing means.

19

77. The system of claim 76, wherein the first de-allocate information comprises (a) a first pointing means to the first location in the first memory means, and (b) a second pointing means to a first de-allocate function, which includes instructions for de-allocating a location of the first memory means.

78. The system of claim 77, wherein the second pointing means points to a de-allocate function in a layer of the operating system, the layer being above the device driver.

79. The system of claim 76, wherein the first de-allocate information comprises: (a) a pointing means to the first location of the first memory means; and (b) information indicative of a length of allocated memory.

80. The system of claim 76, wherein the controlling means is further operable to perform:

third allocating a third portion of the device driver to a second location of the second memory means;

if the third allocating is successful, storing third de-allocate information in the de-allocate information storing means, the third de-allocate information block comprising (a) a pointing means to the second memory location in the second memory means and (b) a pointing means to a second de-allocate function, which includes instructions for de-allocating a location of the second memory means; and

if said third allocating is not successful, de-allocating the first location of the second memory means and de-allocating the first location of the first memory means using first and second de-allocate information in the de-allocate information storing means.

81. The system of claim 76, wherein the first and second portions of the device driver comprise separate instances of the device driver.

82. The system of claim 76, wherein the stacking means is a first-in-first-out structure.

83. The system of claim 76, wherein the stacking means is a first-in-last-out structure.

84. A system comprising:

a stacking means for storing de-allocate information; and a controlling means operable to (a) allocate locations in a plurality of memory means to store portions of a device driver; (b) store de-allocate information for each successfully-allocated memory location in the stacking means; and (c) if an allocation is not successful, de-allocate a previously-successful allocated memory location by using de-allocate information in the stacking means.

85. The system of claim 84, wherein if an allocation is not successful, the controlling means is operable to de-allocate all previously-successful allocated memory locations by using de-allocate information in the stacking means.

86. A system comprising:

a stacking means for storing de-allocate information blocks; and

a controlling means operable to (a) retrieve a first de-allocate information block from the stacking means;

(b) de-allocate a location in a first memory means specified by the first de-allocate information block; (c) retrieve a second de-allocate information block from the stacking means; and (d) de-allocate a location in a second memory means specified by the second de-allocate information block.

87. The system of claim 86, wherein the controlling means is operable to retrieve a third de-allocate information block from the stacking means; and de-allocate a second location in the second memory means specified by the third de-allocate information block.

20

88. A system comprising:

a first hardware means for performing a first peripheral function;

a second hardware means for performing a second peripheral function;

a stacking means for storing de-initialize information; and

a controlling means operable to (a) initialize the first and second hardware means, (b) store a first de-initialize information block and a second de-initialize information block in the stacking means, and (c) if an initialization of the second hardware means is not successful, de-initializing the previously-successful initialized first hardware means by using the first de-initialize information block in the stacking means.

89. The system of claim 88, wherein the first and second hardware means are selected from a group consisting of a physical (PHY) layer chip, a media access controller (MAC), an application specific integrated circuit (ASIC), and a peripheral component interconnect (PCI) bus, controller.

90. The system of claim 88, wherein the stacking means is a first-in-last-out structure.

91. The system of claim 88, wherein the first de-initialize information block comprises a first pointing means to the first hardware means and a second pointing means to a de-initialize function; the second de-initialize information block comprising a third pointing means to the second hardware means and a fourth pointing means to a de-initialize function.

92. The system of claim 88, wherein the first and second hardware means are within a peripheral device.

93. The system of claim 88, wherein the first and second hardware means are within a network interface device.

94. A system comprising:

a memory means;

a first software means for performing a first function;

a second software means for performing a second function;

a stacking means for storing de-allocation information; and

a controlling means operable to (a) allocate locations in the memory for the first and second software means, (b) store a first de-allocate information block and a second de-allocate information block in the stacking means, and (c) if an allocation of the second software means is not successful, de-allocate the previously-successful allocated first software means by using the first de-allocate information block in the stacking means.

95. The system of claim 94, wherein the first and second software means are selected from a group consisting of a communications software part, a database, a statistics software part, and a calculations software part.

96. The system of claim 94, wherein the first de-allocate information block comprises a pointing means to a first location in the memory means allocated for the first software means; the second de-allocate information block comprising (a) a pointing means to a second location in the memory allocated for the second software means.

97. A system comprising:

a memory means;

a first stack for storing de-allocate information;

a second stack for storing de-allocate information; and

a controlling means operable to (a) allocate a location in the memory means for a free buffer; (b) store first de-allocate information for the allocated memory location of the free buffer in the first stacking means; (c) store data in the free buffer and use the first de-allocate

21

information to de-allocate the memory location of the free buffer; and (d) store second de-allocate information for the memory location of a used buffer in the second stacking means.

98. The system of claim **97**, wherein the first de-allocate information comprises a pointing means to the memory means location of the free buffer.

99. The system of claim **97**, wherein the first de-allocate information further comprises a counting means of how often the memory means location has been used.

100. The system of claim **97**, wherein the first de-allocate information further comprises a date and time when the memory means location was allocated.

22

101. The system of claim **97**, wherein the controlling means is further operable to use the second de-allocate information to de-allocate the memory location of the used buffer; and store first de-allocate information for the allocated memory location of the free buffer in the first stacking means again.

102. The system of claim **97**, wherein the controlling means is further operable to add at least one de-allocate information to the first stacking means when a number of free buffers falls below a pre-determined threshold number.

* * * * *