

53

wherein the unassigned resource unit is explicitly indicated with the information of the unassigned resource unit based on the bandwidth field and the at least one subfield, and

wherein the information of the unassigned resource unit includes information of a C26 field indicating whether a user is allocated to a center 26-tone resource unit of 80 MHz upon the bandwidth related to a transmission of the received wireless packet indicated by the bandwidth field being 80 MH or more, not 20 MHz or 40 MHz.

2. The wireless communication terminal of claim 1, wherein the HE-SIG-B field consists of HE-SIG-B content channel 1 and HE-SIG-B content channel 2 in units of 20 MHz respectively, and

wherein the C26 field is carried in both the HE-SIG-B content channel 1 and the HE-SIG-B content channel 2.

3. The wireless communication terminal of claim 2, wherein when the received wireless packet is transmitted in a total bandwidth of 80 MHz, both of a C26 field carried in the HE-SIG-B content channel 1 and a C26 field carried in the HE-SIG-B content channel 2 indicate whether a user is allocated to a center 26-tone resource unit in the total bandwidth of 80 MHz.

4. The wireless communication terminal of claim 3, wherein when the C26 field indicates that a user is allocated to the center 26-tone resource unit, a user field corresponding to the center 26-tone resource unit is carried in a user specific field of the HE-SIG-B content channel 1.

5. The wireless communication terminal of claim 2, wherein when the received wireless packet is transmitted in a total bandwidth of 160 MHz or 80+80 MHz, the total bandwidth includes a first 80 MHz bandwidth and a second 80 MHz bandwidth, a first C26 field carried in the HE-SIG-B content channel 1 indicates whether a user is allocated to a first center 26-tone resource unit in the first 80 MHz bandwidth, and a second C26 field carried in the HE-SIG-B content channel 2 indicates whether a user is allocated to a second center 26-tone resource unit in the second 80 MHz bandwidth.

6. The wireless communication terminal of claim 5, wherein when the first C26 field indicates that a user is allocated to the first center 26-tone resource unit, a user field corresponding to the first center 26-tone resource unit is carried in a user specific field of the HE-SIG-B content channel 1, and

wherein when the second C26 field indicates that a user is allocated to the second center 26-tone resource unit, a user field corresponding to the second center 26-tone resource unit is carried in a user specific field of the HE-SIG-B content channel 2.

7. A wireless communication method of a wireless communication terminal, the method comprising:

receiving a wireless packet including an high efficiency (HE)-signal (SIG)-A and HE-SIG-B;

obtaining bandwidth information indicated via a bandwidth field included in the HE-SIG-A;

obtaining information of an unassigned resource unit via at least one subfield included in the HE-SIG-B,

54

wherein the bandwidth field is related to bandwidth over which the received wireless packet is transmitted, and wherein the bandwidth field of HE-SIG-A is used to obtain the information of the unassigned resource unit; and

decoding a data of the received wireless packet based on the total bandwidth information and the information of the unassigned resource unit,

wherein the unassigned resource unit is explicitly indicated with the information of the unassigned resource unit based on the bandwidth field and the at least one subfield, and

wherein the information of the unassigned resource unit includes information of a C26 field indicating whether a user is allocated to a center 26-tone resource unit of 80 MHz upon the bandwidth related to a transmission of the received wireless packet indicated by the bandwidth field being 80 MH or more, not 20 MHz or 40 MHz.

8. The wireless communication method of claim 7, wherein the HE-SIG-B field consists of HE-SIG-B content channel 1 and HE-SIG-B content channel 2 in units of 20 MHz respectively, and

wherein the C26 field is carried in both the HE-SIG-B content channel 1 and the HE-SIG-B content channel 2.

9. The wireless communication method of claim 8, wherein when the received wireless packet is transmitted in a total bandwidth of 80 MHz, both of a C26 field carried in the HE-SIG-B content channel 1 and a C26 field carried in the HE-SIG-B content channel 2 indicate whether a user is allocated to a center 26-tone resource unit in the total bandwidth of 80 MHz.

10. The wireless communication method of claim 9, wherein when the C26 field indicates that a user is allocated to the center 26-tone resource unit, a user field corresponding to the center 26-tone resource unit is carried in a user specific field of the HE-SIG-B content channel 1.

11. The wireless communication method of claim 8, wherein when the received wireless packet is transmitted in a total bandwidth of 160 MHz or 80+80 MHz, the total bandwidth includes a first 80 MHz bandwidth and a second 80 MHz bandwidth, a first C26 field carried in the HE-SIG-B content channel 1 indicates whether a user is allocated to a first center 26-tone resource unit in the first 80 MHz bandwidth, and a second C26 field carried in the HE-SIG-B content channel 2 indicates whether a user is allocated to a second center 26-tone resource unit in the second 80 MHz bandwidth.

12. The wireless communication method of claim 11, wherein when the first C26 field indicates that a user is allocated to the first center 26-tone resource unit, a user field corresponding to the first center 26-tone resource unit is carried in a user specific field of the HE-SIG-B content channel 1, and

wherein when the second C26 field indicates that a user is allocated to the second center 26-tone resource unit, a user field corresponding to the second center 26-tone resource unit is carried in a user specific field of the HE-SIG-B content channel 2.

* * * * *