



(19) **United States**
(12) **Patent Application Publication**
Salafia et al.

(10) **Pub. No.: US 2010/0261492 A1**
(43) **Pub. Date: Oct. 14, 2010**

(54) **INTEGRATED CALL HANDLER AND EMAIL SYSTEMS AND METHODS**

filed on Jan. 9, 2007, which is a continuation-in-part of application No. 10/913,880, filed on Aug. 6, 2004, now Pat. No. 7,515,693.

(75) Inventors: **Christopher Michael Salafia**, Killingworth, CT (US); **Jeremy Edward Turk**, Guilford, CT (US); **Philip M. Salafia**, Old Lyme, CT (US); **Francois Gerard Koutchouk**, Castro Valley, CA (US)

Publication Classification

(51) **Int. Cl.**
H04W 4/12 (2009.01)
(52) **U.S. Cl.** **455/466**

Correspondence Address:
MAIER & MAIER, PLLC
1000 DUKE STREET
ALEXANDRIA, VA 22314 (US)

(57) **ABSTRACT**

Apparatuses, systems and methods are presented for handling calls. In one embodiment, an emergency call handling system capable of receiving visual information from callers and correlating the visual information to particular incidents is disclosed. To obtain visual information, a call handler may generate and send an electronic mail message to the caller. The caller may reply to the electronic mail message and attach an image captured with, for example, a camera phone. The visual information may then be correlated to the call between the caller and call handler. In addition, unsolicited visual information received by the emergency call handling system may be prioritized, triaged and delivered to the call handler. The visual information may be used to assess an emergency situation. The visual information may be forwarded to emergency service providers.


(73) Assignee: **POWERPHONE, INC.**, Madison, CT (US)

(21) Appl. No.: **12/824,967**

(22) Filed: **Jun. 28, 2010**

Related U.S. Application Data

(63) Continuation-in-part of application No. 11/835,208, filed on Aug. 7, 2007, now Pat. No. 7,764,769, which is a continuation-in-part of application No. 11/621,473,






FIG.1




FIG. 2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG. 8




FIG.9




FIG.10




FIG. 11




Fig. 12




Fig. 13

INTEGRATED CALL HANDLER AND EMAIL SYSTEMS AND METHODS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This patent application is a continuation-in-part of pending U.S. patent application Ser. No. 11/835,208, filed Aug. 7, 2007, which was a continuation-in-part of U.S. patent application Ser. No. 11/621,473, filed Jan. 9, 2007, which is a continuation-in-part of U.S. patent application Ser. No. 10/913,880, filed Aug. 6, 2004, which claims priority to U.S. Provisional Patent Application No. 60/821,915, filed Aug. 9, 2006, the disclosures of which are incorporated by reference in their entireties herein.

BACKGROUND

[0002] Call handling of either emergency or non-emergency related situations is a process of interacting with a caller to exchange information. The caller may have contacted a particular agency or service provider to gain assistance. A call handling system is the system used by a call handler to communicate with the caller. For example, a caller may dial 911 seeking emergency assistance. Another example is where a caller dials an information service to obtain driving directions or addresses. In either situation, the call may be handled by a call handler using a call handling system.

[0003] A particular caller may contact a particular agency or service provider to forward information. For example, a caller may dial 911 to report an emergency situation that the caller has witnessed, such as a crime, an automobile accident or a building fire. An example of a non-emergency situation would be where the caller calls to report local driving or weather conditions or a crime tip line. Whether the caller is calling to gain assistance or report information, a call handler, who may be specially trained in quickly and efficiently exchanging information with a caller, may handle the call.

[0004] A critical application of call handling is in the provision of emergency services. In an emergency situation, the call handler may need to quickly extract information from the caller in order to assist the caller. Such is typically the case in emergency medical situations where the call handler must ascertain the type and extent of injury in order to give relevant instructions. Generally, in an emergency situation, a caller will dial 911 and be connected to a local Public Safety Answering Point (PSAP). The PSAP is generally staffed with a group of specially trained call handlers. Typically, the call handlers will respond to callers according to protocols, often dispatching emergency service providers. Call handling is often employed with Computer Aided Dispatch (CAD) systems that dispatch response units, such as police, fire and/or medical units, based on received information. For example, call handling of prior art CAD systems typically involves call handlers who receive calls describing certain events. The call handlers subsequently convey this information to a dispatch unit by manually inputting information into the CAD system, which then recommends the appropriate dispatch unit(s) for response to the event.

[0005] Typically, a call handler working in a PSAP will receive textual information, displayed on a computer terminal, regarding the probable location of a caller. If the caller is calling from a landline, systems at the PSAP may access an automatic location information (ALI) database to determine

the location of the caller. Accordingly, errors in the ALI database may result in incorrect determinations of caller location. Therefore, the call handler may need to verify the location of the caller. If the caller is calling from a mobile wireless device (e.g., cell phone), location information, if available at all, may not be determinable in the same manner as for landlines. Location information of a caller using a mobile wireless device presented to a call handler may be derived from triangulating signals transmitted by the cell phone. The accuracy of such a location may be dependent on the number of cell towers and signal strength. Global Positioning System (GPS) location data may also be available if the caller is using a cell phone with GPS capabilities. However, GPS systems may be unreliable, for example, if the caller is indoors. Accordingly, in the case of mobile wireless devices, the call handler may need to provide and/or verify the location of the caller.

[0006] Generally, the location of the caller is only one part of the information that is exchanged between the caller and the call handler in an emergency situation. For example, at the scene of a major traffic accident, the caller may need to communicate the number of people injured, the number of vehicles involved, location and condition of the vehicles, current conditions (e.g., fog, ice, etc.), and many other aspects of the situation. In current emergency call handling systems, all of this information is communicated verbally between the caller and the call handler and the call handler may forward this information, either verbally or textually, to at least one emergency services provider.

SUMMARY

[0007] One exemplary embodiment can describe an information processing system. The information processing system can include a communication module operable to send first data with a unique identifier to a communication device configured to receive the first data and reply with second data, the second data containing the unique identifier of the first data; and a data receiving module configured to receive incoming data, filter incoming data and weight incoming data.

[0008] Another exemplary embodiment describes a method of routing information. The method of routing information can include steps for calling a call center from a communication device; sending a first MMS from the call center to the communication device, the MMS having a unique identifier included therein; replying to the MMS from the call center with the communication device with a second MMS, the second MMS including the unique identifier; filtering the second MMS through a data processing module; and associating the second MMS with the call from the communication device to the call center.

[0009] Yet another exemplary embodiment may include a system for routing data. The system for routing data can have at least one MMS message sent from a communication device to a data processing module; and at least one engine for that determines if the at least one MMS message is a solicited message related to a phone call made to a call center and associates the at least one MMS message with the phone call if it is a solicited message or evaluates other aspects of the at least one MMS message if the at least one MMS message is not solicited.

[0010] Still other exemplary embodiments generally relates to call handling. More specifically, this invention relates to correlating call information to visual information received from the caller. The present inventors have recog-

nized that many aspects of the process of call handling may be significantly enhanced through the incorporation of the transfer of visual and/or textual information. The transfer of visual information may occur between a caller and a call handler. For example, in an emergency situation, a caller may dial 911 to contact a call handler at a PSAP. It may then be beneficial for the caller to transfer visual information regarding the emergency to the call handler. By reviewing the visual information, the call handler may gain a better understanding of the emergency situation. The call handler may forward the information, including the visual information, to at least one emergency services provider.

[0011] The visual information may, for example, include information regarding the exact location of the caller. This may be particularly valuable where the caller is calling from a mobile wireless device, such as a cell phone, and an exact location would otherwise be unavailable or difficult to obtain. The visual information may include images of a victim, a suspect, an accident scene or any other emergency or non-emergency subject that may enhance the effectiveness of the communication between the call handler and caller. The call handler may also send information to the caller, such as, for example, visual instruction on how to handle a particular situation or perform a particular task, images, forms, or Uniform Resource Locators (URLs).

[0012] Whether in an emergency situation or a non-emergency situation, the transfer of visual information between the caller and the call handler may result in faster and more efficient transfer of information. In emergency situations, this may result in faster and more appropriate provision of emergency services. A call handler may also forward the visual information received from the caller to third parties, such as, for example, an emergency services provider. The emergency services provider may use the visual information to determine an appropriate response, for example, in terms of equipment, personnel and procedures to be used in response to the emergency.

[0013] The visual information may serve as a recordation of the events that prompted the caller to contact the call handler. The visual information may be an image of a suspect and may serve as evidence in a criminal investigation. The visual information may be in the form of an image of a vehicle involved in an accident or crime. The visual information may be of a suspected missing person. The visual information may be used as evidence in subsequent civil proceedings. The visual information may be used to help determine a cause of an emergency situation or be used by investigators to analyze a particular chain of events.

[0014] Accordingly, systems and methods are presented herein to enable the efficient transfer of visual information between a caller and a call handler. These systems and methods provide the aforementioned benefits. It will be appreciated that other benefits of the ability to quickly and efficiently transfer visual information between a caller and call handler will be apparent to those skilled in the art and are intended to be within the scope of the present invention.

[0015] In an aspect of the present invention, an information processing system is provided that includes a network interface, a telephonic interface, a call handler interface, a storage unit, and a processing module. The network interface may be operable to receive and transmit packetized information over a computer network. In one embodiment, the computer network may be the Internet. The packetized information may be

in the form of electronic mail messages consisting of text, visual information in the form of image files, or a combination thereof.

[0016] The telephonic interface may be used for audio communication between at least one call handler and at least one caller over a telephone network. In one embodiment, the telephone network may be the public switched telephone network (PSTN), a cellular network, or a combination thereof. The telephonic interface may be a standard telephone headset or handset. The telephone network may include a PSAP. The audio communication may be an emergency related, non-emergency related, or a combination thereof. In one embodiment, the audio communication between the caller and the call handler may be emergency related. To initiate the audio communication, the caller may dial 911.

[0017] The call handler interface may be operable to generate at least one outgoing message. The call handler interface may be operable to send the outgoing message to the caller. The outgoing message may include a unique identifying component. In one embodiment, the call handler interface may be in the form of a personal computer or computer terminal accessible by the call handler. The outgoing message may be an electronic message, for example, an electronic mail message. The call handler interface may be operable to present to the call handler a plurality of outgoing message templates. The call handler may then select a particular outgoing message template that is appropriate for the circumstances of the call. The selecting of the outgoing message template may be in the form of selecting a particular outgoing message template identified by a menu item or an item in a pull-down menu presented to the operator by a display screen of the call handler interface. The call handler may then use the selected outgoing message template to generate an outgoing message to be sent to the caller. The outgoing message may be sent over the computer network.

[0018] The unique identifying component of the outgoing message may, for example, be located in a message header of the outgoing message. In one embodiment, the unique identifying component may be a string of alphanumeric characters. For example, the unique identifying component may include alphanumeric characters representing the date on which the outgoing message was first generated concatenated with a sequential serial number.

[0019] The storage unit may be configured to store information related to the caller, the particular call between the caller and the call handler, or any combination thereof. In one embodiment, the storage unit may, for example, be a hard drive such as those commonly used to store information in digital form.

[0020] The processing module may be coupled to the storage unit, the call handler interface, and the network interface. The unique identifying component of a particular outgoing message may be stored in the storage unit in relation to information pertaining to the particular call that resulted in the generation of the outgoing message. The processing module may be operable to correlate an incoming message received over the computer network to the information pertaining to the particular call that resulted in the generation of the outgoing message and the subsequent reception of the incoming message. In one embodiment, the processing module may be operable to present to the call handler the incoming message along with information related to the particular call that resulted in the reception of the incoming message.

[0021] In another aspect of the present invention, an emergency call handling system is provided that includes a network interface module, a communication interface, a call handler interface, a storage unit, and a processor module. The network interface may be operable to receive and transmit packetized information over a computer network, such as the Internet. The communication interface may be interconnected with a PSAP. The call handler interface may generate an outgoing message that includes a unique identifying component. The storage unit may store the unique identifying component in relation to a record of a call. The processing module may correlate incoming messages received over the computer network to the record, stored in the storage unit, of a particular call. The call handler interface may display at least part of an incoming message along with a record of the specific call with which the incoming message was correlated.

[0022] In another aspect of the present invention, a call handling system is provided that includes a database, a call handler interface, and an electronic message processing module. The database may be configured to store a plurality of electronic message templates, information regarding a call from a caller, and a unique identifying component for the call. The call handler interface may be operable to enable a call handler to select an electronic message template from the plurality of electronic message templates stored in the database. The call handler interface may be operable to initiate the sending of an electronic message to the caller, where the electronic message contains the unique identifying component for that call. The call handler interface may be operable to display information regarding the call and an image contained in a response to the electronic message sent by the call handler. The electronic message processing module may be operable to correlate the information regarding a particular call to the image contained in a response from the caller to the electronic message received by the caller. In one embodiment, the call may be emergency related.

[0023] In still another aspect, a method of communicating with a caller is provided that includes receiving a call, making a decision, based on the call, to obtain visual information from the caller, assigning a unique identifying component to a first message, including that unique identifying component in the first message, sending the first message, receiving a second message in response to the first message, and correlating the second message to the call. The call may be received over a telephone network, such as the PSTN, and may be emergency related. The decision to obtain visual information may be made as a result of the interaction between a call handler and a caller. The first message may be generated by selecting a message template from a plurality of available message templates. The first and second messages may be electronic mail messages. The unique identifying component assigned to the first message may be located in a header of the first message.

[0024] The first message may be sent to the caller over a computer network, such as the Internet. In one embodiment, the first message may contain an instruction regarding how to reply to the first message. For example, the instruction may direct the caller to reply to the first message by creating a second message and attaching visual information to the second message. This may be accomplished by the caller by, for example, attaching an image captured with a camera phone to a reply to the first image and sending that reply message (i.e., the second message) to a call handler. In one embodiment, the

electronic mail message address of the caller may be determined and inserted into the first message prior to sending. The electronic mail message address of the caller may be determined by concatenating the phone number of the caller with a domain name of the caller. The domain name may be obtained by looking up the domain name in a database for the particular service provider of the caller.

[0025] The second message may contain visual information. The second message may contain the unique identifying component that was inserted into the first message. The visual information contained in the second message may be correlated to the call based on the unique identifying component. In one embodiment, the method of communicating with the caller may include displaying information about the call along with the visual information provided in the second message.

[0026] The method may include forwarding the visual information received in the second message. The visual information may be forwarded to an emergency services provider.

[0027] In a yet another aspect, a method of correlating visual information to a call is provided. The method includes receiving a call from a caller, sending an electronic mail message to the caller where the message includes a unique identifying component, receiving a reply message from the caller where the reply message includes the unique identifying component and visual information, and correlating the reply message to the call at least partially based on the unique identifying component.

[0028] In an additional aspect, an information processing system is provided that includes a message priority module, a triage interface, and an integration module. The message priority module may be operable to assign priority scores to electronic messages received by the information processing system. The triage interface may be operable to display at least a portion of the electronic messages along with corresponding priority scores assigned by the message priority module. The triage interface may be operable to display a single message based on that message's corresponding priority score (e.g., the triage interface may display the electronic message with the highest priority score). The integration module may be operable to present "triaged" electronic messages to a communications system. Such an information processing system may be operable to process and prioritize unsolicited incoming messages.

[0029] In an embodiment, the information processing system may further include a communications module operable to receive electronic messages over a computer network, such as the Internet. Such messages may be packetized for delivery over the computer network. The messages may be in the form of electronic mail messages. The messages may include text, audio, images, video clips, or any combination thereof. The communications module may be operable to selectively forward the received electronic messages to the message priority module. This selective forwarding may be based at least in part on the source of the received electronic messages. The messages may be emergency related. In the latter regard, the information processing system may, for example, be configured to process solicited and unsolicited messages received by a PSAP or other emergency response system.

[0030] In an embodiment, the information processing system may include an information database. The database may include data relating to unique identifying components correlated to communications events. Incoming messages containing such unique identifying components may be for-

warded directly from the message priority module to the integration module. The database may also include data relating to phone numbers correlated to predeterminable sources, phone numbers correlated to communications events, locations of communications events, or any combination thereof.

[0031] The information processing system may be operable to communicate with a database (e.g., an Automatic Number Identification (ANI) database and/or an ALI database) containing location information for cellular phone users. The message priority engine may determine a particular priority score based, at least in part, on a source of that particular message.

[0032] The triage interface may allow an operator, such as a triage interface operator, to process the messages in an order at least partially based on the assigned priority score. In this regard, the triage interface may be operable to order the electronic messages based on the assigned priority scores. This ordered list may allow a triage interface operator to select and forward at least one of the received and triaged messages to the communications system. The communications system may, for example, be an electronic messaging system, a call handling system, or a combination thereof. In embodiments where the communications system includes a call handling system, the call handling system may, for example, be a CAD system, a Records Management System (RMS), or any other system designed to handle communications between a caller and a call handler.

[0033] In an embodiment, the information processing system may include a reporting interface. The reporting interface may be operable to report on the status of various components of the information processing system. For example, the reporting interface may be operable to present statistics pertaining to the performance and status of the communications module, the message priority module, the triage interface, the integration module, or any combination thereof.

[0034] In still another aspect, an emergency call handling system is provided that includes a communications module, a message priority module, a triage interface, a call handler workstation, and an integration module. The communications module may be operable to receive packetized messages over a computer network, such as the Internet. The message priority module may be operable to assign emergency-related priority scores to the received messages. The triage interface may be operable to display at least a portion of the received messages along with corresponding emergency-related priority scores assigned by the message priority module. The call handler workstation may include an audio interface and a computer terminal. The integration module may be operable to present triaged, received messages to the call handler through the call handler workstation.

[0035] In another aspect, a method is provided for processing a message for display at a communications workstation. The method includes receiving a message over a computer network, verifying the message is from an approved source (e.g., a cellular phone), assigning a priority score to the received message, forwarding the received message to the communications workstation based on the assigned priority score, and displaying the forwarded received message at the communications workstation. In an embodiment, the communications workstation may be a call handler workstation.

[0036] In yet another aspect, a method is provided for performing triage on a plurality of received messages. The method includes receiving a plurality of messages over a computer network, assigning an emergency related priority

score to each of the received messages, and ordering the received messages based on the assigned emergency related priority scores. The emergency related priority score may, for example, be based on the source of the message, the origination location of the message, or a combination thereof. In particular, the priority score may reflect messages where the message originated from an emergency responder, a known emergency information provider, a source related to previously received calls, a source related to a call previously placed, a source related to a currently active emergency situation, or a combination thereof.

[0037] In another aspect, a call handling system is provided that includes a message priority module. The message priority module may be operable to assign priority scores to electronic messages received by the call handling system. In an embodiment, a triage interface may be included. The triage interface may be operable to display at least a portion of the electronic messages along with corresponding priority scores assigned by the message priority module. In an embodiment, the call handling system may include an integration module. The integration module may be operable to present triaged electronic messages to a call handler. The call handling system may further include a telephonic interface for audio communication between a call handler and a caller over a telephone network.

[0038] In yet another aspect, a method is provided for contacting potential eyewitnesses to an event. The method may include determining a location and a time period of an event, obtaining a listing of cellular phones proximate to the location during the time period of the event, and delivering messages to the cellular phones proximate to the location during the time period. In an embodiment, the obtaining step may include querying an ANIALI database. The listing of cellular phones may be prioritized based on information related to the cellular phones.

[0039] Various embodiments and aspect described herein may be combined. Embodiments, features and steps described in conjunction with a particular aspect may be combined with other aspects described herein. Additional aspects and corresponding advantages of the present invention will be apparent to those skilled in the art upon consideration of the further description that follows.

BRIEF DESCRIPTION OF THE DRAWINGS

[0040] FIG. 1 is a block diagram of communication flow between a caller, a call handler and an emergency services provider.

[0041] FIG. 2 is a block diagram of a communication network.

[0042] FIG. 3 is a flowchart of a process for handling an emergency call and gathering visual information.

[0043] FIG. 4 is an illustration of a graphical user interface usable to generate an electronic mail message.

[0044] FIG. 5 is an illustration of a graphical user interface for communicating textual and visual information to a call handler.

[0045] FIG. 6 is a flowchart of a method of communicating with a caller.

[0046] FIG. 7 is a flowchart of a method of correlating visual information to a call.

[0047] FIG. 8 is a block diagram of a system operable to process certain types of communications.

[0048] FIG. 9 is a block diagram of an embodiment of the system of FIG. 8 integrated with the system of FIG. 2.

[0049] FIG. 10 is a flowchart of a method of displaying a message at a call handler workstation.

[0050] FIG. 11 is a flowchart of a method of performing triage on a plurality of received messages.

[0051] FIG. 12 is an exemplary diagram of an incident linked multimedia system.

[0052] FIG. 13 is an exemplary diagram of an incident linked multimedia architecture.

DETAILED DESCRIPTION OF THE DRAWINGS

[0053] While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof have been shown by way of example in the drawings and will herein be described in detail. Those skilled in the art will appreciate that the features described below can be combined in various ways to form multiple variations of the invention. Accordingly, the invention is not limited to the specific examples described below.

[0054] FIG. 1 is a block diagram of communication flow between a caller 102, a call handler 104, and an emergency services provider 106. Generally, the caller 102 may initiate communication with the call handler 104. In the case of an emergency call, the caller 102 may dial 911 and be routed to an appropriate emergency services call handler 104. The caller 102 and the call handler 104 may exchange information regarding an emergency situation. The call handler 104 may also contact the emergency services provider 106. The emergency services provider of block 106, as used herein, may represent a single emergency services provider such as an ambulance service, or the emergency services provider of block 106 may represent multiple emergency services providers that may be engaged during any particular emergency situation. For example, in a large-scale emergency, multiple firefighting, law-enforcement, and medical units may be dispatched.

[0055] The call handler 104 may exchange information with the emergency services provider 106 regarding the emergency and the status of the caller 102. Generally, in prior art systems, the information exchanged between the caller 102 and call handler 104 is in the form of oral communications over a telephone network. Other information, such as location data of the caller 102, is also provided to the call handler 104, generally by equipment and databases interconnected to the telephone network. This information may also be provided to the emergency services provider 106.

[0056] Embodiments described herein provide systems and methods, which supplement the above information with visual information. This visual information may be captured by the caller 102, for example, with a camera phone, and forwarded to the call handler 104 using the apparatuses, systems and methods described herein. The call handler 104 may use the visual information in a variety of ways such as, for example, to determine a location of an emergency situation and/or to determine a course of action. The call handler 104 may forward the visual information to at least one emergency services provider 106 using the apparatuses, systems and methods described herein. The emergency services provider 106 may use the visual information, for example, to assess an emergency situation prior to arrival, to determine a location of the emergency situation, and/or otherwise assist in the provision of emergency services. The visual information may also be used in later investigations of, for example, the emergency situation and/or the performance of the call handler 104 and/

or the emergency services provider 106 in their response to the emergency situation and provision of emergency services.

[0057] FIG. 2 is a block diagram of one embodiment interconnected to various communication networks to enable communication, including the transfer of visual information, between the call handler 104, the caller 102, and the emergency services provider 106. In the embodiment illustrated in FIG. 2, the caller 102 is communicating using a cell phone. Although generally described herein in terms of a caller 102 communicating using a cell phone, the caller 102 may be interconnected through other means such as, for example, land lines and satellite links. A caller 102 with the ability to receive and send electronic messages may communicate with the call handler 104 using the apparatuses, systems and methods described herein.

[0058] The caller 102 may be interconnected to one or more proximate cell towers 220 through wireless communication links. The cell towers 220 may be interconnected to a cellular network 222. The cell phone of the caller 102 may have the capability to generate, send, and receive electronic messages. The cell phone of the caller 102 may also have the capability to capture visual information which may be in the form of digital images which may be still images and/or video clips. The cell phone of the caller 102 may also have the capability to capture audio information. The electronic messages may be in the form of text messages and/or messages including visual and/or audio information.

[0059] The cellular network 222 may in turn be interconnected to the PSTN 224 and the Internet 226. A PSAP 212 may be interconnected to the PSTN 224. The PSAP 212 is typically a local facility responsible for answering 911 calls and forwarding related information to emergency service providers 106. The PSAP 212 may contain multiple call handler workstations such as call handler workstation 202. The call handler workstation 202 may contain a phone 204 for audio communications with the call handler 104 and a terminal 206. The terminal 206 may be in the form of a computer interface including, for example, a video display device, keyboard and mouse. The PSAP 212 may be interconnected to the emergency services provider 106 in a variety of ways. For example, the PSAP 212 may be directly connected to the emergency services provider 106 via a dedicated communication line or wireless communication link. Alternatively or additionally, the PSAP 212 may be connected to the emergency services provider 106 via the PSTN 224.

[0060] A typical prior art 911 call from a cell phone user will now be described with reference to the aforementioned features of FIG. 2. The caller 102 dials 911 on his or her cell phone and presses send to connect the call. The cell phone communicates with one or more proximate cell towers 220 and interconnects with the cellular network 222.

[0061] The cellular network 222 in turn interconnects with the PSTN 224 and the call is routed to a PSAP 212. Textual information about the call may appear on the terminal 206 of a call handler workstation 202 and an audio communication link between the caller 102 and the call handler 104 may be established. The textual information may include location data forwarded to the PSAP 212 by the cellular network 222. The location data may, for example, be based on cell tower 220 location and cell phone signal attributes or on GPS information obtained from the cell phone, the cellular services provider or some other source. The textual information may include a phone number of the caller 102. The call handler 104 and the caller 102, via the established audio communi-

cation link, discuss the emergency situation and the call handler 104 determines the appropriate emergency services provider 106 to respond to the emergency situation. The call handler 104 may then communicate details of the emergency situation to the emergency services provider 106. The call handler 104 may maintain communication with the caller 102 and the emergency services provider 106 as needed.

[0062] Additional features of FIG. 2 that facilitate textual and visual communication between the call handler 104 and the caller 102 will now be described. Currently, many cell phones and cellular networks possess the ability to generate, send, and receive electronic messages, such as electronic mail (e.g., e-mail), through interconnection to the Internet 226. Many cell phones possess the ability to capture visual information in the form of digital images, including still images and digital video. The PSAP 212 may contain or be interconnected to an electronic message processing module 228. The electronic message processing module 228 may facilitate the sending and receiving of electronic messages between the PSAP 212 and the Internet 226 and therefore to any other user or users connected to the Internet 226. This may be accomplished through one or more network interfaces of the electronic message processing module 228. In this regard, electronic messages may be communicated between the PSAP 212 and the caller 102.

[0063] The electronic message processing module 228 may include a single electronic message processing unit capable of processing incoming and outgoing electronic messages or the electronic message processing module 228 may, as shown in FIG. 2, include an outgoing electronic message processor 214 and an incoming electronic message processor 216. The incoming electronic message processor 216 may be linked to a database 208. The database 208 may contain information pertaining to outgoing electronic messages (i.e., outgoing from the PSAP 212) and telephone communications between various callers and the PSAP 212. The database 208 may also contain other various sets of information such as templates used in the generation of electronic messages and information related to domain names used by various cellular communication providers. The database 208 may be located within or remote from the PSAP 212. The database 208 may be an information storage unit such as, for example, a computer hard drive. An administration module 210 may also be interconnected to the database 208 and the PSAP 212. The administration module 210 may facilitate the maintenance and updating of various components within the PSAP 212. As with the database 208, the administration module 210 may be located within or remote from the PSAP 212. The PSAP 212 may also be directly interconnected to the Internet 226. Similarly, the electronic message processing module 228 may be located within the PSAP 212. The electronic message processing module 228 may be located within the call handler workstation 202.

[0064] FIG. 3 is a flowchart of an exemplary process for handling an emergency call and gathering visual information. The steps of FIG. 3 will now be described in detail in conjunction with the features illustrated in FIG. 2.

[0065] The first step 302 is the caller initiating an emergency call. This may be in response to a perceived emergency such as a medical emergency, a crime, an accident, or other situation requiring the presence of an emergency services provider 106. The initiation of the call may take the form of a caller 102 dialing 911 on his or her cell phone. This will initiate communication between the cell phone and one or

more local cell towers 220 which will enable the caller 102 to communicate with the cellular network 222 of the caller's 102 cellular service provider. In the next step 304, the call may be routed through the cellular network 222 to the PSTN 224 and to the PSAP 212. The routing of cellular calls to appropriate PSAPs may be accomplished in a variety of ways known to those skilled in the art.

[0066] In the next step 306, the call may be presented to the call handler 104 at the PSAP 212. This may be in the form of a visual display of data associated with the call displayed on the terminal 206 of the call handler workstation 202 and a telephonic connection between the call handler 104 (via a phone 204) and the caller 102. The visual display of data on the terminal 206 may include information such as, for example, the telephone number of the caller 102, the cellular service provider of the caller 102, and approximate location of the caller 102, the name of the person or entity associated with the cell phone, and the time and date of the call. The visual display of data on the terminal 206 may be received from an ANI/ALI database. Other information may also be presented to the call handler 104 to assist the call handler 104 in the handling of the call. This may include blank fields for information to be determined by the call handler 104 during the course of the call.

[0067] The next step 307 may be for the call handler 104 and caller 102 to discuss the emergency situation. The discussion may be guided by emergency call protocols followed by the call handler 104. The discussion may include a determination by the call handler 104 that the caller 102 has the capability to send and receive electronic messages and that additional information in the form of a textual message or visual message from the caller 102 would be of value. The value may be immediate in that the information contained in the electronic message may, for example, aid in the response to the emergency situation. The value may be less immediate in that, for example, the information may serve as evidence for a later criminal investigation or forensic evidence for an investigation into the causes of the emergency situation.

[0068] Once it has been determined that an electronic message from the caller 102 would be beneficial, the next step 308 may be for the call handler 104 to initiate an image acquisition protocol. This initiation may take any of a variety of forms, such as entering a command using a keyboard or clicking on a button on the display of the terminal 206 using a mouse. Once the image acquisition protocol has been initiated, the call handler workstation 202 or a computer system within the PSAP 212 may generate a unique identifying component, which may be used to identify an outgoing message from the call handler 104 to the caller 102 and a possible future incoming message or messages from the caller 102 to the PSAP 212. The unique identifying component may be a unique string of alphanumeric characters. The unique string may be generated based on the time of the request for the unique string, the previously generated unique string (e.g., the unique strings may be sequential), or on any other suitable methodology. In an implementation, the unique string may be a numeric string representing the date of the call along with a sequential number where the sequential number is reset to 1 at the beginning of each day. The unique identifying component may be stored in a database 208 along with or in relation to information that identifies a particular call between the caller 102 at the call handler 104.

[0069] A pop-up window 400, such as that illustrated in FIG. 4, may be displayed on the terminal 206 in response to

the initiation of the image acquisition protocol by the call handler 104. The pop-up window 400 may present multiple electronic mail templates to the call handler 104 in the form of a pull down list of electronic mail templates accessed by activating the pull-down menu button 401 adjacent to the electronic mail template window 402 and selecting an appropriate electronic mail template. For example, and as illustrated in FIG. 4, an electronic mail template may be titled "Request for Caller Location Picture." The electronic mail template "request for caller location picture" 402 may be one of several electronic mail templates available. Other electronic mail templates may, for example, include templates to instruct the caller 102 to provide images of: a location of an incident, a particular item such as a suspicious package, suspected hazardous material, a victim, a vehicle involved in an accident, and a suspect. Through the administration module 210, electronic mail templates may be added, removed or modified by administrative personnel.

[0070] Once an electronic mail template has been selected by the call handler 104 in step 310, pre-determined fields of the electronic mail may be automatically populated. For example as shown in the pop-up window 400 when the "request for caller location picture" electronic mail template is selected, the system may automatically populate the electronic mail with a subject 408 titled "caller location picture 1" and predetermined text in the body 410 of the message. The predetermined text, as illustrated in FIG. 4, may include instruction on how to reply to the electronic mail. Not shown in FIG. 4, but nonetheless a part of the electronic mail message, is the unique identifying component which may be attached to the electronic mail message. For example, the unique identifying component may be located within a message header that is generally not displayed for a user. The header containing the unique identifying component may be a custom header. In one implementation, the outgoing email may include a custom header named "Call-ID."

[0071] The next step 312 may be for the call handler 104 to acquire a domain name for the caller 102. This step may include the call handler 104 determining the service provider of the caller 102 and selecting an appropriate domain name from a pull-down menu of domain names 404 located in the pop-up window 400. For example, and as illustrated in FIG. 4, the call handler 104 may determine that the caller's 102 service provider is Service Provider X. The call handler 104 may then select Service Provider X from the pull-down menu of domain names 404. The system may then automatically populate the "send to" field 406 with the domain name used by Service Provider X, which may be "@mail.ServProX.com". The call handler 104 may manually enter a domain name for the caller 102. The call handler 104 may then determine a phone number from which the caller 102 is calling and enter that information as the specific address in the "send to" field 406. The call handler 104 may obtain the caller's 102 domain name and/or phone number from the display of caller information presented to the call handler 104 on the terminal 206 of the call handler workstation 202. The call handler 104 may obtain the caller's 102 domain name and/or phone number by other methods such as, for example, asking the caller 102. Alternatively, the call handler workstation 202 may automatically populate the "send to" field 406 with the caller's 102 phone number and domain name. This may then be verified by the call handler 104 during the course of the call. Information correlating particular service providers to particular domain names used by users of that service may be

present in the database 208. The database 208 may be accessible by the call handler 104. The database 208 may also be used to lookup domain names by the system when the call handler workstation 202 automatically populates the "send to" field 406. The database 208 may be updated through use of the administration module 210.

[0072] The next step 314 may be for the call handler 104 to enter any required custom instructions into the electronic mail message. The custom instructions may be generated as a result of the discussion between the call handler 104 and the caller 102. The next step 316 may be for the call handler 104 to send the electronic mail message to the caller 102. The call handler 104 may perform this function by clicking on or activating a send button 412 in the pop-up window 400.

[0073] The electronic mail message may then be transferred from the call handler workstation 202 to an outgoing electronic message processor 214. The outgoing electronic message processor 214 may send the electronic mail to the caller 102 over the Internet 226 and the caller's 102 cellular network 222. Accordingly, the next step 318 may be for the caller 102 to receive the electronic mail from the call handler 104. The outgoing electronic message processor 214 may packetize the outgoing message for delivery over the Internet 226 to the caller 102.

[0074] The caller 102 may generate a reply to the electronic message from the call handler 104 in the next step 320. This may be followed by the step 322 of the caller 102 attaching an image to the reply message. The image may have been previously captured or it may be captured after the caller 102 receives the electronic message from the call handler 104. As previously stated, the image may be a still image or a video image (e.g., a sequential series of still images with or without accompanying audio). The next step 324 may be for the caller 102 to send the reply message to the PSAP 212. By generating the reply message as a response to the electronic message from the call handler 104, the reply message may contain the unique identifying component that was part of the electronic message sent from the call handler 104 to the caller 102.

[0075] During typical operation, the incoming electronic message processor 216 may periodically pull incoming electronic messages (e.g., electronic mail messages) from a configured inbox by, for example, using POP3 protocol. Other protocols, however, may be used, such as the IMAP protocol. The inbox may be configured to receive and reassemble packetized messages. The incoming electronic message processor 216 may perform this function periodically at a predetermined interval. The incoming electronic message processor 216 may perform this function in response to a specific request such as, for example, a request from the call handler 104 or a supervisor. The incoming electronic message processor 216 may be separate from the outgoing electronic message processor 214. Alternatively, the incoming electronic message processor 216 and the outgoing electronic message processor 214 may both be part of an electronic message processing module 228. For example, the functions described herein of the outgoing electronic message processor 214 and incoming electronic message processor 216 may both be performed by the same computer or electronic device.

[0076] Returning to the process illustrated in FIG. 3, the next step 326 may be for the incoming electronic message processor 216 to pull the incoming electronic mail from the caller 102 from the configured inbox. The next step 328 may be for the incoming electronic message processor 216 to correlate the unique identifying component contained within

the reply electronic mail to the call between the caller 102 in the call handler 104. This may be followed by step 330 where the incoming electronic message processor 216 sends the reply message from the caller 102 to the call handler workstation 202 of the particular call handler 104 who is handling the call for the caller 102. The entire reply message may be sent to the call handler 104 or only the image contained within the message may be sent to the call handler 104.

[0077] The next step 332 may be for the call handler workstation 202 to display the visual information sent by the caller 102 along with information pertaining to the call between the caller 102 and the call handler 104. The display may be automatic in that it pops-up on the terminal 206 without any call handler 104 action. Alternatively, an alert may appear somewhere on the display screen of the call handler workstation 202 and/or an audible signal may be produced to alert the call handler 104 that an image is available. The call handler 104 may then activate a button or other feature to view the visual information.

[0078] An example of a display including visual information according to step 332 is illustrated in FIG. 5. Call display window 500 is an exemplary window that may display call information on the terminal 206 of the call handler workstation 202. The call display window 500 may include a listing section 508 where recent calls to the PSAP 212 or to the particular call handler workstation 202 within the PSAP 212 may be displayed. This display, for example, may be in the form of a list as illustrated in FIG. 5. The main window 502 may display details of an in-process call between the call handler 104 and the caller 102. The main window 502 may display details of a particular call by selecting a call in the listing section 508. As illustrated in FIG. 5, the main window 502 is displaying details of an in-process call between the call handler 104 and the caller 102. As illustrated, such information may include caller 102 name, a phone number, and location.

[0079] Other information may also be displayed. Some of the information contained in the fields within the main window 502 may be populated automatically by the call handler workstation 202 with information derived from the original call. For example, known methods of transferring information between a caller and a receiver of that call such as caller ID and the aforementioned accessing of the ANIALI database may be used to populate fields within the main window 502. During the call between the call handler 104 and the caller 102, the call handler 104 may also manually populate fields within the main window 502 with information regarding the call as it is discovered by the call handler 104. Such information may include details about the situation that prompted the caller 102 to call the call handler 104 (e.g., by dialing 911).

[0080] Returning to the process illustrated in FIG. 3 and step 332 in particular, the display of the visual information sent by the caller 102 may take the form of a pop-up window 506 which may appear on the terminal 206 of the call handler workstation 202. The pop-up window 506 may appear or pop-up when the call to which the pop-up window 506 has been correlated is displayed in the main window 502. In this regard the visual information within the pop-up window 506 and the textual information within the main window 502 are linked and are configured to appear together on the terminal 206 of the call handler workstation 202.

[0081] The sequence of events with respect to the sending and receiving electronic messages between the caller 102 and the call handler 104 may vary, for example, depending on

PSAP 212 protocols and capabilities and on equipment capabilities of the caller 102. For example, the caller 102 may place an emergency call that is routed to the PSAP 212 and during that call, receive and reply to the electronic mail sent by the call handler 104. In such a scenario, the pop-up window 506 may appear in front of the call handler 104 while the call handler 104 is still a direct audio communication with the caller 102. In another scenario, the caller 102 may disconnect from the call handler 104, then proceed to receive and reply to the electronic message of the call handler 104, and then reconnect with the call handler 104. This reconnection may be through the caller 102 initiating the call or through the call handler 104 initiating the call. In yet another scenario, the caller 102 may disconnect from the call handler 104, then proceed to receive and reply to the electronic mail message without ever reestablishing an audio connection with the call handler 104. As can be readily appreciated, other scenarios or sequences of audio communication and information transfer between the caller 102 any call handler 104 may take place.

[0082] Returning to the process illustrated in FIG. 3, in the next step 334, the call handler 104 may discuss the image within a pop-up window 506 with the caller 102. This discussion may, for example, relate to details of the image, the current situation of the caller 102, or any other topic regarding the situation that prompted the original call from the caller 102.

[0083] The next step 336 may be for the call handler 104 to forward the image (or images) to one or more in emergency services providers 106. Such a transfer of visual information between the call handler 104 located within the PSAP 212 and the emergency services provider 106 may be accomplished in a variety of ways. For example, the transfer of information may include transferring information over the Internet 226. Alternatively, the visual information may be transferred from the PSAP 212 to the emergency services provider 106 over the PSTN 224 (e.g., via facsimile transmission). The visual information may be transferred between the PSAP 212 and the emergency services provider 106 via a direct link such as a direct wireless link or a hardwired link between the emergency services provider 106 and the PSAP 212 (e.g., local area network or wireless network connection). Other methods known to those skilled in the art may also be used to transfer the visual information (e.g., hand deliver a print out of the visual information to the emergency services provider 106 in instances where the physical location of the PSAP 212 is close enough to the emergency services provider 106 to make such a delivery method reasonable).

[0084] The audio communication link between the caller 102, the call handler 104 and the emergency services provider 106 may continue to be active. In such a scenario, the emergency services provider 106 may request additional information of the caller 102, and the caller 102 may provide additional information in the form of additional verbal information or additional visual information. The various communication links may, for example, remain in place until (and after) the emergency services provider personnel arrive at the location of the caller 102.

[0085] After communication between the caller 102 and the call handler 104 has ended, information regarding that communication may be archived in step 338. The archived information may include details regarding the call, call handler 104 notes on the call, the original electronic mail message or electronic mail messages sent from the call handler 104 to the caller 102, and any replies, including any visual information,

sent from the caller **102** to the PSAP **212**. The archived information may be in the form of a CAD incident record. This archived information may be used later for various purposes including, for example, PSAP **212** performance review, law enforcement investigations, and general emergency situation forensic investigations. The information may be archived in the database **208**.

[0086] FIG. 6 illustrates, in flowchart form, a method of communicating with a caller. The first step **602** in the method is to receive a call from a caller. The call may be received over the PSTN, over the Internet (e.g., VOIP), over any other type of network, or over a combination thereof. The call may be emergency related. The next step **604** may be to determine if visual information is available and would be valuable to aid in the communication with the caller and/or the provision of emergency services.

[0087] The next step **606** may be to assign a unique identifying component to a first message to be sent to the caller. The first message may be an electronic mail message. The unique identifying component may be an alphanumeric sequence. The first message may be generated, in part, by selecting a message template from a plurality of message templates. The next step **608** may be to include the unique identifying component in the first message to the caller. The unique identifying component may be located within a header of the first message.

[0088] The next step **610** may be to send the first message to the caller. The first message may be sent to the caller over a computer network. The computer network may be the Internet. The first message may include instruction for replying to the first message. The instruction may direct the caller to attach visual information to a second reply message. A domain name used in addressing the first message may be determined based on the service provider of the caller. This determination may include interrogating a database where domain names are cross-referenced to service providers.

[0089] The next step **612** may be to receive a second message in response to the first message. The second message may include visual information. The second message may include the unique identifying component that was included in the first message. The unique identifying component may be located in a header of the second message. The second message may be generated by the caller attaching visual information to the second message. The visual information may be in the form of a digital image or digital video. The next step **614** may be to correlate the second message to the received call. The correlation may at least partially be based on the unique identifying component. The correlation step may include populating data fields within the database **208** with information regarding the correlation process. In an implementation, the populated fields include fields for the date and time the second message is received along with information on when and how the second message was correlated or matched to a call. The method may further include displaying the visual information along with information regarding the call. The method may further include forwarding information regarding the call and/or the visual information. This forwarding may be to an emergency services provider.

[0090] FIG. 7 illustrates, in flowchart form, a method of correlating visual information to a call. The first step **702** in a method may be to receive a call from a caller. The call may be emergency related. The following step **704** may be to send an electronic mail message to the caller, where the electronic

mail message includes a unique identifying component. This may be followed by the step **706** of receiving a reply message from the caller that includes the unique identifying component. The next step **708** may be to correlate the reply message to the call, where the correlation is at least partially based on the unique identifying component. The visual information and information about the call may be displayed. The information regarding the call and the visual information may be forwarded to an emergency services provider. The electronic mail message may be generated by selecting a message template from a plurality of message templates.

[0091] When the aforementioned incoming electronic message processor **216** receives an electronic message and is unable to correlate that electronic message to a particular call, the uncorrelated electronic message may be forwarded to or stored in a unique location. This information may then be manually reviewed (e.g., by PSAP **212** personnel) to determine if the information (e.g., visual information attached to the message) contained within the message is pertinent to a current call, a recent call, or other emergency or significant event.

[0092] It will be appreciated that, although FIG. 2 illustrates a single call handler workstation **202** within the PSAP **212**, typically a PSAP **212** will contain multiple call handler workstations **202** which may be manned by multiple call handlers **104** and that the systems described herein may be operable to forward the relevant electronic messages from the caller **102** to the particular call handler **104** in the PSAP **212** that is handling that particular call. It should also be appreciated that although a single database **208** is illustrated in FIG. 2, each database function described herein may be handled by a separate database. This database (or databases) may be accessed directly as illustrated in FIG. 2 or may be accessed through a connection through other means, such as through the Internet **226** or over the PSTN **224**. The databases accessed by the call handler workstation **202** may include ALI and WALI (wireless automatic location information) databases.

[0093] Due to the popularity of cell phones and other portable communication devices that possess the ability to capture and transfer visual images, the above descriptions have generally focused on communications between a caller **102** using a cell phone and a PSAP **212**. However, the described apparatuses, systems and methods may also be used by callers using different types of equipment. For example, a caller who does not possess a camera phone may still be able to capture digital images and transfer them to the PSAP **212** if they, for example, have a digital camera, the means to download images to a computer, and Internet access from the computer. In such a circumstance, the call handler **104** may direct the outgoing electronic message to an electronic mail address of the user that the user may be able to receive at the computer.

[0094] Additionally, the apparatuses systems and methods described herein may be used to deliver non-visual information from the caller **102** to the call handler **104**. For example, if the caller **102** perceives an emergency situation as a result of receiving a threatening electronic mail message, the apparatuses, systems and methods described herein may be used to forward the threatening electronic mail message to the call handler **104** and emergency services providers **106**. In another example, the caller **102** may have made an audio recording relating to an emergency situation, such as a verbal threat or comment about criminal activity. The audio recording may have been made on the caller's **102** cell phone. In

such a situation, the apparatuses, systems and methods described herein may be used to send the audio file to the call handler **104** and emergency services providers **106**.

[0095] FIG. 8 is a block diagram of an incident linked multimedia system **800** (labeled "ILMS **800**" in FIG. 8) operable to process communications received over a computer network. The received communications may or may not contain a unique identifying component. Such communications may be emergency related, but are not necessarily made in response to a request from a call handler. For example, an emergency situation, such as an automobile accident, may be witnessed by a cell phone user who captures an image of the accident scene with his or her cell phone and immediately sends it to an address set up to receive emergency messages. As will be appreciated, such an address set up to receive emergency messages may receive a significant amount of messages during any particular time period; both emergency and nonemergency related. Accordingly, the incident linked multimedia system **800** may be operable to receive messages, pass messages containing a unique identifying component to a call handler, assign a priority score to received messages that do not contain a unique identifying component, triage the received messages that do not contain a unique identifying component, and forward the prioritized and triaged messages that do not contain a unique identifying component to personnel designated to review such messages. The personnel designated to review such messages may include individuals who are specifically charged with reviewing prioritized and triaged messages. The personnel designated to review such messages may, for example, include dispatchers, operators, call handlers, or any combination thereof.

[0096] The incident linked multimedia system **800** may include a portable communications module **801**. The portable communications module **801** may be operable to send and receive communications over a computer network, such as the Internet **226**. The portable communications module **801** may provide a Simple Mail Transfer Protocol (SMTP) service that is capable of filtering inbound message traffic. The filtered messages may be forwarded to a message priority engine **802**, described below. As noted above, a mail address set up to receive emergency related communications may also receive a significant volume of nonemergency related communications. Accordingly, the portable communications module **801** may be configured to filter incoming traffic based on specific criteria.

[0097] For example, the portable communications module **801** may be a secure gateway that may restrict inbound traffic to that received from authorized cell phone company servers and other authorized sources. Outbound traffic may also be similarly restricted. In this regard, the portable communications module **801** may filter out communications not originating from cell phone users. The other authorized sources may, for example, include communications addressed to specific unpublished email addresses. For example, emergency messages incorrectly sent to other government entities may be forwarded to a specific unpublished email address. The portable communications module **801** may process such messages similarly to messages received from the authorized cell phone company servers.

[0098] The portable communications module **801** may be capable of secure communications (e.g., may employ encryption techniques). Furthermore, the portable communications module **801** may perform self-testing to ensure availability. Such testing may be performed continuously. The portable

communications module **801** may be designed to be the fault tolerant and feature redundant components to further ensure availability. Typically, the portable communications module **801** will not store any messages. However, the portable communications module **801** may store messages under certain circumstances, such as, for example, when messages are undeliverable.

[0099] The portable communications module **801** may be configured such that messages sent to an emergency mail address are not mixed with regular local government messages. For example, an emergency related domain address could be created such as report911.com (this address is used herein for exemplary purposes only). Messages sent to this domain could be forwarded to appropriate emergency centers. For example, messages sent to Boston@report911.com could be forwarded to a Boston area emergency center whereas messages sent to Philadelphia@report911.com could be forwarded to a Philadelphia area emergency center.

[0100] The portable communications module **801** may be a managed service remotely located relative to a PSAP (e.g., PSAP **212** of FIG. 2). Furthermore, a single portable communications module **801** may serve a plurality of incident linked multimedia systems **800** located at various locations. For example, a single portable communications module **801** may handle emergency related Internet-based communications for several PSAPs.

[0101] The aforementioned emergency related messages may be forwarded from the portable communications module **801** to the message priority engine **802** associated with the appropriate PSAP. The message priority engine **802** may first determine if an incoming message contains a unique identifying component. If the message does contain a unique identifying component, it may be forwarded directly to an integration module **807**, which may present the message to the call handler **104** handling the communications related to the unique identifying component.

[0102] For messages that do not contain a unique identifying component, the message priority engine **802** may be operable to assign a priority score to each message. The priority score may represent a determination of the potential relevance of the particular message. The priority score may be at least partially based on attributes of the message and/or attributes of the source of the message.

[0103] A priority score assigned by the message priority engine **802** may be related to the cell phone number from which the message originated. For example, a message may be received from a cell phone number recognized to be that of an emergency services provider or other emergency related person or entity. Accordingly, a database **803** may be maintained that contains a list of emergency personnel cell phone numbers. The database **803** may be a part of the incident linked multimedia system **800**, as shown in FIG. 8, or it may be external to the incident linked multimedia system **800**.

[0104] When the message priority engine **802** receives a message from the portable communications module **801**, the message priority engine **802** may compare the source of the message to known cell phone numbers contained within the database **803** to determine the priority score for that message. Other cell phone numbers may be present within the database **803** and may be used to assign priority scores. For example, the cell phone numbers of private parties known to provide emergency information may be stored within the database **803**. Such private parties may, for example, include private

security personnel and private parties known to be participating in neighborhood watch programs.

[0105] The status of a particular cell phone number as belonging to an emergency related person or entity may be stored in an external database **804**. The external database **804** may, for example, be a database maintained by the PSAP. The external database **804** may, for example, be a database maintained by a telephone service provider or other entity. For example, telephone service providers typically maintain ANIALI databases. These databases may contain identification and location numbers for the subscribers to the telephone service provider. Special codes may be added to these databases to identify particular cell phone numbers as those related to emergency personnel or entities. Accordingly, the message priority engine **802** may query such databases to determine if a received message is from an emergency related source. Such a query may be accomplished through the integration module **807**. It will be appreciated that the message priority engine **802** may query (e.g., through the integration module **807**) the local database **803** and/or a remote database **804** (e.g., ANIALI) to determine if a particular call is from an emergency related source.

[0106] The database **803** may also contain a list of cell phone numbers that have been involved with previous emergency events. For example, a specific cell phone number may be known to have provided valuable information during past emergency incidents. Accordingly, the message priority engine **802** may assign a priority score at least partially based on this positive history. Similarly, specific cell phone numbers that have in the past provided false or nonuseful information may also be stored in the database **803** and the message priority engine **802** may assign a priority score at least partially based on this negative history. Other cell phone numbers that have been involved with previous emergency events may also be stored in the database **803**. These may include cell phone numbers that exist in the log of outbound calls and/or messages made by an emergency call center.

[0107] The database **803** may be updated frequently (e.g., continuously) with information related to the currently active emergency calls being handled by the PSAP. This may include active call caller ID information, queued calls, and any cell phone numbers referenced by a call handler. Cell phone numbers may be referenced by a call handler, for example, where a cell phone number of a third-party has been collected by emergency responders during an incident in progress and/or where a caller mentions a cell phone number during the call. Accordingly, the message priority engine **802** may assign a priority score at least partially based on the relationship between the message source and any currently active calls.

[0108] The priority score determined by the message priority engine **802** may also be based on attributes of the source of the message. For example, the message priority engine **802** may query a database such as external database **804** that contains current positions of cell phone users. A cell phone carrier may maintain such a database. Alternatively once queried, the cell phone carrier may determine the position of a particular cell phone. The cell phone carrier may determine the approximate position of a cell phone user by which tower the cell phone user is using to access the cell phone system. The cell phone carrier may be able to obtain a more accurate location by triangulating the cell phone signal between multiple towers. Moreover, cell phones with GPS capabilities may be operable to provide accurate location information.

The message priority engine **802** may also query a database that contains the billing addresses of cell phone users. Consequently, the message priority engine **802** may be able to determine the approximate position from which a received message originated or may have originated. The current position and cell phone billing address databases may be accessed through a direct connection or through the Internet **226**.

[0109] The database **803** may also contain information regarding the location of currently active events being handled by the PSAP. Accordingly, the message priority engine **802** may be capable of querying the database **803** to determine if the location of the source of a received message is proximate to any active communications and assign an appropriate priority score based on such proximity.

[0110] A particular user (e.g., a PSAP) may customize the priority score determined by the message priority engine **802** based on factors such as those described above. For example, a particular local government may wish to assign a higher priority score to certain local government employees. Other factors, such as the total time a particular message has been residing in the queue, may also contribute to the priority score assigned to a particular message. The message priority engine **802** may also maintain a listing of all of the current messages that have not been responded to and their corresponding priority score.

[0111] After the message priority engine **802** has determined a priority score for a particular message, that message, along with its priority score, may be forwarded to a triage interface **806**. The triage interface **806** may allow a call handler **104** or other triage interface **806** operator to process inbound messages that have had a priority score determination. For example, a triage interface **806** operator may view a list of incoming messages along with their priority scores and select the message with the highest priority score for processing. For example, the triage interface may display for the triage interface operator, the message with the highest current priority (e.g., the message with the highest priority score) so that the triage interface operator may process the message.

[0112] Once a message is selected or the highest priority message is presented to the triage interface operator, the triage interface operator may use the triage interface **806** to process the message. Several processing options may be available. The selected message may be associated with an existing active call. Once associated, the message may be forwarded to the integration module **807** and the call handler handling the existing active call. As noted, the triage interface operator may be a call handler and accordingly, the triage interface operator may select a message from the triage interface and handle the call himself or herself as the call handler.

[0113] The selected message may be associated with an existing closed call. The message may then be reviewed during a post-call investigation or review. The triage interface operator may change the priority level of the selected message. For example, the priority level may be lowered and other higher priority messages may be processed. The triage interface operator may view an explanation of the priority score prior to further processing. The triage interface operator may annotate or add information to the message prior to further processing.

[0114] The triage interface operator may respond to the message. The response may be to the sender of the original message, or it may be to another interested party, such as, for example, an individual or location (e.g., a business) described in the original message, or to an individual or location that

could use or benefit from the information contained in the original message. Such a response may then be transferred to the portable communications module **801**, which in turn may send the response message via the Internet **226**.

[0115] The triage interface operator may open a new call based on the message and pass the message to the communications system **808** via the integration module **807**. The new call may be to the sender of the original message, or it may be to another interested party. The communications system **808** may be CAD system, an RMS, or any other type of call handling system. The communications system **808** may handle emergency and/or non-emergency related calls.

[0116] The triage interface operator may forward the message to other types of personnel. For example, the triage operator may forward the message directly to an emergency services provider for an immediate response. For example, the triage interface operator may forward the message to law enforcement authorities for further investigation. Indeed, the triage interface operator may forward the message to any appropriate recipient for any appropriate reason, such as response, investigation, recordation of evidence, and statistics gathering.

[0117] The triage interface **806** may support multiple simultaneous users. In this regard, multiple triage interface operators may be simultaneously processing the same priority queue. The triage interface **806** may be accessed by call handlers or other designated personnel at their call handler workstations (e.g., a call handler workstation located within the communications system **808**) or other designated workstations. This integration of the triage interface **806** into the call handler workstations or other designated workstations may be accomplished by the integration module **807**.

[0118] The integration module **807** may be operable to integrate the above noted incident linked multimedia system **800** features into an existing communications system **808**, thereby enabling call handlers and other call center personnel to access the incident linked multimedia system **800** features. The integration module **807** may reside outside of the communications system **808** to which it is linked. In this regard, the integration module **807** may be accessible through a Graphical User Interface (GUI) at a call handler workstation **202** or other designated workstation. Such an arrangement may allow a call handler **104** or other designated personnel to access the functionality of the incident linked multimedia system **800** through the integration module **807**. Such an arrangement enables the incident linked multimedia system **800** to provide valuable information to call handlers, other designated personnel, responders and callers while minimizing overhead to the communications system **808**. Accordingly, the integration module **807** may include program interfaces able to communicate with and be integrated into existing communications **808**. The integration module **807** may utilize standards-based XML Web Services to enhance compatibility. In this regard, the integration module **807** may be remotely located from the communications system **808** and communicate with the communications system **808** over an Internet connection. The integration module **807** may include web hosting capabilities and an authentication module to authenticate communications between the integration module **807** and the various communications systems **808** that may be serviced by the incident linked multimedia system **800**.

[0119] The integration module **807** may also generate outgoing messages to callers that contain unique identifying

components as described herein. For example, the call handler **104** may determine that visual information supplied by a caller **102** may be beneficial. Using a GUI at the call handler workstation **202**, the call handler **104** may generate an outgoing message containing a unique identifying component. Once generated the message may be transferred to the portable communications module **801** and sent to the caller **102** via the Internet **226**. In general, the integration module **807** may serve as an interface between existing communications systems **808** and the message handling and communication systems discussed herein.

[0120] The integration module **807** may also generate outgoing messages to callers that contain other types of information. For example, the call handler **104** may send a message to the caller **102** that includes instructions and/or information. The instructions and/or information may, for example, contain text, images, video, audio, forms, URLs, or any combination thereof.

[0121] A reporting interface **809** may also be included in the incident linked multimedia system **800**. The reporting interface may provide a means to assess the performance of the incident linked multimedia system **800** and its various individual modules and components. This performance assessment may be performed without revealing any confidential information contained within specific communications.

[0122] For example, the reporting interface **809** may be operable to report performance statistics related to message delivery times, dropped messages, noncompliant messages, message traffic volume, and message sizes. Such statistics may be sortable in a variety of ways such as by cell phone carrier or by time or date received. The reporting interface **809** may also be operable to generate real-time information regarding the queue of inbound and outbound messages, including routing path, source and target mail servers, and messages awaiting delivery to the message priority engine **802**. The reporting interface **809** may also be operable to report on the status and performance of the message priority engine **802**. For example, priority score determination processing times may be reported. Also, statistics related to priority score determination, such as the frequency that various criteria are present in a message and used to determine a priority score, may be reported. Furthermore detailed explanations for each determined priority score may be available for review through the reporting interface **809**. The reporting interface **809** may also maintain an exceptions list and a log of manual message processing such as message reprioritization.

[0123] The reporting interface **809** may also contain information relating to the configuration of the incident linked multimedia system **800**. Such information may include current message prioritization parameters, message handling parameters, and communications system **808** access settings.

[0124] The reporting interface **809** may also include administrative capabilities or system administration functions may be performed through a separate administration module (not shown) situated similarly to the reporting interface **809**. For example, the reporting interface **809** or administration module may allow a user to alter the configuration of the incident linked multimedia system **800**. For example, current message prioritization parameters, message handling parameters, and communications system **808** access settings may be changeable through the reporting interface **809** or administration module.

[0125] As noted, the incident linked multimedia system **800** may be capable of querying an ANIALI database to determine a potential location of a caller. Similarly, the incident linked multimedia system **800** may be capable of querying a database (e.g., an ANIALI database) to determine all cellular phones that may have been in the area of an incident during a particular time period. For example, if an emergency situation is occurring at a particular location, the incident linked multimedia system **800** may be operable to interrogate an ANIALI database and determine cellular phones in the incident area. Once a listing of cellular phones in the area of an incident during a particular time period is obtained, each cellular phone may be assigned a priority score in a manner similar to as described hereinabove. The listing may then be triaged and messages may be sent to, or call handlers or other designated personnel may call, those cellular phones that, based on their priority scores, are most likely to be able to provide valuable information regarding the incident.

[0126] FIG. 9 is an exemplary embodiment of the incident linked multimedia system **800** integrated into a known communications system similar to that of FIG. 2. The incident linked multimedia system **800** provides communication services, such as Internet-based communications including text, images, and video, to call handlers **104** or other designated personnel working at call handler workstations **202** or other designated workstations within PSAPs **212**. The incident linked multimedia system **800** may also be operable to communicate with external databases **804** such as ANIALI databases.

[0127] The incident linked multimedia system **800** may integrate any of the call handling features and capabilities discussed herein with existing call handling systems (e.g., existing PSTN **224** based PSAPs **212**) including those discussed with reference to FIGS. 1 through 7. As a system separate from the PSAP **212**, the incident linked multimedia system **800** may be scaled and configured independent of the PSAP **212** systems. Furthermore, a portion of the incident linked multimedia system **800** may interact with multiple PSAPs, leading to homogenization and economies of scale. FIG. 9 illustrates the incident linked multimedia system **800** as a stand-alone program (e.g., middleware) that interfaces with the external database **804**, the Internet **226**, and the software running at the PSAP **212**. In another embodiment, the incident linked multimedia system **800** may be fully integrated with software running at the PSAP **212**. FIG. 10 is a flowchart of a method of processing a message for display at a call handler workstation **202**. The first step **1001** in the method may be to receive a message over a computer network. The message may be emergency related. The computer network may be the Internet **226**. It may then be determined if the message is from an approved source. This may be accomplished, for example, by verifying that the domain from which the message was sent is an approved domain (e.g., white listed). For example, if the message originated from a cellular phone user associated with a particular cellular phone company, the source of the message may be the user's cellular phone number followed by the @ symbol, followed by the cellular phone carrier's domain, followed by .com. If the message is from an approved source, the next step **1002** may be to verify the message as such. The following step **1003** may be to assign a priority score to the message. The message priority engine **802** may perform the assignment of the priority score. The priority score may be related to a potential level of emergency associated with the message. After a priority

score has been assigned to the message, the message may be forwarded in the following step **1004** to a call handler workstation **202** based on the priority score. The next step **1005** may be display the message at the call handler workstation **202** on the terminal **206**. The display of the message may be immediate or an indicator may be displayed at the call handler workstation **202** and the message may be displayed once a call handler **104** initiates the display of the message (e.g., by selecting the message on the call handler workstation **202** terminal **206**). The call handler **104** may then respond to the message in an appropriate manner (e.g., through contact with the message sender or alerting an emergency services provider **106**). Although the method of FIG. 10 has been described as forwarding a message to a call handler **104** at a call handler workstation **202**, in embodiments where incoming messages are handled by operators, dispatchers or other personnel aside from call handlers **104**, the message may be forwarded to that individual at that individual's workstation.

[0128] FIG. 11 is a flowchart of a method of performing triage on a plurality of received messages. The first step **1001** of the method may be to receive a plurality of messages over a computer network (e.g., the Internet **226**). The next step **1102** illustrated in the flowchart is to assign an emergency related priority score to each of the received messages. The emergency related priority score may be based on, among other things, the source of the message, and/or the origination location of the message. In the next step **1103**, the messages that have been assigned an emergency related priority score may be ordered based on those scores. Accordingly, the plurality of messages ordered in terms of emergency related priority score may then be reviewed and responded to based on their priority scores. The messages may, for example, have come from one or more of: a phone number of an emergency responder; a phone number of a known emergency information provider; a phone number related to previously received calls; a phone number related to a call previously placed; and a phone number related to a currently active emergency situation.

[0129] In still other exemplary embodiments, and now referring to exemplary FIGS. 12-13, one or more exemplary embodiments describing incident linked multimedia (ILM) may be described. ILM can be a software utility that can manage a collection image media from devices, such as mobile devices. ILM may allow for a cost effective solution for collecting and processing solicited and unsolicited image data. This data may then be made available to accessible to existing records management systems.

[0130] ILM **1208**, as shown as a part of communication system **1200** in exemplary FIG. 12, can use the multimedia message service (MMS) to allow a range of media formats to be attached to messages, similar to the short message system (SMS) that is widely utilized. MMS can provide for the transmission of text, audio data, image data and video data, including various fonts, colors and formats, such as JPEG, GIF, MP3, MIDI and MPEG. Additionally, there is no size limit to the data transmitted using MMS. Thus, ILM **1208** may utilize existing cellular and internet infrastructure, for example mobile phone **1202**, cellular network **1204** and internet **1206**, to facilitate communication between any communication network and any user's existing data systems.

[0131] In one exemplary embodiment, ILM **1208** may handle the receipt of messages from any number of senders, for example known senders, by providing the sender with an image request that the sender replies to and attaches their

image thereto. Additionally, ILM 1208 may also be capable of processing unsolicited messages and messages from unknown senders and can append a priority code to each unsolicited message based upon a predefined or desired criteria.

[0132] As shown in exemplary FIG. 12, a caller may place a call using communication device 1202 over cellular network 1204. The call may be made to communication center 1222. During the course of this call, it may be made known that the caller may also send an image relating to their call from communication device 1202 to communication center 1222 over cellular network 1204 or internet 1206.

[0133] During the call described above, a call handler at communication center 1222 can activate a function that sends an MMS message to the communication device 1202 from which the caller is calling from. The sent message can contain a unique identifier that can link the message to the data record in the communication center 1222 database.

[0134] Upon the completion of the call between the caller and communication center 1222 (or at any time during the call), a MMS message may be received and displayed on communication device 1202. The caller may then reply to the MMS message and attach their desired image (or any other type of data file) to the reply message. The message may then be transmitted over network 1204 or internet 1206 and may be received by ILM 1208, where the message may be filtered or checked for the appropriate credentials. Based upon this process, the message may then either pass, for example automatically, through the filter and be filed or otherwise associated to the originating call record or may be placed in a queue in order to be manually checked by an operator.

[0135] Also, in some exemplary embodiments, if an unsolicited message is received by ILM 1208, the inbound MMS message may not contain a unique identifier which could allow it to be associated with an existing call record. Therefore, the filter or checking mechanism of ILM 1208 can evaluate the message based upon other factors, for example the location or phone number of the center, if GPS information is available in the message. Upon review and determination of this information, an acceptance priority may then be allocated to the message and it can be queued based upon this value.

[0136] Still referring to exemplary FIG. 12, ILM 1208, upon receipt and filtering of a message, may have any of a number of capabilities. For example, ILM 1208 may be adapted to be used with computer aided dispatch (CAD) and record management systems (RMS), despite potentially having evolved using different standards. Also, in addition to its ability to filter messages, ILM 1208 may also manage security restrictions from messaging systems, for example cell phone network providers and government agencies. Further, ILM 1208 may also have a flexibility insofar as it may be able to manage a rapid increase in the volume of private and public (for example 911, 311, etc.) messages originating from communications devices and may be able to manage any different data format, for example any of the different text, audio, image or video data formats described above or otherwise available. Also, ILM 1208 can be adapted to differing local requirements for handling inbound requests.

[0137] As shown in exemplary FIG. 12, ILM 1208 may have any of a number of different components, including, but not limited to, integration module 1218, message priority engine 1214, triage interface 1212, reporting interface 1216 and portable communications module 1210.

[0138] Integration module 1218 may allow for ILM 1208 to efficiently process unsolicited or third party messages. Thus, ILM 1208 may be capable of providing valuable context to enrich information that may already be available to call handlers, responders and callers while minimizing overhead to the communication center 1222. In some exemplary embodiments, integration module 1218 may be considered “middleware” for ILM 1208 insofar as it can expose its functionality to existing applications such as CAD and RMS 1220 while also utilizing existing open architecture principles. For example integration module 1218 can include pre-built interfaces to major existing CAD systems as well as be customizable in any desired fashion while also being capable of using standards-based services, such as XML web services, which can allow for low cost access to a variety of systems.

[0139] Message priority engine 1214, as shown in exemplary FIG. 12, can apply a priority weighting to inbound messages that can represent a relevance determinant relating to the message’s credentials for acceptance by ILM 1208. Message priority engine 1214 can then return a priority score for each message. Exemplary factors used in the determination of a priority score can be different, depending on the type of message received. For example, for messages that may be a direct response to requests by a call handler (i.e. “solicited messages”) can have a unique identifier of an active call, may have originated within a specified timeframe after the closing of a call and can include a custom code requested vocally by a call handler.

[0140] A message received by message priority engine 1214 that is received from a recognized number can be weighted as it may be from a recognized list of emergency personnel numbers, part of a private watch list maintained by one or more sources or may otherwise contain a special code added by the phone number carrier into the automatic number identification/automatic location information (ANIALI). A message from a known number where previous messages may have been received from this number can be weighted as it may exist in the CAD or RMS databases 1220, may exist in an ILM database and may carry a relevance ranking and/or may exist in a log of outbound calls or SMS made by communication center 1222.

[0141] Still other messages weighted by the message priority engine 1214 can include messages that are determined to relate to a current call, for example an active or queued caller ID in the CAD system 1220, a message that is referenced in notes from a call handler, such as cell numbers of third parties collected by responders during an incident in progress or cell numbers mentioned by a caller during a call, and any messages that are included on a daily active responders list. Also, some messages that are received may have been determined to originate from a location in close proximity to an existing incident location. This location can be determined by, for example, tower triangulated position, phone internal GPS (x, y or z coordinates), phone billing address and/or any other matching physical criteria, for example speed, path or direction or the like.

[0142] The message priority engine 1214 may also be fully customizable, for example allowing for the changing of any weighting or other priorities to the internal rules. Examples of this can include, but are not limited to, a desire to assign more weight of messages originating from a city employee, creation of a rule based on the frequency of messages from a given number or any other desired rules. Additionally, in some further exemplary embodiments, the message priority

engine **1214** can include any desired pre-defined rules and/or protocols for looking up or retrieving information.

[0143] The triage interface **1212** of ILM **1208** can allow for a call handler to process inbound messages with various actions. These actions can include, but are not limited to, associating a message with an existing active or closed call (e.g. passing information over), changing a priority level, viewing an explanation of the ILM engine priority score (e.g. when desired criteria are met), annotating or adding information to a message and/or opening a new call and passing it over to the CAD **1220**. Additionally, the triage interface **1212** can support multiple users and may also allow for any number of users to process the same message queue.

[0144] Reporting interface **1216** can provide the ability to assess the performance of ILM **1208**. Reporting interface **1216** may also be able to assess performance without exposing or revealing any confidential information, such as text or images, which may be contained in messages routed through ILM **1208**. Reporting interface **1216** may also provide detailed information as to the status of ILM **1208**, which can include, but is not limited to, reports by cell phone carrier (such as time to delivery, dropped messages and non-compliant text formats, among others), a real time queue of inbound and outbound messages, including, but not limited to, routing path, source and target mail servers and messages awaiting prioritization. Reporting interface **1216** can also provide statistics, including, but not limited to, volume by hour and size of the messages, act as a message prioritization monitor, for example showing time to completion, categorized priorities, frequency of each score, detailed explanation of each score and other related information, provide an exception list and provide configuration features, such as, but not limited to, a source of prioritization, weights, routers, archives, CAD system access, RMS access and archive locations. Additionally, reporting interface **1216** can also provide a log of manual message processing, for example allowing for reprioritization.

[0145] Another element of ILM **1208** as shown in exemplary FIG. **12** is portable communications module **1210**. Portable communications module **1210** may include a variety of functions, such as providing SMTP service that can be capable of filtering inbound traffic and securing sending outbound traffic to cell phone companies/carriers/providers. Portable communications module **1210** can be a standalone SMTP mail server, or any other type of mail server. For example, portable communications module **1210** can provide for secure communications, such as secure SMTP, and encryption. Portable communications module **1210** can also restrict inbound and outbound traffic to a list of authorized cell phone company servers, perform “keep alive” testing continuously to ensure availability and have a fault-tolerant and redundant design. Also, portable communications module **1210** can also have proxy support for emergency centers, for example preventing relevant email from mixing with regular email traffic and also may be capable of providing hosted support, for example translating and routing inbound messages to a desired emergency center.

[0146] In another exemplary embodiment, and referring to exemplary FIG. **13**, an architectural structure **1300** of ILM **1302** may be shown. Here, portable communications module **1210** (shown here as SMTP/POP3 Server **1314**) can include, for example, an email processing service **1312**, for example a Windows®-based service, which may link a message processing implementation **1318** component through a message

processing interface **1316**. These elements may then handle any solicited call messages, as described previously. Further, email processing service **1312** can have a second interface **1310** to message priority engine **1306** that can handle unsolicited call messages. Both interfaces **1310** and **1316** can be accessible publicly, for example, to allow third parties to develop and plug-in custom engines as desired.

[0147] Still referring to exemplary FIG. **13**, incoming messages can initially pass through message processing interface **1316**, which may check for validation and match a message with an existing call record. As desired, matched mail messages may or may not be stored in ILM database **1322**.

[0148] In, in exemplary FIG. **13**, an incoming mail message fails to generate a match with a call record, it may be passed to the message priority engines **1306** and **1308** to obtain a priority weighting. The messages can be delegated to any desired configurable message priority engines or multiple engines that can allow for the ability to prioritize on a range of criteria. For example, if first engine **1306** matches and processes the message, it can return a weighting score. Alternatively, if first engine **1306** does not match the message, it may be passed to the next priority engine and so forth until it can be processed by priority engine **N 1308**. Additionally, as stated above, public access or interfaces may be made for any priority engine, allow third parties to develop and plug-in any desired custom engine.

[0149] In a further exemplary embodiment, reporting and administrative functions of ILM **1302** can be access through an incident linked multimedia web service **1324**. The incident linked multimedia web service **1324** can include any of a number of features or modules. For example ILM webs service **1226** may allow for the exposure of ILM data from ILM database **1322** to external CAD systems, for example system **1338** and ILM triage interface **1340**, through any standard web service, for example any standard XML web service. This data can include unsolicited mail messages and attachments (if any). Therefore, any message that may not be automatically prioritized or categorized with a priority engine (e.g. priority engines **1306** and **1308**) can be held for process in triage interface **1340**.

[0150] Another module may be reporting service interface **1328**. Interface **1328** can be used to provide useful web-based reports to a user. A further exemplary module may be administration module **1330** which can allow a user to configure ILM system **1302**, manage any user accounts and perform any other desired administrative tasks.

[0151] Authentication module may then be used to govern any or all access to web service **1324**. For example, before or after any action is taken through modules **1326** through **1330**, a user attempting to perform that action may be authenticated or otherwise be shown to have or not have appropriate access. Additionally, triage interfaces **1336** and **1340** in CACH **1334** and external CAD systems **1338** may be presented on a client side of ILM web service **1324** and may allow the service API to query for unsolicited messages in order that the user may manually process them.

[0152] It will be appreciated that the apparatuses, systems and methods described herein have many uses outside the context of emergency situations and may be used by non-emergency call handling systems. For example, information services that may be enhanced through visual communication, such as services providing driving directions, may also utilize various aspects of the embodiments described herein.

[0153] While the invention has been illustrated and described in the drawings and foregoing description, such illustration and description is to be considered as exemplary and not restrictive in character. Embodiments of the invention and minor variants thereof have been shown and described. Those skilled in the art will appreciate variations of the above-described embodiments that fall within the scope of the invention. Protection is desired for all changes and modifications that come within the scope and spirit of the invention. Accordingly, the invention is not limited to the specific examples and illustrations discussed above.

What is claimed:

- 1. An information processing system, comprising:
 - a communication module operable to send first data with a unique identifier to a communication device configured to receive the first data and reply with second data, the second data containing the unique identifier of the first data; and
 - a data receiving module configured to receive incoming data, filter incoming data and weight incoming data.
- 2. The information processing system of claim 1, wherein the first data and the second data are one of MMS messages and SMS messages.
- 3. The information processing system of claim 1, wherein the incoming data is one of an MMS message and an SMS message.
- 4. The information processing system of claim 1, wherein the data receiving module further comprises at least one message priority engine that prioritizes incoming data according to at least one of the contents of the incoming data, the source of the incoming data and the transmission location of the incoming data.
- 5. The information processing system of claim 1, further comprising at least one message priority engine that prioritizes incoming data according to user-customizable rules.
- 6. The information processing system of claim 1, further comprising a triage interface in the data receiving module operable to associate the incoming data with data at a call center.
- 7. The information processing system of claim 1, further comprising a portable communications module in the data receiving module operable to provide secure incoming and outgoing communications from the data receiving module.

- 8. A method of routing information, comprising:
 - calling a call center from a communication device;
 - sending a first MMS from the call center to the communication device, the MMS having a unique identifier included therein;
 - replying to the MMS from the call center with the communication device with a second MMS, the second MMS including the unique identifier;
 - filtering the second MMS through a data processing module; and
 - associating the second MMS with the call from the communication device to the call center.
- 9. The method of claim 8, wherein the filtering and associating are accomplished through recognition of the unique identifier.
- 10. The method of claim 8, further comprising sending, in the second MMS message, one of text, image, video or audio data.
- 11. A system for routing data, comprising:
 - at least one MMS message sent from a communication device to a data processing module; and
 - at least one engine for that determines if the at least one MMS message is a solicited message related to a phone call made to a call center and associates the at least one MMS message with the phone call if it is a solicited message or evaluates other aspects of the at least one MMS message if the at least one MMS message is not solicited.
- 12. The system for routing data of claim 11, wherein the at least one engine determines if the at least one MMS message is solicited by evaluating the presence of a unique identifier attached to the at least one MMS message.
- 13. The system for routing data of claim 11, wherein the at least one engine determines if the at least one MMS message is from a recognized phone number.
- 14. The system for routing data of claim 13, further comprising a database of known phone numbers.
- 15. The system for routing data of claim 11, wherein the at least one engine determines if the at least one MMS message is from an existing incident location.
- 16. The system for routing data of claim 11, wherein the at least one engine is a message priority engine that provides a weighted ranking to at least one MMS message.
- 17. The system for routing data of claim 11, wherein the at least one MMS message contains one of text, audio, video and image data.

* * * * *