



US009237431B2

(12) **United States Patent**
Wang et al.

(10) **Patent No.:** **US 9,237,431 B2**
(45) **Date of Patent:** **Jan. 12, 2016**

(54) **METHOD AND APPARATUS FOR EXTENDED EMERGENCY SERVICE**

(75) Inventors: **Xiaomei Wang**, Walnut Creek, CA (US);
Loc Vo, Pleasant Hill, CA (US)

(73) Assignee: **Verizon Patent and Licensing Inc.**,
Basking Ridge, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 623 days.

(21) Appl. No.: **12/578,316**

(22) Filed: **Oct. 13, 2009**

(65) **Prior Publication Data**

US 2011/0086607 A1 Apr. 14, 2011

(51) **Int. Cl.**

H04W 76/00 (2009.01)

H04W 4/22 (2009.01)

H04M 3/51 (2006.01)

H04M 3/42 (2006.01)

H04W 4/12 (2009.01)

(52) **U.S. Cl.**

CPC **H04W 4/22** (2013.01); **H04M 3/5116** (2013.01); **H04W 76/007** (2013.01); **H04M 3/42382** (2013.01); **H04M 2207/206** (2013.01); **H04M 2242/04** (2013.01); **H04W 4/12** (2013.01)

(58) **Field of Classification Search**
USPC 455/521, 456.1-457, 414.1, 466
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2001/0036174 A1* 11/2001 Herring 370/352
2002/0078151 A1* 6/2002 Wickam et al. 709/204
2002/0197977 A1* 12/2002 Brooks 455/404
2005/0282518 A1* 12/2005 D'Evelyn et al. 455/404.1
2007/0025541 A1* 2/2007 Mohler 379/220.01
2007/0206533 A1* 9/2007 Wiatrowski et al. 370/329
2009/0186596 A1* 7/2009 Kaltsukis 455/404.2


* cited by examiner

Primary Examiner — Daniel Lai

(57) **ABSTRACT**

An approach is provided for receiving a voice-based emergency call and routing it to a local Public Safety Answering Point (PSAP) along with anchoring information identifying the caller and their location. The PSAP may provide options for the caller to choose to use non-voice-based messaging service concurrent with the voice-based emergency call. If the caller desires and chooses to communicate via non-voice-based messages, then a text messaging application at the PSAP is used to communicate with the caller. The PSAP utilizes the anchoring information obtained from the concurrent voice-based emergency call when communicating with the caller.

13 Claims, 8 Drawing Sheets






FIG. 1





FIG. 2A

FIG. 2B






FIG. 3

FIG. 4




FIG. 5





FIG. 6






FIG. 7

1

METHOD AND APPARATUS FOR EXTENDED EMERGENCY SERVICE

BACKGROUND INFORMATION

Modern telecommunications services, particularly wire-
less mobile communication devices, are essential public
safety tools. During emergencies, these devices are indispen-
sible for contacting the appropriate people or authorities.
Traditionally, a person would use a mobile device to call for
help when an emergency arises. During an emergency call,
the caller identity and caller location (i.e., anchoring infor-
mation) would be provided to the public safety answering
point (PSAP) to assist the emergency handling. However,
there are certain circumstances when the mobile device user
may not be able to make a voice call (e.g., when the user
cannot speak because of injuries, or when the user must hide
his or her call for help from an assailant who is still at the
scene). Under these circumstances, the person may be forced
to use non-voice communications (e.g., text messaging,
instant messaging, or electronic mail) because of the inher-
ently "silent" nature of these types of communications. These
types of non-voice communications, however, present a
unique set of problems for use during emergencies, especially
on the lack of anchoring information to the PSAP.

Therefore, there is a need for an approach that enables a
user to easily and discretely communicate with emergency
call operators using non-voice messages.

BRIEF DESCRIPTION OF THE DRAWINGS

Various exemplary embodiments are illustrated by way of
example, and not by way of limitation, in the figures of the
accompanying drawings in which like reference numerals
refer to similar elements and in which:

FIG. 1 is a diagram of a system capable of providing
emergency text-based messaging according to an exemplary
embodiment;

FIGS. 2A and 2B are, respectively, a diagram of an emer-
gency messaging platform and a diagram of a user device
capable of concurrently communicating over a voice channel
and a messaging channel, according to various exemplary
embodiments;

FIG. 3 is a flowchart of processes for supporting text-based
messaging according to an exemplary embodiment;

FIG. 4 is a flowchart of a process for a Public Safety
Answering Point to support text-based emergency messag-
ing, according to an exemplary embodiment;

FIG. 5 is a flowchart of a process for routing a text-based
emergency message initiation, according to an exemplary
embodiment;

FIG. 6 is a diagram of a mobile device capable of using text
messaging as part of an emergency service session, according
to an exemplary embodiment; and

FIG. 7 is a diagram of a computer system that can be used
to implement various exemplary embodiments.

DESCRIPTION OF THE PREFERRED EMBODIMENT

A preferred method and apparatus for extending emer-
gency call services to include non-voice messages are
described. In the following description, for the purposes of
explanation, numerous specific details are set forth in order
to provide a thorough understanding of the preferred embodi-
ments of the invention. It is apparent, however, that the pre-
ferred embodiments may be practiced without these specific

2

details or with an equivalent arrangement. In other instances,
well-known structures and devices are shown in block dia-
gram form in order to avoid unnecessarily obscuring the
preferred embodiments of the invention.

Although various exemplary embodiments are described
with respect to a mobile device, it is contemplated that these
embodiments have applicability to any device capable of
communicating over a network using voice and non-voice
technologies.

FIG. 1 is a diagram of a system capable of providing
emergency text-based messaging according to an exemplary
embodiment. Emergency calls, or 911 calls, are one example
of a type of call that relies on the identification and location of
the calling party to be determined in order to provide a ser-
vice. Thus, while various embodiments are described herein
in relation to emergency calls, the principles may also be
utilized in any type of voice call that utilizes location and
identification information about the calling party when pro-
viding a service. In system 100, one or more mobile devices
101a-101n are configured to communicate over a wireless
network 103103 using voice sessions as well as other non-
voice sessions, e.g., short messaging service (SMS),
enhanced messaging service (EMS), multimedia messaging
service (MMS), instant messaging (IM), etc. Mobile devices
101a-101n may be any cellular phone, radiophone, satellite
phone, smart phone, wireless phone, or any other suitable
mobile device, such as a personal digital assistant (PDA),
pocket personal computer, tablet, customized hardware, etc.

Enhanced 911 (E911) service is a feature of the emer-
gency call system that automatically associates a physical address
with a calling party's Automatic Number Identification
(ANI). In other words, the E911 service provides emergency
responders with the location of the emergency without the
calling party having to provide such information. The final
location of the 911 operator handling the call is known as a
Public Safety Answering Point (PSAP). Traditionally, PSAPs
handle emergency voice calls without any capability to utilize
other communication means. In general, the ANI information
for a 911 caller is used to look up the address of the calling
party in an Automatic Location Identification (ALI) database.
For mobile devices, identifying the nearest PSAP for the
caller can be enhanced by including geographical or spatial
information (for determining local information) in the tele-
phone call set-up as well. As shown in the example of FIG. 1,
a constellation of global positioning system (GPS) satellites
111 can communicate with the mobile devices 101a-101n to
provide such location information.

By way of example, one or more mobile devices 101a-
101n may be configured to determine corresponding spatial
positioning information through conventional satellite posi-
tioning system (SPS) technology, such as GPS technology;
however, any suitable navigational or location determination
technology may be utilized, such as advanced forward link
trilateration (A-FLT), assisted-GPS (A-GPS), enhanced cel-
lular identification (CELL-ID), wireless area network
(WLAN) positioning, etc. SPS technology utilizes a constel-
lation of satellites that transmit signals to receivers (not
shown) of, for example, one or more mobile devices 101a-
101n, so that the receivers may determine corresponding
spatial positions (or locations), speeds, directions, and/or tim-
ing for mobile devices 101a-101n.

Public Safety Answering Point (PSAP) 107 operates in
conjunction with an emergency messaging platform 109 to
provide a hybrid capability. That is, the mobile devices 101a-
101n can utilize, according to certain embodiments, a
"hybrid" approach to obtaining emergency service by
employing both a voice session and an SMS session. As

shown, each of the mobile devices **101a-101n** can utilize an emergency messaging module **105a-105n**, respectively, that facilitates the concurrent communication sessions for the purposes of providing emergency services. This approach stems from the recognition that if the caller is unable to speak, is hearing-impaired, or otherwise wishes to communicate “quietly,” then the caller must use additional, teletype equipment or software to be able to communicate with the operator at the PSAP **107**.

In system **100**, according to certain embodiments, one or more networks, such as data network **113**, service provider network **115**, telephony network **117**, and/or wireless network **103**, are provided to handle various communication sessions, voice communications as well as non-voice communications. Networks **103** and **113-117** may be any suitable wireline and/or wireless network. For example, telephony network **117** may include a circuit-switched network, such as the public switched telephone network (PSTN), an integrated services digital network (ISDN), a private branch exchange (PBX), or other like network.

Wireless network **103** may employ various technologies including, for example, code division multiple access (CDMA), enhanced data rates for global evolution (EDGE), general packet radio service (GPRS), mobile ad hoc network (MANET), global system for mobile communications (GSM), Internet protocol multimedia subsystem (IMS), universal mobile telecommunications system (UMTS), etc., as well as any other suitable wireless medium, e.g., microwave access (WiMAX), wireless fidelity (WiFi), long term evolution (LTE), satellite, and the like. Meanwhile, data network **113** may be any local area network (LAN), metropolitan area network (MAN), wide area network (WAN), the Internet, or any other suitable packet-switched network, such as a commercially owned, proprietary packet-switched network, such as a proprietary cable or fiber-optic network.

Although depicted as separate entities, networks **103** and **113-117** may be completely or partially contained within one another, or may embody one or more of the aforementioned infrastructures. For instance, service provider network **115** may embody circuit-switched and/or packet-switched networks that include facilities to provide for transport of circuit-switched and/or packet-based communications. It is further contemplated that networks **103** and **113-117** may include components and facilities to provide for signaling and/or bearer communications between the various components or facilities of system **100**. In this manner, networks **103** and **113-117** may embody or include portions of a signaling system 7 (SS7) network, or other suitable infrastructure to support control and signaling functions. As such, the conjunction of networks **103** and **113-117** may be adapted to facilitate the remote control and tracking services of system **100**.

Under the scenario of FIG. 1, emergency messaging platform **109** is maintained by a service provider, and thus, can interact with the PSAP **107** via the service provider network **115**. The PSAP **107**, thus, may provide the capability for the caller to employ non-voice-based messaging service concurrent with the voice-based emergency call. While specific reference will be made hereto, it is contemplated that system **100** may embody many forms and include multiple and/or alternative components and facilities. In one embodiment, the platform **109** can be deployed as part of the PSAP **107**.

Although the hybrid approach is described with respect to mobile devices **101a-101n**, it is contemplated that this approach is applicable to any device capable of supporting a voice call and a non-voice form of communication—e.g., computing device **119**. Computing device **119** may be any suitable computing device, such as a voice over internet pro-

ocol (VoIP) phone, skinny client control protocol (SCCP) phone, session initiation protocol (SIP) phone, IP phone, personal computer, softphone, workstation, terminal, server, etc.

As mentioned, one type of voice call in particular that a mobile device (e.g., mobile device **101a**) may initiate involves an emergency call to a 911 operator within PSAP **107**. For this purpose, the wireless network **103** may provide services and features that allow it to identify and locate the caller. In particular, the wireless network **103** includes an anchoring service that can identify the location of the caller and, based on that information, locate a local 911 operator to handle the call. Consequently, the anchoring service can route the call to the local 911 operator and provide the operator both the identity of the caller and the location of the caller. Any of the various anchoring services for wired, wireless, and voice over IP (VoIP) networks are contemplated.

Based on the determination of the local 911 operator, the wireless network **103** can communicate through telephony network **117** to the local Public Safety Answering Point **107**. At the PSAP **107**, operators have access to platform **109** that allows each operator to handle voice calls and non-voice messaging applications.

According to one embodiment, the platform **109** allows the 911 operator at the PSAP **107** to communicate with a caller utilizing either a voice call, a non-voice messaging method, or both. A 911 caller may for example, be hearing impaired, have speech difficulty, be having a medical emergency or be in a situation where it is not preferable to communicate by voice with the operator. The system **100** allows both voice and non-voice communication to handle such circumstances.

FIGS. 2A and 2B are, respectively, a diagram of an emergency messaging platform and a diagram of a user device capable of concurrently communicating over a voice channel and a messaging channel, according to various exemplary embodiments. As seen in FIG. 2A, emergency messaging platform **200** may comprise computing hardware (such as described with respect to FIG. 7), as well as include one or more components configured to execute the processes described herein for providing the emergency services of system **100**. In one implementation, platform **200** includes communication interface **201**, controller (or processor) **203**, memory **205**, messaging module **207**, and user interface module **209**. Platform **200** may also communicate with one or more repositories, such as an anchoring information database **211**. Users may access platform **200** (or the features and functionality provided thereby) via devices **101a-101n**, and **107**. While specific reference will be made to this particular implementation, it is also contemplated that platform **200** may embody many forms and include multiple and/or alternative components. For example, it is contemplated that the components of platform **200** may be combined, located in separate structures, or separate locations.

According to one embodiment, platform **200** embodies one or more application servers accessible to **101a-101n**, and **107** over one or more networks **103** and **113-117**. Platform **200** may provide a user interface, e.g., web portal or other networked application, to permit user to access the features and functionality of platform **200** via devices **101a-101n** and **119**. According to certain embodiments, user interface module **209** may be configured via a web browser or other network-based application or system, such as a voice browser or interactive voice recognition system.

Messaging module **207** provide messaging services in support of emergency communications initiated by the devices **101a-101n**. According to exemplary embodiments, messaging module **207** may be configured to generate control signals

for transmission to device **101a** utilizing any suitable bearer, such one or more call control setup messages, short messaging service (SMS) messages, enhanced messaging service (EMS) messages, multimedia messaging service (MMS) messages, electronic mail, files, or any other suitable bearer, as well as any suitable combination thereof. In particular implementations, these bearer mediums may include control signals in various forms, including attention (AT) commands, menu traversal paths, function codes, voice data, dual-tone multi-frequency (DTMF) signals, scripts, strings, parameters, object variables, and the like. It is noted that these control signals can be used in lieu of “software code,” and therefore, may be directly integrated into the control logic of mobile device **101a**, thereby requiring less processing and hence, less power. It is contemplated, however, that coded instructions may also be utilized.

Additionally, platform **200** may include one or more controllers (or processors) **203** for effectuating the aforementioned features and functionality of the emergency services of system **100**, as well as one or more memories **205** for permanent and/or temporary storage of one or more of the aforementioned variables, parameters, information, signals, etc. In this manner, the features and functionalities of emergency messaging may be executed by controller(s) **203** and/or memories **205**, such as in conjunction with one or more of the various components of platform **200**.

In one embodiment, the platform **200** includes a voice call application **213**, which allows an operator to communicate with a caller over a voice traffic channel. The voice call application **213** also has access to anchoring information database **211**, which stores anchoring information received by the platform **200** as the call is routed to the platform **200**. The anchoring information may, for example, include the identity and the location of the caller to assist in handling the emergency call.

The platform **200** also includes a text message module **207** that permits the operator to communicate using text messages, and/or other non-voice-based messages. Although the text message module **207** may be configured to communicate with the wireless network **103** to acquire the anchoring information, this information can be retrieved from the anchoring information database **211**. The text message module **207** utilizes the anchoring information to aid in communicating with the caller using non-voice-based messages.

On the user side, as shown in FIG. 2B, a user device **250**, which may be a mobile device (e.g., mobile device **101a** of FIG. 1) or a computer **119**, includes a messaging module **251** that is configured to establish a text-based messaging session, as well as a voice module **253** configured to establish a voice-based call. Such voice-based call can be traditional plain-old-telephone service (POTS) calls or packetized voice calls (e.g., VoIP). These communication sessions can occur concurrently during an emergency call. It is noted that these communication sessions can be established over a circuit-switched network, a packet-switch network, or a combination thereof. Thus, communication interface **255** can be appropriately configured depending on the transport systems and networks. Although only a single interface **255** is shown, it is noted that multiple communication interfaces may be utilized, depending on the technologies involved. Moreover, the user device **250** employs a user interface module **257** to enable control by the user of the device of these various communication sessions; in one embodiment, the user interface module **257** provides a graphical user interface (GUI) as shown in FIG. 6. Additionally, a controller **259** is configured to coordinate the concurrent communication sessions provided by the messaging module **251** and voice module **253**; for example, the

controller **259** generates the appropriate signaling to control the communication interface **255** for transmissions over the voice channel and the messaging channel.

FIG. 3 is a flowchart of processes for supporting text-based messaging according to an exemplary embodiment. Initially, in step **301**, a caller, using one of the mobile devices **101a-101n**, places an emergency voice call (e.g., 911 call) over the wireless network **103**. In step **303**, the wireless network **103** routes the emergency voice call to the PSAP **107** that is, for example, nearest the caller (denoted as the “local PSAP”). As part of this routing, the wireless network **103** identifies the caller and location, determines the local PSAP (which in this example is PSAP **107**), and then routes the call along with anchoring information to the PSAP **107**.

By way of example, at the PSAP **107**, an automated message may be provided to the caller via an interactive voice response (IVR) unit (not shown): “Press 1 for text messaging, press 2 to speak to the operator, or hold on the line for the operator.” If the caller presses “1”, then the PSAP **107** can initiate a text messaging service provided by the platform **109**, which generates and transmits an introductory text message to the caller. According to certain embodiments, by having the caller first utilize a voice call for the emergency service, the wireless network **103** can utilize the existing services, e.g., E911 anchoring service, to locate the user. Additionally, the SMS delivery time is enhanced as the mobile device (e.g., **101a**) is already on a traffic channel, and thus, negates the need to page the mobile device.

As noted, mobile devices **101a-101n** each contain an emergency messaging module **105a-105n** to facilitate sending and receiving emergency messages between the devices **101** and PSAP **107**. The emergency messaging modules **105a-105n** enable the transmission of non-voice messages between the mobile devices **101a-101n** and the PSAP **107**. As discussed above, there are certain emergency situations where a user may not prefer to make a voice call for assistance and must rely on non-voice communications such short message service (SMS), multimedia messaging service (MMS), instant messaging (IM), and electronic mail. In this manner, the emergency messaging feature can be an end-to-end service, in which protocols are executed at the devices **101a-101n** by the emergency messaging modules **105a-105n** and at the PSAP **107** by the platform **109**.

Typically, a text message is associated with a “To:” field, or the like, to specify addressing information of a recipient, and a “From:” field to indicate the source. In generating the text message, the emergency platform **109** via messaging module **207** can fill in this “To:” address using the anchoring information provided with the initial voice call. Also, the messaging module **207** can fill in the “From:” address using a pre-determined address (e.g., as to notify the recipient that this is part of an emergency service). For example, the address may be of a form similar to “Operator34@PSAP.ca.gov”. In this way, any reply message can be quickly routed and delivered to a specific PSAP and a specific operator. Other forms and types of addresses may be utilized depending on the text messaging application being utilized.

In one embodiment, the initial text message (as initiated by the PSAP **107**) may provide further instructions to the caller. By having the PSAP **107** send the first SMS to the E911 user with a routable address, the wireless network **103** does not have to guess where and how to route an SMS message to a generic short code 911, for example; or whether any local PSAP already have developed the capability to support the messaging service.

The message, for example, may ask the caller to confirm they are making an emergency 911 “call” and then tell them

not to terminate the voice call. Also messages can be sent to instruct the caller to drop the voice call if it is determined that a true emergency does not exist so as to free up the voice channels. Other instructional messages may include sending a prompt to the caller to re-initiate the voice call if a location update is needed or if the voice call is inadvertently dropped.

In response to receiving the emergency call, the PSAP 107 may send an automatic message to the caller, in step 305, prompting the caller on how to proceed. For example, the PSAP 107, via an IVR, may prompt the caller over the voice call to select the following options, e.g.: “Press 1 for Speak to the Operator” or “Press 2 to Use Text Messaging”. According to one embodiment, the default operation may be for the PSAP 107 to automatically initiate a voice-based connection if no selection is received from the caller after a predetermined time period (e.g., about 5 seconds). In step 307, the caller selects an option to proceed either using voice-based communication or non-voice-based communication; in this manner, the PSAP 107 communicates using the selected communication option. Accordingly, the PSAP 107 operates in conjunction with the emergency messaging platform 200 to provide the messaging option; in addition, the platform 200 may itself control the voice call with using the voice call application 213. In step 309, the caller and the PSAP 107 communicate per the caller’s selection until the emergency is satisfactorily addressed.

One benefit of the process described with respect to FIG. 2 is that the anchoring services already in place for handling emergency voice calls may be utilized to provide the needed information for communicating with the caller using non-voice message applications, such as email, IM, SMS, and MMS. Also, PSAP 107 can use the commonly available solution such as a short code (if for example, the PSAP 107s want to go through an aggregator to a wireless operator), or email address (if a public data network, e.g., Internet, is preferred). That is, if short code is used, the text messages could be made free-of-charge to the 911 user; however, using short code requires the message to go through an aggregator to reach the wireless network 103.

FIG. 4 is a flowchart of a process for a Public Safety Answering Point to support text-based emergency messaging, according to an exemplary embodiment. For the purposes of illustration, the process is described with respect to the emergency message platform 109 operating in conjunction with the PSAP 107 (but as a separate entity). However, it is contemplated that the emergency messaging platform 109 can reside within the PSAP 107, or otherwise integrated. In step 401, an emergency call is received at the PSAP 107 and; or by the voice call application 213, if the platform 200 is so configured. As described in more detail below, the PSAP 107 allows an operator to handle the voice-based 911 call as presently performed. As part of handling such a call, the PSAP 107 receives anchoring information, in step 403, about the caller (i.e., obtained from the concurrent voice-based emergency call). For example, typical anchoring information relates to the caller identity such as the ANI information for that calling number and the caller’s geographic location which can be provided through GPS information or other services within the wireless network. This anchoring information can then be supplied to the emergency messaging platform 109.

Typically, at this point, the operator would respond to the incoming voice call by opening a voice communication channel and talking with the caller. However, the caller, as described above, may not prefer to have a voice-based session with the operator. Thus, in step 405, a determination is made whether or not the caller desires a voice-based session or a

non-voice-based session. If a voice-based session is desired, then the anchoring information is already available and the voice call proceeds. If, however, a non-voice session is desired, then the voice platform shares the anchoring information, in step 407, with messaging module 207, which may provide one or more messaging services, e.g., email, IM, MMS, SMS, and the like. Sharing of the anchoring information may be accomplished by the operator manually entering the information within the messaging module 207 or by automatic messaging passing (or signaling) between the PSAP 107 and the messaging module 207 of emergency messaging platform 109. In step 409, the non-voice emergency session is established, so that the caller can communicate with the operator using one of the various messaging services supported by the messaging module 207.

FIG. 5 is a flowchart of a process for routing a text-based emergency message initiation, according to an exemplary embodiment. By way of example, this process is described with respect to text messaging (e.g., SMS), it is contemplated that other messaging services can be utilized. While it may be useful to allow an emergency call to be initiated by a caller sending a text message to “911”, there are benefits to having the 911 call be a voice call—e.g., the operator can listen in on the activities surrounding the caller. Thus, even though text-based, or non-voice-based, emergency messages are contemplated, it can be beneficial for the initial communication to be via a voice traffic channel. According to the flowchart of FIG. 5, if a text-message 911 call is initiated by a mobile device (e.g., mobile device 101a) and received by a messaging gateway (not shown) of the wireless network 103, in step 501, then the gateway can be configured to send a reply. In particular, the network 103 can send a text message, in step 503, that includes instructions for initiating a 911 voice call. Such instructions can be concise, but of sufficient length to convey that the caller initiate a voice call by dialing the digits “911.” Then, in step 505, when the voice call is initiated, the call is routed to the local PSAP 107 with the anchoring information of the caller.

Optionally, after establishment of the emergency voice session with the mobile device 101a, the messaging platform 109, in communication with the PSAP 107, can automatically establish text messaging session with the device 101a, per step 507.

FIG. 6 is a diagram of a mobile device capable of using text messaging as part of an emergency service session, according to an exemplary embodiment. In this example, a user may employ mobile device 600 to submit an emergency call, whereby a non-voice session is established as part of the emergency service. For illustrative purposes, mobile device 600 is described with respect to a mobile phone, such as a cellular phone, configured to provide a GUI 601 to users via display 603.

GUI 601 includes a text box 601a that illustrates the messages between the user and the operator of the PSAP 107. In this example, the operator confirms whether the emergency text messaging session is intended, and to remain on the voice channel: “Are you making an emergency 911 call? Please reply to this message with ‘Y’ or ‘N.’ Please do not end the voice call.” As shown, the user enters a response of “Y” to indicate that the emergency service is intentionally invoked. Another textbox 601b is designated for input by the user. Under this example, the user is trapped in the basement of the user’s home, either inadvertently or deliberately because the user is seeking a place of safety, for instance, from intruders. Hence, the user can type “trapped in basement” in the textbox 601b. The ability to remain “silent” permits the user to stay out of potential danger—i.e., detection by the intruders. In

one embodiment, a status box or bar **601c** can be displayed to alert the user if the voice call is somehow dropped. If the status were "OFF" as seen in status box **601d**, this indication can be tied to a series of other options and menus to the user (e.g., box **601e**), so that the user may automatically reestablish the voice communication without having to speak. Under such a scenario, the operator can be automatically notified that the voice call has been terminated, and that the caller will attempt to another voice call. In this manner the PSAP **107** and platform **109** would not treat the incoming call as a new call.

In this example, mobile phone **600** includes one or more transducers (e.g., speakers) **605** to output audible signals to the user. Cursor buttons **607**, keypad **609**, and microphone **611** enable users to interact with GUI **601** of display **603**. As such, mobile device **600** is, in exemplary embodiments, also capable of speech synthesis and voice recognition. Moreover, the display **603** can be a touch-screen, such that controllers and buttons can be readily activated; for example, the reestablish call box **601e** can be a button that activates the reestablishment of the call upon selection.

The described processes, according to certain embodiments, provide a number of benefits. One benefit is that the existing methods and techniques for identifying and locating a 911 caller may be utilized as well as the existing methods for providing that information to a local PSAP. Because the mobile device will already have a voice channel open, the speed of sending and receiving a text message is improved. Also, there is no need to change a portion of the network or a mobile device. Further, any mobile device with text message capabilities can communicate with a PSAP offering a non-voice based message system. In addition, the voice call and the text message session can occur in parallel so that the PSAP may monitor both the background noise and sounds of the voice call as well as the specific text messages being sent and received; such enhanced communications can contribute to resolution of the emergency situation.

The processes described herein for providing emergency messaging may be implemented via software, hardware (e.g., general processor, Digital Signal Processing (DSP) chip, an Application Specific Integrated Circuit (ASIC), Field Programmable Gate Arrays (FPGAs), etc.), firmware or a combination thereof. Such exemplary hardware for performing the described functions is detailed below.

FIG. 7 illustrates computing hardware (e.g., computer system) upon which these embodiments can be implemented. The computer system **700** includes a bus **701** or other communication mechanism for communicating information and a processor **703** coupled to the bus **701** for processing information. The computer system **700** also includes main memory **705**, such as random access memory (RAM) or other dynamic storage device, coupled to the bus **701** for storing information and instructions to be executed by the processor **703**. Main memory **705** also can be used for storing temporary variables or other intermediate information during execution of instructions by the processor **703**. The computer system **700** may further include a read only memory (ROM) **707** or other static storage device coupled to the bus **701** for storing static information and instructions for the processor **703**. A storage device **709**, such as a magnetic disk or optical disk, is coupled to the bus **701** for persistently storing information and instructions.

The computer system **700** may be coupled via the bus **701** to a display **711**, such as a cathode ray tube (CRT), liquid crystal display, active matrix display, or plasma display, for displaying information to a computer user. An input device **713**, such as a keyboard including alphanumeric and other

keys, is coupled to the bus **701** for communicating information and command selections to the processor **703**. Another type of user input device is a cursor control **715**, such as a mouse, a trackball, or cursor direction keys, for communicating direction information and command selections to the processor **703** and for controlling cursor movement on the display **711**.

According to an embodiment of the invention, the processes described herein are performed by the computer system **700**, in response to the processor **703** executing an arrangement of instructions contained in main memory **705**. Such instructions can be read into main memory **705** from another computer-readable medium, such as the storage device **709**. Execution of the arrangement of instructions contained in main memory **705** causes the processor **703** to perform the process steps described herein. One or more processors in a multi-processing arrangement may also be employed to execute the instructions contained in main memory **705**. In alternative embodiments, hard-wired circuitry may be used in place of or in combination with software instructions to implement the embodiment of the invention. Thus, embodiments of the invention are not limited to any specific combination of hardware circuitry and software.

The computer system **700** also includes a communication interface **717** coupled to bus **701**. The communication interface **717** provides a two-way data communication coupling to a network link **719** connected to a local network **721**. For example, the communication interface **717** may be a digital subscriber line (DSL) card or modem, an integrated services digital network (ISDN) card, a cable modem, a telephone modem, or any other communication interface to provide a data communication connection to a corresponding type of communication line. As another example, communication interface **717** may be a local area network (LAN) card (e.g. for Ethernet™ or an Asynchronous Transfer Model (ATM) network) to provide a data communication connection to a compatible LAN. Wireless links can also be implemented. In any such implementation, communication interface **717** sends and receives electrical, electromagnetic, or optical signals that carry digital data streams representing various types of information. Further, the communication interface **717** can include peripheral interface devices, such as a Universal Serial Bus (USB) interface, a PCMCIA (Personal Computer Memory Card International Association) interface, etc. Although a single communication interface **717** is depicted in FIG. 6, multiple communication interfaces can also be employed.

The network link **719** typically provides data communication through one or more networks to other data devices. For example, the network link **719** may provide a connection through local network **721** to a host computer **723**, which has connectivity to a network **725** (e.g. a wide area network (WAN) or the global packet data communication network now commonly referred to as the "Internet") or to data equipment operated by a service provider. The local network **721** and the network **725** both use electrical, electromagnetic, or optical signals to convey information and instructions. The signals through the various networks and the signals on the network link **719** and through the communication interface **717**, which communicate digital data with the computer system **700**, are exemplary forms of carrier waves bearing the information and instructions.

The computer system **700** can send messages and receive data, including program code, through the network(s), the network link **719**, and the communication interface **717**. In the Internet example, a server (not shown) might transmit requested code belonging to an application program for

11

implementing an embodiment of the invention through the network 725, the local network 721 and the communication interface 717. The processor 703 may execute the transmitted code while being received and/or store the code in the storage device 709, or other non-volatile storage for later execution. In this manner, the computer system 700 may obtain application code in the form of a carrier wave.

The term "computer-readable medium" as used herein refers to any medium that participates in providing instructions to the processor 703 for execution. Such a medium may take many forms, including but not limited to non-volatile media, volatile media, and transmission media. Non-volatile media include, for example, optical or magnetic disks, such as the storage device 709. Volatile media include dynamic memory, such as main memory 705. Transmission media include coaxial cables, copper wire and fiber optics, including the wires that comprise the bus 701. Transmission media can also take the form of acoustic, optical, or electromagnetic waves, such as those generated during radio frequency (RF) and infrared (IR) data communications. Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, any other magnetic medium, a CD-ROM, CDRW, DVD, any other optical medium, punch cards, paper tape, optical mark sheets, any other physical medium with patterns of holes or other optically recognizable indicia, a RAM, a PROM, and EPROM, a FLASH-EPROM, any other memory chip or cartridge, a carrier wave, or any other medium from which a computer can read.

Various forms of computer-readable media may be involved in providing instructions to a processor for execution. For example, the instructions for carrying out at least part of the embodiments of the invention may initially be borne on a magnetic disk of a remote computer. In such a scenario, the remote computer loads the instructions into main memory and sends the instructions over a telephone line using a modem. A modem of a local computer system receives the data on the telephone line and uses an infrared transmitter to convert the data to an infrared signal and transmit the infrared signal to a portable computing device, such as a personal digital assistant (PDA) or a laptop. An infrared detector on the portable computing device receives the information and instructions borne by the infrared signal and places the data on a bus. The bus conveys the data to main memory, from which a processor retrieves and executes the instructions. The instructions received by main memory can optionally be stored on storage device either before or after execution by processor.

While certain exemplary embodiments and implementations have been described herein, other embodiments and modifications will be apparent from this description. Accordingly, the invention is not limited to such embodiments, but rather to the broader scope of the presented claims and various obvious modifications and equivalent arrangements.

What is claimed is:

1. A method comprising:

receiving a voice-based call from a mobile device;
receiving anchoring information about the voice-based call;

initiating an inquiry to the mobile device related to whether communicating via a non-voice-based messaging session is desired by a user of the mobile device; and
selectively initiating a non-voice-based messaging session related to the voice-based call to communicate with the mobile device using the anchoring information;

receiving an indicator from the mobile device that communicating via the non-voice-based messaging session is

12

desired, wherein the voice-based call and the non-voice-based messaging session are concurrently utilized;
determining whether the voice-based call is an emergency call;

initiating release of the voice-based call when the voice-based call is not an emergency call; and
maintaining the non-voice-based messaging session.

2. A method of claim 1, wherein the voice-based call is an emergency call.

3. A method of claim 1, wherein the anchoring information includes an identification of the mobile device and a location of the mobile device.

4. A method of claim 3, wherein the anchoring information is provided by a wireless communication network serving the mobile device.

5. A method of claim 1, wherein the non-voice-based messaging session utilizes messages relating to an electronic mail, an instant messaging (IM) message, a short message service (SMS) message, or a multimedia messaging service (MMS) message.

6. An apparatus comprising:

a communication interface configured to receive a voice-based call from a mobile device; and

a processor configured to receive anchoring information about the voice-based call, initiate an inquiry to the mobile device related to whether communicating via a non-voice-based messaging session is desired by a user of the mobile device, and to selectively initiate the non-voice-based messaging session related to the voice-based call, when desired, to communicate with the mobile device using the anchoring information, wherein the communication interface is further configured to receive an indicator from the mobile device by the voice-based call that communicating via the non-voice-based messaging session is desired, wherein the voice-based call and the non-voice-based messaging session are concurrently utilized, and wherein the processor is further configured to determine whether the voice-based call is an emergency call, to initiate release of the voice-based call when the voice-based call is not an emergency call, and to maintain the non-voice-based messaging session.

7. An apparatus of claim 6, wherein the voice-based call is an emergency call.

8. An apparatus of claim 6, wherein the anchoring information includes an identification of the mobile device and a location of the mobile device.

9. An apparatus of claim 8, wherein the anchoring information is provided by a wireless communication network serving the mobile device.

10. An apparatus of claim 6, wherein the non-voice-based messaging session utilizes messages relating to an electronic mail, an instant messaging (IM) message, a short message service (SMS) message, or a multimedia messaging service (MMS) message.

11. A method comprising:

determining anchoring information associated with an emergency voice call placed by a mobile device associated with a user;

determining a public safety answering point designated for serving the mobile device;

initiating establishment of the emergency voice call between the mobile device and the public safety answering point to permit communication between the user and an operator of the public safety answering point;

initiating an inquiry to the mobile device related to whether communicating via a non-voice-based messaging session is desired by the user; and

initiating establishment of the non-voice-based messaging session, based on the anchoring information, between a messaging platform coupled to the public safety answering point and the mobile device to permit communication between the operator and the user when communicating via a non-voice-based messaging session is desired; and terminating the emergency voice call, while maintaining the non-voice-based messaging session. 5

12. A method of claim 11, wherein the anchoring information includes an identification of the mobile device and a location of the mobile device. 10

13. A method of claim 11, wherein the non-voice-based messaging session utilizes messages relating to an electronic mail, an instant messaging (IM) message, a short message service (SMS) message, or a multimedia messaging service (MMS) message. 15

* * * * *