

19

wherein the first seat attachment adapter is coupled to the first seat attachment housing and the second seat attachment adapter is coupled to the second seat attachment housing.

14. The stroller of claim 13, wherein each of the first seat attachment adapter and the second seat attachment adapter comprises:

- a first end comprising a connector portion coupled to one of the first seat attachment housing and the second seat attachment housing; and
- a distal second end, wherein the second seat is removably coupled to the second end.

15. The stroller of claim 10, wherein the first seat is one of a baby seat, a car seat, a stroller seat, a bassinet, a baby carrier, or a pram and the second seat is one of a second baby seat, a second car seat, a second stroller seat, a second bassinet, a second baby carrier, or a second pram.

16. The stroller of claim 10, further comprising:

- a third seat attachment adapter coupled to the first upper tube support frame at the first vertical position; and
- a fourth seat attachment adapter coupled to the second upper tube support frame at the first vertical position; wherein the first seat is removably coupled to the third seat attachment adapter and the fourth seat attachment adapter.

17. A stroller, comprising:

- a stroller frame comprising:
 - a first upper tube support frame;
 - a second upper tube support frame;
 - a first back wheel support frame;
 - a second back wheel support frame;
 - a first front wheel support frame;
 - a second front wheel support frame;
- a plurality of wheels comprising at least one front wheel and a plurality of back wheels;
- a first seat coupled to the stroller frame at a first vertical position of the stroller frame;
- a first seat attachment housing disposed adjacent the first front wheel support frame;
- a second seat attachment housing disposed adjacent the second front wheel support frame;

20

a first seat attachment adapter coupled to the first seat attachment housing at a second vertical position of the stroller frame that is below the first vertical position when the first upper tube support frame is substantially parallel with the first front wheel support frame when the stroller frame is unfolded from a folded configuration;

a second seat attachment adapter coupled to the second seat attachment housing at a third vertical position of the stroller frame that is below the first vertical position when the second upper tube support frame is substantially parallel with the second front wheel support frame when the stroller frame is unfolded from a folded configuration;

wherein the first seat is coupled along the first upper tube support frame and the second upper tube support frame and wherein a second seat is removably coupled to the first seat attachment adapter and the second seat attachment adapter.

18. The stroller of claim 17, wherein each of the first seat attachment adapter and the second seat attachment adapter comprises:

- a first end comprising a connector portion coupled to one of the first seat attachment housing and the second seat attachment housing; and
- a distal second end, wherein the second seat is removably coupled to the second end.

19. The stroller of claim 17, further comprising a handle comprising a first end coupled to the first upper tube support frame and a distal second end coupled to the second upper tube support frame.

20. The stroller of claim 17, further comprising:

- a third seat attachment adapter coupled to the first upper tube support frame; and
 - a fourth seat attachment adapter coupled to the second upper tube support frame;
- wherein the first seat is removably coupled to the third seat attachment adapter and the fourth seat attachment adapter.

* * * * *