



- (51) International Patent Classification:  
G06K 9/46 (2006.01)
- (21) International Application Number:  
PCT/IL2013/050856
- (22) International Filing Date:  
22 October 2013 (22.10.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
61/717,216 23 October 2012 (23.10.2012) US  
61/759,643 1 February 2013 (01.02.2013) US
- (72) Inventor; and  
(71) Applicant : SIVAN, Ishay [IL/IL]; 12 Dissentchik Street,  
6935635 Tel Aviv (IL).
- (74) Agent: REINHOLD COHN AND PARTNERS; P.O.B.  
13239, 6113102 Tel Aviv (IL).
- (81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,  
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,  
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,  
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,

KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,  
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,  
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,  
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM,  
ZW.

- (84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,  
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,  
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,  
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,  
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
KM, ML, MR, NE, SN, TD, TG).


**Declarations under Rule 4.17:**

— of inventorship (Rule 4.17(iv))

**Published:**

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments (Rule 48.2(h))

(54) Title: REAL TIME ASSESSMENT OF PICTURE QUALITY



(57) Abstract: A computerized method for computing the photo quality of a captured image in a device image acquisition system, comprising on-board combining of a plurality of quality indicators computed from said captured image and its previous image frames quality indicators and a confidence level for at least one of said quality indicators; and using a processor to determine, based on said combining, whether photo quality is acceptable and taking differential action depending on whether quality is or is not acceptable.

WO 2014/064690 A1

## REAL TIME ASSESSMENT OF PICTURE QUALITY

5

### REFERENCE TO CO-PENDING APPLICATIONS

10

Priority is claimed from two US provisional applications as per the forms attached hereto.

### FIELD OF THIS DISCLOSURE

15

The present invention relates generally to image processing and more particularly to analysis of photographed images.

### BACKGROUND FOR THIS DISCLOSURE

20

Cameras today, even those with good "auto mode" functions, still rely on the camera user to assess a picture's quality, either at the time of taking the picture, or at a later stage. Certain software, such as Photoshop, offers tools to enhance a picture to an extent. Many users simply take more than one picture, say 5-6 pictures, so they will be able to choose one good one.

25

Conventional technology constituting background to certain embodiments of the present invention is described in the following publications inter alia:

30

a. US 20130155474 in which a user of the mobile device is provided with feedback prior to the capturing of at least one image of a paper document which provides the user with at least one instruction for adjusting at least one measured parameter. Parameter values may be combined into a group threshold or total overall quality score, such that the combination of all of the measured parameter values produces an overall quality score which exceeds a defined threshold value before the image can be captured by the camera. According to this publication, "The user can be provided detailed information to assist the user in taking a better quality image of the

document. For example, the blurriness may have been the result of motion blur caused by the user moving the camera while taking the image. The test result messages can suggest that the user hold the camera steadier when retaking the image."

5 b. WO 2006040761 / US20070195174 which describe a system in which the interface module further enables to define the scene dynamics of the captured image and attributes of the captured image scene dynamics include image motion speed and motion speed of the subjects and the interface module further enables setting the captured image attributes relative weight for the computation of the total image grade.

10 c. US20090278958 which describes inter alia that "The scoring of a current base image may be based on scores which have been given to previously captured base images. In such a manner, redundant calculation may be avoided."

d. Other systems such as the following patent documents: US7362354; WO2003069559; US7688379; US20090263028; US20060017820; US20060056835; US8125557; WO2011148212; US7920727; US20130155474; US8040382.

15 The disclosures of all publications and patent documents mentioned in the specification, and of the publications and patent documents cited therein directly or indirectly, are hereby incorporated by reference. Materiality of such publications and patent documents to patentability is not conceded

## 20 SUMMARY OF THE INVENTION

Certain embodiments seek to utilize camera hardware such as accelerometers, gyros and autofocus lenses, inter alia, to evaluate pictures taken in real time, and actively assist in obtaining the best picture given the circumstances at hand.

25 Typically, each available sensor, e.g. accelerometers, gyros, sends its raw data to a processing component 400 that outputs a quality indicator e.g. as illustrated in Fig. 1. and Fig 3. Data may also be sent to Device/surrounding objects 4D position computation component 230 for 4D positioning computation. Raw data may be combined with quality indication from other sensors, such as the camera/lens module 200, that can send its own quality indications. For example, some lens modules can estimate the picture focus quality, as it is a part of their auto focus functionality. Some camera/lens modules may have dual cameras or more for achieving 3D data, sophisticated focusing methods like Lytro light field camera, or their own hardware

30

sensors like Google Glass. All this available data can be sent to component 400 and Device/surrounding objects 4D position computation component 230 for use of their functions. Various quality indicators, depending on device capabilities and implementation, may be employed.

- 5 Prior art has used certain independent quality indicators, each giving a quality of one particular aspect of a picture, for a given picture. Some try to quantify the quality by means of a total quality indicator. Typically this is done as follows:

$$QI_{total} = \sum_{i=1}^n QI(t)_i$$

Where n is the number of quality indicators (QI), and t is the time of test.

- 10 Some implementations use a weight function in computation, but the weight is either constant or can be change by the user manually.

$$QI_{total} = \sum_{i=1}^n QI(t)_i * w_i(t)$$

- 15 However, in this invention, the weight of one indicator will take into account data from other quality indicator/s e.g. their quality indicator value, weight, confidence level (explained forthwith) in them and their previous value, weight and confidence level. For example, if both device shake quality indicator and/or camera focus quality indicator indicate a poor quality, disregard use of aesthetic quality indicator in total computation, even if user indicated that he would like to give it a high priority. This will prevent the device from taking a picture when the picture is blurry, as is the case in prior art. Once shake is low and focus is optimal, aesthetic QI  
20 may be used in total quality computations. One quality indicator's importance or relative weight within the total quality indicator may change over time, if some other quality indicator indicates that the first quality indicator becomes less relevant in quantifying the picture quality.

- 25 Furthermore, since each QI algorithm has its own assumptions, and each sensor may have measurement errors, the quality indication (QI) value may therefore not be reliable. Also, a QI value that fluctuates widely may not be reliable, and in certain cases, re-assessment of the quality indicator may be called for. Thus, a "confidence level" in the QI is obtained. These indicators may be relayed to a

processing component that analyses the current relevance of each indicator, and with suitable configuration, provides a “total” quality value.

This total quality indicator and its detailed list of quality indicators can be used to give the user accurate feedback on the picture quality, whether and how it fits  
5 user preferences (configured in 151, used in total QI computation), and provide detailed suggestions on how to take a better picture, if possible.

Suggestions may be provided as an oral message, typically pre-recorded, as an icon on a screen, or as text. Suggestions may use the recorded images as a template for the suggestions. This may include marking over exposed areas in red, or marking a  
10 problematic element with a circle.

The quality indicators’ values and total quality indicator can be shown to the user in real time.

Certain embodiments of the present invention include a method which  
15 comprises combining data from multiple sensors and multiple quality indicators, using available GPU and CPU, to compute, in real time, each quality indicator, and to form a combined total indicator to be shown to the user before and after he has pressed the shutter button. The user may get, or choose to get, suggestions from the application on how to improve the next shot, using the quality indicators and their  
20 correlation.

Further indication to the user can be made if the image is below a certain total quality indicator threshold.

According to one embodiment, quality indications are used to control the lens module 200. For example, focus distance reported may be below hyper focal distance  
25 or very short and accelerometer reports movement in direction perpendicular to focus plan. This can be used to find a way to shorten the shutter speed (increase ISO or change aperture for example). Another example may be to change the focus point and possibly focus distance if the object being tracked has moved.

In another embodiment, when the user presses the “shutter” button to take the  
30 picture (component 105), the device will wait for the total quality indicator to reach a minimum value/threshold, before taking a full resolution picture as shown in Fig 1. Ideally, this time will be close to the shutter release time. A timeout mechanism can ensure a full resolution picture will be taken, even if the threshold is not reached in a given time after the shutter is released.

A list of suggestions to the users may be for instance “blurred image due to camera shake”, or “blurred subject due to subject movement”, or “Image dynamic range is beyond the sensor dynamic abilities –choose area of interest, or take a high dynamic range (HDR) shot”.

5 Embodiments include but are not limited to:

Embodiment 1. A method for computing the photo quality of a captured image in a device image acquisition system, said method comprising:

10 computing at least one total quality indicator based on at least two quality indicators computed from said captured image and its previous image frames, to determine whether the photo quality is acceptable; and providing a corresponding detailed photo quality feedback.

Embodiment 2. A system according to embodiment 1, where automatically activating the capturing apparatus, once a logical criterion based on said quality indicators is met.

15 Embodiment 3: A system, according to embodiment 1 where a message provider is operative where at least one appropriate suggestion from a pre-stored table of suggestions on how the digital image can be improved further, where said message is presented as a suggestion to the user.

20 Embodiment 4: A system, according to embodiment 1 where pictures are taken and saved at each frame, but only pictures with a said logical criterion are marked as so.

Embodiment 5: A system, according to embodiment 1 where the stream of frames is saved as a video and; quality indicators, user preferences, confidence level, and quality importance are used to quantify video quality.

Embodiment 6: A system, according to embodiment 5, used to give a user suggestions on improvement of the video.

25 Embodiment 7: A system, according to embodiment 1, where computed QI and their confidence levels are used to change parameters in the lens/sensor module to achieve better total QI.

Embodiment 8: A system and method as in embodiment 1 used for automatic image capturing of at least one picture once a configured total quality indicator meets a minimum threshold, even without the user pressing a shutter button.

Embodiment 9. A system using blur type detection for alerting the user of object

movement in a region.

Embodiment 10. A system using blur type detection for alerting the user he is moving too fast in a vehicle to achieve a non-blurred image.

Embodiment 11. A system and method described herein for evaluating video quality.

Embodiment 12. A system with device shake recognition, where a device movement gesture can be used for shutter press indication.

Embodiment 13. A system with device shake recognition, where a device movement gesture can be used for delete picture indication.

Also provided, excluding signals, is a computer program comprising computer program code means for performing any of the methods shown and described herein when said program is run on a computer; and a computer program product, comprising a typically non-transitory computer-usable or -readable medium e.g. non-transitory computer -usable or -readable storage medium, typically tangible, having a computer readable program code embodied therein, said computer readable program code adapted to be executed to implement any or all of the methods shown and described herein. It is appreciated that any or all of the computational steps shown and described herein may be computer-implemented. The operations in accordance with the teachings herein may be performed by a computer specially constructed for the desired purposes or by a general purpose computer specially configured for the desired purpose by a computer program stored in a typically non-transitory computer readable storage medium. The term "non-transitory" is used herein to exclude transitory, propagating signals or waves, but to otherwise include any volatile or non-volatile computer memory technology suitable to the application.

Any suitable processor, display and input means may be used to process, display e.g. on a computer screen or other computer output device, store, and accept information such as information used by or generated by any of the methods and apparatus shown and described herein; the above processor, display and input means including computer programs, in accordance with some or all of the embodiments of the present invention. Any or all functionalities of the invention shown and described herein, such as but not limited to steps of flowcharts, may be performed by a conventional personal computer processor, workstation or other programmable device or computer or electronic computing device or processor, either general-purpose or

specifically constructed, used for processing; a computer display screen and/or printer and/or speaker for displaying; machine-readable memory such as optical disks, CDROMs, DVDs, BluRays, magnetic-optical discs or other discs; RAMs, ROMs, EPROMs, EEPROMs, magnetic or optical or other cards, for storing, and keyboard or mouse for accepting. The term "process" as used above is intended to include any type of computation or manipulation or transformation of data represented as physical, e.g. electronic, phenomena which may occur or reside e.g. within registers and /or memories of a computer or processor. The term processor includes a single processing unit or a plurality of distributed or remote such units.

10 The above devices may communicate via any conventional wired or wireless digital communication means, e.g. via a wired or cellular telephone network or a computer network such as the Internet.

The apparatus of the present invention may include, according to certain embodiments of the invention, machine readable memory containing or otherwise storing a program of instructions which, when executed by the machine, implements some or all of the apparatus, methods, features and functionalities of the invention shown and described herein. Alternatively or in addition, the apparatus of the present invention may include, according to certain embodiments of the invention, a program as above which may be written in any conventional programming language, and optionally a machine for executing the program such as but not limited to a general purpose computer which may optionally be configured or activated in accordance with the teachings of the present invention. Any of the teachings incorporated herein may wherever suitable operate on signals representative of physical objects or substances.

25 The embodiments referred to above, and other embodiments, are described in detail in the next section.

Any trademark occurring in the text or drawings is the property of its owner and occurs herein merely to explain or illustrate one example of how an embodiment of the invention may be implemented.

30 Unless specifically stated otherwise, as apparent from the following discussions, it is appreciated that throughout the specification discussions, utilizing terms such as, "processing", "computing", "estimating", "selecting", "ranking", "grading", "calculating", "determining", "generating", "reassessing", "classifying", "generating", "producing", "stereo-matching", "registering", "detecting",

"associating", "superimposing", "obtaining" or the like, refer to the action and/or processes of a computer or computing system, or processor or similar electronic computing device, that manipulate and/or transform data represented as physical, such as electronic, quantities within the computing system's registers and/or memories, into  
5 other data similarly represented as physical quantities within the computing system's memories, registers or other such information storage, transmission or display devices. The term "computer" should be broadly construed to cover any kind of electronic device with data processing capabilities, including, by way of non-limiting example, personal computers, servers, computing system, communication devices,  
10 processors (e.g. digital signal processor (DSP), microcontrollers, field programmable gate array (FPGA), application specific integrated circuit (ASIC), etc.) and other electronic computing devices.

The present invention may be described, merely for clarity, in terms of terminology specific to particular programming languages, operating systems,  
15 browsers, system versions, individual products, and the like. It will be appreciated that this terminology is intended to convey general principles of operation clearly and briefly, by way of example, and is not intended to limit the scope of the invention to any particular programming language, operating system, browser, system version, or individual product.

20 Elements separately listed herein need not be distinct components and alternatively may be the same structure.

Any suitable input device, such as but not limited to a sensor, may be used to generate or otherwise provide information received by the apparatus and methods shown and described herein. Any suitable output device or display may be used to  
25 display or output information generated by the apparatus and methods shown and described herein. Any suitable processor may be employed to compute or generate information as described herein e.g. by providing one or more modules in the processor to perform functionalities described herein. Any suitable computerized data storage e.g. computer memory may be used to store information received by or  
30 generated by the systems shown and described herein. Functionalities shown and described herein may be divided between a server computer and a plurality of client computers. These or any other computerized components shown and described herein may communicate between themselves via a suitable computer network.

## BRIEF DESCRIPTION OF THE DRAWINGS

Certain embodiments of the present invention are illustrated in the following drawings:

5 Fig. 1 is a functional block diagram of a system and method for real time assessment of picture quality produced on a device, e.g. as shown in Fig. 2, having multiple sensors including use of hardware sensor data to generate and utilize picture quality indications.

10 Fig. 2 illustrates a hardware and operating system (OS) layer which is operative in conjunction with the functional block diagram of Fig. 1.

Figs. 3 and 4 illustrates component 400 in detail and a sample of a quality indicator computation dependence, all according to certain embodiments.

Computational components described and illustrated herein can be implemented in various forms, for example, as hardware circuits such as but not limited to custom VLSI circuits or gate arrays or programmable hardware devices such as but not limited to FPGAs, or as software program code stored on at least one tangible or intangible computer readable medium and executable by at least one processor, or any suitable combination thereof. A specific functional component may be formed by one particular sequence of software code, or by a plurality of such, which collectively act or behave or act as described herein with reference to the functional component in question. For example, the component may be distributed over several code sequences such as but not limited to objects, procedures, functions, routines and programs and may originate from several computer files which typically operate synergistically.

25 Data can be stored on one or more tangible or intangible computer readable media stored at one or more different locations, different network nodes or different storage devices at a single node or location.

It is appreciated that any computer data storage technology, including any type of storage or memory and any type of computer components and recording media that retain digital data used for computing for an interval of time, and any type of information retention technology, may be used to store the various data provided and employed herein. Suitable computer data storage or information retention apparatus may include apparatus which is primary, secondary, tertiary or off-line; which is of

any type or level or amount or category of volatility, differentiation, mutability, accessibility, addressability, capacity, performance and energy use; and which is based on any suitable technologies such as semiconductor, magnetic, optical, paper and others.

5

#### **DETAILED DESCRIPTION OF THE INVENTION**

Certain embodiments of the present invention include a system and method for real time assessment of picture quality produced on a device having multiple sensors, such as a smartphone. In one embodiment, all of the sensors, such as but not limited to an image sensor, accelerometer or gyroscope, are embedded in one device. It may be that they reside in different devices, but send their data to one device where the total indicators are computed.

Fig. 1 is a functional block diagram of a system and method for real time assessment of picture quality produced on a device, e.g. as shown in Fig. 2, having multiple sensors including use of hardware sensor data to generate and utilize picture quality indications.

Referring now to Fig. 1, a Lens/sensor module 200 such as OmniVision OM8865 may be characterized by and/or generate photographic parameters, including but not limited to some or all of:

- a) The current image the sensor receives, referred to as a frame or image
- b) ISO speed (current, min, max)
- c) Is camera focused (yes/no/estimate if available).
- d) Aperture
- e) Focal length
- f) Shutter speed
- g) Focus rectangle, or area of interest
- h) Sensor type and size -- for example BSI2 CMOS 1/2.5 inch
- i) Depth of Field
- j) Scene mode or user preferences.

These parameters may be used for computing quality indicator values and their confidence level, as indicated in Fig 3.

The module 200 sends continuous video frames of the scene in front of the device lens, and data from other sensors is continuously received and analyzed in real

time.

Typically, a smartphone includes all such sensor and hardware inside the smartphone. However, it is possible that the image may be sent to the device from an external camera via a cable or Wi-Fi. The image sensor sends its data to the device  
5 operating system that may send the whole image or a preview of it to the GPU 122 of Fig. 2 at a rate of X frames per second. This image data is passed on to various programmed GPU vertex and fragment shaders. It is then used for fast computation of some of the quality indicators.

Fig. 2 illustrates a hardware and operating system (OS) layer, which is  
10 operative in conjunction with the functional block diagram of Fig. 1.

### **Errors and probability in quality indicators**

When prior art computes a quality indicator value, it was done without taking into account the possibility of error in the computed QI, as all sensors give out errors.

For example, a user wishes to compute a quality indicator for device shake based on data from accelerometers. Accelerometers have precision errors and drifting errors over time. If the user wishes to compute a speed vector, this will be relevant. The speed may be assumed to be  $100 \pm 3$ . A GPS can estimate location and speed errors via its location computation. Errors may also occur as a result of blurriness of some sort, or may result from image resolution and many other factors. For example,  
20 assuming a device is moving at a constant speed, and  $V_i$  is the computed speed in frame  $i$ , where  $1 \leq i \leq n$ , then if value  $V_n$  is 2 standard deviation from the average speed measured so far, (and assuming a normal distribution), then probability for this value is 5%, denoted  $P_i(t)$ . Most of the time the speed may not be constant, but the  
25 above technique can nonetheless can be applied, mutatis mutandis, when errors can be estimated. The probability factor P, is closely related to the nature of the quality indicator and hardware used. For example, a GPS device has its own algorithm for that e.g. Kalman Filters. Beyond mere errors, recognition or pattern algorithms have assumptions that can be related to "probability" of the feature been searched. For  
30 example in object recognition, if 4 out of 5 features for this object (face, lamp, chair) have been recognized, a probability P of 80% is indicated. Other examples may be comparison to a similar image for same scene recognition, as objects have moved or just look similar. Aesthetic fit algorithms employ "probability" which pertains to this.

**Confidence level of quality indicator**

Thus far, only a current image has been illustrated, but previous data can aid in computation of a better confidence level. This depends on the QI in question and the nature of the errors, but assuming a general case, one way of computing the confidence level of QI<sub>i</sub> denoted C<sub>i</sub>(t) is

$$C_i(t) = P_i(t_{j2}) * N(P_i(t_{j2}))$$

$$N(x) = e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

$$\mu_i = \sum_{k=t1}^{t2} \frac{P(t_k)_i}{k2 - k1}; \quad \sigma_i = \sqrt{\frac{1}{n} \sum_{k=1}^n (P(t_k)_i - \mu_i)^2}$$

t<sub>j2</sub> is the time of frame j<sub>2</sub>, the last frame so far.

t<sub>j1</sub> is the time of minimum frame j<sub>1</sub> computation which may be used.

N(x) is a formula for a normal distribution, σ the standard deviation and μ the mean value. The values in the distribution here are P<sub>i</sub>(t)

In the formula for computing normal distribution and standard deviation, there is a limit on the “looking back” portion of the computation, so when a significant event occurs at frame j<sub>1</sub>, it may be reset.

This example uses normal distribution, since nothing is known about the QI at hand, but this need not be the only distribution function. For example, if the location is measured by an accelerometer, accelerometer readout errors and drifting errors over time may be used to construct a better distribution function. For example, an accelerometer distribution function may be different for high acceleration and for low acceleration, since in low values the distribution will be more spread out than in high values.

Mean μ<sub>i</sub> and standard deviation σ<sub>i</sub> are computed from a specific frame j<sub>1</sub> until the current time (or just until the previous frame). This way a significant event in j<sub>2</sub> can be an indication to reset j<sub>1</sub> to j<sub>2</sub>, so the computations will not use frames before j<sub>2</sub>.

In another embodiment, one that doesn't use old data N=1, thus

$$C_i(t) = P_i(t_{j2})$$

There may be other methods to compute confidence. For example, GPS location algorithms (such as a Kalman filter) have their own way of computing confidence in the location, especially but not limited to, the mean of error in position.

If current GPS data say location has changed 3 meters in the last 15 milliseconds, but accelerometer data shows no change, and assuming that it is known from past computations that speed is relative zero, then the GPS data may not be trusted, and confidence in the GPS QI for movement, is low.

5 In another example, it may be that the lens module 200 report image is in focus, however independent focus blur QI 244 image is not in focus. This can affect the confidence of QI in component 248, where lens module QI is computed.

One way to compute the confidence level that is dependent on other values can be expressed as

$$C_i(t) = P_i(t_{j2}) * N(P_i(t_{j2})) * \prod_{k=1}^n f_{ik}(t, QI(t)_k)$$

10 Where n is the number of available quality indicators, and i and k are running indices of the current quality indicator in question. The function  $f_{ik}$  denotes a function specific to these quality indicator correlations. If there is no correlation, the function will be regarded as the scalar 1. In the above example, i being QI in component 248, and one some value  $1 \leq k \leq n; k \neq i$  where k is the index for QI in component 244, 15 the value of  $f_{ik}$  can be 0.5 if  $QI(t)_k < 0.7$ . (In this example all QI and confidence levels are normalized to 1).

More examples of use and computation of confidence levels are now described, as other components and quality indicators are introduced.

20 **Quality indicators use of previous frames data**

The QI used in the total quality indicator,  $QI\_ForTotal(t)_i$  employs the current value of  $QI_i(t)$  but also the confidence level. The confidence level is a function of old values inherited by virtue of distribution formula  $N(t)$ . So if the QI value is 25 significantly different then expected, the QI value's confidence level may drop thereby bypassing a current QI that may be problematic.

Other ways to bypass or wholly or partially discount a current wayward QI value include, say, recognition of an object or face. The object may have been in the field of view one frame ago, with high confidence, say 1/30 of a second ago. Now the QI say 30 the object is no longer there, perhaps with low  $P_i(t)$  value. It is possible however that the object in fact is still there; just the recognition algorithm has misses the object. In

this example the method may override the current QI with the previous one, at least for a frame or two. More generally, old QI may be employed, particularly if its confidence level exceeds newer QI values, to generate an improved current QI value. One embodiment could be an average of the last few frames that had a high  
5 confidence level. The availability of old QI, errors in them via  $P_i$ , and the computation of  $C_i$  provide other methods for determining the value of  $QI_i(t)$  e.g. for use in the total indicator. Algorithms of deep learning in neural networks, applied to confidence level data inter alia, may be used to better compute a current value of the quality indicator.

10 The following are examples of quality indicators and computational functionalities therefor, some or all of which may be provided as shown in Fig. 1:

#### **Blur detection in component 244**

15

Image blur can be of 2 types: focus or movement. In order to detect blur, quantify it and alert the user, its origin may be determined, so the user will have information on why the picture has inferior quality.

20 Blur caused by movement can be either due to the imaging device having moved (usually shake) and/or because the object which was photographed, moved. Both movements refer to the time the image is taken, and the shutter speed.

25 There are many algorithms for testing blur via frequency distribution in k space transformation such as DCT or other Fourier transform variants, for example prior art US20110096180. Other ways may be testing signal-to-noise ratio and searching for peak signal-to-noise ratio (PSNR). These algorithms can be used to create a blur quality indicator in component 244. This may assist in double checking the camera module 200 own focus assessment used in computation of QI in component 248. This is an advantageous step, since many quality indicators function better when they use previous frames, assuming they are all in focus. Retesting  
30 lens/camera module 200 own focus assessment may therefore be helpful.

#### **Device movement indication based on accelerometer**

Camera shake and movement can be quantified using an accelerometer  
206 to measure device 3D acceleration, and integrating this over time to determine

camera speed. The time of resetting the speed to zero is advantageous, since computation rounding and sensor errors may accumulate over time. This can be done in a few ways, for example: zero speed can be accessed when the device's acceleration is minimal and back and forth over a long time (meaning device is  
 5 around some point in space).

**Device movement quality indicator 270**

A person of skill in the field of photography would recognize the rule of thumb of focal length which may be reciprocal to the shutter speed if one wants to  
 10 avoid camera shake due to hand shake. Component 200 provides these two parameters. Device/surrounding objects 4D position computation component 230 provides a position of the device as a function of time in some degree of confidence. Given an average hand jitter speed, one can set a threshold of the accepted speed of the device. For example, assume that for a shutter speed 1/15 of a second, speed may  
 15 be less than 2 mm per second. 1 mm per second may provide excellent quality, 2 mm per second good quality and 2 cm per second very poor quality. Also a depth of field of the picture (DOF) can to be computed, using the focus distance, aperture of the lens and so on. If the depth of field is small and subject distance is short (macro photography), then movement of the device in the z axis may have a profound effect  
 20 on quality but for most pictures and devices this is not the case.

For example, a scene with a baby taken from 50 cm away with a Nikon D300, 50mm focal length lens, aperture of 1.8, means the depth of field may be 2.7 cm. This means that the baby's face may not be fully in focus, and an inferior quality may be indicated. For the same configuration with f/8 aperture, an excellent quality may be  
 25 indicated.

These computations may aid in determining the importance of movement in the Z axis to the value of the QI. Let a function  $I_3(x)$  be the importance of the z axis. In one embodiment  $I_3(x)$  may be an exponential function of some sort. The other axes, x and y, each have their own function. They can also have an exponential function, but with  
 30 a different factor. Given the speed  $V_i$  in each direction as given by Device/surrounding objects 4D position computation component 230 the following can be computed:

$$QI_{\text{device motion}} = \frac{\sum_1^3 I_i(x_i) * V_i(t)}{3}$$

This is one possible method for computation of the base QI for device motion which is not intended to be limiting. Other embodiments may for example use confidence levels .

Component 200 may have some kind of image stabilization - sensor shift, lens  
5 stabilization or other. In this case the lens or sensor movement speed in these image stabilizations may be incorporated into the speed  $V_i(t)$  in the formula above, for the QI to be correct. If this cannot be achieved with sufficient accuracy, the errors may be incorporated into this QI confidence level.

#### 10 **Object movement component 220**

There are many methods of computing a motion vector. A block matching method may be used, or a gradient method, etc., or if the motion vector information is included in the input image signal in some form, this information may be utilized. The motion of the objects in the image frame is caused by the combination of two factors:  
15 real object movement and apparent movement caused by device movement.

When computing object speed in the image frame, one must subtract the device movement as computed in Device/surrounding objects 4D position computation component 230 from the object speed vector computed.

Methods of statistical pattern recognition may be used to fully recognize  
20 actual objects, such as a chair, a tree, a face or a car. If either the imaging device or object is moving, the identity of the object may be considered as a factor for the related confidence level; e.g. a car is much more likely to be moving during imaging than is a tree. Objects that are in the focus rectangle or area of interest are more significant to quality. If there is some movement at a far end region (or: at a  
25 significant distance), this may not greatly affect the quality indicator.

#### **Object movement quality indicator 260**

The data from component 220 can be used to create a quality indicator about blur due to subject movement. Normally, no movement would indicate excellent quality, and high-speed movement would indicate low quality.

30 Some objects are more important than others for a “good” picture. For example, often a face is more important than a chair. In order to compute this subject movement quality indicator, each object may be recognized and its movement vector and significance may be factored into the quality indicator dependent on this object’s movement.

This computed data may be used to alert the user of motion of a specific object that is considered important such as a face located in the center of an image.

One way of computation of this quality indicator, noted  $QI_{\text{subject movement}}$ , may be:

5 
$$QI_{\text{subject movement}} = \frac{\sum_n A(x_i) * B(x_i) * S(x_i)}{n}$$

where  $A(x)$  – binary/multi-value indicator: is object inside or outside of; within, close to or far from, the focus/interest area rectangle

$B(x)$  – importance of object to a picture

- 10  $S(x)$  – object speed factor. A desired speed may be assigned a “high” value of 1, and 0 may be assigned for non-desired speed, with possible values in the middle. If the object is not to look blurred, it should be standing still relative to the current shutter speed. In that case a high value may be a slow speed. However, speed of an object may be desirable, e.g. to create the artistic impression of movement in the picture.
- 15 such a case, a high value may be assigned to a high speed.
- Each factor is normalized to 1 in this example.

- In one embodiment, if the motion vector’s estimation quality is not sufficient, the camera module may be instructed to take a picture of a different exposure, say a
- 20 shorter one, to measure the movement more precisely.

**Computing object motion vector via corners detection**

- Algorithms such as Harris corner detection or its variants such as Shi Tomas corners detection may be used to determine whether the new image frame has more or less
- 25 details than the previous frame. This determination may be combine with data from the gyroscope and accelerometer, if provided, to indicate whether or not the device has moved and/or the quality has severely deteriorated or increased.

- The total quality indicator can be shown to the user in real time. Also, given a configurable “minimum” quality, an indication to the user can be made if the image
- 30 total quality indicator is below this minimum.

In each region, the number of corners are counted and their center of gravity is computed. This is done for each region on each frame. The path of each center of

gravity may then be followed over each region and a motion vector may thereby be computed. This may be feasible if the speed of the object is slow, since when the speed is quick, the corners may become blurred.

#### 5 **Image leveled to horizon quality indicator 271**

The device gyroscope 205 and accelerometer 206, both of which may or may not be provided or available, may be used to compute device angle to the horizon, or how the device is leveled. Using this data, a quality indicator for “device leveled according to its orientation”, is computed. For example, zero to 3 degrees is “excellent” quality,  
10 3 to 5 degrees is “good” quality and so on. The user may hold the device either horizontally or vertically.

#### **Camera focus quality indicator 248**

As already mentioned, component 200 may send to component 248 data if component 200 is currently in focus, thereby to form an “excellent” quality indicator  
15 level for already-focused and “bad” quality indicator for still-focusing. Some camera modules may provide a focus estimation of their own. In such cases, this may be incorporated into or replace the quality indicator to provide more than a yes/no quality indication.

Furthermore, when the lens focuses, the frames received from the camera module  
20 are blurred, so the quality indicators related to the blur or object motion detection may be affected. In one implementation, the frames with low focus quality, may be removed when computing these quality indicators.

The lens/camera module 200 may also report its own focus confidence level.

Ideally, the focus indication sent by component 200 may coincide with component  
25 244 QI. However, if it does not, say 244 indicates out of focus and 200 indicates in focus, this can be used to lower 248 confidence level, as demonstrated in the confidence level section.

#### **Face detection quality indicator 249**

This quality indicator indicates whether there is a face or faces and whether the  
30 face is smiling and/or looking at the camera. These indicators are passed on to a component 249 that analyzes the relevance of each of them, and yields a “total” quality value for this quality indicator.

Furthermore, one may determine if each face is smiling and/or looking at the camera. This data may be used for a quality indicator. For example, a scene in which

over 90% of the faces are looking at the camera and 80% are smiling, equals “excellent” face quality, while a scene in which none are looking and none are smiling indicates “bad” quality. Importance of the smiling/not smiling factor may be configured by the user via component 151.

5           **Recognized face quality indicator 250**

The device may have a list of configured faces to recognize and for each, pre-stored, their importance, say a user family member or work colleague. The data may also include specific face features. This is denoted as component 212,

Recognition of these faces in component 217 may be used by component 250 to  
10 produce a quality indicator based on importance as well as face quality, as before. Face importance may change over time by the user, or automatically, by learning user preferences. Confidence level may be computed similarly to 249. However, since it is a known person, more data may be obtained to enhance face recognition, such as face features from various angles, glasses, etc.

15           **ISO level and camera hardware exposure data 245**

Data such as ISO level, exposure time, focal length, and aperture and focus area is sent from the lens/camera module 200.

Depending on the device capabilities, such as maximum and minimum ISO, a quality indicator is produced. High ISO gives bad quality vs low ISO that gives a high  
20 quality indicator.

An optional exposure time quality indicator may be created, if a minimum exposure time is configured.

**Lens focal length, aperture, focus distance, sensor type and model and  
              depth of field 247**

25           Depending on the device capabilities to change focal length and aperture, and given a known configured scene, a quality indicator may be provided to indicate how these parameters confront the given scene. For example, if the scene is a portrait and no face is detected by component 216 yields a bad QI.

Another example may be to use the sensor type and model (component 200) to  
30 yield a QI related to it – professional quality may yield good quality, when a poor quality, less costly component, yields poor quality.

Another embodiment for this QI is for testing background blurring, which may sometimes actually be desired. For example, a scene with face recognition in 216 and a very small aperture, say f10 with focus distance in the hyper focal distance of

component, 200 yields a bad quality, whereas a wide aperture, say f2.8 on these conditions, yields a good quality.

#### **Under and overexposed quality indicator 243**

Given configurable under and over thresholds (say 5% from pure white and 3%  
5 from pure black) the image frame given to the GPU is processed to compute areas that are underexposed and areas that are overexposed, e.g. similar to the zone system by Ansel Adams known in the field of photography.

The image frame is divided to a configurable number of areas; say 256 areas or  
1024 areas. If a configurable number of percentages of pixels in an area (say 95%) are  
10 under or over exposed, the area is marked as under or over exposed. If the image sensor or operating system supports scene recognition/ scene mode, or object recognition is present, then the image sensor or operating system may be used in the evaluation of this quality indicator. For example, if the sun or a lamp is the brightest area in the image, they may be ignored. A point of bright light like the sun or a light  
15 bulb may be recognized by their pattern and may be ignored.

On another embodiment, the computation may be based on percentage of over and underexposed pixels in the image.

An image in which a large percentage is marked as over or under exposed, say over  
40%, may get a bad over/under quality indicator. The same thresholding method may  
20 be used for the method of areas described before e.g. if over 40% of 256 areas are considered over exposed.

In another embodiment, pixel or areas inside or outside the focus area of the picture,  
as given by the lens/camera module 200, may have a different weight e.g. pixels or  
areas outside the focus area may have a lower affect on the quality indicator value.

25 This indicator may be used to indicate to the device that an High dynamic range (HDR) shot may be taken, and may be done either automatically or by notifying the user. Depending on the device, this may be done automatically by taking 2 pictures with different exposure settings.

#### **Histogram quality indicator 241**

30 The under/over quality indicator is a special case of a more general quality indicator taking into account not just the histogram extreme, but also its central part, and also taking into account function structure and lens/camera module 200's available dynamic range.

This may be no reference, or a full reference (meaning in computation there is or

there is not a reference to a preferred image), e.g. as in “The Design of High-Level Features for Photo Quality Assessment“ by Yan Ke, Xiaoou Tang and Feng Jing.

#### **Obstructing the lens quality indicator 246**

Obstructing the lens may occur as a result of putting the finger partly or fully on the  
5 lens. For example, in bright conditions there may be a brown-red area in one corner.  
In dark conditions there may be no light at all in that location. Confidence in having  
recognized the situation may be enhanced as more frames are taken and the camera is  
moved around because if there is no obstruction on the lens, then the size of the area  
previously believed to be obstructed, would change significantly. There may be other  
10 objects causing obstruction that may be recognized. If they are recognized, their name  
can be used in feedback to the user, instructing him to remove the obstruction.

The amount of area and confidence may be used to give this quality indicator a  
degree/rating between “excellent” and “bad”. For example, a finger blocking the lens  
may look on the image as a brownish area, probably in a corner of the frame. If the  
15 color were green, or it is an isolated area in the middle, the confidence would be low.

For the previous example (finger blocking appearing as a brownish area) the  
confidence is high.

#### **Functionality 230 - Measuring distance to objects and creating a 4D 20 environment measurement in real time e.g. by computation of Device/surrounding objects 4D position**

As already described, the speed of the device in each direction may be measured and  
the distance traveled may be computed.

With the help of a GPS (e.g. based on unit 202 in Fig. 1) and/or step counting  
25 hardware (unit 203) accuracy in the range of a few dozen or a dozen or centimetres or  
even a single centimetre may be computed by a person skilled in the area for the  
device 3D relative position in time, thereby to yield 4D position.

This could be used by component 270 to yield better QI accuracy. By measuring the  
boundaries of an object in one location and again in another location, after moving the  
30 device, the distance to the object may be measured (assuming the object is still). e.g.  
via parallax. Parallax is the apparent displacement of an object because of a change in  
the observer's point of view. Since cameras today easily achieve 8MP and more,  
typically, distance can be computed providing parameters such as lens focal length  
from component 200.

The 3D scene is built according to the input images from the image capturing unit 200 or any other sources. It can be based on multi-view image geometry techniques as introduced in “Multiple View Geometry in Computer Vision” by R. I. Hartley, A. Zisserman, Cambridge University Press (2004). The user may help by moving the device, either by walking a few steps or holding the device at full arm’s length and swinging it pointing to the scene in question. However, a full 3D scene reconstruction is not required. A partial reconstruction, including scene change in time, may suffice.

Since the methods used to estimate the distance include integrated estimation, such as the distance is between 2 to 3 meters, a confidence level on each object can be constructed, similar to that described in the confidence level section. Also, since the device position itself may have errors or uncertainties, this also can be used in the confidence level of each object. This confidence level can then be used by quality indicators using this component data, so that they may implement their own confidence level.

#### **Aesthetic rules quality indicators 240**

In photography, there exist ‘golden rules’ for fitting of the composition to a section that may give a better aesthetic looking picture. There are heuristics that provide a means of achieving an eye-pleasing composition such as but not limited to: rule of thirds, golden triangle, golden spiral, shapes and lines, amputation avoidance, visual balance, and diagonal dominance.

For example, when taking a picture on a beach, the sea and sky meet on the horizon ‘line’. To fit this rule, one must put the line either at one third-height or two-thirds height, thereby fitting the “rule of thirds”. Either one is “correct”. However, putting the line in the middle creates a composition that is considered less favorable to the viewer.

There are various methods of testing a fit to this rule, for example in “Photographic”, *Volume 29 (2010), Number 2* “Optimizing Photo Composition” by L. G. Liu, R. J. Chen, L. Wolf, and D. Cohen-Or.

Further types of aesthetic models exist, based on chroma and exposure. Some may only give a non-reference quality indication without suggestion on coordinate change, as in the previous article. For example, a model is described in published US20130188866.

In another embodiment, multiple aesthetic qualities may be used.

This aesthetic QI, can be used for suggestion to the user to move from his

current location to another location, together with the other quality indicators like under/over, it may be suggested to the user that he should move from his current location.

For example, a lamp in the street behind a person at night will not be good even if it fits a golden rule. Using data from Device/surrounding objects 4D position computation component 230, we can assess distance to the person's face, say 2 meters, the distance to a lamp of 4 meters height 4 meters behind him, we can suggest to the user that he should move 2 steps to the right and one forward, tilting the device 20 degrees to the left if he wishes to achieve a better aesthetic QI score and a better total QI.

#### **Functionality 242: Same scene quality indicator**

One of the problems solved by certain embodiments of the present invention include a processing system to reduce or eliminate any need to take multiple pictures of the same scene, in order to get one good picture. If the proposed system negates this need, it may be helpful to indicate to the user he is taking unnecessary pictures that may only be a burden at a later stage.

This is a heuristic quality indicator, taking into account the time, location of device, angle of device, object movement in the device and other parameters, including but not limited to photographic parameters such as ISO and focal length. It may require these parameters of previous pictures taken in recent time. One possible implementation includes comparing each QI and its confidence data to the QI and associated confidence level of a previously recorded and saved image in the last say 5 seconds (configurable). If the data of each QI is the same, it may be concluded that it is a "bad" same scene quality indicator.

25

#### **Functionality 400 and 401: Combining the separate quality indicators to total quality indicators**

As described herein, some quality indicators and their confidence levels may depend on other QI data. For example, aesthetic QI computation 240 may need the data on image leveled to horizon from component 271. If confidence of 271 is very low, it may not use any other data. Some, but not limited to, examples of QI computation components can be seen in Fig 3.

Some quality indicators may be considered mandatory (unless specifically turned

off) since they cause unacceptable blurring of the image:

- Focus
- Subject movement
- Device movement

5 Each device may have different hardware capabilities, thereby may not yield all the possible quality indicators or may not be able to process detail indicators, due to slow hardware. Some indicators may be ignored, if so configured by the user. One is then left with a set of indicators with which to compute.

A QI use in a total indicator may vary depending on situation. For example,  
 10 “overexposed” quality indicator computation 243 may use data from object recognition in component 220. If the picture shows a sunset, it is likely that there will be over and underexposed areas, so in one embodiment it may be chosen to decrease importance of a sun-lit area and be less sensitive to overexposed QI in total computation. In another example, face exposure check may be increased if the face  
 15 quality indicator suggests there is a face.

$$QI\_ForTotal(t)_i = QI(t)_i * \prod_{j=1}^n f_{ij}(t, QI(t)_j, C_j)$$

As can be seen in this formula, there is a dependency in the confidence level  $C_j$  before it is used, so data of QI with low confidence level may not be used. There may be other ways to formulate these connections. This may be employed as a general case.

$$QI_{total} = \sum_{i=1}^n QI\_ForTotal(t)_i * w(t, C_i)_i$$

$W(t)_i$  is the weight of each QI in the total and may be used to ignore QI if desired.  
 20  $W(t)_i$  is dependent on time, since the user may choose to change it.  $W(t)_i$  may be dependent on the confidence level. For example, if it is not desired to include below say 10% confidence, and  $w_i$  will be zero if  $C_i < 0.1$ .

There can be more than one type of total QI. For example, when computing total QI, and only mandatory QI are chosen (QI's considered mandatory by an application or  
 25 use case), a mandatory total QI may be provided. This QI may be used to decide when to take the picture, e.g. as described below. Another option is to use all the QI to get a sense of the picture quality as a whole. One can choose to formulate other total QI for other needs.

This formula is just one way to achieve a total indicator that is dependent on quality

indicators, their confidence levels and their relations. The idea is to enable a general formula as quality indicators are added or removed in some embodiments, or for different implementations with various levels of complexity and interconnections between QI.

5           **Functionality 502: Taking a picture at the proper time using total quality indicator**

It may be that the picture will not be taken when the shutter is pressed, but only when a minimum threshold on specific QI with specific confidence level is met, when a total QI minimum threshold is met, or timeout occurs.

10 In such cases, the user may be shown, in real time, the QI values and possible suggestions, as indicated in 501. The data for the suggestions may be in 520, where QI and their confidence level may be used to show suggestions. Suggestions can be shown for QI how a value is no good, and confidence level beyond a threshold, say 0.7

15           The QI indication user interface may be a number, and may even be an icon representing the quality. For example 5 smiles may each represent a quality indicator. Smiling face – good, crying face – bad, and so on.

20           A picture, once taken, may be shown to the user with its quality indicators, together with further suggestions on how to improve (for example “image is underexposed in a large area”).

25           The image may not be saved or may be deleted if total QI or any other predetermined QI is below some quality indicator threshold. After the image is saved, the quality indicators may be saved along with the image (one embodiment may be to use the EXIF convention used in JPEG files) so that they may be used at a later stage, such as when a user wants to see the picture quality days after it was taken.

**Suggestions to the user on how to improve the picture and component 520**

30           The user may choose to get suggestions from the application on how to improve the next shot. The application may use the quality indicators and their correlation to answer that.

                  This can be done before a final picture is taken and/or after. The application may use quality indicators, their confidence level, importance and their correlation to respond. This is where the database with user suggestions, component 520, is used. The data in this can be a table of text to be shown for every given QI with a low

value. In a more complex embodiment, it can be an SQL table being queried by multiple QI. An example of such a query on the database may be “select \* from suggestion\_table where QI1 > 0.9 and QI2 < 0.2” In this example QI1 can be module 200 ISO speed and QI2 can be device shake QI. The text retrieved can be “Try to use  
5 higher ISO speed to counteract device shake”. Another example can be QI1 is QI of 248 and QI2 is of 244. The text retrieved can be “focus may be off. Focus one another subject and try again”. There may be more complicated queries and embodiments, as a person in the field of databases can easily construct, given ideas from a person in the field of photography.

10 Text suggestions may be accompanied by an image explaining them. For example, if there is a low quality indicator of under/over exposure, the implication may be presented to the user via text, and overexposed areas on a picture preview may be painted in red, and underexposed areas may be in blue.

The confidence levels may aid in recognizing the best suggestion to be retrieved  
15 from a table of suggestions. For example, one may use a QI with confidence larger than 0.5, and show suggestions in the order of confidence levels. In another example, certain QIs may always have priority over others, even if their confidence levels are lower than others, as long as they are higher than, say 0.7.

#### **Device movement gestures as indications for shutter press and delete**

20 In another embodiment the user may not need to indicate he is ready by first pressing the shutter. In such cases, the device may assume that the user is ready at any time, or may wait for the device to be stationary hence pointed at some specific point in space for a certain configured time. For example, the user may pull the device out of his pocket and point it to the desired scene and hold it there for a duration of one second.  
25 The device hardware may detect that the device has been in motion for a few seconds, and then held relatively still in space, pointing at a certain direction for say one second. The system may assume that the user pulls the device out of his pocket in order to take a picture, and thus goes into “take picture” mode, waiting for the quality indicators to be above the threshold, then taking the picture automatically. The user  
30 may hear the sound of a picture being taken and return the device to his pocket. A shake gesture (available in mobile OS like iOS) may be an indication to the device to delete the picture and start again. Alternatively, the shake gesture may be recognized via the device shake QI.

#### **Using the system to evaluate video quality**

A quality ranking system over continuous frames, may be used to evaluate a video comprising said frames. One method would be to compute and average the total quality indicators over frames.

In another embodiment a different set of weight functions  $w_i$  may be used e.g. 5 different weights for different frames.

**Further examples of system use are as follows:**

- 10 a) If device shake QI is bad or camera focus QI is bad, disregard use of aesthetic QI in total computation, even if user has indicated he would like to give it a high priority. This will prevent the device from taking a picture when the picture is blurry. The suggestion to the user can be “Hold still” or “wait for focus”. Once shake is low and focus is optimal, aesthetic QI in total quality computations may be used.
- 15 b) Quality reported by lens module 200 showing focus is fine, but independent focus blur QI 244 shows the lens is completely out of focus e.g. due to a poor lens module focus application. Therefore, confidence in the lens focus quality indicator drops and the weight of this indicator in the total quality may be reduced.
- 20 c) Device movement QI confidence level computed in 270 is low due to errors in computing location in Device/surrounding objects 4D position computation component 230, or to sub standard accelerometer, but face recognition system 216 with excellent confidence level, insists on a face for 10 frames straight. In this case, use face recognition QI in total QI even if shake in 270 is high, but only at a reduced percentage of, say, 50% of normal face QI.
- 25 d) Device movement importance is high if the depth of field of the lens is very small (for instance, in macro photography). For a quality picture, high confidence and low value of device shake QI in 270 are desirable, and their weight in the total QI may be high. User suggestions can be to hold still or use a flash, for example.
- 30 e) If previous frames indicated a face in the far left or right of the picture, and now there is no face, it is very possible that the picture has “half a face”, amputation, so that may be the feedback to the user. For example, a face has been identified by the face recognizing QI, but attributes low confidence as a result. The system can alert the user of a possible face amputation.
- f) A person may want to take a picture of, say, his spouse in a scenic location, or

near a historic building. He may choose to give aesthetic QI and recognized person a high priority. This priority may enable to build a total QI with that weight, and to instruct the photographer to move a few meters to the right and left for example, to get an approximated 3D environment in  
5 Device/surrounding objects 4D position computation component 230. The device may measure all QI, especially the aesthetic QI, and may instruct the photographer on the best location to stand. This may depend on the place with the best total QI.

The system may if desired be implemented as a web-based system employing  
10 software, computers, routers and telecommunications equipment as appropriate.

Any suitable deployment may be employed to provide functionalities e.g. software functionalities shown and described herein. For example, a server may store certain applications, for download to clients, which are executed at the client side, the server side serving only as a storehouse. Some or all functionalities e.g. software  
15 functionalities shown and described herein may be deployed in a cloud environment. Clients e.g. mobile communication devices such as smartphones may be operatively associated with but external to the cloud.

It is appreciated that terminology such as "mandatory", "required", "need" and "must" refer to implementation choices made within the context of a particular  
20 implementation or application described herewithin for clarity and are not intended to be limiting since in an alternative implantation, the same elements might be defined as not mandatory and not required or might even be eliminated altogether.

It is appreciated that software components of the present invention including programs and data may, if desired, be implemented in ROM (read only memory) form  
25 including CD-ROMs, EPROMs and EEPROMs, or may be stored in any other suitable typically non-transitory computer-readable medium such as but not limited to disks of various kinds, cards of various kinds and RAMs. Components described herein as software may, alternatively, be implemented wholly or partly in hardware and/or firmware, if desired, using conventional techniques. Conversely, components  
30 described herein as hardware may, alternatively, be implemented wholly or partly in software, if desired, using conventional techniques.

Included in the scope of the present invention, inter alia, are electromagnetic signals carrying computer-readable instructions for performing any or all of the steps or operations of any of the methods shown and described herein, in any suitable order

including simultaneous performance of suitable groups of steps as appropriate; machine-readable instructions for performing any or all of the steps of any of the methods shown and described herein, in any suitable order; program storage devices readable by machine, tangibly embodying a program of instructions executable by the machine to perform any or all of the steps of any of the methods shown and described herein, in any suitable order; a computer program product comprising a computer useable medium having computer readable program code, such as executable code, having embodied therein, and/or including computer readable program code for performing, any or all of the steps of any of the methods shown and described herein, in any suitable order; any technical effects brought about by any or all of the steps of any of the methods shown and described herein, when performed in any suitable order; any suitable apparatus or device or combination of such, programmed to perform, alone or in combination, any or all of the steps of any of the methods shown and described herein, in any suitable order; electronic devices each including a processor and a cooperating input device and/or output device and operative to perform in software any steps shown and described herein; information storage devices or physical records, such as disks or hard drives, causing a computer or other device to be configured so as to carry out any or all of the steps of any of the methods shown and described herein, in any suitable order; a program pre-stored e.g. in memory or on an information network such as the Internet, before or after being downloaded, which embodies any or all of the steps of any of the methods shown and described herein, in any suitable order, and the method of uploading or downloading such, and a system including server/s and/or client/s for using such; a processor configured to perform any combination of the described steps or to execute any combination of the described modules; and hardware which performs any or all of the steps of any of the methods shown and described herein, in any suitable order, either alone or in conjunction with software. Any computer-readable or machine-readable media described herein is intended to include non-transitory computer- or machine-readable media.

Any computations or other forms of analysis described herein may be performed by a suitable computerized method. Any step described herein may be computer-implemented. The invention shown and described herein may include (a) using a computerized method to identify a solution to any of the problems or for any of the objectives described herein, the solution optionally include at least one of a

decision, an action, a product, a service or any other information described herein that impacts, in a positive manner, a problem or objectives described herein; and (b) outputting the solution.

The scope of the present invention is not limited to structures and functions specifically described herein and is also intended to include devices which have the capacity to yield a structure, or perform a function, described herein, such that even though users of the device may not use the capacity, they are if they so desire able to modify the device to obtain the structure or function.

Features of the present invention which are described in the context of separate embodiments may also be provided in combination in a single embodiment.

For example, a system embodiment is intended to include a corresponding process embodiment. Also, each system embodiment is intended to include a server-centered "view" or client centered "view", or "view" from any other node of the system, of the entire functionality of the system, computer-readable medium, apparatus, including only those functionalities performed at that server or client or node.

Conversely, features of the invention, including method steps, which are described for brevity in the context of a single embodiment or in a certain order may be provided separately or in any suitable subcombination or in a different order. "e.g." is used herein in the sense of a specific example which is not intended to be limiting. Devices, apparatus or systems shown coupled in any of the drawings may in fact be integrated into a single platform in certain embodiments or may be coupled via any appropriate wired or wireless coupling such as but not limited to optical fiber, Ethernet, Wireless LAN, HomePNA, power line communication, cell phone, PDA, Blackberry GPRS, Satellite including GPS, or other mobile delivery. It is appreciated that in the description and drawings shown and described herein, functionalities described or illustrated as systems and sub-units thereof can also be provided as methods and steps therewithin, and functionalities described or illustrated as methods and steps therewithin can also be provided as systems and sub-units thereof. The scale used to illustrate various elements in the drawings is merely exemplary and/or appropriate for clarity of presentation and is not intended to be limiting.

**CLAIMS:**

1. A digital image acquisition system comprising  
an image capture component for capturing in a buffer, a current digital image  
5 having pixels;  
at least one digital processor programmed for real time computation of  
multiple quality indicators characterizing quality of the current digital image;  
automatic image capturing, and storing in user-accessible memory, of at least  
one image only after a first logical criterion predefined on said multiple quality  
10 indicators, is satisfied; and  
a message provider operative, while said first logical criterion is still not  
satisfied, to select, based on at least one second logical criterion pre-defined on at  
least one of said multiple quality indicators, at least one appropriate suggestion from a  
pre-stored table of suggestions of how a user of the system may cause said first  
15 logical criterion to be satisfied and to present said appropriate suggestion to the user,  
wherein at least one of said logical criteria are pre-defined over a time-  
dependent confidence level defined over at least one of said quality indicators.
2. A system according to claim 1 wherein at least one of said indicators  
20 characterizing quality is computed based on analyzing said pixels.
3. A system according to claim 1 wherein at least one of said indicators  
characterizing quality is computed based on comparing said pixels to previous frame  
data generated by said image capture component.  
25
4. A system according to claim 3 wherein said comparing comprises identifying  
an object in a current and a previous frame and computing the object's speed.
5. A system according to claim 1 wherein at least one of said indicators  
30 characterizing quality is computed based on data received from at least one hardware  
component operatively associated with the image capture component.
6. A system according to claim 5 wherein said hardware component includes at  
least one of an accelerometer, gyro, GPS receiver.

7. A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on 4D device coordinates.
- 5 8. A system according to claim 1 wherein said logical criterion comprises whether or not a total quality indicator computed by combining said multiple quality indicators, exceeds a predetermined threshold.
9. A system according to claim 1 wherein said logical criterion comprises  
10 whether or not each of said multiple quality indicators, exceeds a predetermined threshold.
10. A system according to claim 1 wherein said logical criterion comprises a logical expression combining with at least one OR, several logical conditions of  
15 whether or not certain individual indicators from among said multiple quality indicators, exceeds a predetermined respective threshold.
11. A method for computing the photo quality of a captured image in a device image acquisition system, said method comprising:  
20 on-board combining of:  
a plurality of quality indicators computed from said captured image and its previous image frames quality indicators and  
a confidence level for at least one of said quality indicators,; and  
determining, based on said combining, whether photo quality is acceptable  
25 and taking differential action depending on whether quality is or is not acceptable.
12. A method according to claim 11 and also comprising automatically activating the capturing apparatus, after a logical criterion based on at least one said quality indicator is met.  
30
13. A method according to claim 11 and also comprising, based on said combining, at least one appropriate suggestion from a pre-stored table of suggestions on how picture quality can be improved.

14. A system according to claim 1 wherein said pre-stored table of suggestions includes a suggestion of changing at least one characteristic of said image capture component.
- 5 15. A method according to claim 11 wherein a stream of frames is saved as video and at least quality indicators are used to quantify quality of said video.
16. A method according to claim 11 and also comprising giving a user suggestions on improvement of the video.
- 10 17. A method according to claim 11 wherein at least one lens/sensor module parameter is changed, based on said combining, to achieve better total QI.
18. A method according to claim 11 and also comprising automatic image capturing of at least one picture once a configured total quality indicator meets a minimum threshold, even without the user pressing a shutter button.
- 15 19. A method according to claim 11 wherein blur type detection is used for alerting the user of object movement in a region.
- 20 20. A method according to claim 11 wherein blur type detection is used for alerting the user he is moving too fast in a vehicle to achieve a non-blurred image.
21. A method according to claim 11 wherein at least one quality indicator is used as a delete-picture indication.
- 25 22. A system according to claim 1 wherein said automatic capturing occurs only after a user presses a shutter button.
- 30 23. A system according to claim 1 wherein said automatic capturing occurs regardless of whether a user has pressed a shutter button.
24. A system according to claim 1 wherein one quality indicator comprises a quantification of blurriness in the current image and wherein said table includes a

“Remove Moving Object From Scene Or Cause Object To Remain Stationary” message and wherein the message provider is operative, while said logical criterion is still not satisfied, to select same message, based on a condition pre-defined on said blurriness quantification.

5 25. A system according to claim 5 wherein said logical criterion comprises a criterion predicting based on at least one of an accelerometer and a GPS receiver, a time at which there will be an acceptably low level of image capture component shake, and said automatic image capturing occurs at said time.

10 26. A system according to claim 14 wherein said at least one characteristic of said image capture component comprises at least one of angle and position thereof.


15 27. A computer program product, comprising a non-transitory tangible computer readable medium having computer readable program code embodied therein, said computer readable program code adapted to be executed to implement a digital image acquisition method comprising:

real time computation of multiple quality indicators characterizing quality of a current digital image;


20 automatic image capturing, and storing in user-accessible memory, of at least one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied; and

25 selecting, while said first logical criterion is still not satisfied, based on at least one second logical criterion pre-defined on at least one of said multiple quality indicators, at least one appropriate suggestion from a pre-stored table of suggestions of how a user of the system may cause said first logical criterion to be satisfied and to present said appropriate suggestion to the user,

wherein at least one of said logical criteria are pre-defined over a time-dependent confidence level defined over at least one of said quality indicators.



**Fig. 1**







Fig. 3

Fig. 4



INTERNATIONAL SEARCH REPORT


International application No.

PCT/IL13/50856

| <p><b>A. CLASSIFICATION OF SUBJECT MATTER</b><br/>                 IPC(8) - G06K 9/46 (2014.01)<br/>                 USPC - 382/195<br/>                 According to International Patent Classification (IPC) or to both national classification and IPC</p>   |  |   |  |   |   |  |   |  |  |  |  |   |  |                     |
|--|--|---|--|---|---|--|---|--|--|--|--|---|--|---------------------|
| <p><b>B. FIELDS SEARCHED</b></p> <p>Minimum documentation searched (classification system followed by classification symbols)<br/>                 IPC(8) : G06T 15/00; G06K 9/46; G06K 9/40 (2014.01)<br/>                 USPC : 382/275; 382/195; 352/38</p> <p>Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched</p> <p>Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)<br/>                 MicroPatent (US-G, US-A, EP-A, EP-B, WO, JP-bib, DE-C,B, DE-A, DE-T, DE-U, GB-A, FR-A); Google/ GooglePatents; IEEE; ProQuest<br/>                 Keywords: Digital image and quality indicator and blurr and confidence</p>  |  |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| <p><b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b></p> <table border="1"> <thead> <tr> <th>Category*</th> <th>Citation of document, with indication, where appropriate, of the relevant passages</th> <th>Relevant to claim No.</th> </tr> </thead> <tbody> <tr> <td>X<br/>---<br/>A</td> <td>US 2004/0174434 A1 (WALKER, J et al.) 9 September 2004; Abstract; paragraphs [0044], [0506], [0715].</td> <td>11-13 and 15-21<br/>-----<br/>1-10, 14, and 22-27</td> </tr> <tr> <td>A</td> <td>US 8131118 B1 (JING, Y et al.) 6 March 2012; Whole document.</td> <td>1-10, 14, and 22-27</td> </tr> <tr> <td>A</td> <td>US 2011/0279700 A1 (STEINBERG, E et al.) 17 November 2011; Whole document.</td> <td>1-10, 14, and 22-27</td> </tr> </tbody> </table>   |  |   | Category*  | Citation of document, with indication, where appropriate, of the relevant passages  | Relevant to claim No.   | X<br>---<br>A  | US 2004/0174434 A1 (WALKER, J et al.) 9 September 2004; Abstract; paragraphs [0044], [0506], [0715].  | 11-13 and 15-21<br>-----<br>1-10, 14, and 22-27  | A  | US 8131118 B1 (JING, Y et al.) 6 March 2012; Whole document. | 1-10, 14, and 22-27  | A | US 2011/0279700 A1 (STEINBERG, E et al.) 17 November 2011; Whole document. | 1-10, 14, and 22-27 |
| Category*  | Citation of document, with indication, where appropriate, of the relevant passages   | Relevant to claim No.   |  |   |   |  |   |  |  |  |  |   |  |                     |
| X<br>---<br>A  | US 2004/0174434 A1 (WALKER, J et al.) 9 September 2004; Abstract; paragraphs [0044], [0506], [0715].   | 11-13 and 15-21<br>-----<br>1-10, 14, and 22-27   |  |   |   |  |   |  |  |  |  |   |  |                     |
| A  | US 8131118 B1 (JING, Y et al.) 6 March 2012; Whole document.   | 1-10, 14, and 22-27   |  |   |   |  |   |  |  |  |  |   |  |                     |
| A  | US 2011/0279700 A1 (STEINBERG, E et al.) 17 November 2011; Whole document.   | 1-10, 14, and 22-27   |  |   |   |  |   |  |  |  |  |   |  |                     |
| <p><input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/></p>  |  |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| <p>* Special categories of cited documents:</p> <table border="0"> <tr> <td>"A" document defining the general state of the art which is not considered to be of particular relevance</td> <td>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td> </tr> <tr> <td>"E" earlier application or patent but published on or after the international filing date</td> <td>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td> </tr> <tr> <td>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td> <td>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td> </tr> <tr> <td>"O" document referring to an oral disclosure, use, exhibition or other means</td> <td>"&amp;" document member of the same patent family</td> </tr> <tr> <td>"P" document published prior to the international filing date but later than the priority date claimed</td> <td></td> </tr> </table> |  |   | "A" document defining the general state of the art which is not considered to be of particular relevance | "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention | "E" earlier application or patent but published on or after the international filing date | "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone | "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) | "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art | "O" document referring to an oral disclosure, use, exhibition or other means | "&" document member of the same patent family                | "P" document published prior to the international filing date but later than the priority date claimed |   |  |                     |
| "A" document defining the general state of the art which is not considered to be of particular relevance   | "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention  |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| "E" earlier application or patent but published on or after the international filing date  | "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone   |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  | "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| "O" document referring to an oral disclosure, use, exhibition or other means   | "&" document member of the same patent family  |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| "P" document published prior to the international filing date but later than the priority date claimed   |  |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| <p>Date of the actual completion of the international search<br/>                 3 February 2014 (03.02.2014)</p>   |  | <p>Date of mailing of the international search report<br/> <b>18 FEB 2014</b></p>   |  |   |   |  |   |  |  |  |  |   |  |                     |
| <p>Name and mailing address of the ISA/US<br/>                 Mail Stop PCT, Attn: ISA/US, Commissioner for Patents<br/>                 P.O. Box 1450, Alexandria, Virginia 22313-1450<br/>                 Facsimile No. 571-273-3201</p>   |  | <p>Authorized officer:<br/>                 Shane Thomas<br/>                 PCT Helpdesk: 571-272-4300<br/>                 PCT OSP: 571-272-7774</p> |  |   |   |  |   |  |  |  |  |   |  |                     |

PCT

Print Out (Original in Electronic Form)

|              |   |  |
|--------------|---|--|
| VIII-4-1     | <p>Declaration: inventorship (only for the purposes of the designation of the United States of America)<br/>                 Declaration of Inventorship (Rules 4.17(iv) and 51bis.1(a)(iv)) for the purposes of the designation of the United States of America:</p> | <p>I hereby declare that I believe I am the original inventor or an original joint inventor of a claimed invention in the application.</p> <p>This declaration is directed to international application No. PCT/IL2013/050856.</p> <p>I hereby declare that the above-identified international application was made or authorized to be made by me.</p> <p>I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.</p> |
| VIII-4-1-1   | Name (LAST, First)  | SIVAN, Ishay   |
| VIII-4-1-1-2 | Residence:<br>(city and either US state, if applicable, or country)   | Tel Aviv, Israel   |
| VIII-4-1-1-3 | Mailing Address:  | 12 Dissentchik Street 6935635 Tel Aviv Israel  |
| VIII-4-1-1-4 | Inventor's Signature:<br>(The signature must be that of the inventor, not that of the agent)  |   |
| VIII-4-1-1-5 | Date:   | 27/11/13   |

## PATENT COOPERATION TREATY

From the INTERNATIONAL SEARCHING AUTHORITY

To: Reinhold Cohn and Partners  
P.O.B. 13239  
6113102 Tel Aviv  
Israel

**PCT**

NOTIFICATION OF TRANSMITTAL OF  
THE INTERNATIONAL SEARCH REPORT AND  
THE WRITTEN OPINION OF THE INTERNATIONAL  
SEARCHING AUTHORITY, OR THE DECLARATION

(PCT Rule 44.1)

|  |  |                              |
|--|--|------------------------------|
| Date of mailing<br>(day/month/year)              |  | <b>18 FEB 2014</b>           |
| Applicant's or agent's file reference<br>2247936 | <b>FOR FURTHER ACTION</b> See paragraphs 1 and 4 below |                              |
| International application No.<br>PCT/IL13/50856  | International filing date<br>(day/month/year)          | 22 October 2013 (22.10.2013) |
| Applicant<br>Ishay Sivan                         |  |                              |

1.  The applicant is hereby notified that the international search report and the written opinion of the International Searching Authority have been established and are transmitted herewith.

**Filing of amendments and statement under Article 19:**  
The applicant is entitled, if he so wishes, to amend the claims of the international application (see Rule 46):

**When?** The time limit for filing such amendments is normally two months from the date of transmittal of the international search report.

**Where?** Directly to the International Bureau of WIPO, 34 chemin des Colombettes  
1211 Geneva 20, Switzerland, Facsimile No.: +41 22 338 82 70

**For more detailed instructions, see PCT Applicant's Guide, International Phase, paragraphs 9.004 – 9.011.**

2.  The applicant is hereby notified that no international search report will be established and that the declaration under Article 17(2)(a) to that effect and the written opinion of the International Searching Authority are transmitted herewith.

3.  **With regard to any protest** against payment of (an) additional fee(s) under Rule 40.2, the applicant is notified that:

the protest together with the decision thereon has been transmitted to the International Bureau together with any request to forward the texts of both the protest and the decision thereon to the designated Offices.

no decision has been made yet on the protest; the applicant will be notified as soon as a decision is made.

4. **Reminders**

The applicant may submit comments on an informal basis on the written opinion of the International Searching Authority to the International Bureau. The International Bureau will send a copy of such comments to all designated Offices unless an international preliminary examination report has been or is to be established. Following the expiration of 30 months from the priority date, these comments will also be made available to the public.

Shortly after the expiration of **18 months** from the priority date, the international application will be published by the International Bureau. If the applicant wishes to avoid or postpone publication, a notice of withdrawal of the international application, or of the priority claim, must reach the International Bureau before the completion of the technical preparations for international publication (Rules 90bis.1 and 90bis.3).

Within **19 months** from the priority date, but only in respect of some designated Offices, a demand for international preliminary examination must be filed if the applicant wishes to postpone the entry into the national phase **until 30 months** from the priority date (in some Offices even later); otherwise, the applicant must, **within 20 months** from the priority date, perform the prescribed acts for entry into the national phase before those designated Offices.

In respect of other designated Offices, the time limit of **30 months** (or later) will apply even if no demand is filed within 19 months.

For details about the applicable time limits, Office by Office, see [www.wipo.int/pct/en/texts/time\\_limits.html](http://www.wipo.int/pct/en/texts/time_limits.html) and the *PCT Applicant's Guide, National Chapters*.

|   |   |
|---|---|
| Name and mailing address of the ISA/<br>Mail Stop PCT, Attn: ISA/US<br>Commissioner for Patents<br>P.O. Box 1450, Alexandria, Virginia 22313-1450<br>Facsimile No. 571-273-3201 | Authorized officer<br><br>Shane Thomas<br><br>PCT Helpdesk: 571-272-4300<br>Telephone No. PCT OSP: 571-272-7774 |
|---|---|

Form PCT/ISA/220 (July 2010)

## PATENT COOPERATION TREATY

## PCT

## INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

|  |   |  |   |
|--|---|--|---|
| Applicant's or agent's file reference<br>2247936 | <b>FOR FURTHER ACTION</b>   |  | see Form PCT/ISA/220<br>as well as, where applicable, item 5 below. |
| International application No.<br>PCT/IL13/50856  | International filing date ( <i>day/month/year</i> )<br>22 October 2013 (22.10.2013) | (Earliest) Priority Date ( <i>day/month/year</i> )<br>23 October 2012 (23.10.2012) |   |
| Applicant<br>Ishay Sivan                         |   |  |   |

This international search report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This international search report consists of a total of 2 sheets.

It is also accompanied by a copy of each prior art document cited in this report.

## 1. Basis of the report

a. With regard to the **language**, the international search was carried out on the basis of:

the international application in the language in which it was filed.

a translation of the international application into \_\_\_\_\_ which is the language of a translation furnished for the purposes of international search (Rules 12.3(a) and 23.1(b)).

b.  This international search report has been established taking into account the **rectification of an obvious mistake** authorized by or notified to this Authority under Rule 91 (Rule 43.6bis(a)).

c.  With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, see Box No. I.

2.  **Certain claims were found unsearchable** (see Box No. II).

3.  **Unity of invention is lacking** (see Box No. III).

4. With regard to the **title**,

the text is approved as submitted by the applicant.

the text has been established by this Authority to read as follows:

## REAL TIME ASSESSMENT OF PICTURE QUALITY

5. With regard to the **abstract**,

the text is approved as submitted by the applicant.

the text has been established, according to Rule 38.2, by this Authority as it appears in Box No. IV. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. With regard to the **drawings**,

a. the figure of the **drawings** to be published with the abstract is Figure No. 1

as suggested by the applicant.

as selected by this Authority, because the applicant failed to suggest a figure.

as selected by this Authority, because this figure better characterizes the invention.

b.  none of the figures is to be published with the abstract.

INTERNATIONAL SEARCH REPORT

International application No.  
PCT/IL13/50856

| <p><b>A. CLASSIFICATION OF SUBJECT MATTER</b><br/>                 IPC(8) - G06K 9/46 (2014.01)<br/>                 USPC - 382/195<br/>                 According to International Patent Classification (IPC) or to both national classification and IPC</p>   |  |   |  |   |   |  |   |  |  |  |  |   |  |                     |
|--|--|---|--|---|---|--|---|--|--|--|--|---|--|---------------------|
| <p><b>B. FIELDS SEARCHED</b></p> <p>Minimum documentation searched (classification system followed by classification symbols)<br/>                 IPC(8) : G06T 15/00; G06K 9/46; G06K 9/40 (2014.01)<br/>                 USPC : 382/275; 382/195; 352/38</p> <p>Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched</p> <p>Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)<br/>                 MicroPatent (US-G, US-A, EP-A, EP-B, WO, JP-bib, DE-C,B, DE-A, DE-T, DE-U, GB-A, FR-A); Google/ GooglePatents; IEEE; ProQuest<br/>                 Keywords: Digital image and quality indicator and blur and confidence</p>   |  |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| <p><b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b></p> <table border="1"> <thead> <tr> <th>Category*</th> <th>Citation of document, with indication, where appropriate, of the relevant passages</th> <th>Relevant to claim No.</th> </tr> </thead> <tbody> <tr> <td>X<br/>—<br/>A</td> <td>US 2004/0174434 A1 (WALKER, J et al.) 9 September 2004; Abstract; paragraphs [0044], [0506], [0715].</td> <td>11-13 and 15-21<br/>-----<br/>1-10, 14, and 22-27</td> </tr> <tr> <td>A</td> <td>US 8131118 B1 (JING, Y et al.) 6 March 2012; Whole document.</td> <td>1-10, 14, and 22-27</td> </tr> <tr> <td>A</td> <td>US 2011/0279700 A1 (STEINBERG, E et al.) 17 November 2011; Whole document.</td> <td>1-10, 14, and 22-27</td> </tr> </tbody> </table>   |  |   | Category*  | Citation of document, with indication, where appropriate, of the relevant passages  | Relevant to claim No.   | X<br>—<br>A  | US 2004/0174434 A1 (WALKER, J et al.) 9 September 2004; Abstract; paragraphs [0044], [0506], [0715].  | 11-13 and 15-21<br>-----<br>1-10, 14, and 22-27  | A  | US 8131118 B1 (JING, Y et al.) 6 March 2012; Whole document. | 1-10, 14, and 22-27  | A | US 2011/0279700 A1 (STEINBERG, E et al.) 17 November 2011; Whole document. | 1-10, 14, and 22-27 |
| Category*  | Citation of document, with indication, where appropriate, of the relevant passages   | Relevant to claim No.   |  |   |   |  |   |  |  |  |  |   |  |                     |
| X<br>—<br>A  | US 2004/0174434 A1 (WALKER, J et al.) 9 September 2004; Abstract; paragraphs [0044], [0506], [0715].   | 11-13 and 15-21<br>-----<br>1-10, 14, and 22-27   |  |   |   |  |   |  |  |  |  |   |  |                     |
| A  | US 8131118 B1 (JING, Y et al.) 6 March 2012; Whole document.   | 1-10, 14, and 22-27   |  |   |   |  |   |  |  |  |  |   |  |                     |
| A  | US 2011/0279700 A1 (STEINBERG, E et al.) 17 November 2011; Whole document.   | 1-10, 14, and 22-27   |  |   |   |  |   |  |  |  |  |   |  |                     |
| <p><input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/></p>  |  |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| <p>* Special categories of cited documents:</p> <table border="0"> <tr> <td>"A" document defining the general state of the art which is not considered to be of particular relevance</td> <td>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td> </tr> <tr> <td>"E" earlier application or patent but published on or after the international filing date</td> <td>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td> </tr> <tr> <td>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td> <td>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td> </tr> <tr> <td>"O" document referring to an oral disclosure, use, exhibition or other means</td> <td>"&amp;" document member of the same patent family</td> </tr> <tr> <td>"P" document published prior to the international filing date but later than the priority date claimed</td> <td></td> </tr> </table> |  |   | "A" document defining the general state of the art which is not considered to be of particular relevance | "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention | "E" earlier application or patent but published on or after the international filing date | "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone | "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) | "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art | "O" document referring to an oral disclosure, use, exhibition or other means | "&" document member of the same patent family                | "P" document published prior to the international filing date but later than the priority date claimed |   |  |                     |
| "A" document defining the general state of the art which is not considered to be of particular relevance   | "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention  |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| "E" earlier application or patent but published on or after the international filing date  | "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone   |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  | "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| "O" document referring to an oral disclosure, use, exhibition or other means   | "&" document member of the same patent family  |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| "P" document published prior to the international filing date but later than the priority date claimed   |  |   |  |   |   |  |   |  |  |  |  |   |  |                     |
| <p>Date of the actual completion of the international search<br/>3 February 2014 (03.02.2014)</p>  |  | <p>Date of mailing of the international search report<br/><b>18 FEB 2014</b></p>  |  |   |   |  |   |  |  |  |  |   |  |                     |
| <p>Name and mailing address of the ISA/US<br/>                 Mail Stop PCT, Attn: ISA/US, Commissioner for Patents<br/>                 P.O. Box 1450, Alexandria, Virginia 22313-1450<br/>                 Facsimile No. 571-273-3201</p>   |  | <p>Authorized officer:<br/>Shane Thomas<br/><br/>                 PCT Helpdesk: 571-272-4300<br/>                 PCT OSP: 571-272-7774</p> |  |   |   |  |   |  |  |  |  |   |  |                     |

## PCT Recordation of Search History

Case/PCT Application Number: PCT/IL13/50856

CLIN Number/Technical Field of PCT Application: 5

Date(s) during which the search was conducted: 1 February 2014 (01.02.2014) – 3 February 2014 (03.02.2014)

Date of Completion of Recordation of Search History Form: 3 February 2014 (03.02.2014)

Research Analyst Initials: DMB

Search Approval Official (SAO) Initials: CEH

### Field of Search/Classification Information:

IPC(8) Classification(s): G06T 15/00; G06K 9/46; G06K 9/40 (2014.01)

USPC Classification(s): 382/275; 382/195; 352/38

### Database(s) Searched (Patent and Non-Patent Literature (NPL), Including Sub-Databases and Files Searched) and Search Terms Used:

MicroPatent (US-G, US-A, EP-A, EP-B, WO, JP-bib, DE-C,B, DE-A, DE-T, DE-U, GB-A, FR-A); Google/ GooglePatents; IEEE; ProQuest

Keywords: Digital image and quality indicator and blurr and confidence

### Database Search String Recordation, Including Dates of Searches):

## Patent Database Search Strategy/Results:

| #  | results  | action | last run |
|----|--|--------|----------|
| 52 | <p>Full patent spec. (image adj acquisit*)and (quality near5 indicator*)</p> <p><u>5 hits</u></p> <p>Current US Class 382275 or 382195 or 352038</p> <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p> <p>Years 1836-2014</p>           |        | 2/3/2014 |
| 51 | <p>Full patent spec. (image adj acquisit*)and (quality near5 indicator*)</p> <p><u>17 hits</u></p> <p>Current IPC-R G06T001500 or G06K000946 or G06K000940</p> <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p> <p>Years 1836-2014</p> |        | 2/3/2014 |
| 50 | <p>Full patent spec. (image adj acquisit*)</p> <p><u>1808 hits</u></p> <p>Current IPC-R G06T001500 or G06K000946 or G06K000940</p> <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p> <p>Years 1836-2014</p>                             |        | 2/3/2014 |
| 48 | <p><u>3 hits</u></p> <p>Assignee/Applicant (3-D adj Virtual adj Lens)</p>  |        | 2/3/2014 |

|    |              |                        |   |          |
|----|--------------|------------------------|---|----------|
|    |              | Databases              | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA   |          |
|    |              | Years                  | 1836-2014   |          |
|    |              | Assignee/Applicant     | (3D adj lens*)  |          |
| 47 | no hits      | Databases              | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA   | 2/3/2014 |
|    |              | Years                  | 1836-2014   |          |
|    |              | Assignee/Applicant     | 3D lens*  |          |
| 46 | no hits      | Databases              | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA   | 2/3/2014 |
|    |              | Years                  | 1836-2014   |          |
|    |              | Full patent spec.      | (quality near5 (indicator*)) and ((4D or 4-dimension* or 4 adj dimension*) near5 (coordinate* or co-ordinate*)) |          |
|    | <u>1 hit</u> |                        |   | 2/3/2014 |
| 45 |              | Databases              | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA   |          |
|    |              | Years                  | 1836-2014   |          |
|    |              | Patent/Publication No. | US2012045618 or 2004174434  |          |
|    | <u>1 hit</u> |                        |   | 2/3/2014 |
| 44 |              | Databases              | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA   |          |
|    |              | Years                  | 2005-2014   |          |
|    |              | Patent/Publication No. | WO2013006731 or W02011148212  |          |
|    | <u>1 hit</u> |                        |   | 2/3/2014 |
| 43 |              | Databases              | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA   |          |
|    |              | Years                  | 2005-2014   |          |

|    |                 |  |          |
|----|-----------------|--|----------|
| 42 | <u>8 hits</u>   | Full patent spec. quality near4 indicator*) and ((delet* or remov*) near5 (digital near5 (picture or image))             | 2/3/2014 |
|    |                 | Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
|    |                 | Years 1836-2014  |          |
|    |                 | Full patent spec. (digital adj camera*) and (quality near4 indicator*) and ((delet* or remov*) near5 (picture or image)) |          |
|    | <u>70 hits</u>  |  | 2/3/2014 |
|    |                 | Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
| 41 |                 | Years 1836-2014  |          |
|    |                 | Full patent spec. (digital adj camera*) and face and blur* and alert* and ((object or user) near5 moving)                |          |
|    | <u>212 hits</u> |  | 2/3/2014 |
|    |                 | Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
| 40 |                 | Years 1836-2014  |          |
|    |                 | Full patent spec. (image* near5 acquisit*) and face and blur* and alert* and (object near5 moving)                       |          |
|    | <u>184 hits</u> |  | 2/3/2014 |
|    |                 | Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
| 38 |                 | Years 1836-2014  |          |
|    | <u>28 hits</u>  | Full patent spec. (image* near5 acqu*) and (quality near5 indicator*) and threshold and face and blur*                   | 2/3/2014 |
| 36 |                 |  |          |

|    |                  |                   |  |          |
|----|------------------|-------------------|--|----------|
|    |                  | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
|    |                  | Years             | 1836-2014  |          |
|    |                  | Full patent spec. | (image* near5 Capt*) and (quality near5 indicator*) and threshold and face           |          |
|    | <u>123 hits</u>  |                   |  | 2/3/2014 |
|    |                  | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
| 35 |                  | Years             | 1836-2014  |          |
|    |                  | Full patent spec. | (image* near5 Capt*) and (quality near5 indicator*) and threshold                    |          |
|    | <u>616 hits</u>  |                   |  | 2/3/2014 |
|    |                  | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
| 34 |                  | Years             | 1836-2014  |          |
|    |                  | Full patent spec. | (digital near5 image* adj acquisition*) and (quality near5 indicator*) and threshold |          |
|    | <u>11 hits</u>   |                   |  | 2/3/2014 |
|    |                  | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
| 33 |                  | Years             | 1836-2014  |          |
|    |                  | Full patent spec. | image* and (quality near5 indicator*) and confidence                                 |          |
|    | <u>1006 hits</u> |                   |  | 2/3/2014 |
|    |                  | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
| 32 |                  | Years             | 1836-2014  |          |

|    |                 |  |          |
|----|-----------------|--|----------|
| 31 | <u>149 hits</u> | Full patent spec. image* and (quality near5 indicator*) and confidence and (accelerometer* or gyro*)                         | 2/3/2014 |
|    |                 | Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
|    |                 | Years 1836-2014  |          |
|    |                 | Full patent spec. image* and (quality near5 indicator*) and confidence and (accelerometer* or gyro* or GPS*)                 |          |
|    | <u>274 hits</u> |  | 2/3/2014 |
|    |                 | Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
|    |                 | Years 1836-2014  |          |
|    |                 | Full patent spec. (image* near5 acquir*) and (quality near5 indicator*) and confidence and (accelerometer* or gyro* or GPS*) |          |
|    | <u>47 hits</u>  |  | 2/3/2014 |
|    |                 | Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
|    |                 | Years 1836-2014  |          |
|    |                 | Full patent spec. (image* near5 captur*) and (quality near5 indicator*) and confidence and (accelerometer* or gyro* or GPS*) |          |
|    | <u>45 hits</u>  |  | 2/3/2014 |
|    |                 | Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
|    |                 | Years 1836-2014  |          |
| 28 |                 |  |          |

|    |                   |   |          |
|----|-------------------|---|----------|
|    | Full patent spec. | (image* near5 acquisition*) and (quality near5 indicator*) and confidence and (accelerometer* or gyro* or GPS*) |          |
|    | <u>20 hits</u>    |   | 2/3/2014 |
|    | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA   |          |
| 27 | Years             | 1836-2014   |          |
|    | Full patent spec. | (image* near5 acquisition*) and (quality near5 indicator*) and confidence                                       |          |
|    | <u>137 hits</u>   |   | 2/3/2014 |
|    | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA   |          |
| 26 | Years             | 1836-2014   |          |
|    | Full patent spec. | (digital near5 image* near5 acquisition*) and (quality near5 indicator*) and confidence                         |          |
|    | no hits           |   | 2/3/2014 |
|    | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA   |          |
| 25 | Years             | 1836-2014   |          |
|    | Full patent spec. | (digital adj image* adj acquisition*) and (quality near5 indicator*) and confidence                             |          |
|    | no hits           |   | 2/3/2014 |
|    | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA   |          |
| 24 | Years             | 1836-2014.  |          |
|    | Full patent spec. | (digital adj image* adj acquisition) and quality and confidence   |          |
|    | <u>284 hits</u>   |   | 2/3/2014 |
| 23 |                   |   |          |

|    |                  |                   |  |          |
|----|------------------|-------------------|--|----------|
|    |                  | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
|    |                  | Years             | 1836-2014  |          |
|    |                  | Full patent spec. | (digital adj image* adj acquisition)   |          |
|    | <u>2440 hits</u> | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  | 2/3/2014 |
| 22 |                  | Years             | 1836-2014  |          |
|    |                  | Full patent spec. | (digital adj image* adj acquisition) and ((quality near4 indicator*)) and confidence   |          |
|    | no hits          | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  | 2/3/2014 |
|    |                  | Years             | 1836-2014  |          |
| 21 |                  | Full patent spec. | digital and image* and ((quality near2 indicator*)) and ((real adj time) or dynamic*) and (table or chart) and confidence              |          |
|    | <u>277 hits</u>  | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  | 2/3/2014 |
|    |                  | Years             | 1836-2014  |          |
| 20 |                  | Full patent spec. | digital and image* and (TQI or IQI* or (quality adj indicator*)) and ((real adj time) or dynamic*) and (table or chart) and confidence |          |
|    | <u>279 hits</u>  | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  | 2/3/2014 |
|    |                  | Years             | 1836-2014  |          |
| 18 |                  | Databases         | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
|    |                  | Years             | 1836-2014  |          |

|    |                        |  |          |
|----|------------------------|--|----------|
| 17 | <p><u>254 hits</u></p> | <p>Full patent spec. digital and image* and (TQI or IQI* or (quality adj indicator*)) and ((real adj time) or dynamic*) and (stor* near5(table or chart or data or information or content)) and confidence</p>                   | 2/3/2014 |
|    |                        | <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p>   |          |
|    |                        | <p>Years 1836-2014</p>   |          |
|    |                        | <p>Full patent spec. camera and (image near5 acquisition) and (TQI or IQI* or (quality adj indicator*)) and ((real adj time) or dynamic*) and (stor* near5(table or chart or data or information or content)) and confidence</p> |          |
|    | <p><u>6 hits</u></p>   |  | 2/3/2014 |
|    |                        | <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p>   |          |
|    |                        | <p>Years 1836-2014</p>   |          |
|    |                        | <p>Full patent spec. (image adj acquisition) and (TQI or QI* or (quality adj indicator*)) and ((real adj time) or dynamic*) and (stor* near5(table or chart or data or information or content)) and confidence</p>               |          |
|    | <p><u>210 hits</u></p> |  | 2/3/2014 |
|    |                        | <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p>   |          |
| 15 |                        |  |          |

|           |   |                 |
|-----------|---|-----------------|
|           | <p>Years 1836-2014</p> <p>Full patent spec. (image adj acquisition) and (TQI or QI* or (quality adj indicator*)) and ((real adj time) or dynamic*) and (pre-stor* near5(table or chart or data or information or content)) and confidence</p>                             | <p>2/3/2014</p> |
| <p>14</p> | <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p> <p>Years 1836-2014</p> <p>Full patent spec. (image adj acquisition) and (TQI or QI* or (quality adj indicator*)) and ((real adj time) or dynamic*) and confidence and threshold</p>                        | <p>2/3/2014</p> |
| <p>13</p> | <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p> <p>Years 1836-2014</p> <p>Full patent spec. (image adj acquisition) and (TQI or QI* or (quality adj indicator*)) and ((real adj time) or dynamic*) and confidence and (accelerometer* or gyro* or GPS)</p> | <p>2/3/2014</p> |
| <p>12</p> | <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p> <p>Years 1836-2014</p>   |                 |

5 hits

2 hits

30 hits

|    |                         |  |          |
|----|-------------------------|--|----------|
| 11 | <p><u>486 hits</u></p>  | <p>Full patent spec. (image adj acquisition) and (TQI or QI* or (quality adj indicator*)) and ((real adj time) or dynamic*) and confidence</p>                           | 2/3/2014 |
|    |                         | <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p>   |          |
|    |                         | <p>Years 1836-2014</p>   |          |
|    | <p>no hits</p>          | <p>Full patent spec. (image adj acquisition) and (TQI or QI* or (quality adj indicator*)) and ((real adj time) or dynamic*) and confidence and (4D near4 coordinat*)</p> | 2/3/2014 |
|    |                         | <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p>   |          |
|    |                         | <p>Years 1836-2014</p>   |          |
| 10 | <p><u>2479 hits</u></p> | <p>Full patent spec. (image adj acquisition) and (TQI or QI* or (quality adj indicator*)) and ((real adj time) or dynamic*)</p>  | 2/3/2014 |
|    |                         | <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p>   |          |
|    |                         | <p>Years 1836-2014</p>   |          |
| 8  | <p><u>2 hits</u></p>    | <p>Full patent spec. (digital adj image adj acquisition) and (TQI or (quality adj indicator*)) and (real adj time)</p>   | 2/3/2014 |
| 7  |                         |  |          |

|   |                 |                           |  |          |
|---|-----------------|---------------------------|--|----------|
|   |                 | Databases                 | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
|   |                 | Years                     | 1836-2014  |          |
|   |                 | Full patent spec.         | (digital adj image) and (TQI or (quality adj indicator*)) and (real adj time)                |          |
|   | <u>108 hits</u> |                           |  | 2/3/2014 |
|   |                 | Databases                 | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
| 6 |                 | Years                     | 1836-2014  |          |
|   |                 | Claims, Title or Abstract | (digital adj image) and (TQI or (quality adj indicator*)) and (real adj time)                |          |
|   | no hits         |                           |  | 2/3/2014 |
|   |                 | Databases                 | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
| 5 |                 | Years                     | 1836-2014  |          |
|   |                 | Title or Abstract         | (digital adj image) and (TQI or (quality adj indicator*)) and (real adj time)                |          |
|   | no hits         |                           |  | 2/3/2014 |
|   |                 | Databases                 | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
| 4 |                 | Years                     | 1836-2014  |          |
|   |                 | Title or Abstract         | (digital adj image adj acquisition)and (TQI or (quality adj indicator*)) and (real adj time) |          |
|   | no hits         |                           |  | 2/3/2014 |
|   |                 | Databases                 | USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA  |          |
| 3 |                 | Years                     | 1836-2014  |          |

|         |   |          |
|---------|---|----------|
| no hits | <p>Title or Abstract (digital adj image adj acquisition)and (TQI or (total adj quality adj indicator*)) and (real adj time)</p> <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p> <p>Years 1836-2014</p> | 2/3/2014 |
| no hits | <p>Title or Abstract (digital adj image adj acquisition)and (TQI or (total adj quality adj management)) and (real adj time)</p> <p>Databases USG USA EPA EPB WO JP DEG DEA DET DEU GBA FRA</p> <p>Years 1836-2014</p> | 2/3/2014 |

### Non-Patent Literature (NPL) Search Strategy/Results:

Google/ GooglePatents

3 February 2014 (03.02.2014)

- Digital image and quality indicator
- Digital image and quality indicator and blurr
- Digital image and quality indicator and confidence

IEEE

3 February 2014 (03.02.2014)

- Digital image and quality indicator
- Digital image and quality indicator and blurr

- Digital image and quality indicator and confidence

ProQuest

3 February 2014 (03.02.2014)

- Digital image and quality indicator
- Digital image and quality indicator and blurr
- Digital image and quality indicator and confidence

## PATENT COOPERATION TREATY

From the  
INTERNATIONAL SEARCHING AUTHORITY

To: Reinhold Cohn and Partners  
P.O.B. 13239  
6113102 Tel Aviv  
Israel

# PCT

WRITTEN OPINION OF THE  
INTERNATIONAL SEARCHING AUTHORITY

(PCT Rule 43bis.1)

Date of mailing  
(day/month/year)

**18 FEB 2014**

|   |  |  |  |
|---|--|--|--|
| Applicant's or agent's file reference<br>2247936  |  | <b>FOR FURTHER ACTION</b><br>See paragraph 2 below             |  |
| International application No.<br>PCT/IL13/50856   | International filing date (day/month/year)<br>22 October 2013 (22.10.2013) | Priority date (day/month/year)<br>23 October 2012 (23.10.2012) |  |
| International Patent Classification (IPC) or both national classification and IPC<br>IPC(8) - G06K 9/46 (2014.01)<br>USPC - 382/195 |  |  |  |
| Applicant<br>Ishay Sivan  |  |  |  |

1. This opinion contains indications relating to the following items:

- Box No. I Basis of the opinion
- Box No. II Priority
- Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- Box No. IV Lack of unity of invention
- Box No. V Reasoned statement under Rule 43bis.1(a)(i) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- Box No. VI Certain documents cited
- Box No. VII Certain defects in the international application
- Box No. VIII Certain observations on the international application

## 2. FURTHER ACTION

If a demand for international preliminary examination is made, this opinion will be considered to be a written opinion of the International Preliminary Examining Authority ("IPEA") except that this does not apply where the applicant chooses an Authority other than this one to be the IPEA and the chosen IPEA has notified the International Bureau under Rule 66.1 bis(b) that written opinions of this International Searching Authority will not be so considered.

If this opinion is, as provided above, considered to be a written opinion of the IPEA, the applicant is invited to submit to the IPEA a written reply together, where appropriate, with amendments, before the expiration of 3 months from the date of mailing of Form PCT/ISA/220 or before the expiration of 22 months from the priority date, whichever expires later.

For further options, see Form PCT/ISA/220.

|   |  |  |
|---|--|--|
| Name and mailing address of the ISA/US<br>Mail Stop PCT, Attn: ISA/US<br>Commissioner for Patents<br>P.O. Box 1450, Alexandria, Virginia 22313-1450<br>Facsimile No. 571-273-3201 | Date of completion of this opinion<br><br>3 February 2014 (03.02.2014) | Authorized officer:<br><br>Shane Thomas<br><br>PCT Helpdesk: 571-272-4300<br>PCT OSP: 571-272-7774 |
|---|--|--|

Form PCT/ISA/237 (cover sheet) (July 2011)

WRITTEN OPINION OF THE  
INTERNATIONAL SEARCHING AUTHORITY

International application No.

PCT/IL13/50856

## Box No. I Basis of this opinion

1. With regard to the **language**, this opinion has been established on the basis of:
- the international application in the language in which it was filed.
- a translation of the international application into \_\_\_\_\_ which is the language of a translation furnished for the purposes of international search (Rules 12.3(a) and 23.1(b)).
2.  This opinion has been established taking into account the **rectification of an obvious mistake** authorized by or notified to this Authority under Rule 91 (Rule 43*bis*.1(a))
3. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, this opinion has been established on the basis of a sequence listing filed or furnished:
- a. (means)
- on paper
- in electronic form
- b. (time)
- in the international application as filed
- together with the international application in electronic form
- subsequently to this Authority for the purposes of search
4.  In addition, in the case that more than one version or copy of a sequence listing has been filed or furnished, the required statements that the information in the subsequent or additional copies is identical to that in the application as filed or does not go beyond the application as filed, as appropriate, were furnished.
5. Additional comments:

**WRITTEN OPINION OF THE  
INTERNATIONAL SEARCHING AUTHORITY**

International application No.

PCT/IL13/50856

**Box No. V Reasoned statement under Rule 43bis.1(a)(i) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**

## 1. Statement

|                               |        |                            |     |
|-------------------------------|--------|----------------------------|-----|
| Novelty (N)                   | Claims | <u>1-10, 14, and 22-27</u> | YES |
|                               | Claims | <u>11-13 and 15-21</u>     | NO  |
| Inventive step (IS)           | Claims | <u>1-10, 14, and 22-27</u> | YES |
|                               | Claims | <u>11-13 and 15-21</u>     | NO  |
| Industrial applicability (IA) | Claims | <u>1-27</u>                | YES |
|                               | Claims | <u>NONE</u>                | NO  |

## 2. Citations and explanations:

Claims 11-13 and 15-21 lack novelty under PCT Article 33(2) as being anticipated by US 2004/0174434 A1 to Walker, J et al. (hereinafter 'Walker').

As to claim 11, Walker discloses a method for computing the photo quality of a captured image in a device image acquisition system, said method comprising: on-board combining of a plurality of quality indicators computed from said captured image (camera may determine a rating for an image based on a variety of quality factors, paragraph [0506]) and its previous image frames quality indicators and a confidence level for at least one of said quality indicators; and determining, based on said combining, whether photo quality is acceptable and taking differential action depending on whether quality is or is not acceptable (camera may either store or delete automatically captured images based on whether their ratings exceed a threshold, paragraph [0715]).

As per claim 12, Walker discloses a method according to claim 11. Walker further discloses a method also comprising automatically activating the capturing apparatus, after a logical criterion based on at least one said quality indicator is met acceptable (camera may either store (capture) or delete automatically captured images based on whether their ratings exceed a threshold (logical criterion), paragraph [0715]).

As per claim 13, Walker discloses a method according to claim 11. Walker further discloses a method also comprising, based on said combining, at least one appropriate suggestion from a pre-stored table of suggestions on how picture quality can be improved (system may determine various conditions from a database table and prompt the user to improve image quality, Figure 10; paragraphs [0228]-[0244]).

As per claim 15, Walker discloses a method according to claim 11. Walker further discloses wherein a stream of frames is saved as video and at least quality indicators are used to quantify quality of said video (camera used in system of improving image quality output may be a video camera, paragraphs [0079]).

As per claim 16, Walker discloses a method according to claim 15. Walker further discloses a method also comprising giving a user suggestion on improvement of the video (camera, which may be a video camera, may guide the user such as by recommending that the user adjust a setting on the camera, paragraphs [0079] and [0566]).

As per claim 17, Walker discloses a method according to claim 11. Walker further discloses wherein at least one lens/sensor module parameter is changed, based on said combining, to achieve better total QI (an imaging device that may be a lens and an image sensor maybe embodied in a camera in which the camera may determine a rating of an image and store this rating with the image in which a rating may be an indication of the quality of the image and may be based on a variety of different factors, including: exposure, sharpness, composition, subject, and indications from a user and the ratings may be helpful in allowing the camera to sort images, paragraphs [0044], [0506]).

As per claim 18, Walker discloses a method according to claim 11. Walker further discloses a method also comprising automatic image capturing of at least one picture once a configured total quality indicator meets a minimum threshold, even without the user pressing a shutter button (the camera may capture an image and then determine a rating for the image based on the quality of the image and if the rating of the image is higher than a threshold value, then the camera may store the automatically-captured image in which an image may be captured automatically that may be without any indication from a user such that the camera may capture images and store them in a buffer even if a user has not pressed the shutter button on the camera, paragraphs [0282], [0715]).

As per claim 19, Walker discloses the method according to claim 11. Walker further discloses wherein blur type detection is used for alerting the user of object movement in a region (Camera may determine a portion of an image is blurred such as if by movement and may ask a user "Are you taking a picture of a sporting event?", paragraph [0303]).

---Continued Within the Next Supplemental Box---

WRITTEN OPINION OF THE  
INTERNATIONAL SEARCHING AUTHORITY

International application No.

PCT/IL13/50856

**Box No. VIII Certain observations on the international application**

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

Claim 16 recites 'the video'. There is a lack of antecedent basis for this limitation in the claim.

For the purposes of this examination, Claim 16 has been best understood to depend upon Claim 15, which resolves the lack of antecedent basis.

WRITTEN OPINION OF THE  
INTERNATIONAL SEARCHING AUTHORITY

International application No.

PCT/IL13/50856

## Supplemental Box

In case the space in any of the preceding boxes is not sufficient.

Continuation of:

\*\*\*-Continued from Box V: Citations and Explanations-\*\*\*.

As per claim 20, Walker discloses a method according to claim 11. Walker further discloses wherein blur type detection is used for alerting the user he is moving too fast in a vehicle to achieve a non-blurred image (different types of visual indicators may be used to alert a user such that a red question mark may be overlaid on the corner of a displayed image to indicate that the camera has a question related to the image, in which the camera may determine a question based on one or more properties of an image such as motion relating to an image that may be movement of a subject or movement of the camera in which the camera may determine if a portion of an image is blurred such as if by movement and may ask a user are you in a moving vehicle? (alerting the user) and based on the user's response, the camera may then adjust a setting on the camera (achieve non-blurred image), paragraphs [0160], [0300], [0303], [0444]).

As per claim 21, Walker discloses a method according to claim 11. Walker further discloses wherein at least one quality indicator is used as a delete-picture indication (the camera may capture an image and then determine a rating for the image based on the quality of the image and if the rating of the image is higher than a threshold value, then the camera may store the automatically-captured image and if the rating is worse than the threshold value, then the automatically-captured image may be compressed or deleted, paragraph [0715]).

Claim 1 meets the criteria set out in PCT Article 33(2)-(3), because the prior art does not teach or fairly suggest a digital image acquisition system comprising an image capture component for capturing in a buffer, a current digital image having pixels; at least one digital processor programmed for real time computation of multiple quality indicators characterizing quality of the current digital image; automatic image capturing, and storing in user-accessible memory, of at least one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied; and a message provider operative, while said first logical criterion is still not satisfied, to select, based on at least one second logical criterion pre-defined on at least one of said multiple quality indicators, at least one appropriate suggestion from a pre-stored table of suggestions of how a user of the system may cause said first logical criterion to be satisfied and to present said appropriate suggestion to the user, wherein at least one of said logical criteria are pre-defined over a time dependent confidence level defined over at least one of said quality indicators.

In the closest prior art, Walker discloses a digital image acquisition system comprising an image capture component for capturing in a buffer, a current digital image having pixels (camera may capture images, which include pixels, into a buffer, paragraphs [0213] and [0282]); at least one digital processor programmed for computation of multiple quality indicators characterizing quality of the current digital image (camera may calculate a rating for an image based on a variety of quality factors, paragraph [0506]); automatic image capturing, and storing in user-accessible memory, of at least one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied (camera may either store (capture) or delete automatically captured images based on whether their ratings exceed a threshold (logical criterion), paragraph [0715]); and a message provider operative to select, based on at least one second logical criterion, at least one appropriate suggestion from a pre-stored table of suggestions of how a user of the system may cause an image to be improved and to present said appropriate suggestion to the user (system may determine various conditions from a database table and prompt the user to improve image quality, Figure 10; paragraphs [0228]-[0244]).

Claims 2-10, 14, and 22-26 also meet the criteria set out in PCT Article 33(2)-(3), because they depend upon Claim 1.

Claim 27 meets the criteria set out in PCT Article 33(2)-(3), because the prior art does not teach or fairly suggest a computer program product, comprising a non-transitory tangible computer readable medium having computer readable program code embodied therein, said computer readable program code adapted to be executed to implement a digital image acquisition method comprising: real time computation of multiple quality indicators characterizing quality of a current digital image; automatic image capturing, and storing in user-accessible memory, of at least one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied; and selecting, while said first logical criterion is still not satisfied, based on at least one second logical criterion pre-defined on at least one of said multiple quality indicators, at least one appropriate suggestion from a pre-stored table of suggestions of how a user of the system may cause said first logical criterion to be satisfied and to present said appropriate suggestion to the user, wherein at least one of said logical criteria are pre-defined over a time-dependent confidence level defined over at least one of said quality indicators.

In the closest prior art, Walker discloses a computer program product, comprising a non-transitory tangible computer readable medium having computer readable program code embodied therein, said computer readable program code adapted to be executed to implement a digital image acquisition method comprising: computation of multiple quality indicators characterizing quality of a current digital image (camera may calculate a rating for an image based on a variety of quality factors, paragraph [0506]); automatic image capturing, and storing in user-accessible memory, of at least one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied (camera may either store (capture) or delete automatically captured images based on whether their ratings exceed a threshold (logical criterion), paragraph [0715]); and selecting, based on at least one second logical criterion, at least one appropriate suggestion from a pre-stored table of suggestions of how a user of the system may cause an image to be improved and to present said appropriate suggestion to the user (system may determine various conditions from a database table and prompt the user to improve image quality, Figure 10; paragraphs [0228]-[0244]).

Claims 1-27 have industrial applicability as defined by PCT Article 33(4) because the subject matter can be made or used in industry.

## PATENT COOPERATION TREATY

## PCT

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

|   |   |   |
|---|---|---|
| Applicant's or agent's file reference<br>2247936  | <b>FOR FURTHER ACTION</b>   | See Form PCT/IPEA/416   |
| International application No.<br>PCT/IL13/50856   | International filing date ( <i>day/month/year</i> )<br>22 October 2013 (22.10.2013) | Priority date ( <i>day/month/year</i> )<br>23 October 2012 (23.10.2012) |
| International Patent Classification (IPC) or national classification and IPC<br>IPC: <b>H04N 5/228</b> ( 2006.01), <b>5/222</b> ( 2006.01); <b>G06K 9/40</b> ( 2006.01)<br>USPC: 348/208.15,333.04;382/275  |   |   |
| Applicant<br>ISHAY SLVAN  |   |   |
| <p>1. This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36.</p> <p>2. This REPORT consists of a total of <u>4</u> sheets, including this cover sheet.</p> <p>3. This report is also accompanied by ANNEXES, comprising:</p> <p>a. <input checked="" type="checkbox"/> (<i>sent to the applicant and to the International Bureau</i>) a total of <u>0</u> sheets, as follows:</p> <p style="margin-left: 20px;"><input checked="" type="checkbox"/> sheets of the description, claims and/or drawings which have been amended and/or sheets containing rectifications authorized by this Authority, unless those sheets were superseded or cancelled, and any accompanying letters (see Rules 46.5, 66.8, 70.16, 91.2, and Section 607 of the Administrative Instructions).</p> <p style="margin-left: 20px;"><input type="checkbox"/> sheets containing rectifications, where the decision was made by this Authority not to take them into account because they were not authorized by or notified to this Authority at the time when this Authority began to draw up this report, and any accompanying letters (Rules 66.4bis, 70.2(e), 70.16 and 91.2).</p> <p style="margin-left: 20px;"><input type="checkbox"/> superseded sheets and any accompanying letters, where this Authority either considers that the superseding sheets contain an amendment that goes beyond the disclosure in the international application as filed, or the superseding sheets were not accompanied by a letter indicating the basis for the amendments in the application as filed, as indicated in item 4 of Box No.I and the Supplemental Box (see Rule 70.16(b)).</p> <p>b. <input type="checkbox"/> (<i>sent to the International Bureau only</i>) a total of (indicate type and number of electronic carrier(s)) _____ containing a sequence listing, in electronic form only, as indicated in the Supplemental Box Relating to Sequence Listing (see paragraph 3bis of Annex C of the Administrative Instructions).</p> |   |   |
| <p>4. This report contains indications relating to the following items:</p> <p><input checked="" type="checkbox"/> Box No. I      Basis of the report</p> <p><input type="checkbox"/> Box No. II      Priority</p> <p><input type="checkbox"/> Box No. III      Non-establishment of opinion with regard to novelty, inventive step and industrial applicability</p> <p><input type="checkbox"/> Box No. IV      Lack of unity of invention</p> <p><input checked="" type="checkbox"/> Box No. V      Reasoned statement under Article 35(2) with regard to novelty, inventive step and industrial applicability; citations and explanations supporting such statement</p> <p><input type="checkbox"/> Box No. VI      Certain documents cited</p> <p><input checked="" type="checkbox"/> Box No. VII      Certain defects in the international application</p> <p><input checked="" type="checkbox"/> Box No. VIII      Certain observations on the international application</p>  |   |   |
| Date of submission of the demand<br>19 August 2014 (19.08.2014)   | Date of completion of this report<br>08 December 2014 (08.12.2014)                  |   |
| Name and mailing address of the IPEA/ US<br>Mail Stop PCT, Attn: IPEA/US<br>Commissioner for Patents<br>P.O. Box 1450<br>Alexandria, Virginia 22313-1450<br>Facsimile No. (571) 273-3201  | Authorized officer<br><br>USMAN KHAN<br><br>Telephone No. (571) 270-1131            |   |

Form PCT/IPEA/409 (cover sheet) (July 2011)

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/IL13/50856

**Box No. I Basis of the report**

1. With regard to the language, this report is based on:

- the international application in the language in which it was filed.
- a translation of the international application into English which is the language of a translation furnished for the purposes of:
  - international search (Rules 12.3(a) and 23.1(b)).
  - publication of the international application (Rule 12.4(a)).
  - international preliminary examination (Rules 55.2(a) and/or 55.3(a) and (b)).

2. With regard to the elements of the international application, this report is based on (*replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report*):

- the international application as originally filed/furnished
- the description:
  - pages 1-30 as originally filed/furnished
  - pages\* NONE received by this Authority on \_\_\_\_\_
  - pages\* NONE received by this Authority on \_\_\_\_\_
- the claims:
  - pages 31-34 as originally filed/furnished
  - pages\* NONE as amended (together with any statement) under Article 19
  - pages\* NONE received by this Authority on \_\_\_\_\_
  - pages\* NONE received by this Authority on \_\_\_\_\_
- the drawings:
  - pages 1/4-4/4 as originally filed/furnished
  - pages\* NONE received by this Authority on \_\_\_\_\_
  - pages\* NONE received by this Authority on \_\_\_\_\_
- a sequence listing - see Supplemental Box Relating to Sequence Listing.

3.  The amendments have resulted in the cancellation of:

- the description, pages \_\_\_\_\_
- the claims, Nos. \_\_\_\_\_
- the drawings, sheets/figs \_\_\_\_\_
- the sequence listing (*specify*): \_\_\_\_\_

4.  This report has been established as if (some of) the amendments annexed to this report and listed below had not been made, since either they are considered to go beyond the disclosure as filed, or they were not accompanied by a letter indicating the basis for the amendments in the application as filed, as indicated in the Supplemental Box (Rules 70.2(c) and (c-bis)):

- the description, pages \_\_\_\_\_
- the claims, Nos. \_\_\_\_\_
- the drawings, sheets/figs \_\_\_\_\_
- the sequence listing (*specify*): \_\_\_\_\_

5.  This report has been established:

- taking into account the **rectification of an obvious mistake** authorized by or notified to this Authority under Rule 91 (Rules 66.1(d-bis) and 70.2(e)).
- without taking into account the **rectification of an obvious mistake** authorized by or notified to this Authority under Rule 91 (Rules 66.4bis) and 70.2(e)).

6.  Supplementary international search report(s) from Authority(ies) \_\_\_\_\_ has/have been received and taken into account in establishing this report (Rule 45bis.8(b) and (c)).

\* If item 4 applies, some or all of those sheets may be marked "superseded."

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.  
PCT/IL13/50856

**Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**

1. Statement

|                               |                                 |     |
|-------------------------------|---------------------------------|-----|
| Novelty (N)                   | Claims <u>1-10,14 and 22-27</u> | YES |
|                               | Claims <u>11-13 and 15-21</u>   | NO  |
| Inventive Step (IS)           | Claims <u>1-10,14,22-27</u>     | YES |
|                               | Claims <u>11-13 and 15-21</u>   | NO  |
| Industrial Applicability (IA) | Claims <u>1-27</u>              | YES |
|                               | Claims <u>NONE</u>              | NO  |

2. Citations and Explanations (Rule 70.7)  
Please See Continuation Sheet

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/IL13/50856

**Box No. VII Certain defects in the international application**

The following defects in the form or contents of the international application have been noted:

Claims 11 – 13, 15 - 21 contain(s) the following defect(s) in the form or contents thereof: claim 11 line 6 includes “, ;”. Claim 30 states in line 9 "said detecting said no movement" this statement seems to have an extra "said". Claim 31 lines line 7 is missing a semicolon. Please check the other claims for similar issues.

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/IL13/50856

**Box No. VIII Certain observations on the international application**

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

Claim 17 is objected to under PCT Article 6 as lacking clarity because claim 17 is indefinite for the following reason(s): claim 17 there is no explanation of what QI stands for.

Additionally, claim 11 is not (1) be tied to particular machine, or (2) transform underlying subject matter (such as an article or material) to a different state or thing.

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.  
PCT/IL13/50856

## Supplemental Box

In case the space in any of the preceding boxes is not sufficient.  
Continuation of:

**V. 2. Citations and Explanations:**

The claim amendments filed have not been entered. The claims are being examined as originally filed.

Claims 1 - 10, 14, and 22 - 27 meet the criteria set out in PCT Article 33(2) and (3), and thus have novelty and inventive step (nonobviousness), because the prior art taken singularly or in combination fails disclose or fairly suggest the claimed invention. Specifically, the prior art fails to disclose automatic image capturing, and storing in user-accessible memory, of at least one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied; and a message provider operative, while said first logical criterion is still not satisfied, to select, based on at least one second logical criterion pre-defined on at least one of said multiple quality indicators, at least one appropriate suggestion from a pre-stored table of suggestions of how a user of the system may cause said first logical criterion to be satisfied and to present said appropriate suggestion to the user, wherein at least one of said logical criteria are pre-defined over a time- dependent confidence level defined over at least one of said quality indicators.

Claims 1 - 10, 14, and 22 - 27 meet the criteria set out in PCT Article 33(4), and thus have industrial applicability, because the subject matter claimed can be made or used in industry.

Claims 11-13, 15 - 21 lack an inventive step under PCT Article 33(2) as being anticipated by US 2004/0174434 A1 to Walker, J et al. (hereinafter 'Walker').

Regarding claim 11, Walker teaches a method for computing photo quality of a captured image in a device image acquisition system (paragraph 0044), said method comprising: an board combining of: a plurality of quality indicators computed from said captured image

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.  
PCT/IL13/50856**Supplemental Box**

(paragraph 0506) and its previous image frames quality indicators (paragraph 0506) and a confidence level for at least one of said quality indicators (paragraph 0506); and determining, based on said combining, wherein photo quality is acceptable and taking differential action depending on whether quality is or is not acceptable (paragraph 0715).

Regarding claim 12, Walker teaches automatically activating the capturing apparatus, after a logical criterion based on at least one said quality indicator is met (paragraph 0715)

Regarding claim 13, Walker teaches comprising, based on said combining, at least one appropriate suggestion from a pre-stored table of suggestions on how picture quality can be improved (figure 10 and paragraphs 0228 - 0244).

Regarding claim 15, Walker teaches a stream of frames is saved as video and at least quality indicators are used to quantify quality of said video (paragraph 0079).

Regarding claim 16, Walker teaches comprising giving a user suggestions on improvement of the video (paragraphs 0079 and 0556).

Regarding claim 17, Walker teaches wherein at least one lens/sensor module parameter is changed, based on said combining, to achieve better total QI (paragraphs 0044 and 0506).

Regarding claim 18, Walker teaches automatic image capturing of at least one picture once a configured total quality indicator meets a minimum threshold, even without the user pressing a shutter button (paragraphs 0282 and 0715).

Regarding claim 19, Walker teaches wherein blur type detection is used for alerting the user of object movement in a region (paragraph 0303).

Regarding claim 20, Walker teaches wherein blur type detection is used for alerting the user he is moving too fast in a vehicle to achieve a non-blurred image (paragraphs 0160, 0303, and 0444).

Regarding claim 21, Walker teaches wherein at least one quality indicator is used as a delete-picture indication (paragraph 0715).

## PATENT COOPERATION TREATY

## PCT

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

|  |  |  |
|--|--|--|
| Applicant's or agent's file reference<br>2247936   | <b>FOR FURTHER ACTION</b>  | See Form PCT/IPEA/416  |
| International application No.<br>PCT/IL13/50856  | International filing date (day/month/year)<br>22 October 2013 (22.10.2013) | Priority date (day/month/year)<br>23 October 2012 (23.10.2012) |
| International Patent Classification (IPC) or national classification and IPC<br>IPC: <b>H04N 5/228</b> ( 2006.01), <b>5/222</b> ( 2006.01); <b>G06K 9/40</b> ( 2006.01)<br>USPC: 348/208.15,333.04;382/275   |  |  |
| Applicant<br>ISHAY SLVAN   |  |  |
| <p>1. This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36.</p> <p>2. This REPORT consists of a total of <del>13</del> sheets, including this cover sheet.</p> <p>3. This report is also accompanied by ANNEXES, comprising:</p> <p>a. <input checked="" type="checkbox"/> (sent to the applicant and to the International Bureau) a total of <u>17</u> sheets, as follows:</p> <p><input checked="" type="checkbox"/> sheets of the description, claims and/or drawings which have been amended and/or sheets containing rectifications authorized by this Authority, unless those sheets were superseded or cancelled, and any accompanying letters (see Rules 46.5, 66.8, 70.16, 91.2, and Section 607 of the Administrative Instructions).</p> <p><input type="checkbox"/> sheets containing rectifications, where the decision was made by this Authority not to take them into account because they were not authorized by or notified to this Authority at the time when this Authority began to draw up this report, and any accompanying letters (Rules 66.4bis, 70.2(e), 70.16 and 91.2).</p> <p><input type="checkbox"/> superseded sheets and any accompanying letters, where this Authority either considers that the superseding sheets contain an amendment that goes beyond the disclosure in the international application as filed, or the superseding sheets were not accompanied by a letter indicating the basis for the amendments in the application as filed, as indicated in item 4 of Box No.I and the Supplemental Box (see Rule 70.16(b)).</p> <p>b. <input type="checkbox"/> (sent to the International Bureau only) a total of (indicate type and number of electronic carrier(s)) _____ containing a sequence listing, in electronic form only, as indicated in the Supplemental Box Relating to Sequence Listing (see paragraph 3bis of Annex C of the Administrative Instructions).</p> |  |  |
| <p>4. This report contains indications relating to the following items:</p> <p><input checked="" type="checkbox"/> Box No. I Basis of the report</p> <p><input type="checkbox"/> Box No. II Priority</p> <p><input type="checkbox"/> Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability</p> <p><input type="checkbox"/> Box No. IV Lack of unity of invention</p> <p><input checked="" type="checkbox"/> Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step and industrial applicability; citations and explanations supporting such statement</p> <p><input type="checkbox"/> Box No. VI Certain documents cited</p> <p><input checked="" type="checkbox"/> Box No. VII Certain defects in the international application</p> <p><input checked="" type="checkbox"/> Box No. VIII Certain observations on the international application</p>   |  |  |
| Date of submission of the demand<br>19 August 2014 (19.08.2014)  | Date of completion of this report<br>24 March 2015 (24.03.2015)            |  |
| Name and mailing address of the IPEA/ US<br>Mail Stop PCT, Attn: IPEA/US<br>Commissioner for Patents<br>P.O. Box 1450<br>Alexandria, Virginia 22313-1450<br>Facsimile No. (571) 273-3201   | Authorized officer<br><br>USMAN KHAN<br><br>Telephone No. (571) 270-1131   |  |

Form PCT/IPEA/409 (cover sheet) (July 2011)

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/IL13/50856

**Box No. I Basis of the report**1. With regard to the **language**, this report is based on:

- the international application in the language in which it was filed.
- a translation of the international application into English which is the language of a translation furnished for the purposes of:
- international search (Rules 12.3(a) and 23.1(b)).
- publication of the international application (Rule 12.4(a)).
- international preliminary examination (Rules 55.2(a) and/or 55.3(a) and (b)).

2. With regard to the **elements** of the international application, this report is based on (*replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report*):

- the international application as originally filed/furnished
- the description:  
 pages 1-30 as originally filed/furnished  
 pages\* NONE received by this Authority on \_\_\_\_\_  
 pages\* NONE received by this Authority on \_\_\_\_\_
- the claims:  
 pages 31-34 as originally filed/furnished  
 pages\* NONE as amended (together with any statement) under Article 19  
 pages\* 1-6 received by this Authority on 23 OCTOBER 2014(23.10.2014)  
 pages\* NONE received by this Authority on \_\_\_\_\_
- the drawings:  
 pages 1/4-4/4 as originally filed/furnished  
 pages\* NONE received by this Authority on \_\_\_\_\_  
 pages\* NONE received by this Authority on \_\_\_\_\_
- a sequence listing - see Supplemental Box Relating to Sequence Listing.

3.  The amendments have resulted in the cancellation of:

- the description, pages \_\_\_\_\_
- the claims, Nos. \_\_\_\_\_
- the drawings, sheets/figs \_\_\_\_\_
- the sequence listing (*specify*): \_\_\_\_\_

4.  This report has been established as if (some of) the amendments annexed to this report and listed below had not been made, since either they are considered to go beyond the disclosure as filed, or they were not accompanied by a letter indicating the basis for the amendments in the application as filed, as indicated in the Supplemental Box (Rules 70.2(c) and (c-bis)):

- the description, pages \_\_\_\_\_
- the claims, Nos. \_\_\_\_\_
- the drawings, sheets/figs \_\_\_\_\_
- the sequence listing (*specify*): \_\_\_\_\_

5.  This report has been established:

- taking into account the **rectification of an obvious mistake** authorized by or notified to this Authority under Rule 91 (Rules 66.1(d-bis) and 70.2(e)).
- without taking into account the **rectification of an obvious mistake** authorized by or notified to this Authority under Rule 91 (Rules 66.4bis) and 70.2(e)).

6.  Supplementary international search report(s) from Authority(ies) \_\_\_\_\_ has/have been received and taken into account in establishing this report (Rule 45bis.8(b) and (c)).

\* If item 4 applies, some or all of those sheets may be marked "superseded."

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.  
PCT/IL13/50856

**Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**

1. Statement

|                               |                                 |     |
|-------------------------------|---------------------------------|-----|
| Novelty (N)                   | Claims <u>1-10,14,22-27</u>     | YES |
|                               | Claims <u>11-13,15-21,28-32</u> | NO  |
| Inventive Step (IS)           | Claims <u>1-10,14,22-27</u>     | YES |
|                               | Claims <u>11-13,15-21,28-32</u> | NO  |
| Industrial Applicability (IA) | Claims <u>1-32</u>              | YES |
|                               | Claims <u>NONE</u>              | NO  |

2. Citations and Explanations (Rule 70.7)  
Please See Continuation Sheet

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/IL13/50856

**Box No. VII Certain defects in the international application**

The following defects in the form or contents of the international application have been noted:

Claims 11 - 13, 15 - 21, and 30 - 31 contain(s) the following defect(s) in the form or contents thereof: claim 11 line 6 includes ",,".  
Claim 30 states in line 9 includes "said detecting said no movement" this statement seems to be have grammer issues. Claim 31 line 7 is missing a semicolon. Please check the other claims for similar issues.

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/IL13/50856

**Box No. VIII Certain observations on the international application**

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

Claims 11 – 13, 15 – 21, and 28 – 32 are objected to under PCT Article 6 as lacking clarity because claims 11 – 13, 15 – 21, and 28 – 32 are indefinite for the following reason(s): claim 17 includes no explanation of what QI stands for. Claim 28 is unclear since it does not clearly state when to store and when not to store the image. Claim 30 line 6 states "at list a" there seems to be grammar issues with this limitation. Claim 30 states in line 5 "detecting no movement relative to said movement", examiner is unsure how no movement can be detected relative to a movement. Claim 31 line 8 states "at least on of" there seems to be grammar issues with this limitation. Claim 31 line 9 states "e", line 10 states "said least one". Please check all claims for similar issues.

Additionally, body of claims 11 and 32 are not (1) be tied to a particular machine, or (2) transform underlying subject matter (such as an article or material) to a different state or thing.

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.  
PCT/IL13/50856**Supplemental Box**

In case the space in any of the preceding boxes is not sufficient.  
Continuation of:

**V. 2. Citations and Explanations:**

Claims 1 - 10, 14, and 22 - 27 meet the criteria set out in PCT Article 33(2) and (3), and thus have novelty and inventive step (nonobviousness), because the prior art taken singularly or in combination fails disclose or fairly suggest the claimed invention. Specifically, the prior art fails to disclose automatic image capturing, and storing in user-accessible memory, of at least one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied; and a message provider operative, while said first logical criterion is still not satisfied, to select, based on at least one second logical criterion pre-defined on at least one of said multiple quality indicators, at least one appropriate suggestion from a pre-stored table of suggestions of how a user of the system may cause said first logical criterion to be satisfied and to present said appropriate suggestion to the user, wherein at least one of said logical criteria are pre-defined over a time- dependent confidence level defined over at least one of said quality indicators.

Claims 1 - 10, 14, and 22 - 27 meet the criteria set out in PCT Article 33(4), and thus have industrial applicability, because the subject matter claimed can be made or used in industry.

Claims 11-13, 15 - 21, and 22 - 27 lack an inventive step under PCT Article 33(2) as being anticipated by US 2004/0174434 A1 to Walker, J et al. (hereinafter 'Walker').

Regarding claim 11, Walker teaches a method for computing photo quality of a captured image in a device image acquisition system (paragraph 0044), said method comprising: combining of: a plurality of quality indicators computed from said captured image (paragraph 0506) and its previous image frames quality indicators (paragraph 0506; note plurality of images used e.g. paragraph 0108, 0298, 0309 - 0311, 0474, 0481, 0511 - 0520, 0551, 0604-0608) and a confidence level for at least one of said quality indicators (paragraph 0506; note

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.  
PCT/IL13/50856

## Supplemental Box

the applicant does not claim specifically what steps/requirements are included as a confidence level and what is not included as a confidence level hence the examiner can broadly read this limitation until the applicant further limits the claims); and determining, based on said combining, a photo quality (paragraph 0715).

Regarding claim 12, Walker teaches automatically activating the capturing apparatus, after a logical criterion based on at least one said quality indicator is met (paragraph 0715).

Regarding claim 13, Walker teaches based on said combining, at least one appropriate suggestion from a pre-stored table of suggestions on how picture quality can be improved (figure 10 and paragraphs 0228 - 0244).

Regarding claim 15, Walker teaches a stream of frames is saved as video and at least quality indicators are used to quantify quality of said video (paragraph 0079).

Regarding claim 16, Walker teaches comprising giving a user suggestions on improvement of the video (paragraphs 0079 and 0556).

Regarding claim 17, Walker teaches wherein at least one lens/sensor module parameter is changed, based on said combining, to achieve better total QI (paragraphs 0044 and 0506).

Regarding claim 18, Walker teaches automatic image capturing of at least one picture once a configured total quality indicator meets a minimum threshold, even without the user pressing a shutter button (paragraphs 0282 and 0715).

Regarding claim 19, Walker teaches wherein blur type detection is used for alerting the user of object movement in a region (paragraph 0303).

Regarding claim 20, Walker teaches wherein blur type detection is used for alerting the user he is moving too fast in a vehicle to achieve a non-blurred image (paragraphs 0160, 0303, and 0444).

Regarding claim 21, Walker teaches wherein at least one quality indicator is used as a delete-picture indication (paragraph 0715):

Regarding claim 28, Walker teaches determining if said photo quality is acceptable and taking differential action depending on whether said photo quality is acceptable or allowing storing said captured image, only if said photo quality is not acceptable (paragraph 0504 and 0715).

Regarding claim 29, Walker teaches a digital image acquisition system comprising a camera lens module 200 configured for receiving captured digital image (paragraph 0044); and a computing module 400 (figures 4 - 6) programmed for computing total quality value (paragraph 0506); wherein said total quality value being for providing photo quality feedback (paragraph 0506); wherein said total quality value being computed according to a plurality of quality indicators computed from said digital image and its previous image frames quality indicators (paragraph 0506; note plurality of images used e.g. paragraph 0108, 0298, 0309 - 0311, 0474, 0481, 0511 - 0520, 0551, 0604-0608) or wherein said total quality value being computed according to a confidence level of at least one of quality indicators computed from said digital image (paragraph 0506, 0244, and 0715; note the applicant does not claim specifically what steps/requirements are included as a confidence level and what is not included as a confidence level hence the examiner can broadly read this limitation until the applicant further limits the claims).

Regarding claim 30, Walker teaches a method for controlling an electronic device configured for capturing images (paragraph 0044), comprising: detecting movement of said electronic device, using a motion sensing component (paragraph 0090, 0223, 0226); detecting no movement relative to said movement, using said motion sensing component (paragraph 0090, 0223, 0226); said no movement being for a list a predetermined period of time (paragraph 0090, 0223, 0226); instructing said device to switch to preview mode as a result of said detecting said no movement (paragraph 0100 note applicant does not claim that the mode switch is automatic); measuring photo quality while in preview mode (paragraph 0506); and instructing said device to capture an image as a result of detecting that said photo quality exceeds a threshold (paragraph 0506, 0244, and 0715).

Regarding claim 31, Walker teaches a method for computing photo quality of a captured image in a device image acquisition system (paragraph 0044) said method comprising: comparing; at least one first image quality indicator computed from said captured image with at least one second-image quality indicator computed from said previous image frames (paragraph 0506, 0244, and 0715); and said first-image and said second-image quality indicators being related to a scene (paragraph 0506, 0244, and 0715); determining photo quality at least on of said captured image as not acceptable if said first-image quality indicator as being substantially similar to said least one second-image quality indicator; and determining photo quality of said captured image as acceptable otherwise; thereby preventing storing similar frames from said scene (paragraph 0506, 0244, and 0715).

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.  
PCT/IL13/50856

**Supplemental Box**

Regarding claim 32, Walker teaches a method for controlling an electronic device configured for capturing images (paragraph 0044), comprising: measuring at least one quality indicator (paragraph 0506, 0244, and 0715); determining, based on said photo quality, at least one parameter related to lens of said electronic device or to sensor module of said electronic device (paragraphs 0506, 0244, and 0715).

## CLAIMS

1. A digital image acquisition system comprising
- 5            an image capture component for capturing in a buffer, a current digital image having pixels;
- at least one digital processor programmed for real time computation of multiple quality indicators characterizing quality of the current digital image;
- automatic image capturing, and storing in user-accessible memory, of at least
- 10          one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied; and
- a message provider operative, while said first logical criterion is still not satisfied, to select, based on at least one second logical criterion pre-defined on at least one of said multiple quality indicators, at least one appropriate suggestion from a
- 15          pre-stored table of suggestions of how a user of the system may cause said first logical criterion to be satisfied and to present said appropriate suggestion to the user,
- wherein at least one of said logical criteria are pre-defined over a time-dependent confidence level defined over at least one of said quality indicators.
- 20          2.        A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on analyzing said pixels.
3.        A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on comparing said pixels to previous frame
- 25          data generated by said image capture component.
4.        A system according to claim 3 wherein said comparing comprises identifying an object in a current and a previous frame and computing the object's speed.
- 30          5.        A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on data received from at least one hardware component operatively associated with the image capture component.

02247936\40-01

6. A system according to claim 5 wherein said hardware component includes at least one of an accelerometer, gyro, GPS receiver.

7. A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on 4D device coordinates.

8. A system according to claim 1 wherein said logical criterion comprises whether or not a total quality indicator computed by combining said multiple quality indicators, exceeds a predetermined threshold.

10

9. A system according to claim 1 wherein said logical criterion comprises whether or not each of said multiple quality indicators, exceeds a predetermined threshold.

15

10. A system according to claim 1 wherein said logical criterion comprises a logical expression combining with at least one OR, several logical conditions of whether or not certain individual indicators from among said multiple quality indicators, exceeds a predetermined respective threshold.

20

11. A method for computing photo quality of a captured image in a device image acquisition system, said method comprising:

combining of: a plurality of quality indicators computed from said captured image and its previous image frames quality indicators and

25

a confidence level for at least one of said quality indicators; and

determining, based on said combining, a photo quality.

Deleted: the

Deleted: on-board

Deleted: whether  
Deleted: is acceptable and taking differential action depending on whether quality is or is not acceptable.

30

12. A method according to claim 11 and also comprising automatically activating the capturing apparatus, after a logical criterion based on at least one said quality indicator is met.

13. A method according to claim 11 and also comprising, based on said combining, at least one appropriate suggestion from a pre-stored table of suggestions on how picture quality can be improved.

02247936\40-01

14. A system according to claim 1 wherein said pre-stored table of suggestions includes a suggestion of changing at least one characteristic of said image capture component.

5

15. A method according to claim 11 wherein a stream of frames is saved as video and at least quality indicators are used to quantify quality of said video.

16. A method according to claim 15 and also comprising giving a user suggestions on improvement of the video.

10

Deleted: 1

17. A method according to claim 11 wherein at least one lens/sensor module parameter is changed, based on said combining, to achieve better total QI.

15

18. A method according to claim 11 and also comprising automatic image capturing of at least one picture once a configured total quality indicator meets a minimum threshold, even without the user pressing a shutter button.

19. A method according to claim 11 wherein blur type detection is used for alerting the user of object movement in a region.

20

20. A method according to claim 11 wherein blur type detection is used for alerting the user he is moving too fast in a vehicle to achieve a non-blurred image.

21. A method according to claim 11 wherein at least one quality indicator is used as a delete-picture indication.

25

22. A system according to claim 1 wherein said automatic capturing occurs only after a user presses a shutter button.

30

23. A system according to claim 1 wherein said automatic capturing occurs regardless of whether a user has pressed a shutter button.

0224793640-01

24. A system according to claim 1 wherein one quality indicator comprises a quantification of blurriness in the current image and wherein said table includes a "Remove Moving Object From Scene Or Cause Object To Remain Stationary" message and wherein the message provider is operative, while said logical criterion is still not satisfied, to select same message, based on a condition pre-defined on said blurriness quantification.

25. A system according to claim 5 wherein said logical criterion comprises a criterion predicting based on at least one of an accelerometer and a GPS receiver, a time at which there will be an acceptably low level of image capture component shake, and said automatic image capturing occurs at said time.

26. A system according to claim 14 wherein said at least one characteristic of said image capture component comprises at least one of angle and position thereof.

27. A computer program product, comprising a non-transitory tangible computer readable medium having computer readable program code embodied therein, said computer readable program code adapted to be executed to implement a digital image acquisition method comprising:

real time computation of multiple quality indicators characterizing quality of a current digital image;

automatic image capturing, and storing in memory, of at least one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied; and

selecting, while said first logical criterion is still not satisfied, based on at least one second logical criterion pre-defined on at least one of said multiple quality indicators, at least one appropriate suggestion from a pre-stored table of suggestions of how a user of the system may cause said first logical criterion to be satisfied and to present said appropriate suggestion to the user,

wherein at least one of said logical criteria are pre-defined over a time-dependent confidence level defined over at least one of said quality indicators.

28. The method of claim 11 further comprising determining if said photo quality is acceptable and taking differential action depending on whether said photo quality is acceptable or allowing storing said

02247936\40-01

captured image, only if said photo quality is not acceptable.

29. A digital image acquisition system comprising

5 a camera lens module 200 configured for receiving captured digital image; and

a computing module 400 programmed for computing total quality value; wherein said total quality value being for providing photo quality feedback;

10 wherein said total quality value being computed according to a plurality of quality indicators computed from said digital image and its previous image frames quality indicators or wherein said total quality value being computed according to a confidence level of at least one of quality indicators computed from said digital image.

15 30. A method for controlling an electronic device configured for capturing images, comprising:

detecting movement of said electronic device, using a motion sensing component;

20 detecting no movement relative to said movement, using said motion sensing component; said no movement being for at list a predefined period of time;

instructing said device to switch to preview mode as a result of said detecting said no movement;

measuring photo quality while in preview mode; and

25 instructing said device to capture an image as a result of detecting that said photo quality exceeds a threshold.

31. A method for computing photo quality of a captured image in a device image acquisition system, said method comprising:

comparing :

30 at least one first-image quality indicator computed from said captured image with at least one second-image quality indicator computed from said previous image frames ; and said first-image and said second-image quality indicators being related to a scene

Formatted: Not Highlight

02247936\40-01

5 determining photo quality at least on of said captured image as not acceptable if said e first-image quality indicator as being substantially similar to said least one second-image quality indicator; and determining photo quality of said captured image as acceptable otherwise; thereby preventing storing similar frames from said scene

10 32. A method for controlling an electronic device configured for capturing images, comprising:

measuring at least one quality indicator;

determining, based on said measuring, a photo quality; and

amending, based on said photo quality, at least one parameter related to lens of said electronic device or to sensor module of said electronic device

15

02247936\40-01

CLAIMS

1. A digital image acquisition system comprising  
5            an image capture component for capturing in a buffer, a current digital image having pixels;  
              at least one digital processor programmed for real time computation of multiple quality indicators characterizing quality of the current digital image;  
              automatic image capturing, and storing in user-accessible memory, of at least  
10 one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied; and  
              a message provider operative, while said first logical criterion is still not satisfied, to select, based on at least one second logical criterion pre-defined on at least one of said multiple quality indicators, at least one appropriate suggestion from a  
15 pre-stored table of suggestions of how a user of the system may cause said first logical criterion to be satisfied and to present said appropriate suggestion to the user,  
              wherein at least one of said logical criteria are pre-defined over a time-dependent confidence level defined over at least one of said quality indicators.
- 20 2. A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on analyzing said pixels.
3. A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on comparing said pixels to previous frame  
25 data generated by said image capture component.
4. A system according to claim 3 wherein said comparing comprises identifying an object in a current and a previous frame and computing the object's speed.
- 30 5. A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on data received from at least one hardware component operatively associated with the image capture component.

6. A system according to claim 5 wherein said hardware component includes at least one of an accelerometer, gyro, GPS receiver.
7. A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on 4D device coordinates.
8. A system according to claim 1 wherein said logical criterion comprises whether or not a total quality indicator computed by combining said multiple quality indicators, exceeds a predetermined threshold.
9. A system according to claim 1 wherein said logical criterion comprises whether or not each of said multiple quality indicators, exceeds a predetermined threshold.
10. A system according to claim 1 wherein said logical criterion comprises a logical expression combining with at least one OR, several logical conditions of whether or not certain individual indicators from among said multiple quality indicators, exceeds a predetermined respective threshold.
11. A method for computing photo quality of a captured image in a device image acquisition system, said method comprising:  
 combining of:  
 a plurality of quality indicators computed from said captured image and its previous image frames quality indicators and  
 a confidence level for at least one of said quality indicators; and  
 determining, based on said combining, a photo quality .
12. A method according to claim 11 and also comprising automatically activating the capturing apparatus, after a logical criterion based on at least one said quality indicator is met.
13. A method according to claim 11 and also comprising, based on said combining, at least one appropriate suggestion from a pre-stored table of suggestions on how picture quality can be improved.

14. A system according to claim 1 wherein said pre-stored table of suggestions includes a suggestion of changing at least one characteristic of said image capture component.

5

15. A method according to claim 11 wherein a stream of frames is saved as video and at least quality indicators are used to quantify quality of said video.

16. A method according to claim 15 and also comprising giving a user suggestions on improvement of the video.

10

17. A method according to claim 11 wherein at least one lens/sensor module parameter is changed, based on said combining, to achieve better total QI.

18. A method according to claim 11 and also comprising automatic image capturing of at least one picture once a configured total quality indicator meets a minimum threshold, even without the user pressing a shutter button.

15

19. A method according to claim 11 wherein blur type detection is used for alerting the user of object movement in a region.

20

20. A method according to claim 11 wherein blur type detection is used for alerting the user he is moving too fast in a vehicle to achieve a non-blurred image.

21. A method according to claim 11 wherein at least one quality indicator is used as a delete-picture indication.

25

22. A system according to claim 1 wherein said automatic capturing occurs only after a user presses a shutter button.

30

23. A system according to claim 1 wherein said automatic capturing occurs regardless of whether a user has pressed a shutter button.

24. A system according to claim 1 wherein one quality indicator comprises a quantification of blurriness in the current image and wherein said table includes a “Remove Moving Object From Scene Or Cause Object To Remain Stationary” message and wherein the message provider is operative, while said logical criterion is still not satisfied, to select same message, based on a condition pre-defined on said blurriness quantification.

25. A system according to claim 5 wherein said logical criterion comprises a criterion predicting based on at least one of an accelerometer and a GPS receiver, a time at which there will be an acceptably low level of image capture component shake, and said automatic image capturing occurs at said time.

26. A system according to claim 14 wherein said at least one characteristic of said image capture component comprises at least one of angle and position thereof.

27. A computer program product, comprising a non-transitory tangible computer readable medium having computer readable program code embodied therein, said computer readable program code adapted to be executed to implement a digital image acquisition method comprising:

real time computation of multiple quality indicators characterizing quality of a current digital image;

automatic image capturing, and storing in memory, of at least one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied; and

selecting, while said first logical criterion is still not satisfied, based on at least one second logical criterion pre-defined on at least one of said multiple quality indicators, at least one appropriate suggestion from a pre-stored table of suggestions of how a user of the system may cause said first logical criterion to be satisfied and to present said appropriate suggestion to the user,

wherein at least one of said logical criteria are pre-defined over a time-dependent confidence level defined over at least one of said quality indicators.

28. The method of claim 11 further comprising determining if said photo quality is acceptable and taking differential action depending on whether said photo quality is acceptable or allowing storing said

captured image, only if said photo quality is not acceptable.

29. A digital image acquisition system comprising

a camera lens module 200 configured for receiving captured digital  
5 image; and

a computing module 400 programmed for computing total quality  
value; wherein said total quality value being for providing photo quality  
feedback;

wherein said total quality value being computed according to a plurality of  
10 quality indicators computed from said digital image and its previous image frames  
quality indicators or wherein said total quality value being computed according to  
a confidence level of at least one of quality indicators computed from said digital  
image.

15 30. A method for controlling an electronic device configured for capturing  
images, comprising:

detecting movement of said electronic device, using a motion  
sensing component;

20 detecting no movement relative to said movement, using said  
motion sensing component; said no movement being for at list a  
predefined period of time;

instructing said device to switch to preview mode as a result of  
said detecting said no movement;

measuring photo quality while in preview mode; and

25 instructing said device to capture an image as a result of detecting  
that said photo quality exceeds a threshold.

31. A method for computing photo quality of a captured image in a device  
image acquisition system, said method comprising:

comparing :

30 at least one first-image quality indicator computed from said captured  
image with at least one second-image quality indicator computed from  
said previous image frames ; and said first-image and said second-image  
quality indicators being related to a scene

determining photo quality at least on of said captured image as not acceptable if said e first-image quality indicator as being substantially similar to said least one second-image quality indicator; and determining photo quality of said captured image as acceptable otherwise; thereby preventing storing similar frames from said scene

5

32. A method for controlling an electronic device configured for capturing images, comprising:

measuring at least one quality indicator;

10

determining, based on said measuring, a photo quality; and

amending, based on said photo quality, at least one parameter related to lens of said electronic device or to sensor module of said electronic device

15

## CLAIMS

1. A digital image acquisition system comprising
- 5            an image capture component for capturing in a buffer, a current digital image having pixels;
- at least one digital processor programmed for real time computation of multiple quality indicators characterizing quality of the current digital image;
- automatic image capturing, and storing in user-accessible memory, of at least
- 10          one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied; and
- a message provider operative, while said first logical criterion is still not satisfied, to select, based on at least one second logical criterion pre-defined on at least one of said multiple quality indicators, at least one appropriate suggestion from a
- 15          pre-stored table of suggestions of how a user of the system may cause said first logical criterion to be satisfied and to present said appropriate suggestion to the user,
- wherein at least one of said logical criteria are pre-defined over a time-dependent confidence level defined over at least one of said quality indicators.
- 20          2.          A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on analyzing said pixels.
3.          A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on comparing said pixels to previous frame
- 25          data generated by said image capture component.
4.          A system according to claim 3 wherein said comparing comprises identifying an object in a current and a previous frame and computing the object's speed.
- 30          5.          A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on data received from at least one hardware component operatively associated with the image capture component.

6. A system according to claim 5 wherein said hardware component includes at least one of an accelerometer, gyro, GPS receiver.
7. A system according to claim 1 wherein at least one of said indicators characterizing quality is computed based on 4D device coordinates.
8. A system according to claim 1 wherein said logical criterion comprises whether or not a total quality indicator computed by combining said multiple quality indicators, exceeds a predetermined threshold.
9. A system according to claim 1 wherein said logical criterion comprises whether or not each of said multiple quality indicators, exceeds a predetermined threshold.
10. A system according to claim 1 wherein said logical criterion comprises a logical expression combining with at least one OR, several logical conditions of whether or not certain individual indicators from among said multiple quality indicators, exceeds a predetermined respective threshold.
11. A method for computing the photo quality of a captured image in a device image acquisition system, said method comprising:  
on-board-combining of:  
a plurality of quality indicators computed from said captured image and its previous image frames quality indicators and  
a confidence level for at least one of said quality indicators,; and  
determining, based on said combining, whether a photo quality, is acceptable and taking differential action depending on whether quality is or is not acceptable.
12. A method according to claim 11 and also comprising automatically activating the capturing apparatus, after a logical criterion based on at least one said quality indicator is met.
13. A method according to claim 11 and also comprising, based on said combining, at least one appropriate suggestion from a pre-stored table of suggestions on how

02247936/40-01

picture quality can be improved.

14. A system according to claim 1 wherein said pre-stored table of suggestions includes a suggestion of changing at least one characteristic of said image capture component.

15. A method according to claim 11 wherein a stream of frames is saved as video and at least quality indicators are used to quantify quality of said video.

10 16. A method according to claim 14 and also comprising giving a user suggestions on improvement of the video.

17. A method according to claim 11 wherein at least one lens/sensor module parameter is changed, based on said combining, to achieve better total QI.

15

18. A method according to claim 11 and also comprising automatic image capturing of at least one picture once a configured total quality indicator meets a minimum threshold, even without the user pressing a shutter button.

20 19. A method according to claim 11 wherein blur type detection is used for alerting the user of object movement in a region.

20. A method according to claim 11 wherein blur type detection is used for alerting the user he is moving too fast in a vehicle to achieve a non-blurred image.

25

21. A method according to claim 11 wherein at least one quality indicator is used as a delete-picture indication.

22. A system according to claim 1 wherein said automatic capturing occurs only after a user presses a shutter button.

30

23. A system according to claim 1 wherein said automatic capturing occurs regardless of whether a user has pressed a shutter button.

24. A system according to claim 1 wherein one quality indicator comprises a quantification of blurriness in the current image and wherein said table includes a "Remove Moving Object From Scene Or Cause Object To Remain Stationary" message and wherein the message provider is operative, while said logical criterion is still not satisfied, to select same message, based on a condition pre-defined on said blurriness quantification.

25. A system according to claim 5 wherein said logical criterion comprises a criterion predicting based on at least one of an accelerometer and a GPS receiver, a time at which there will be an acceptably low level of image capture component shake, and said automatic image capturing occurs at said time.

26. A system according to claim 14 wherein said at least one characteristic of said image capture component comprises at least one of angle and position thereof.

27. A computer program product, comprising a non-transitory tangible computer readable medium having computer readable program code embodied therein, said computer readable program code adapted to be executed to implement a digital image acquisition method comprising:

real time computation of multiple quality indicators characterizing quality of a current digital image;

automatic image capturing, and storing in memory, of at least one image only after a first logical criterion predefined on said multiple quality indicators, is satisfied; and

selecting, while said first logical criterion is still not satisfied, based on at least one second logical criterion pre-defined on at least one of said multiple quality indicators, at least one appropriate suggestion from a pre-stored table of suggestions of how a user of the system may cause said first logical criterion to be satisfied and to present said appropriate suggestion to the user,

wherein at least one of said logical criteria are pre-defined over a time-dependent confidence level defined over at least one of said quality indicators.

28. The method of claim 11 further comprising determining if said photo quality is acceptable and taking differential action depending on whether said photo quality is acceptable or allowing storing said

captured image, only if said photo quality is not acceptable.

29. A digital image acquisition system comprising

a camera lens module 200 configured for receiving captured digital  
 5 image; and

a computing module 400 programmed for computing total quality  
value; wherein said total quality value being for providing photo quality  
feedback;

10 wherein said total quality value being computed according to a plurality of  
quality indicators computed from said digital image and its previous image frames  
quality indicators or wherein said total quality value being computed according to  
a confidence level of at least one of quality indicators computed from said digital  
image.

15 30. A method for controlling an electronic device configured for capturing  
images, comprising:

detecting movement of said electronic device, using a motion  
sensing component;

20 detecting no movement relative to said movement, using said  
motion sensing component; said no movement being for at list a  
predefined period of time;

instructing said device to switch to preview mode as a result of  
said detecting said no movement;

measuring photo quality while in preview mode; and

25 instructing said device to capture an image as a result of detecting  
that said photo quality exceeds a threshold.

31. A method for computing photo quality of a captured image in a device  
image acquisition system, said method comprising:

comparing :

30 at least one first-image quality indicator computed from said captured  
image with at least one second-image quality indicator computed from  
said previous image frames ; and said first-image and said second-image  
quality indicators being related to a scene

determining photo quality at least on of said captured image as not acceptable if said e first-image quality indicator as being substantially similar to said least one second-image quality indicator; and determining photo quality of said captured image as acceptable otherwise; thereby preventing storing similar frames from said scene

5

32. A method for controlling an electronic device configured for capturing images, comprising:

measuring at least one quality indicator;

10

determining, based on said measuring, a photo quality; and

amending, based on said photo quality, at least one parameter related to lens of said electronic device or to sensor module of said electronic device

15