

OLED DISPLAY

FUNDAMENTALS AND APPLICATIONS



TAKATOSHI
TSUJIMURA

 **WILEY**

SID

Series in Display Technology

OLED Displays Fundamentals and Applications

Wiley-SID Series in Display Technology

Series Editor:

Anthony C. Lowe

A complete list of the titles in this series appears at the end of this volume.

OLED Displays

Fundamentals and Applications

Takatoshi Tsujimura



A John Wiley & Sons, Inc., Publication

Copyright © 2012 by John Wiley & Sons, Inc. All rights reserved.

Published by John Wiley & Sons, Inc., Hoboken, New Jersey.

Published simultaneously in Canada.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, scanning, or otherwise, except as permitted under Section 107 or 108 of the 1976 United States Copyright Act, without either the prior written permission of the Publisher, or authorization through payment of the appropriate per-copy fee to the Copyright Clearance Center, Inc., 222 Rosewood Drive, Danvers, MA 01923, (978) 750-8400, fax (978) 750-4470, or on the web at www.copyright.com. Requests to the Publisher for permission should be addressed to the Permissions Department, John Wiley & Sons, Inc., 111 River Street, Hoboken, NJ 07030, (201) 748-6011, fax (201) 748-6008, or online at <http://www.wiley.com/go/permissions>.

Limit of Liability/Disclaimer of Warranty: While the publisher and author have used their best efforts in preparing this book, they make no representations or warranties with respect to the accuracy or completeness of the contents of this book and specifically disclaim any implied warranties of merchantability or fitness for a particular purpose. No warranty may be created or extended by sales representatives or written sales materials. The advice and strategies contained herein may not be suitable for your situation. You should consult with a professional where appropriate. Neither the publisher nor author shall be liable for any loss of profit or any other commercial damages, including but not limited to special, incidental, consequential, or other damages.

For general information on our other products and services or for technical support, please contact our Customer Care Department within the United States at (800) 762-2974, outside the United States at (317) 572-3993 or fax (317) 572-4002.

Wiley also publishes its books in a variety of electronic formats. Some content that appears in print may not be available in electronic formats. For more information about Wiley products, visit our web site at www.wiley.com.

Library of Congress Cataloging-in-Publication Data

Tsujimura, Takatoshi.

OLED displays: fundamentals and applications / Takatoshi Tsujimura.

p. cm.

Includes bibliographical references and index.

ISBN 978-1-118-14051-2

1. Flat panel displays. 2. Electroluminescent devices. 3. Organic semiconductors.

I. Title.

TK7882.I6T83 2011

621.3815'422-dc23

2011027371

Printed in Singapore.

10 9 8 7 6 5 4 3 2 1

Contents

- Series Editor’s Foreword..... ix**
- Preface..... xi**

- 1 Introduction..... 1**

- 2 OLED Display Structure 5**
 - 2.1 OLED Definition 5
 - 2.2 OLED Device Principles and Mechanisms 8
 - 2.2.1 Basic Device Structure..... 8
 - 2.2.2 Light Emission Mechanism..... 10
 - 2.2.3 Emission Efficiency..... 26
 - 2.2.4 Lifetime and Image Burning..... 30

- 3 OLED Manufacturing Process 37**
 - 3.1 Material Preparation 37
 - 3.1.1 Basic Material Properties 37
 - 3.1.2 Purification Process 41
 - 3.2 Evaporation Process 42
 - 3.2.1 Principle..... 42
 - 3.2.2 Evaporation Sources..... 47
 - 3.3 Shadow Mask Patterning..... 54
 - 3.4 Encapsulation 57
 - 3.4.1 Dark Spot and Edge Growth Defects..... 57
 - 3.4.2 Light Emission from the Bottom and Top of the OLED Device 58
 - 3.5 Problem Analysis..... 61
 - 3.5.1 Ionization Potential Measurement..... 61
 - 3.5.2 HPLC Analysis 64
 - 3.5.3 Cyclic Voltammetry..... 65

v

- 4 OLED Display Module..... 69**
 - 4.1 Comparison between OLED and LCD Modules..... 69
 - 4.2 Basic Display Design and Related Characteristics..... 71
 - 4.2.1 Luminous Intensity, Luminance, and Illuminance..... 71
 - 4.2.2 OLED Current and Power Efficiencies..... 76
 - 4.2.3 Color Reproduction..... 80
 - 4.2.4 Uniform Color Space..... 87
 - 4.2.5 White Point Determination..... 88
 - 4.3 Passive-Matrix OLED Display..... 91
 - 4.3.1 Structure..... 91
 - 4.3.2 Pixel Driving..... 93
 - 4.4 Active-Matrix OLED Display..... 96
 - 4.4.1 OLED Module Components..... 96
 - 4.4.2 Two-Transistor One-Capacitor (2T1C) Driving Circuit..... 97
 - 4.4.3 Ambient Performance..... 100
 - 4.4.4 Subpixel Rendering..... 101

- 5 TFT Substrate for OLED Driving 105**
 - 5.1 TFT Structure..... 105
 - 5.2 TFT Process..... 110
 - 5.2.1 Low-Temperature Polysilicon Process Overview..... 110
 - 5.2.2 Thin-Film Formation..... 111
 - 5.2.3 Patterning Technique..... 112
 - 5.2.4 Excimer Laser Crystallization..... 116
 - 5.3 MOSFET Basics..... 120
 - 5.4 LTPS-TFT-Driven OLED Display Design..... 122
 - 5.4.1 OFF Current..... 123
 - 5.4.2 Driver TFT Size Restriction..... 124
 - 5.4.3 Restriction Due to Voltage Drop..... 125
 - 5.4.4 LTPS-TFT Pixel Compensation Circuit..... 132
 - 5.4.5 Circuit Integration by LTPS-TFT..... 139

- 6 Next-Generation OLED Technologies..... 143**
 - 6.1 Color-Patterning Technologies..... 143
 - 6.1.1 White + Color Filter Patterning..... 143
 - 6.1.2 Color Conversion Medium (CCM) Patterning..... 145
 - 6.1.3 Laser-Induced Thermal Imaging (LITI) Method..... 145
 - 6.1.4 Radiation-Induced Sublimation Transfer (RIST) Method..... 146
 - 6.1.5 Dual-Plate OLED Display (DOD) Method..... 148
 - 6.1.6 Other Methods..... 150

6.2	Solution-Processed Materials and Technologies	151
6.3	Next-Generation OLED Manufacturing Tools.....	155
6.3.1	Vapor Injection Source Technology (VIST) Deposition....	155
6.3.2	Hot-Wall Method.....	159
6.3.3	Organic Vapor-Phase Deposition (OVPD) Method	162
6.4	OLED Television Applications.....	162
6.4.1	Performance Target.....	163
6.4.2	High-Yield Manufacturing by White + Color Filter Method.....	164
6.5	Next-Generation TFT Technologies for OLED Display.....	175
6.5.1	Sequential Lateral Solidification (SLS) Method.....	175
6.5.2	Microcrystalline and Superamorphous Silicon.....	176
6.5.3	Solid-Phase Crystallization	178
6.5.4	Oxide Semiconductors	181
7	OLED Lighting	187
7.1	Color Rendering Index.....	187
7.2	OLED Lighting Requirement.....	191
7.2.1	Correlated Color Temperature (CCT).....	191
7.2.2	Other Requirements.....	192
7.3	Light Extraction Enhancement.....	197
7.3.1	MicroLens Array Structure.....	197
7.3.2	Diffusion Structure.....	198
7.3.3	Diffraction Structure.....	200
7.4	OLED Lighting Design.....	200
7.4.1	Resistance Reduction	201
7.4.2	Current Reduction	201
8	New OLED Applications	205
8.1	Flexible Display.....	205
8.1.1	Flexible Display Applications	205
8.1.2	Barrier Technology for Flexible Displays.....	205
8.1.3	WVTR Measurement	208
8.1.4	Organic TFTs for Flexible Displays.....	210
8.2	Transparent Displays.....	215
8.3	Tiled Display.....	217
8.3.1	Passive-Matrix Tiling.....	217
8.3.2	Active-Matrix Tiling.....	220
	Appendix	225
	About the Author.....	229
	Index	231




Figure 4.10 Graph showing dependence of voltage on current efficiency.

in Fig. 4.10. Thus, the efficiency is subjected to the voltage (due to concentration quenching, described in Section 2.2.2.7; densely generated excitons by larger current cause more chance of losing energy by collision to the quencher or other excitons), which needs to be taken into account in the display design. In particular, in the case of a phosphorescent device, collision between two triplet excitons causes quenching (as the high current generates many excitons by which many triplet excitons collide with each other to form a singlet state). This is called *triplet-triplet (T-T) annihilation*, which can significantly reduce efficiency in the high-current region. This is called the *rolloff phenomenon*.

4.2.3 Color Reproduction

Color reproduction is an important factor in ensuring color fidelity, especially for photo images. Large-scale color reproduction can be achieved by applying display schemes containing the primary colors red, green, and blue, as discussed below. Emission spectra of red, green, and blue subpixels are shown in Fig. 4.11.




Figure 4.11 Example of emission spectrum of RGB (red + green + blue) subpixels.

Here we assume that the emission spectrum is $S(\lambda)$ and the color matching functions (sensitivity of the human eye to each wavelength; see the Appendix for actual values.) are $\bar{x}(\lambda)$, $\bar{y}(\lambda)$, $\bar{z}(\lambda)$; we can then express the tristimulus values (a parameter set, converted from human eye stimulus values as to three color primaries, designed so that only a positive value appears; standardized as CIE1931XYZ color space) as follows, using an integral ranging from 380 to 780 nm.

$$X = K \int_{380}^{780} S(\lambda)\bar{x}(\lambda)d\lambda \tag{4.17}$$

$$Y = K \int_{380}^{780} S(\lambda)\bar{y}(\lambda)d\lambda \tag{4.18}$$

$$Z = K \int_{380}^{780} S(\lambda)\bar{z}(\lambda)d\lambda \tag{4.19}$$

Here, we define the K so that calculated Y is equal to the display luminance. Using the CIE1931-XYZ value, the (x, y) locus (generally used to indicate the display color reproduction capability) can be expressed as follows:

$$x = \frac{X}{X + Y + Z} \tag{4.20}$$




Figure 4.12 Plot of the area reproducible by RGB color mixture.

$$y = \frac{Y}{X + Y + Z} \tag{4.21}$$

This (x, y) value set can be calculated for red, green, and blue, respectively, as (x_R, y_R) , (x_G, y_G) , (x_B, y_B) .

The actual measurement results of an OLED emitter are shown in Fig. 4.12. The color range that can be shown by the combination of these three color primaries is found within the triangle that is made by the three color primaries in the (x, y) coordinate. This area is called the *color gamut*. To determine the color reproduction capability of a display, the metric NTSC% is often used (NTSC = National [US] Television System Committee). It is defined as the ratio of the area of the triangle achievable by the display divided by the area of the standard NTSC triangle, expressed as a




Figure 4.10 Graph showing dependence of voltage on current efficiency.

in Fig. 4.10. Thus, the efficiency is subjected to the voltage (due to concentration quenching, described in Section 2.2.2.7; densely generated excitons by larger current cause more chance of losing energy by collision to the quencher or other excitons), which needs to be taken into account in the display design. In particular, in the case of a phosphorescent device, collision between two triplet excitons causes quenching (as the high current generates many excitons by which many triplet excitons collide with each other to form a singlet state). This is called *triplet-triplet (T-T) annihilation*, which can significantly reduce efficiency in the high-current region. This is called the *rolloff phenomenon*.

4.2.3 Color Reproduction

Color reproduction is an important factor in ensuring color fidelity, especially for photo images. Large-scale color reproduction can be achieved by applying display schemes containing the primary colors red, green, and blue, as discussed below. Emission spectra of red, green, and blue subpixels are shown in Fig. 4.11.




Figure 4.11 Example of emission spectrum of RGB (red + green + blue) subpixels.

Here we assume that the emission spectrum is $S(\lambda)$ and the color matching functions (sensitivity of the human eye to each wavelength; see the Appendix for actual values.) are $\bar{x}(\lambda)$, $\bar{y}(\lambda)$, $\bar{z}(\lambda)$; we can then express the tristimulus values (a parameter set, converted from human eye stimulus values as to three color primaries, designed so that only a positive value appears; standardized as CIE1931XYZ color space) as follows, using an integral ranging from 380 to 780 nm.

$$X = K \int_{380}^{780} S(\lambda)\bar{x}(\lambda)d\lambda \tag{4.17}$$

$$Y = K \int_{380}^{780} S(\lambda)\bar{y}(\lambda)d\lambda \tag{4.18}$$

$$Z = K \int_{380}^{780} S(\lambda)\bar{z}(\lambda)d\lambda \tag{4.19}$$

Here, we define the K so that calculated Y is equal to the display luminance. Using the CIE1931-XYZ value, the (x, y) locus (generally used to indicate the display color reproduction capability) can be expressed as follows:

$$x = \frac{X}{X + Y + Z} \tag{4.20}$$




Figure 4.12 Plot of the area reproducible by RGB color mixture.

$$y = \frac{Y}{X + Y + Z} \tag{4.21}$$

This (x, y) value set can be calculated for red, green, and blue, respectively, as (x_R, y_R) , (x_G, y_G) , (x_B, y_B) .

The actual measurement results of an OLED emitter are shown in Fig. 4.12. The color range that can be shown by the combination of these three color primaries is found within the triangle that is made by the three color primaries in the (x, y) coordinate. This area is called the *color gamut*. To determine the color reproduction capability of a display, the metric NTSC% is often used (NTSC = National [US] Television System Committee). It is defined as the ratio of the area of the triangle achievable by the display divided by the area of the standard NTSC triangle, expressed as a

percentage. For example, XEL-1, the 11-in. OLED television commercialized in 2007, claimed a color gamut of 110%.

Although NTSC was introduced as a cathode ray tube (CRT) television standard, eventually most CRT fluorescence materials were designed with emission color coordinates close to the European Broadcasting Union (EBU) standard or the Rec709 standard (the international standard for HDTV studios), which are much smaller in area than is the NTSC triangle (Fig. 4.13).




Figure 4.13 Graphical representation of the three color standards applied in television manufacture.

On the other hand, digital cameras and computers often use the s-RGB standard, which is shown in Fig. 4.14 (it has the same color coordinates as EBU and Rec709). The Joint Photographic Experts Group (JPEG) standard also normally uses the s-RGB color coordinate standard; however, as the s-RGB triangle is not large enough to reproduce high fidelity colors, a new header standard EXIF2.2 has introduced the s-Ycc standard, which uses an extended dynamic range with grayscale values that extend from negative values to values greater than 255, while normal s-RGB uses 0 to 255 to express gray scales. The newer header standard EXIF2.21 can also handle the Adobe-RGB standard, which is popular in the publishing industry (Fig. 4.14).




Figure 4.14 Graphical representation of the three color standards applied in digital camera manufacture.

TABLE 4.2 (x, y) Coordinate of Color Primaries for Each Standard

Standard	Red	Green	Blue
NTSC	(0.67,0.33)	(0.21,0.71)	(0.14,0.08)
Rec-709(HDTV)	(0.64,0.33)	(0.30,0.60)	(0.15,0.06)
EBU	(0.64,0.33)	(0.29,0.60)	(0.15,0.06)
s-RGB	(0.64,0.33)	(0.30,0.60)	(0.15,0.06)
Adobe-RGB	(0.64,0.33)	(0.21,0.71)	(0.15,0.06)

The (x, y) color coordinates for four of these standards are listed in Table 4.2.

To ensure color fidelity, s-RGB can reproduce most colors realistically because there are not many vivid colors outside the s-RGB triangle in the real world, as illustrated in Figs. 6.28 and 6.29. However, although highly saturated colors rarely occur, they have an intense impact on a viewer, so a color gamut wider than that of s-RGB is useful for showing such colors.

In the television industry, the image boosting technique, which converts an original image into a more impressive image, such as one with more vivid colors, by means of graphic engine IC chips or a graphics processing unit (GPU), is often used to enhance the image impression. A wider color gamut is useful for such an application as well.

As discussed earlier, the (x, y) coordinate is popular as a display color metric; however, there are problems with using the standard. Distance in the (x, y) coordinate is not proportional to differences in perception of the human visual system, so a larger area does not always mean better display capability. Figure 4.15 shows 10 times the perception limits of the human eye in different regions of the (x, y) color space reported by McAdam et al. [2]; this is known as the “McAdam ellipse.” As it is an ellipse, not a circle, the human eye does not have the same sensitivity for the x axis and the y axis. Also as shown in Fig. 4.15, the human eye is very sensitive to blue colors (left bottom of graph) but is less sensitive to red (right bottom) and is very insensitive to green colors (top). This illustrates that human eye sensitivity depends on the location on the (x, y) coordinate. Therefore it is not very meaningful to discuss the area to judge the display capability on the basis of an (x, y) coordinate system.

The issues discussed above explain why many display companies and research institutes have used (u', v') color coordinates to express display capability. The CIE1976 color space coordinates (u', v') can be expressed as




Figure 4.15 Graphical representation of McAdam ellipse, showing the human eye's perception limit (at 10× magnification).

$$u' = \frac{4x}{(-2x+12y+3)} = \frac{4X}{(X+15Y+3Z)} \tag{4.22}$$

$$v' = \frac{9y}{(-2x+12y+3)} = \frac{9Y}{(X+15Y+3Z)} \tag{4.23}$$

Performance comparisons using the (u', v') color coordinates indicate how a color display color can actually be perceived by the human eye.

Also, uniform color space is sometimes factored into any discussion of display capability or color boosting because the defective criteria (such as the luminance variation limit or the image burning limit according to life-time test discussed in Section 2.2.4, uniformity criteria discussed in Section 5.4.4, or the metal bus design discussed in Section 5.4.3) should be determined according to the limit of human perception.

4.2.4 Uniform Color Space

CIE-LAB and CIE-UV are two well-known uniform color spaces. On these uniform color spaces, lightness and color can be treated equally so that the length = 1 on the color space is almost equal to the human eye perception limit.

In CIE-LAB uniform color space (Fig. 4.16), lightness L^* is defined as

$$L^* = 116f \frac{Y}{Y_n} - 16$$

$$a^* = 500 \left(f \frac{X}{X_n} - f \frac{Y}{Y_n} \right)$$

$$b^* = 200 \left(f \frac{Y}{Y_n} - \frac{Z}{Z_n} \right)$$




Figure 4.16 CIE-LAB uniform color space.

In the case of $t > \left(\frac{6}{29}\right)^3$, $f(t) = t^{1/3}$. In other cases, $f(t)$ is $\frac{1}{3}\left(\frac{29}{6}\right)^2 t + \frac{4}{29}$.

Plotting a^* , b^* , and L^* on a three-dimensional graph, the angle of the line made by the plotted point and the original point in plane a^*-b^* shows the hue, and the distance between the plotted point and the original point in plane a^*-b^* is the chroma, as in the Munsell color system widely used in color science. In this color space, the color difference (including lightness difference) is defined as ΔE_{ab} by the following equation:

$$\Delta E_{ab} = \sqrt{\Delta L^{*2} + \Delta a^{*2} + \Delta b^{*2}}$$

For CIE-LUV uniform color space, the (u^*, v^*) coordinate is defined by the following equations:

$$u^* = 13L^*(u - u'_n)$$

$$v^* = 13L^*(v - v'_n)$$

Color difference can be expressed as follows for CIE-LUV uniform color space:

$$\Delta E_{uv} = \sqrt{\Delta L^{*2} + \Delta u^{*2} + \Delta v^{*2}}$$

Color difference $\Delta E = 1$ is known to be close to the human perception limit and is a useful criterion for determining parameters for display design, such as

- Acceptable display white point variation
- Acceptable lifetime and viewing angle
- Acceptable image sticking level.

4.2.5 White Point Determination

To display a white image, all red, green, and blue subpixels need to emit light. The white color changes the impression of a display quite a bit. The color should be selected according to the purpose of the display.

When tristimulus values of red, green, and blue are (X_R, Y_R, Z_R) , (X_G, Y_G, Z_G) , (X_B, Y_B, Z_B) respectively, then

$$X_{\text{white}} = X_R + X_G + X_B \tag{4.24}$$

$$Y_{\text{white}} = Y_R + Y_G + Y_B \tag{4.25}$$

$$Z_{\text{white}} = Z_R + Z_G + Z_B \tag{4.26}$$

Then the (x,y) coordinate of the white emission can be calculated as follows:

$$x_{\text{white}} = \frac{X_{\text{white}}}{X_{\text{white}} + Y_{\text{white}} + Z_{\text{white}}} \quad (4.27)$$

$$y_{\text{white}} = \frac{Y_{\text{white}}}{X_{\text{white}} + Y_{\text{white}} + Z_{\text{white}}} \quad (4.28)$$

The white coordinate (white point) is expressed by the CIE coordinates as well as by the blackbody radiation temperature.

To express the color of white emission, a blackbody temperature is often used. Radiant intensity from a black object having temperature T at wavelength between λ and $d\lambda$ can be expressed as (Planck radiation law)

$$P(\lambda) = \frac{8\pi hc^2}{\lambda^5} \cdot \frac{1}{e^{\frac{hc}{\lambda k_B T}} - 1}$$

(P , total radiant intensity from a black object toward all direction; c , speed of light; h , Planck constant; k_B , Boltzmann constant. It is necessary to pay attention to a potentially confusing definition. “Warm” color temperature, which normally means a color coordinate closer to red, has a low color temperature, while “cold” color temperature, normally a color coordinate closer to blue, has a high color temperature.)

Fig. 4.17 shows the spectrum of the radiant intensity for various color temperatures.




Figure 4.17 Black body emission spectrum for each color temperature.




Figure 4.18 Graphical representation of blackbody versus color temperatures.

Figure 4.18 shows the CIE coordinate of each blackbody temperature. (The line that the color coordinate follows when temperature is changed is called Planckian locus or blackbody locus.)

In television applications, a temperature of 6500 K (designated as D65) is used to display the white point, which has been introduced by the SMPTE-170M standard in the United States and many other countries. On the other hand, Asian countries such as Japan are using high-temperature color points. For example, Japan is using 9300 K (D93) as a target, which was introduced by NHK, a Japanese broadcasting organization. D65 is $(x,y) = (0.3127,0.3290)$ and D93 is $(x,y) = (0.283,0.297)$ on the CIE coordinate. For computer

monitors, three color point temperatures are sometimes available: 5000, 6500, and 9300 K.

When designing OLED displays, it is necessary to adjust the red, green, and blue primary color intensities to ensure adequate white balance.

4.3 PASSIVE-MATRIX OLED DISPLAY

Actual display design methodologies are discussed in the following chapters. There are several forms of OLED displays, such as segment displays (involving formation of electrodes by photolithography to create a pattern where the emission needs to take place and no matrix is formed), passive-matrix displays [3–7], and active-matrix displays. The passive-matrix display design is discussed here.

4.3.1 Structure

Figures 4.19 and 4.20 show passive-matrix OLED (PMOLED) displays (also called *passive OLED displays*). The data line, which is oriented vertically, and scan line, which is oriented horizontally, are formed, and the




Figure 4.19 Matrix driving of a passive-type OLED display.