



US011626066B2

(12) **United States Patent**
Lee

(10) **Patent No.:** **US 11,626,066 B2**

(45) **Date of Patent:** **Apr. 11, 2023**

(54) **PIXEL ARRANGEMENT STRUCTURE FOR ORGANIC LIGHT EMITTING DIODE DISPLAY**

(58) **Field of Classification Search**
CPC G09G 3/3208; H01L 27/3218; H01L 27/3216

See application file for complete search history.

(71) Applicant: **SAMSUNG DISPLAY CO., LTD.**,
Yongin-si (KR)

(56) **References Cited**

(72) Inventor: **Sang-Shin Lee**, Yongin-si (KR)

U.S. PATENT DOCUMENTS

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin-si (KR)

4,491,863 A 1/1985 Kurahashi
4,642,619 A 2/1987 Togashi
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **17/808,982**

CN 1726593 A 1/2006
CN 1874000 A 12/2006
(Continued)

(22) Filed: **Jun. 24, 2022**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2022/0319404 A1 Oct. 6, 2022

Decision by the Intellectual Property Trial and Appeal Board (IPTAB) of the Korean Intellectual Property Office (KIPO) on Patent Cancellation Request of Korean Patent No. KR 2115531 (corresponding to U.S. Pat. No. 9,818,803) dated Mar. 16, 2021, 12 pages.

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 17/005,753, filed on Aug. 28, 2020, which is a continuation of application No. 13/872,018, filed on Apr. 26, 2013, now Pat. No. 10,832,616, which is a continuation-in-part of application No. 13/614,197, filed on Sep. 13, 2012, now Pat. No. 9,818,803.

Primary Examiner — Kwang-Su Yang

(74) *Attorney, Agent, or Firm* — Lewis Roca Rothgerber Christie LLP

(30) **Foreign Application Priority Data**

Mar. 6, 2012 (KR) 10-2012-0022967
Apr. 23, 2013 (KR) 10-2013-0044993

(57) **ABSTRACT**

A pixel arrangement structure of an organic light emitting diode (OLED) display is provided. The pixel arrangement structure includes: a first pixel having a center coinciding with a center of a virtual square; a second pixel separated from the first pixel and having a center at a first vertex of the virtual square; and a third pixel separated from the first pixel and the second pixel, and having a center at a second vertex neighboring the first vertex of the virtual square. The first pixel, the second pixel, and the third pixel have polygonal shapes.


(51) **Int. Cl.**

G09G 3/3208 (2016.01)
H01L 27/32 (2006.01)

(52) **U.S. Cl.**

CPC **G09G 3/3208** (2013.01); **H10K 59/352** (2023.02); **H10K 59/353** (2023.02)

30 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,965,565 A 10/1990 Noguchi
 5,113,274 A 5/1992 Takahashi et al.
 5,142,392 A 8/1992 Ueki et al.
 5,461,503 A 10/1995 Deffontaines et al.
 5,485,293 A 1/1996 Robinder
 5,742,129 A 4/1998 Nagayama et al.
 6,198,507 B1 3/2001 Ishigami
 6,326,981 B1 12/2001 Mori et al.
 6,366,025 B1 4/2002 Yamada
 6,552,706 B1 4/2003 Ikeda et al.
 6,747,618 B2 6/2004 Arnold et al.
 6,838,819 B2 1/2005 Kim et al.
 6,867,549 B2 3/2005 Cok et al.
 6,882,364 B1 4/2005 Inuiya et al.
 6,933,976 B1 8/2005 Suzuki
 6,950,115 B2 9/2005 Brown Elliott
 7,075,242 B2 7/2006 Miller et al.
 7,110,031 B2 9/2006 Kondo et al.
 7,184,067 B2 2/2007 Miller et al.
 7,187,425 B2 3/2007 Yamazaki
 7,215,347 B2 5/2007 Phan
 7,230,594 B2 6/2007 Miller et al.
 7,274,383 B1 9/2007 Brown Elliot
 7,291,970 B2 11/2007 Kuwabara
 7,301,273 B2 11/2007 Dedene et al.
 7,397,485 B2 7/2008 Miller et al.
 7,612,811 B2 11/2009 Takeuchi et al.
 7,646,430 B2 1/2010 Brown Elliott et al.
 7,710,484 B2 5/2010 Oda
 7,755,652 B2 7/2010 Credelle et al.
 7,982,786 B2 7/2011 Nishida et al.
 8,026,669 B2 9/2011 Kawasaki et al.
 8,026,869 B2 9/2011 Takagi et al.
 8,118,633 B2 2/2012 Yuasa
 8,134,583 B2 3/2012 Credelle
 8,159,511 B2 4/2012 Brown Elliott et al.
 8,223,168 B2 7/2012 Brown Elliott et al.
 8,294,741 B2 10/2012 Brown Elliott et al.
 8,330,352 B2 12/2012 Sung et al.
 8,334,859 B2 12/2012 Liu et al.
 8,350,468 B2 1/2013 Ko et al.
 8,354,789 B2 1/2013 Kim et al.
 8,363,072 B2 1/2013 Hong et al.
 8,395,157 B2 3/2013 Park et al.
 8,405,692 B2 3/2013 Brown Elliott et al.
 8,421,820 B2 4/2013 Brown Elliott et al.
 8,456,496 B2 6/2013 Credelle
 8,519,910 B2 8/2013 Park et al.
 8,519,917 B2 8/2013 Ryu et al.
 8,552,635 B2 10/2013 Kim et al.
 8,587,003 B2 11/2013 Ando
 8,754,913 B2 6/2014 Hwang et al.
 8,830,275 B2 9/2014 Higgins
 8,853,016 B2 10/2014 Park et al.
 8,866,707 B2 10/2014 Koyama et al.
 8,883,532 B2 11/2014 Ando
 9,041,625 B2 5/2015 Hwang et al.
 9,355,601 B2 5/2016 Brown Elliott
 9,398,205 B2 7/2016 Cote et al.
 9,431,469 B2 8/2016 Park et al.
 9,837,476 B2 12/2017 Park et al.
 10,403,211 B2 9/2019 Hai et al.
 10,854,683 B2 12/2020 Lee
 2002/0015110 A1 2/2002 Brown Elliott
 2002/0070909 A1 6/2002 Asano et al.
 2002/0113195 A1 8/2002 Osada
 2002/0140833 A1 10/2002 Hirai
 2003/0117423 A1 6/2003 Brown Elliott et al.
 2003/0128179 A1 7/2003 Credelle
 2003/0128225 A1 7/2003 Credelle et al.
 2003/0218618 A1 11/2003 Phan
 2004/0036421 A1 2/2004 Arnold et al.
 2004/0046714 A1 3/2004 Brown Elliott
 2004/0108818 A1 6/2004 Cok et al.
 2004/0113875 A1 6/2004 Miller et al.

2004/0183764 A1 9/2004 Kim et al.
 2004/0246426 A1 12/2004 Wang et al.
 2005/0001542 A1 1/2005 Kiguchi
 2005/0162079 A1 7/2005 Sakamoto
 2005/0225575 A1 10/2005 Elliott et al.
 2006/0119738 A1 6/2006 Kido
 2006/0152531 A1 7/2006 Lin et al.
 2006/0274090 A1 12/2006 Koyama et al.
 2007/0164335 A1 7/2007 McKee
 2007/0230818 A1 10/2007 Messing et al.
 2008/0001525 A1 1/2008 Chao et al.
 2008/0001527 A1 1/2008 Koo et al.
 2008/0018765 A1 1/2008 Choi et al.
 2008/0273793 A1 11/2008 Oishi
 2008/0308819 A1 12/2008 Louwsma et al.
 2009/0027377 A1 1/2009 Kwon
 2009/0302331 A1 12/2009 Smith et al.
 2009/0321727 A1 12/2009 Yutani et al.
 2010/0033084 A1 2/2010 Ko et al.
 2010/0045695 A1 2/2010 Brown Elliott et al.
 2010/0117528 A1 5/2010 Fukuda
 2010/0117936 A1 5/2010 Lhee et al.
 2010/0133994 A1 6/2010 Song et al.
 2010/0171440 A1 7/2010 Satou et al.
 2010/0253608 A1 10/2010 Kim et al.
 2010/0315318 A1 12/2010 Lee et al.
 2011/0012820 A1 1/2011 Kim et al.
 2011/0018858 A1 1/2011 Ryu et al.
 2011/0084955 A1 4/2011 Kim
 2011/0115772 A1 5/2011 Chung
 2011/0177640 A1* 7/2011 Han H01L 27/3211
 438/34
 2011/0215302 A1 9/2011 Lhee et al.
 2011/0216056 A1 9/2011 Yoo et al.
 2011/0260951 A1 10/2011 Hwang et al.
 2011/0291549 A1 12/2011 Kim et al.
 2011/0291550 A1 12/2011 Kim et al.
 2011/0298836 A1 12/2011 Komiya et al.
 2011/0316892 A1 12/2011 Sung et al.
 2012/0049726 A1 3/2012 Yoo et al.
 2012/0056531 A1 3/2012 Park et al.
 2012/0086330 A1 4/2012 Umeda et al.
 2012/0176298 A1 7/2012 Suh et al.
 2012/0287605 A1 11/2012 Chen et al.
 2012/0313844 A1 12/2012 Im et al.
 2012/0319564 A1 12/2012 Ghosh et al.
 2013/0002911 A1 1/2013 Miyashita et al.
 2013/0037827 A1 2/2013 Levermore et al.
 2013/0057521 A1 3/2013 Kim
 2013/0106891 A1 5/2013 Matsueda et al.
 2013/0127689 A1 5/2013 Gollier
 2014/0191202 A1* 7/2014 Shim H01L 27/3213
 257/40
 2015/0187273 A1 7/2015 Chang et al.
 2015/0192834 A1 7/2015 Morinaga et al.
 2016/0124557 A1 5/2016 Choi
 2016/0171930 A1 6/2016 Song et al.
 2016/0190166 A1 6/2016 Kim et al.
 2019/0333970 A1 10/2019 Lee
 2020/0394955 A1 12/2020 Lee
 2022/0319406 A1 10/2022 Lee

FOREIGN PATENT DOCUMENTS

CN 101009304 A 8/2007
 CN 100439989 C 12/2008
 CN 100448020 C 12/2008
 CN 101449382 A 6/2009
 CN 102354479 A 2/2012
 CN 103311266 A 9/2013
 CN 203260586 U 10/2013
 CN 105206647 A 12/2015
 EP 0 322 106 A2 6/1989
 EP 1168448 A2 1/2002
 EP 1450408 A2 8/2004
 EP 2 637 209 A1 9/2013
 GB 2 437 110 A 10/2007
 JP 02-000826 A 1/1990
 JP 03-078390 A 4/1991

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	3-36239	5/1991
JP	8-227276 A	9/1996
JP	08-335060 A	12/1996
JP	09-182091 A	7/1997
JP	10-39791	2/1998
JP	2000-235891	8/2000
JP	2001-33757 A	2/2001
JP	2001-54127 A	2/2001
JP	2001-76881 A	3/2001
JP	3203907 B2	9/2001
JP	2001-290441 A	10/2001
JP	2003-203770 A	7/2003
JP	2004-507773	3/2004
JP	2004-179028 A	6/2004
JP	2004-192813	7/2004
JP	2005-5227 A	1/2005
JP	2005-62416 A	3/2005
JP	2005-63787 A	3/2005
JP	2005-515505 A	5/2005
JP	2006-18195 A	1/2006
JP	2006-163316 A	6/2006
JP	2006-309182	11/2006
JP	2007-156126 A	6/2007
JP	2008-015521	1/2008
JP	2008-277264 A	11/2008
JP	2008-298966 A	12/2008
JP	2008-300367 A	12/2008
JP	2009-230096 A	10/2009
JP	2010-3880 A	1/2010
JP	2010-153173 A	7/2010
JP	2011-076760	4/2011
JP	2011-198761 A	10/2011
JP	2012-15129 A	1/2012
JP	2012-19206 A	1/2012
JP	2012-028170 A	2/2012
JP	2012-79631 A	4/2012
JP	5177957 B2	4/2013
KR	10-2004-0096706 A	11/2004
KR	10-2006-0118868 A	11/2006
KR	10-0742370 B1	7/2007
KR	10-0807524 B1	2/2008
KR	10-2008-0111130	12/2008
KR	10-2009-0017910 A	2/2009
KR	10-2009-0049515 A	5/2009
KR	10-2011-0023996 A	3/2011
KR	10-2011-0039773 A	4/2011
KR	10-1056258 B1	8/2011
KR	10-2011-0106565 A	9/2011
KR	10-2011-0108050 A	10/2011
KR	10-2011-0117613 A	10/2011
KR	10-2011-0129531	12/2011
KR	10-2012-0000887 A	1/2012
KR	10-2012-0014074 A	2/2012
KR	10-2012-0022967 A	3/2012
KR	10-1332495 B1	11/2013
KR	10-2020-0000840 A	1/2020
TW	200305126 A	10/2003
TW	1277930 B	4/2007
TW	I328207	8/2010
WO	WO 03/053068 A2	6/2003
WO	WO 03/060870 A1	7/2003
WO	WO 2004/073356 A1	8/2004
WO	WO 2005/067352 A1	7/2005

OTHER PUBLICATIONS

English translation of Decision by the Intellectual Property Trial and Appeal Board (IPTAB) of the Korean Intellectual Property Office (KIPO) on Patent Cancellation Request of Korean Patent No. KR 2115531 (corresponding to U.S. Pat. No. 9,818,803) dated Mar. 16, 2021, 15 pages.

English translation of Petition for Patent Invalidation of Chinese Patent No. ZL201310035429.X (corresponding to U.S. Pat. No. 9,818,803) dated Dec. 22, 2020, 31 pages.

English translation of Petition for Patent Invalidation of Chinese Patent No. ZL201510595095.0 (corresponding to U.S. Pat. No. 9,818,803) dated Jan. 22, 2021, 26 pages.

U.S. Office Action dated Apr. 30, 2020, issued in U.S. Appl. No. 16/505,536 (14 pages).

U.S. Office Action dated Sep. 3, 2019, issued in U.S. Appl. No. 16/261,437 (11 pages).

U.S. Office Action dated Oct. 25, 2019, issued in U.S. Appl. No. 16/505,536 (14 pages).

Office action issued in U.S. Appl. No. 15/811,599 by the USPTO, dated Jul. 19, 2019, 19 pages.

U.S. Office Action dated Jul. 11, 2018, issued in U.S. Appl. No. 15/811,599 (19 pages).

U.S. Office Action dated Mar. 19, 2018, issued in U.S. Appl. No. 15/688,760 (13 pages).

EPO Communication Pursuant to Article 94(3) EPC, for Patent Application No. 13 178 648.5, dated Jan. 31, 2019, 8 pages.

English Abstract of TW 2008-02221 A, also published as TW 1328207, listed above.

TIPO Office Action dated Oct. 11, 2016, for Taiwanese Patent Application No. 102124953 (6 pages).

U.S. Office Action dated Oct. 14, 2016 issued in U.S. Appl. No. 13/614,197 (12 pages).

KIPO Office action dated Jul. 11, 2016, with English translation, for Korean Patent application 10-2016-0047800, (11 pages).

JPO Office action dated Feb. 16, 2016, corresponding to Japanese Patent application 2012-108855, (5 pages).

U.S. Office action dated Apr. 7, 2016, for U.S. Appl. No. 13/614,197, (13 pages).

EPO Search Report dated Jul. 8, 2013, for European Patent application 13157562.3, (6 pages).

Extended European Search Report dated Dec. 20, 2013, for European Patent Application No. 13178648.5 (9 pages).

Korean Patent Abstracts for Korean Publication 1020070055908 dated May 31, 2007, corresponding to Korean Patent 10-0742370 dated Jul. 24, 2007, listed above.

EPO Search Report dated Jul. 9, 2014, for European Patent application 14155124.2, (8 pages).

U.S. Office action dated Nov. 7, 2014, for U.S. Appl. No. 13/614,197, (16 pages).

U.S. Office action dated Aug. 29, 2014, for U.S. Appl. No. 14/059,356, (18 pages).

U.S. Office action dated Mar. 12, 2015, for U.S. Appl. No. 13/614,197, (13 pages).

SIPO Office action dated Mar. 11, 2015, corresponding to Chinese Patent application 201310035429.X, (7 pages).

Taiwan Office action dated Mar. 30, 2015, corresponding to Taiwanese Patent application 102101000, (7 pages).

Korean Patent Abstracts of Korean Publication No. 10-2003-0031207 A, published Apr. 21, 2003, which corresponds to KR 10-0807524 B1, 2 pages.

U.S. Office action dated Jul. 15, 2015, for U.S. Appl. No. 13/614,197, (11 pages).

U.S. Office action dated Dec. 2, 2015, for U.S. Appl. No. 13/614,197, (12 pages).

U.S. Final Office Action dated Feb. 1, 2021, issued in U.S. Appl. No. 16/505,536 (8 pages).

U.S. Office Action dated May 25, 2021, issued in U.S. Appl. No. 16/505,536 (15 pages).

U.S. Office Action dated Oct. 21, 2020, issued in U.S. Appl. No. 16/882,384 (24 pages).

U.S. Final Office Action dated Nov. 24, 2021, issued in U.S. Appl. No. 16/505,536 (19 pages).

U.S. Office Action from U.S. Appl. No. 16/505,536, dated May 11, 2022, 53 pages.

Advisory Action for U.S. Appl. No. 13/614,197 dated May 18, 2015, 3 pages.

Advisory Action for U.S. Appl. No. 13/872,018 dated Nov. 14, 2016, 3 pages.

Advisory Action for U.S. Appl. No. 13/872,018 dated Decembers, 2015, 3 pages.

Advisory Action for U.S. Appl. No. 16/505,536 dated Apr. 7, 2021, 3 pages.

(56)

References Cited

OTHER PUBLICATIONS

Ex Parte Quayle Action for U.S. Appl. No. 13/614,197 dated Jan. 5, 2017, 5 pages.
 Ex Parte Quayle Action for U.S. Appl. No. 15/090,591 dated Aug. 5, 2016, 6 pages.
 Final Office Action for U.S. Appl. No. 13/614,197 dated Dec. 2, 2015, 11 pages.
 Final Office Action for U.S. Appl. No. 13/872,018 dated May 11, 2017, 16 pages.
 Final Office Action for U.S. Appl. No. 13/872,018 dated Jun. 23, 2016, 12 pages.
 Final Office Action for U.S. Appl. No. 13/872,018 dated Oct. 16, 2015, 15 pages.
 Final Office Action for U.S. Appl. No. 14/059,356 dated Jun. 18, 2015, 15 pages.
 Final Office Action for U.S. Appl. No. 15/811,599 dated Jan. 21, 2020, 18 pages.
 Final Office Action for U.S. Appl. No. 16/505,536 dated Oct. 27, 2020, 15 pages.
 Notice of Allowance for U.S. Appl. No. 13/614,197 dated Mar. 22, 2017, 7 pages.
 Notice of Allowance for U.S. Appl. No. 13/614,197 dated Jul. 11, 2017, 7 pages.
 Notice of Allowance for U.S. Appl. No. 13/872,018 dated Feb. 19, 2020, 5 pages.
 Notice of Allowance for U.S. Appl. No. 13/872,018 dated May 28, 2020, 5 pages.
 Notice of Allowance for U.S. Appl. No. 14/059,356 dated Apr. 27, 2016, 5 pages.
 Notice of Allowance for U.S. Appl. No. 14/059,356 dated Nov. 25, 2015, 5 pages.
 Notice of Allowance for U.S. Appl. No. 15/090,591 dated Feb. 13, 2017, 5 pages.
 Notice of Allowance for U.S. Appl. No. 15/090,591 dated Jul. 31, 2017, 5 pages.
 Notice of Allowance for U.S. Appl. No. 15/090,591 dated Dec. 9, 2016, 5 pages.
 Notice of Allowance for U.S. Appl. No. 15/688,760 dated Jan. 30, 2019, 5 pages.
 Notice of Allowance for U.S. Appl. No. 15/688,760 dated Sep. 14, 2018, 5 pages.
 Notice of Allowance for U.S. Appl. No. 15/811,599 dated Feb. 14, 2019, 7 pages.
 Notice of Allowance for U.S. Appl. No. 15/811,599 dated Mar. 31, 2020, 5 pages.

Notice of Allowance for U.S. Appl. No. 15/811,599 dated Jul. 10, 2020, 5 pages.
 Notice of Allowance for U.S. Appl. No. 16/261,437 dated Jan. 10, 2020, 6 pages.
 Notice of Allowance for U.S. Appl. No. 16/261,437 dated Apr. 27, 2020, 5 pages.
 Notice of Allowance for U.S. Appl. No. 16/261,437 dated Aug. 14, 2020, 5 pages.
 Notice of Allowance for U.S. Appl. No. 16/261,437 dated Dec. 28, 2020, 5 pages.
 Office Action for U.S. Appl. No. 13/872,018 dated Feb. 29, 2016, 14 pages.
 Office Action for U.S. Appl. No. 13/872,018 dated Jun. 30, 2015, 13 pages.
 Office Action for U.S. Appl. No. 13/872,018 dated Dec. 30, 2016, 14 pages.
 Patent Board Decision on Appeal for U.S. Appl. No. 13/872,018 dated Dec. 2, 2019, 8 pages.
 Restriction Requirement for U.S. Appl. No. 13/872,018 dated Nov. 5, 2014, 8 pages.
 Restriction Requirement for U.S. Appl. No. 15/811,599 dated Mar. 28, 2018, 7 pages.
 U.S. Advisory Action from U.S. Appl. No. 13/614,197, dated Feb. 5, 2016, 3 pages.
 U.S. Notice of Allowance from U.S. Appl. No. 14/059,356, dated Sep. 10, 2015, 5 pages.
 U.S. Restriction Requirement from U.S. Appl. No. 13/614,197, dated Aug. 18, 2014, 7 pages.
 U.S. Restriction Requirement from U.S. Appl. No. 16/505,536, dated Aug. 5, 2019, 7 pages.
 U.S. Office Action dated Jul. 8, 2022, issued in U.S. Appl. No. 17/005,753, 48 pages.
 U.S. Office Action dated Sep. 19, 2022, issued in U.S. Appl. No. 17/808,985 (25 pages).
 U.S. Office Action dated Oct. 14, 2022, issued in U.S. Appl. No. 17/808,983 (23 pages).
 U.S. Office Action dated Nov. 3, 2022, issued in U.S. Appl. No. 17/808,984 (25 pages).
 U.S. Office Action dated Nov. 10, 2022, issued in U.S. Appl. No. 17/865,304 (23 pages).
 Chinese Office Action dated Sep. 13, 2022, issued in Chinese Patent Application No. 201910040602.2 (9 pages).
 U.S. Notice of Allowance dated Dec. 23, 2022, issued in U.S. Appl. No. 16/505,536 (9 pages).
 U.S. Final Office Action dated Jan. 4, 2023, issued in U.S. Appl. No. 17/808,985 (27 pages).

* cited by examiner

FIG. 1




FIG. 2




FIG.4





FIG. 5






FIG. 6

1

**PIXEL ARRANGEMENT STRUCTURE FOR
ORGANIC LIGHT EMITTING DIODE
DISPLAY**

**CROSS-REFERENCE TO RELATED
APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 17/005,753, filed Aug. 28, 2020, which is a continuation of U.S. patent application Ser. No. 13/872,018, filed Apr. 26, 2013, now U.S. Pat. No. 10,832,616, which claims priority to and the benefit of Korean Patent Application No. 10-2013-0044993, filed in the Korean Intellectual Property Office on Apr. 23, 2013, and is a continuation in part of U.S. patent application Ser. No. 13/614,197, filed Sep. 13, 2012, now U.S. Pat. No. 9,818,803, which claims priority to and the benefit of Korean Patent Application No. 10-2012-0022967, filed in the Korean Intellectual Property Office on Mar. 6, 2012. The entire contents of all of the above applications are incorporated herein by reference.

BACKGROUND

1. Field

Aspects of embodiments of the present invention relate generally to a pixel arrangement structure for an organic light emitting diode (OLED) display.

2. Description of the Related Art

A display device is a device that displays an image. Recently, an OLED display has been drawing attention.

The OLED display has a self-luminous characteristic. Because the OLED display does not need a separate light source, unlike a liquid crystal display, it can have a relatively smaller thickness and weight than liquid crystal displays. In addition, the OLED display exhibits high-quality characteristics such as low power consumption, high luminance, high response speed, etc.

In general, the OLED display includes a plurality of pixels for emitting light of different colors. The plurality of pixels emit light to display an image.

Here, the pixel refers to a minimum unit for displaying the images. For instance, there may be a gate line, a data line, and a power line such as a driving power line to drive each pixel. In addition, there may be an insulation layer such as a pixel definition layer to define an area and a shape of each pixel. Further, each pixel may be positioned between its neighboring pixels.

An organic emission layer included in the pixel of an OLED display may be deposited and formed by using a mask such as a fine metal mask (FMM). When reducing a gap between the neighboring pixels to obtain a high aperture ratio of the pixels, deposition reliability may be deteriorated. On the other hand, when increasing the gap between the pixels to improve the deposition reliability, the aperture ratio of the pixels may be deteriorated.

The above information disclosed in this Background section is only for enhancement of understanding of the background of the invention and therefore it may contain information that does not form the prior art that is already known in this country to a person of ordinary skill in the art.

SUMMARY

Aspects of embodiments of the present invention relate generally to a pixel arrangement structure for an OLED

2

display. More particularly, aspects of embodiments of the present invention relate to a pixel arrangement structure of an OLED display that displays an image by emitting light through a plurality of pixels.

5 An exemplary embodiment of the present invention provides a pixel arrangement structure for an OLED display having an improved aperture ratio of each of the pixels while efficiently setting up gaps between the pixels.

10 According to an exemplary embodiment of the present invention, a pixel arrangement structure of an organic light emitting diode display is provided. The pixel arrangement structure includes: a first pixel having a center coinciding with a center of a virtual square; a second pixel separated from the first pixel and having a center at a first vertex of the virtual square; and a third pixel separated from the first pixel and the second pixel, and having a center at a second vertex neighboring the first vertex of the virtual square.

15 The second pixel may include a pair of second pixels. The second pixels may be separated from each other by the first pixel.

20 The third pixel may include a pair of third pixels. The third pixels may be separated from each other by the first pixel.

25 The second pixels and the third pixels may enclose the first pixel in the virtual square.

The first pixel, the second pixels, and the third pixels may have polygonal shapes. The second pixels and the third pixels may have a larger area than the first pixel.

30 The first pixel may have a quadrilateral shape. The second pixels and the third pixels may have hexagonal or octagonal shapes.

The second pixels and the third pixels may have octagonal shapes.

35 The second pixels and the third pixels may have a same area. A distance between the first pixel and the second pixels, a distance between the first pixel and the third pixels, and a distance between the second pixels and the third pixels may be a same first length.

40 The first pixel may include a plurality of first pixels. The plurality of first pixels may have a same quadrilateral shape. A distance between neighboring ones of the plurality of first pixels may be a second length that is longer than the first length.

45 The second pixels may have a larger area than the third pixels. A distance between the second pixels and the third pixels may be a first length. A distance between the first pixel and the second pixels, and a distance between the first pixel and the third pixels may be a same second length.

50 The first pixel may include a plurality of first pixels. The plurality of first pixels may have a same quadrilateral shape. A distance between neighboring ones of the plurality of first pixels may be a third length that is longer than the first length and the second length.

55 The first pixel may include a plurality of first pixels. Neighboring ones of the plurality of first pixels may have quadrilateral shapes that are symmetrical to each other. A distance between the neighboring ones of the plurality of first pixels may be a third length that is longer than the first length and the second length.

60 The first pixel may include a plurality of first pixels. Neighboring ones of the plurality of first pixels may have quadrilateral shapes that are symmetrical to each other.

The second pixels may have a larger area than the third pixels.

65 The third pixels may have a larger area than the second pixels.

3

The first pixel, the second pixel, and the third pixel may be configured to emit different color lights.

The first pixel, the second pixel, and the third pixel may be configured to emit green light, blue light, and red light, respectively.

According to an exemplary embodiment of the present invention, a pixel arrangement structure of an organic light emitting diode (OLED) display is provided. The pixel arrangement structure includes: a first pixel having a center coinciding with a center of a virtual square; a second pixel separated from the first pixel and having a center at a first vertex of the virtual square; and a third pixel separated from the first pixel and the second pixel, and having a center at a second vertex neighboring the first vertex of the virtual square. The first pixel, the second pixel, and the third pixel have polygonal shapes.

In one embodiment, the second pixel includes a pair of second pixels, and the second pixels are separated from each other by the first pixel.

In one embodiment, the third pixel includes a pair of third pixels, and the third pixels are separated from each other by the first pixel.

In one embodiment, the second pixel includes a pair of second pixels, the third pixel includes a pair of third pixels, and the second pixels and the third pixels enclose the first pixel in the virtual square.

In one embodiment, each of the second pixels and the third pixels is larger in area than the first pixel.

In one embodiment, the first pixel has an octagonal shape, and at least one of the second pixel or the third pixel has an octagonal shape.

In one embodiment, the first pixel has an octagonal shape, and one of the second pixel or the third pixel has a hexagonal shape and an other of the second pixel or the third pixel has a quadrilateral shape.

In one embodiment, the virtual square includes a pair of virtual squares sharing a common side, the first pixel includes a pair of first pixels having centers respectively coinciding with centers of the virtual squares, and the first pixels have octagonal shapes that are symmetrical to each other.

In one embodiment, each of the second pixels is larger in area than each of the third pixels.

In one embodiment, a distance between the first pixel and the second pixels as well as a distance between the first pixel and the third pixels is a same first length.

In one embodiment, the virtual square includes a pair of virtual squares sharing a common side, the first pixel includes a pair of first pixels having centers respectively coinciding with centers of the virtual squares, a distance between each of the second pixels and the third pixels is a same second length, and a distance between the first pixels is a third length that is longer than the first length and the second length.

In one embodiment, the first pixel, the second pixel, and the third pixel are configured to emit different color light.

In one embodiment, the first pixel is configured to emit green light, one of the second pixel or the third pixel is configured to emit blue light, and an other of the second pixel or the third pixel is configured to emit red light.

According to an exemplary embodiment of the present invention, the pixel arrangement structure of the OLED display improves the aperture ratio of the pixels while efficiently setting up the gaps between the pixels.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a view of a pixel arrangement structure of an OLED display according to a first exemplary embodiment.

4

FIG. 2 is a view of a pixel arrangement structure of an OLED display according to a second exemplary embodiment.

FIG. 3 is a view of a pixel arrangement structure of an OLED display according to a third exemplary embodiment.

FIG. 4 is a view of a pixel arrangement structure of an OLED display according to a fourth exemplary embodiment.

FIG. 5 is a view of a pixel arrangement structure of an OLED display according to a fifth exemplary embodiment.

FIG. 6 is a view of a pixel arrangement structure of an OLED display according to a sixth exemplary embodiment.

DETAILED DESCRIPTION

Several exemplary embodiments according to the present invention are described hereinafter in detail with reference to the accompanying drawing to allow one of ordinary skill in the art to practice the invention without undue experimentation. The present invention can be embodied in several different forms, and is not limited to the exemplary embodiments that are described herein.

In order to clarify the description of embodiments of the present invention, parts that are not related to the invention may be omitted. In addition, the same elements or equivalents are referred to with the same reference numerals throughout the specification.

Further, since sizes and thicknesses of constituent members shown in the accompanying drawing may be arbitrarily given for better understanding and ease of description, the present invention is not limited to the illustrated sizes and thicknesses.

In addition, unless explicitly described to the contrary, the word "comprise" and variations such as "comprises" or "comprising" will be understood to imply the inclusion of stated elements but not the exclusion of any other elements.

Nevertheless, even though each of the pixels are drawn as stereotypical polygonal shapes in the drawings, the present invention is not limited to this shape. That is, the shapes of the pixels may be modified to avoid interference with the other components of the OLED (e.g., wirings) within the spirit and scope of the appended claims.

A pixel arrangement structure (or pixel arrangement) of an OLED display according to a first exemplary embodiment will be described with reference to FIG. 1. FIG. 1 is a view schematically showing a portion of pixels forming an OLED display.

As shown in FIG. 1, the pixel arrangement structure of the OLED display includes a plurality of first pixels **100**, a plurality of second pixels **200**, and a plurality of third pixels **300**. Here, the pixel refers to a minimum unit for displaying an image (for example, the minimum addressable unit of the display).

Further, among the first pixels **100**, the second pixels **200**, and the third pixels **300**, power lines for driving each of the pixels, such as a gate line, a data line, a driving power line, and the like, may be located. In addition, an insulation layer, such as a pixel defining layer, for defining each of the pixels may be disposed. Finally, an OLED including an anode, an organic emission layer, and a cathode to correspond to each of the first pixels **100**, the second pixels **200**, and the third pixels **300** may be disposed. These configurations are technologies known in the art and further description thereof is omitted for ease of description. A shape of each of the pixels may be defined by the power lines, the pixel defining layer, the anode, or the like, but is not limited thereto.

5

In the pixel arrangement of FIG. 1, each of the first pixels 100 has a smaller area than neighboring second pixels 200 and third pixels 300, and has a quadrilateral (i.e., four-sided) shape among polygon shapes. For example, in the pixel arrangement of FIG. 1, each of the first pixels 100 has the same quadrilateral shape (e.g., a square or rhombus). The first pixels 100 are spaced apart from each other and arranged in rows, such as along a first virtual straight line VL1. The first pixels 100 emit green light, and may include an organic emission layer for emitting green light.

The second pixels 200 are arranged diagonally with respect to the first pixels 100, such as at first vertices P1 along one diagonal of a virtual square VS having one of the first pixels 100 as a center point (or center) of the virtual square VS. In a similar fashion, the third pixels 300 are arranged diagonally with respect to the first pixels 100, such as at second vertices P2 along the other diagonal of the virtual square VS.

In the virtual square VS, each of the second pixels 200 is separated from the first pixel 100, and is centered at one of the first vertices P1 of the virtual square VS. Each of the second pixels 200 has a larger area than the neighboring first pixel 100 and has an octagonal (i.e., eight-sided) shape. In FIG. 1, the second pixels 200 each have the same octagonal shape. In addition, the second pixels 200 are arranged diagonally and separated from each other by the first pixels 100. The second pixels 200 emit blue light, and may include an organic emission layer for emitting blue light.

In a similar fashion, in the virtual square VS, each of the third pixels 300 is separated from the first pixel 100 and the second pixels 200, and is centered at one of the second vertices P2 neighboring the first vertices P1 of the virtual square VS. Each of the third pixels 300 has a larger area than the neighboring first pixel 100 and the same area as each of the second pixels 200. Further, the third pixels have an octagonal shape (e.g., similar to or the same as the second pixels 200). In FIG. 1, the third pixels 300 each have the same octagonal shape. In addition, the third pixels 300 are arranged diagonally and separated from each other by the first pixels 100. The third pixels 300 emit red light, and may include an organic emission layer for emitting red light.

The third pixels 300 and the second pixels 200 are spaced apart from each other and alternately arranged in rows, such as along a second virtual straight line VL2. In a similar fashion, the third pixels 300 and the second pixels 200 are spaced apart from each other and alternately arranged in columns. Accordingly, in the virtual square VS, two of the second pixels 200 having their corresponding centers positioned at the first vertices P1 and two of the third pixels 300 having their corresponding centers positioned at the second vertices P2 to enclose a corresponding one of the first pixels 100 (e.g., in the virtual square VS).

As described above, the center of each of the second pixels 200 is positioned at one of the first vertices P1 of the virtual square VS. In addition, the center of the corresponding first pixel 100 is the center of the virtual square VS. Further, the center of each of the third pixels 300 is positioned at one of the second vertices P2. Moreover, the second pixels 200 and the third pixels 300 each have the same area.

As a non-limiting example, the distance (e.g., a shortest distance) between one of the first pixels 100 and an adjacent one of the second pixels 200 is a first length L1, the distance between one of the first pixels 100 and an adjacent one of the third pixels 300 is the same first length L1, and the distance between one of the second pixels 200 and an adjacent one of the third pixels 300 is the same first length L1, as shown in

6

FIG. 1. In addition, the distance (e.g., a shortest distance) between the neighboring first pixels 100 is a second length L2 that is longer than the first length L1. It should be noted that L1, L2, L3, . . . may be used throughout to represent shortest distances between corresponding pixels.

Therefore, the gap of the first length L1 is formed between adjacent pairs of the first pixels 100 and the second pixels 200, between adjacent pairs of the first pixels 100 and the third pixels 300, and between adjacent pairs of the second pixels 200 and the third pixels 300. In addition, the gap of the second length L2 that is longer than the first length L1 is formed between the neighboring ones of the first pixels 100. This results in improved deposition reliability when using a fine metal mask to form the green, blue, and red organic emission layers respectively included in the first pixels 100, the second pixels 200, and the third pixels 300.

In addition, by enclosing each of the first pixels 100 by a pair of the second pixels 200 and a pair of the third pixels 300, the aperture ratio of the first pixels 100, the second pixels 200, and the third pixels 300 may be improved. Accordingly, a manufacturing time and manufacturing cost of the entire OLED display may be reduced and the display quality of the image of the OLED display may be improved.

As described above, in the pixel arrangement structure of the OLED display of FIG. 1, the first pixels 100, the second pixels 200, and the third pixels 300 have polygonal shapes (e.g., the first pixels have a quadrilateral shape and the second pixels 200 and the third pixels 300 have an octagonal shape). In addition, it is worth considering that the deposition process of the organic emission layer is one of the unique manufacturing characteristics of the OLED display. Accordingly, to improve the deposition reliability of the organic emission layer in the deposition process using the fine metal mask and to improve the aperture ratio of the first pixels 100, the second pixels 200, and the third pixels 300, the center of each of the first pixels 100 is positioned at the center of a virtual square VS formed by a first pair of diagonal vertices P1 and a second pair of diagonal vertices P2. In the virtual square VS, the centers of a pair of the second pixels 200 are positioned at the first vertices P1, and the centers of a pair of the third pixels 300 are positioned at the second vertices P2.

In addition, in the pixel arrangement structure of the OLED display of FIG. 1, the first pixels 100, the second pixels 200, and the third pixels 300 respectively emit green, blue, and red light. However, in pixel arrangement structures of other OLED displays, the first pixels 100, the second pixels 200, and the third pixels 300 may emit light of different colors. For example, at least one of the second pixels 200 or the third pixels may emit white light.

Next, a pixel arrangement structure of an OLED display according to a second exemplary embodiment will be described with reference to FIG. 2. Parts that are different from the exemplary embodiment of FIG. 1 will be described, while the description of parts that are equivalent to the first exemplary embodiment may be omitted. For better comprehension and ease of description, constituent elements of the second exemplary embodiment that are the same as or similar to those of the first embodiment of FIG. 1 will have the same reference numerals.

As shown in FIG. 2, the pixel arrangement structure of the OLED display includes a plurality of first pixels 100, a plurality of second pixels 200, and a plurality of third pixels 300. The plurality of first pixels 100 have the same quadrilateral shape (e.g., a parallelogram). In addition, the second pixels 200 have a larger area than the third pixels 300. The

second pixels **200** and the third pixels **300** may have polygonal shapes, such as octagonal or hexagonal (i.e., six-sided).

In a similar fashion to that of FIG. 1, the centers of a pair of the second pixels **200** are positioned at first vertices **P1** along one diagonal of a virtual square **VS** having a center coinciding with a center of one of the first pixels **100**. In addition, the centers of a pair of the third pixels **300** are positioned at second vertices **P2** along another diagonal of the virtual square **VS**. However, in FIG. 2, the second pixels **200** have a larger area than the third pixels **300**.

As a non-limiting example, the distance between adjacent ones of the second pixels **200** and the third pixels **300** is a third length **L3**, while the distance between each of the first pixels **100** and adjacent ones of the second pixels **200** or the third pixels **300** have a same fourth length **L4**. In addition, the distance between neighboring ones of the first pixels **100** is a fifth length **L5** that is longer than the third length **L3** and the fourth length **L4**.

Accordingly, the gap of the fourth length **L4** is formed between adjacent pairs of the first pixels **100** and the second pixels **200**, and between adjacent pairs of the first pixels **100** and the third pixels **300**. In addition, the gap of the third length **L3** is formed between adjacent pairs of the second pixels **200** and the third pixels **300**. Further, the gap of the fifth length **L5** that is longer than the third length **L3** and the fourth length **L4** is formed between the neighboring ones of the first pixels **100**. This results in improved deposition reliability in the deposition process using the fine metal mask to form the green, blue, and red organic emission layers respectively included in the first pixels **100**, the second pixels **200**, and the third pixels **300**.

In addition, by enclosing each of the first pixels **100** by a pair of the second pixels **200** and a pair of the third pixels **300**, the aperture ratio of the first pixels **100**, the second pixels **200**, and the third pixels **300** may be improved. Accordingly, the manufacturing time and the manufacturing cost of the OLED display may be reduced and the display quality of the image of the OLED display may be improved.

Further, in the pixel arrangement structure of the OLED display of FIG. 2, the second pixels **200** that emit blue have the shortest life span among the first pixels **100**, the second pixels **200**, and the third pixels **300**. Accordingly, the second pixels **200** have a larger area than the third pixels **300**, thereby suppressing the deterioration of the life span of the OLED display. That is, the pixel arrangement structure of the OLED display of FIG. 2 provides improved life span.

Next, a pixel arrangement structure of an OLED display according to a third exemplary embodiment will be described with reference to FIG. 3. Parts that are different from the above exemplary embodiments will be described, while the description of parts that are equivalent to the above exemplary embodiments may be omitted. For better comprehension and ease of description, constituent elements of the third exemplary embodiment that are the same as or similar to the above exemplary embodiments will have the same reference numerals.

As shown in FIG. 3, the pixel arrangement structure of the OLED display includes a plurality of first pixels **100**, a plurality of second pixels **200**, and a plurality of third pixels **300**. Among the plurality of first pixels **100**, the neighboring first pixels **100** have a quadrilateral shape (e.g., parallelogram) and are symmetrical to each other. In addition, the second pixels **200** have a larger area than the third pixels **300**. The second pixels **200** and the third pixels may have polygonal shapes (e.g., hexagonal or octagonal).

In a similar fashion to that of FIGS. 1-2, the centers of a pair of the second pixels **200** are positioned at first vertices **P1** along one diagonal of a virtual square **VS** having a center coinciding with a center of one of the first pixels **100**. In addition, the centers of a pair of the third pixels **300** are positioned at second vertices **P2** along another diagonal of the virtual square **VS**. However, in FIG. 3, the neighboring first pixels **100** have a quadrilateral shape and are symmetrical to each other, while the second pixels **200** have a larger area than the third pixels **300**. This results in improved deposition reliability in the deposition process using the fine metal mask to form the green, blue, and red organic emission layers respectively included in the first pixels **100**, the second pixels **200**, and the third pixels **300**.

In addition, by placing each of the first pixels **100** between a pair of the second pixels **200** and between a pair of the third pixels **300**, the aperture ratio of the first pixels **100**, the second pixels **200**, and the third pixels **300** may be improved. Accordingly, the manufacturing time and the manufacturing cost of the OLED display may be reduced and the display quality of the image of the OLED display may be improved.

Further, in the pixel arrangement structure of the OLED display of FIG. 3, the second pixels **200** that emit blue have the shortest life span among the first pixels **100**, the second pixels **200**, and the third pixels **300**. Accordingly, the second pixels **200** have a larger area than the third pixels **300**, thereby suppressing the deterioration of the life span of the OLED display. That is, the pixel arrangement structure of the OLED display provides improved life span.

Next, a pixel arrangement structure of an OLED display according to a fourth exemplary embodiment will be described with reference to FIG. 4. Parts that are different from the above exemplary embodiments will be described, while the description of parts that are equivalent to the above exemplary embodiments may be omitted. For better comprehension and ease of description, constituent elements of the fourth exemplary embodiment that are the same as or similar to the above exemplary embodiments will have the same reference numerals.

As shown in FIG. 4, the pixel arrangement structure of the OLED display includes a plurality of first pixels **100**, a plurality of second pixels **200**, and a plurality of third pixels **300**. Among the plurality of first pixels **100**, the neighboring first pixels **100** have a quadrilateral shape (e.g., parallelogram) and are symmetrical to each other. In addition, the third pixels **300** have a larger area than the second pixels **200**. The second pixels **200** and the third pixels may have polygonal shapes (e.g., hexagonal or octagonal).

In a similar fashion to that of FIGS. 1-3, the centers of a pair of the second pixels **200** are positioned at the first vertices **P1** along one diagonal of a virtual square **VS** having a center coinciding with a center of one of the first pixels **100**. In addition, the centers of a pair of the third pixels **300** are positioned at second vertices **P2** along another diagonal of the virtual square **VS**. However, in FIG. 4, the neighboring first pixels **100** have a quadrilateral shape and are symmetrical to each other, while the third pixels **300** have a larger area than the second pixels **200**. This results in improved deposition reliability in the deposition process using the fine metal mask to form the green, blue, and red organic emission layers respectively included in the first pixels **100**, the second pixels **200**, and the third pixels **300**.

In addition, by enclosing each of the first pixels **100** by a pair of the second pixels **200** and a pair of the third pixels **300**, the aperture ratio of the first pixels **100**, the second pixels **200**, and the third pixels **300** may be improved.

Accordingly, the manufacturing time and the manufacturing cost of the OLED display may be reduced and the display quality of the image of the OLED display may be improved.

Next, a pixel arrangement structure of an OLED display according to a fifth exemplary embodiment will be described with reference to FIG. 5. Parts that are different from the above exemplary embodiments will be described, while the description of parts that are equivalent to the above exemplary embodiments may be omitted. For better comprehension and ease of description, constituent elements of the fifth exemplary embodiment that are the same as or similar to the above exemplary embodiments will have the same reference numerals.

As shown in FIG. 5, the pixel arrangement structure of the OLED display includes a plurality of first pixels 100, a plurality of second pixels 200, and a plurality of third pixels 300. Among the plurality of first pixels 100, the neighboring first pixels 100 have a octagonal shape and are symmetrical to each other. In addition, the second pixels 200 have a larger area than the third pixels 300. The second pixels 200 and the third pixels 300 may have quadrilateral shapes (e.g., rhombus).

In a similar fashion to that of FIGS. 1-3, the centers of a pair of the second pixels 200 are positioned at the first vertices P1 along one diagonal of a virtual square VS having a center coinciding with a center of one of the first pixels 100. In addition, the centers of a pair of the third pixels 300 are positioned at second vertices P2 along another diagonal of the virtual square VS. However, in FIG. 5, the neighboring first pixels 100 have a octagonal shape and are symmetrical to each other, while the second pixels 200 have a larger area than the third pixels 300. This results in improved deposition reliability in the deposition process using the fine metal mask to form the green, blue, and red organic emission layers respectively included in the first pixels 100, the second pixels 200, and the third pixels 300.

In addition, by enclosing each of the first pixels 100 by a pair of the second pixels 200 and a pair of the third pixels 300, the aperture ratio of the first pixels 100, the second pixels 200, and the third pixels 300 may be improved. Accordingly, the manufacturing time and the manufacturing cost of the OLED display may be reduced and the display quality of the image of the OLED display may be improved.

Hereinafter, a pixel arrangement structure (or pixel arrangement) of an OLED display according to an exemplary embodiment will be described with reference to FIG. 6. FIG. 6 is a view schematically showing a portion of pixels forming an OLED display.

FIG. 6 shows a pixel arrangement structure of an OLED display according to an exemplary embodiment of the present invention.

As shown in FIG. 6, the pixel arrangement structure of the OLED display includes a plurality of first pixels 100, a plurality of second pixels 200, and a plurality of third pixels 300.

According to one embodiment, the pixel refers to a minimum unit for displaying an image (for example, the minimum addressable unit of the display).

In one embodiment, among the first pixels 100, the second pixels 200, and the third pixels 300, power lines for driving each of the pixels, such as a gate line, a data line, a driving power line, and the like, are located. In addition, in one embodiment, an insulation layer, such as a pixel defining layer, for defining each of the pixels is disposed. Further, in one embodiment, an OLED including an anode, an organic emission layer, and a cathode to correspond to each of the first pixels 100, the second pixels 200, and the third pixels

300 is disposed. These configurations are technologies known in the art and further description thereof is omitted for ease of description. In one embodiment, the shape of each of the pixels is defined by the power lines, the pixel defining layer, the anode, or the like.

In the pixel arrangement of FIG. 6, each of the first pixels 100 has a smaller area (e.g., is smaller in area) than neighboring second pixels 200 and third pixels 300, and has a polygon shape. In FIG. 6, the first pixels 100 have an octagonal shape among the polygon shapes. In other embodiments, the first pixels 100 have one or more of various polygon shapes such as a triangle, a rectangle, a pentagon, a hexagon, a heptagon, and the like. For example, the first pixels 100 that neighbor each other among the plurality of first pixels 100 have hexagonal shapes that are symmetrical to each other. In one embodiment, each of the plurality of first pixels 100 has the same hexagonal shape.

In one embodiment, the first pixels 100 are spaced apart from each other and arranged in rows, such as along a first virtual straight line VL1. In one embodiment, the first pixels 100 emit green light, and include an organic emission layer for emitting green light. In other embodiments, the first pixels 100 include an organic emission layer that emits light of one or more of various colors such as blue, red, or white color for emitting blue light, red light, or white light.

In FIG. 6, the second pixels 200 are arranged diagonally with respect to the first pixels 100, namely at first vertices P1 along one diagonal of a virtual square VS having one of the first pixels 100 as a center point (or center) of the virtual square VS. In a similar fashion, in FIG. 6, the third pixels 300 are arranged diagonally with respect to the first pixels 100, namely at second vertices P2 along the other diagonal of the virtual square VS.

In the virtual square VS of FIG. 6, each of the second pixels 200 is separated from the first pixel 100, and is centered at one of the first vertices P1 of the virtual square VS. Each of the second pixels 200 has a larger area than the neighboring first pixel 100 and the neighboring third pixels 300, and has a hexagonal shape. In other embodiments, the second pixels 200 have one or more of various polygonal shapes such as a triangle, a rectangle, a pentagon, a hexagon, a heptagon, and the like.

In FIG. 6, the second pixels 200 each have the same hexagonal shape. In addition, the second pixels 200 are arranged diagonally and separated from each other by the first pixels 100. In one embodiment, the second pixels 200 emit blue light, and include an organic emission layer for emitting blue light. In other embodiments, the second pixels 200 include an organic emission layer that emits light of one or more of various colors such as red, green, or white for emitting red light, green light, or white light.

In a similar fashion, in the virtual square VS of FIG. 6, each of the third pixels 300 is separated from the first pixel 100 and the second pixels 200, and is centered at one of the second vertices P2 neighboring the first vertices P1 of the virtual square VS. Each of the third pixels 300 has a larger area than the neighboring first pixel 100 and a smaller area than the neighboring second pixels 200. The third pixels 300 has a quadrilateral shape among polygon shapes. In other embodiments, the third pixels 300 have one or more of various polygonal shapes such as a triangle, a rectangle, a pentagon, a hexagon, a heptagon, and the like.

In FIG. 6, the third pixels 300 each have the same quadrilateral shape. In addition, the third pixels 300 are arranged diagonally and separated from each other by the first pixels 100. In one embodiment, the third pixels 300 emit red light, and include an organic emission layer for emitting

11

red light. In other embodiments, the third pixels 300 include an organic emission layer that emits light of one or more of various colors such as blue, green, or white for emitting blue light, green light, or white light.

In FIG. 6, each of the second pixels 200 and the third pixels 300 has a hexagonal shape and a quadrilateral shape, respectively. In another embodiment, each of the second pixels 200 and the third pixels 300 respectively has a quadrilateral shape and a hexagonal shape. That is, in this other embodiment, one of the second pixels 200 or the third pixels 300 has a hexagonal shape and the other has a quadrilateral shape.

In one embodiment, the first pixels 100, the second pixels 200, and the third pixels 300 respectively emit green light, blue light, and red light. In other embodiments, the first pixels 100, the second pixels 200, and the third pixels 300 emit light of the same color. In still other embodiments, the first pixels 100, the second pixels 200, and the third pixels 300 emit light of different colors. In some embodiments, the first pixels 100 emit green light, and one of the second pixels 200 or the third pixels 300 emit blue light while the other emit red light.

In FIG. 6, third pixels 300 and the second pixels 200 are spaced apart from each other and alternately arranged in rows, such as along a second virtual straight line VL2. In a similar fashion, in FIG. 6, the third pixels 300 and the second pixels 200 are spaced apart from each other and alternately arranged in columns. Accordingly, in FIG. 6, in the virtual square VS, two of the second pixels 200 have their corresponding centers positioned at the first vertices P1 and two of the third pixels 300 have their corresponding centers positioned at the second vertices P2 to enclose a corresponding one of the first pixels 100 in the virtual square VS.

As described and illustrated in FIG. 6, the center of each of the second pixels 200 is positioned at one of the first vertices P1 of the virtual square VS. In addition, the center of the corresponding first pixel 100 is the center of the virtual square VS. Further, the center of each of the third pixels 300 is positioned at one of the second vertices P2. Therefore, the plurality of second pixels 200 of which the centers are positioned at the first vertices P1 and the plurality of third pixels 300 of which the centers are positioned at the second vertices P2 respectively enclose one of the first pixels 100 in the virtual square VS.

Further, and as illustrated in FIG. 6, the first pixels 100, the second pixels 200, and the third pixels 300 have polygon shapes. In FIG. 6, the distance between one of the first pixels 100 and an adjacent one of the second pixels 200 as well as a distance between one of the first pixels 100 and an adjacent one of the third pixels 300 is the same first length L1. In addition, a distance between one of the second pixels 200 and an adjacent one of the third pixels 300 is a second length L2 that is different from the first length L1. Further, in FIG. 6, a distance between neighboring first pixels 100 is a third length L3 that is longer than the first length L1 and the second length L2.

For example, in some embodiments, the first length L1 is between 15 μm (micrometers) and 35 μm , the second length L2 is between 20 μm and 45 μm , and the third length L3 is between 25 μm and 65 μm .

Therefore, gaps of the first length L1 are formed between adjacent pairs of the first pixels 100 and the second pixels 200, and between adjacent pairs of the first pixels 100 and the third pixels 300. In addition, the gaps of the third length L3 that is longer than the first length L1 are formed between the neighboring ones of the first pixels 100. In one embodiment, this results in improved deposition reliability in the

12

deposition process using the fine metal mask to form the green, blue, and red organic emission layers respectively included in the first pixels 100, the second pixels 200, and the third pixels 300.

In addition, in one embodiment, the plurality of second pixels 200 and the plurality of third pixels 300 are arranged to enclose the first pixels 100 in the virtual squares VS so that an aperture ratio of each of the first pixels 100, the second pixels 200, and the third pixels 300 can be improved. Accordingly, in one embodiment, the manufacturing time and the manufacturing cost of the OLED display is reduced and the display quality of the image of the OLED display is improved.

Further, in the pixel arrangement structure of the OLED display of FIG. 6 according to an exemplary embodiment of the present invention, the second pixels 200 that emit blue light have the shortest life span among the first pixels 100, the second pixels 200, and the third pixels 300. Accordingly, the second pixels 200 have a larger area than the first pixels 100 and the third pixels 300, thereby suppressing the deterioration of the life span of the OLED display. That is, in one embodiment, the pixel arrangement structure of the OLED display of FIG. 6 provides improved life span.

As described above, in the pixel arrangement structure of the OLED display of FIG. 6 according to an exemplary embodiment of the present invention, the first pixels 100, the second pixels 200, and the third pixels 300 have simple polygonal shapes such as an octagon, a hexagon, and a quadrangle. In consideration of the deposition process of the organic emission layer, which in one embodiment is a unique manufacturing feature of the OLED display, a center of one of the first pixels 100 is positioned at the center of the virtual square VS, a center of one of the second pixels 200 is positioned at the first vertex P1, and a center of one of the third pixels 300 is positioned at the second vertex P2 to both improve deposition reliability of the organic emission layer in the deposition process using the fine metal mask and improve an aperture of each of the first, second, and third pixels 100, 200, and 300.

That is, according to an exemplary embodiment of the present invention as illustrated in FIG. 6, the pixel arrangement structure of the OLED display includes a plurality of first pixels 100 having an octagonal shape, a plurality of second pixels 200 having a hexagonal shape, and a plurality of third pixels 300 having a quadrilateral shape. In one or more embodiments, the shapes and arrangement of the first pixels 100, the second pixels 200, and the third pixels 300 improve the deposition reliability of the organic emission layer while also improving the aperture ratio of each of the first pixels 100, the second pixels, 200, and the third pixels 300.

While this invention has been described in connection with what is presently considered to be practical exemplary embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims, and equivalents thereof.

DESCRIPTION OF SOME SYMBOLS

first pixel 100, second pixels 200, third pixels 300

What is claimed is:

1. An organic light emitting diode (OLED) display, comprising:

13

a plurality of individually addressable pixels for displaying an image, the individually addressable pixels being minimum addressable units of the OLED display and comprising:

- a plurality of red pixels comprising an organic emission layer for emitting red light;
- a plurality of blue pixels comprising an organic emission layer for emitting blue light; and
- a plurality of green pixels comprising an organic emission layer for emitting green light,

wherein the OLED display comprises a pixel defining layer defining areas of the plurality of red pixels, the plurality of blue pixels, and the plurality of green pixels,

wherein each of the plurality of red pixels, the plurality of blue pixels, and the plurality of green pixels are spaced apart from each other,

wherein a first green pixel of the plurality of green pixels has a center coinciding with a center of a virtual square, each vertex of the virtual square coinciding with a center of a different one of the plurality of green pixels and each edge of the virtual square overlapping three consecutive green pixels,

wherein at least two blue pixels of the plurality of blue pixels and at least two red pixels of the plurality of red pixels are located entirely within boundaries of the virtual square,

wherein each of the at least two blue pixels has a larger area than each of the at least two red pixels,

wherein each of the at least two blue pixels has a larger area than that of the first green pixel,

wherein the first green pixel has a convex shape such that a line bisecting the first green pixel along a long axis thereof has a greater length than a line bisecting the first green pixel along a short axis thereof, and

wherein a shortest distance between two nearest ones of the plurality of green pixels is greater than a width of a first red pixel of the plurality of red pixels along a first direction parallel to the short axis of the first green pixel.

2. The OLED display of claim 1, wherein a shortest distance between one of the at least two blue pixels and one of the at least two red pixels is greater than a shortest distance between the first green pixel and the one of the at least two blue pixels or a shortest distance between the first green pixel and the one of the at least two red pixels.

3. The OLED display of claim 2, wherein the first green pixel has a different shape than the one of the at least two blue pixels and the one of the at least two red pixels.

4. The OLED display of claim 2, wherein the one of the at least two red pixels has an area that is larger than that of the first green pixel.

5. The OLED display of claim 2, wherein the one of the at least two blue pixels and the one of the at least two red pixels have polygonal shapes with at least four sides.

6. The OLED display of claim 1, wherein a shortest distance between one of the at least two blue pixels and one of the at least two red pixels is equal to a shortest distance between the first green pixel and the one of the at least two blue pixels or a shortest distance between the first green pixel and the one of the at least two red pixels.

7. The OLED display of claim 6, wherein the first green pixel has a different shape than the one of the at least two blue pixels and the one of the at least two red pixels.

8. The OLED display of claim 6, wherein the one of the at least two red pixels has an area that is larger than that of the first green pixel.

14

9. The OLED display of claim 6, wherein the one of the at least two blue pixels and the one of the at least two red pixels have polygonal shapes with at least four sides.

10. The OLED display of claim 1, wherein a shortest distance between the first green pixel and an adjacent one of the plurality of green pixels is greater than a shortest distance between the first green pixel and one of the at least two blue pixels or a shortest distance between the first green pixel and one of the at least two red pixels.

11. The OLED display of claim 1, wherein a shortest distance between the first green pixel and one of the at least two blue pixels is equal to a shortest distance between the first green pixel and one of the at least two red pixels.

12. The OLED display of claim 1, wherein a shortest distance between the first green pixel and an adjacent one of the plurality of green pixels is not equal to a shortest distance between one of the at least two blue pixels and one of the at least two red pixels.

13. The OLED display of claim 1, wherein a width of the first green pixel along the short axis of the first green pixel is different from a width of one of the at least two red pixels along the first direction, or a width of the first green pixel along the long axis of the first green pixel is different from a width of one of the at least two blue pixels along a second direction parallel to the long axis of the first green pixel.

14. The OLED display of claim 1, wherein a shortest distance between the two nearest ones of the plurality of green pixels is greater than a width of the first red pixel along a second direction parallel to the long axis of the first green pixel.

15. A method for manufacturing an organic light emitting diode (OLED) display, comprising:

- depositing, using a fine metal mask, organic light-emitting material configured to emit a first color of light;
- forming a plurality of first pixels to emit the first color of light;
- depositing, using a fine metal mask, organic light-emitting material configured to emit a second color of light;
- forming a plurality of second pixels to emit the second color of light;
- depositing, using a fine metal mask, organic light-emitting material configured to emit a third color of light; and
- forming a plurality of third pixels to emit the third color of light,

wherein the plurality of first pixels, the plurality of second pixels, and the plurality of third pixels are individually addressable pixels for displaying an image, the individually addressable pixels being minimum addressable units of the OLED display,

wherein the OLED display comprises a pixel defining layer defining areas of the plurality of first pixels, the plurality of second pixels, and the plurality of third pixels,

wherein each of the plurality of first pixels, the plurality of second pixels, and the plurality of third pixels are spaced apart from each other,

wherein a first one of the plurality of first pixels has a center coinciding with a center of a virtual square, each vertex of the virtual square coinciding with a center of a different one of the plurality of first pixels and each edge of the virtual square overlapping three consecutive first pixels,

wherein at least two second pixels of the plurality of second pixels and at least two third pixels of the plurality of third pixels are located entirely within boundaries of the virtual square,

15

wherein each of the at least two second pixels has a larger area than each of the at least two third pixels,
 wherein each of the at least two second pixels has a larger area than that of the first one of the plurality of first pixels,
 wherein the first one of the plurality of first pixels has a convex shape such that a line bisecting the first one of the plurality of first pixels along a long axis thereof has a greater length than a line bisecting the first one of the plurality of first pixels along a short axis thereof, and
 wherein a shortest distance between two nearest ones of the plurality of first pixels is greater than a width of one of the third pixels along a first direction parallel to the short axis of the first one of the plurality of first pixels.

16. The method of claim 15, wherein the first one of the plurality of first pixels has a different shape than one of the at least two second pixels and one of the at least two third pixels.

17. The method of claim 15, wherein the one of the at least two third pixels has an area that is larger than that of the first one of the plurality of first pixels.

18. The method of claim 15, wherein one of the at least two second pixels and one of the at least two third pixels have polygonal shapes with at least four sides.

19. The method of claim 15, wherein the plurality of first pixels comprises an organic emission layer for emitting green light, the plurality of second pixels comprises an organic emission layer for emitting blue light, and the plurality of third pixels comprises an organic emission layer for emitting red light.

20. The method of claim 19, wherein a shortest distance between one of the at least two second pixels and one of the at least two third pixels is greater than a shortest distance between the first one of the plurality of first pixels and the one of the at least two second pixels or a shortest distance between the first one of the plurality of first pixels and the one of the at least two third pixels.

21. The method of claim 20, wherein the first one of the plurality of first pixels has a different shape than the one of the at least two second pixels and the one of the at least two third pixels.

16

22. The method of claim 20, wherein the one of the at least two third pixels has an area that is larger than that of the first one of the plurality of first pixels.

23. The method of claim 20, wherein the one of the at least two second pixels and the one of the at least two third pixels have polygonal shapes with at least four sides.

24. The method of claim 19, wherein a shortest distance between one of the at least two second pixels and the one of the at least two third pixels is equal to a shortest distance between the first one of the plurality of first pixels and the one of the at least two second pixels or a shortest distance between the first one of the plurality of first pixels and the one of the at least two third pixels.

25. The method of claim 24, wherein the first one of the plurality of first pixels has a different shape than the one of the at least two second pixels and the one of the at least two third pixels.

26. The method of claim 24, wherein the one of the at least two third pixels has an area that is larger than that of the first one of the plurality of first pixels.

27. The method of claim 24, wherein the one of the at least two second pixels and the one of the at least two third pixels have polygonal shapes with at least four sides.

28. The method of claim 15, wherein a shortest distance between the first one of the plurality of first pixels and an adjacent one of the plurality of first pixels is not equal to a shortest distance between one of the at least two second pixels and one of the at least two third pixels.

29. The method of claim 15, wherein a width of the first one of the plurality of first pixels along the short axis of the first one of the plurality of first pixels is different from a width of one of the at least two third pixels along the first direction, or a width of the first one of the plurality of first pixels along the long axis of the first one of the plurality of first pixels is different from a width of one of the at least two second pixels along a second direction parallel to the long axis of the first one of the plurality of first pixels.

30. The method of claim 15, wherein a shortest distance between the two nearest ones of the plurality of first pixels is greater than a width of the one of the third pixels along a second direction parallel to the long axis of the first one of the plurality of first pixels.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION


PATENT NO. : 11,626,066 B2
APPLICATION NO. : 17/808982
DATED : April 11, 2023
INVENTOR(S) : Sang-Shin Lee

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

Column 13, Line 52, Claim 4	Delete “preen” and Insert -- green --
Column 13, Line 67, Claim 8	Delete “preen” and Insert -- green --
Column 15, Line 20, Claim 17	Delete “wherein the one” and Insert -- wherein one --
Column 16, Line 8 (Approx.), Claim 24	Delete “and the one” and Insert -- and one --

Signed and Sealed this
Eighteenth Day of July, 2023


Katherine Kelly Vidal
Director of the United States Patent and Trademark Office