



- [54] PIVOTAL SUPPORT LOCK APPARATUS FOR TROLLING MOTOR APPARATUS
- [75] Inventors: David G. Friedel; Robert J. Shanahan; Robert F. Kloiber, all of Oshkosh, Wis.
- [73] Assignee: Brunswick Corporation, Skokie, Ill.
- [22] Filed: Sept. 4, 1975
- [21] Appl. No.: 610,302
- [52] U.S. Cl. 115/17; 115/18 E; 248/4
- [51] Int. Cl.² B63H 21/26
- [58] Field of Search 115/17, 18 R, 18 E, 115/41 R; 248/4


[56] **References Cited**
UNITED STATES PATENTS
 3,870,258 3/1975 Shimanckas 115/17 X
Primary Examiner—Trygve M. Blix
Assistant Examiner—Sherman D. Basinger
Attorney, Agent, or Firm—Andrus, Sceales, Starke & Sawall

[57] **ABSTRACT**
 A pivotal mount for a trolling motor includes a deck bracket having a housing arm pivotally mounted at one end. A gear mechanism within the arm has a fixed bevel gear on the pivot arm axis meshing with a bevel gear on a rotatable torque tube. A drive bevel gear is secured to the opposite end and meshes with a gear sector on a coupling head pivotally mounted in the outer end of the arm. The head includes a swivel support element within which the trolling motor unit is rotatably mounted. The coupling head and motor unit are located between a depending propulsion position and transport position in response to the 180° swinging of the pivot arm. The torque tube is coupled to the bevel gears by sliding couplings and is coupled to a locking unit for the arm and a separate locking unit for the gear sector to lock them in the propulsion position and simultaneously release them raising to the transport position.

7 Claims, 8 Drawing Figures







PIVOTAL SUPPORT LOCK APPARATUS FOR TROLLING MOTOR APPARATUS

BACKGROUND OF THE INVENTION

This invention relates to a trolling motor unit for propelling of watercraft particularly at low speeds.

In bass fishing and the like, a trolling motor unit is often employed to very slowly maneuver, position, and hold the watercraft or boat in proper positioning for casting. Generally, the trolling motor unit is mounted to a horizontal deck at the forward end of the watercraft. The mounting includes a pivotal mount assembly permitting the depending of the motor unit from the front of the boat for propulsion of the boat. Alternatively, the trolling motor unit will be raised from the propulsion position and placed in a transport position across the deck. A separate high-powered outboard motor or the like is employed for rapid propulsion of the boat to and from the fishing location or area.

The trolling motor unit will normally include a depending pipe-like support mounted in a swivel bracket. The pipe-like support terminates at the lower end in a lower unit within which a small electric motor is housed for direct driving of the propeller. The upper end of the support tube includes steering means for angular positioning of the lower unit for steering of the watercraft. The propeller speed is controlled by varying the energization of the electric motor. The steering and speed controls are normally switch controls located within the boat coupled by suitable lines and cables to the motor and to the support tube.

The pivotal mount assembly is preferably constructed such that in the transport position, the motor unit is located within the boat and does not protrude over the outer edge of the boat. Generally prior art mounting systems have employed various linkages which provide for positioning between the depending propulsion and a transport position in which the trolling motor unit is located lying on the supporting deck with the lower unit or propeller end of the motor unit lying inwardly of the outer edge of the boat. A parallelogram type linkage is particularly adapted to the desired positioning of the trolling motor.

A unique and highly satisfactory pivotal mount apparatus for trolling motor is disclosed in the copending application of Charles E. Alexander entitled "High Thrust Trolling Motor" bearing Ser. No. 610,304 filed Sept. 4, 1975 and assigned to the same assignee. Generally as more fully disclosed therein, an arm means is pivotally attached to the boat deck for rotation through 180°. The trolling motor unit is secured to the pivotally mounted arm means which incloses a gear drive means including a drive gear member responsive to arm rotation and a driven gear member coupled to the trolling motor unit. The gear mechanism is operable to directly pivot the trolling motor unit through 90°, a depending position in response to pivoting of the support arm means through 180°. Further, in the propulsion position, the motor unit and support should be rigidly locked in place to maintain reliable control of the positioning of the watercraft. The locking system should provide for convenient locking in response to placement in the depending position while providing a reliable and easy release.

SUMMARY OF THE PRESENT INVENTION

The present invention is directed to an improved locking means for a pivotally mounted gear mechanism for trolling motor pivotal arm mount. Generally, in accordance with the present invention, separate locking means are provided to positively hold the pivot arm means in the trolling position and the trolling motor unit in the depending propulsion position. More particularly the gear means, includes a locking mechanism to prevent relative rotation of the driven gear. A separate second hold-down or locking mechanism mechanically locks the arm to the adjacent deck. A single manually operable release means is coupled to simultaneously disengage the arm lock means and the gear lock means. The dual interlock between the arm lock means and the gear lock means will effectively prevent the possibility of an attempt to release and pivot the arm means without release of the motor. This is significant in order to reliably prevent possible accidental damaging of the gear means.

The gear lock mechanism preferably includes the outer end of the torque tube and adjacent portion of the bevel gear sector formed to define a releasable pin and slot coupling elements such that retraction of the torque tube releases the gear mechanism. In the extended propulsion position, the coupling elements are aligned and engage to positively prevent rotation of the head gear sector and thereby lock the trolling motor unit in the depending position relative to the pivot arm. In addition, the torque tube intermediate its length carries an arm locking element such as an eyelet or loop element, forming a part of a two piece latch or locking means, the opposite element such as a hook lever, of which is affixed to the mounting bracket. The arm locking means is constructed with the elements disengaged in response to the retraction of the torque tube to release the gear arm. The lever is provided with a camming means to reset to the lock position in response to placing the arm in the propulsion position.

In the preferred embodiment, the locking means of the assembly is essentially totally enclosed with the gear means and thereby minimizes the danger of fouling of the mechanism with foreign matter which can interfere with the desired operation of the mechanism.

The dual interlocking means provides a highly improved and practical pivotal mount assembly for the safe, reliable and convenient mounting of the trolling motor, as well as its manufacture. The structure of the invention can be manufactured as a rigid, long life assembly which is conveniently and safely operable by the boater or fisherman.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings furnished herewith illustrate the best mode presently contemplated by the inventor for carrying out the subject invention in which the above advantages and features are clearly disclosed as well as others which will be readily understood from the following description of the embodiments shown.

In the drawings:

FIG. 1 is a side elevational view of a trolling motor apparatus constructed in accordance with the teaching of the present invention and located or positioned in the boat propulsion position;

FIG. 2 is a fragmentary view similar to FIG. 1 showing the apparatus of FIG. 1 in the transport position;

FIG. 3 is a top elevational view of the trolling motor apparatus;

FIG. 4 is a vertical section through the pivot arm shown in FIGS. 1-3;

FIG. 5 is a vertical section taken generally on line 5-5 of FIG. 4;

FIG. 6 is a fragmentary sectional view taken generally on line 6-6 of FIG. 5;

FIG. 7 is a vertical section taken generally on line 7-7 of FIG. 4; and

FIG. 8 is a vertical section taken generally on line 8-8 of FIG. 4.

DESCRIPTION OF ILLUSTRATED EMBODIMENT

Referring to the drawings and particularly to FIGS. 1 and 2, the present invention is directed to the construction of a trolling motor unit 1 which is attached to watercraft or boat 2 and particularly to a forward horizontal deck 2a. The trolling motor unit 1 is secured to the deck 2a by a suitable pivotable mount assembly 3 for selective positioning of the trolling motor unit 1 between the depending propulsion position shown in FIG. 1 and a raised transport position shown in FIG. 2 wherein the trolling motor rests on the deck and generally within the confines or the outermost edge of the watercraft 2. Thus, the trolling motor unit 1 is uniquely adapted for application to bass fishing and the like where an accurate maneuverability at very low speeds is desired. In such systems however, the watercraft 2 will generally be provided with a completely alternative high speed drive such as an outboard motor, not shown, for propelling of the watercraft to the fishing location.

The trolling motor unit may be of any suitable construction and it is only generally described herein. The present invention is particularly directed to the pivotal mount assembly 3 and the interconnection to the trolling motor 1 for positioning between the positions of FIGS. 1 and 2.

Generally, the trolling motor unit 1 includes a lower unit 4 secured to the lower end of a tubular support 5 in the form of a smooth pipe member. The pipe member 5, in turn, is rotatably mounted within a swivel tube 6 the upper end of which terminates in a head 7 having a handle 7a projecting therefrom. The lower unit 4 houses a suitable electric motor 8 which is coupled to rotate a propeller 9 secured to the aft end of the lower unit 4 in accordance with conventional practice. The electric motor 8 energization level is controlled to vary the speed of the propeller 9. Thus, suitable power leads 10 are shown extended from the motor 8 and a control circuit, not shown, which may also be located within the unit 4 through the pipe member 5, head 7, and handle 7a for interconnection to a suitable power supply such as a battery 11 in series with a suitable variable current control unit 12. Generally, the control unit 12 will be a foot operated device to allow the fisherman to control the speed of the propulsion without interfering with casting and the like.

In addition and in accordance with conventional practice, trolling motor unit 1 is rotated within the swivel unit 6 for turning and steering movement of the boat 2. In the illustrated embodiment of the invention, a suitable rack and pinion unit 13 is housed within the upper head 7 and coupled to the uppermost end of the conduit 5. The rack and pinion unit 13 is connected by a push-pull cable 14 to a suitable foot control 15 provided within the boat.

The trolling motor unit 1 including the lower unit 4 and interconnecting steering and speed controls may of course be of any suitable construction and consequently no further description thereof is given other than in connection with and for purposes of fully explaining the illustrated pivotal mount assembly 3 forming a preferred novel embodiment of the present invention.

Thus referring particularly to FIGS. 1 through 4, the pivotal mount assembly 3 generally includes a pivot support member or arm 16 which is pivotally interconnected at one end to a mounting bracket 17 by a pivot assembly 18. The opposite or outer end of the arm 16 includes a head 19 attached to the swivel tube 6 and pivotally interconnected by a pivot assembly or means 20 at the outer end of the arm 16. The arm 16 as more fully developed hereinafter defines a tubular housing within which a gear train positioning means 21 is housed and includes a positioning gear means 22 for selectively positioning of the head 19 and the interconnected trolling motor unit 1 and in response to the pivoting of the arm 16 through 180° and particularly between the propulsion position of FIG. 1 and the transport position of FIG. 2. Thus, the gear means 22 is activated automatically by the pivoting of the arm through a drive gear means 23 housed in the fixed pivotally mounted end of the arm 16 with a preferred and novel construction of such a system shown in FIGS. 4-8. In the transport position the arm 16 extends forwardly over and from the bracket 17 with the intermediate portion thereof resting within a U-shaped saddle support 24 integrally formed to the upper side of the mounting bracket 17. In the raised transport position of FIG. 2, the head end of the trolling motor unit is supported resting on the deck and the lower unit 4 rests on the upper wall of the bracket 24. Further, in the depending position of FIGS. 1 and 4, the pivot mount assembly 3 is locked to the deck and the trolling motor unit 1 is locked in such depending position. In the illustrated embodiment of the invention, an arm locking means 25 releasably locks the arm to the bracket 17 to prevent pivoting of the arm from the extended dependent support position. In addition, a gear locking means 26 is provided at gear means 22 to positively interlock and prevent rotation and loading of the gear means 21 with the trolling motor in the propulsion position. A common release means 27 is provided at the pivotally mounted inner end of the arm 16 and interconnected to simultaneously release the locking means 25 and 26 as more fully developed hereinafter.

In the transport position of FIG. 2, the arm 16 mechanism is not interlocked. A tie-down strap 28 is provided to secure the unit 1 to the bracket 17. The strap 28 may be of a resilient rubber-like strap with one end fixed to one side of the saddle 24 and adapted to loop over the trolling motor pipe 5. The opposite end is releasably interconnected to the opposite side of saddle 24 to hold the trolling motor in transport position. As shown in FIG. 1 the releasable end has a latch loop 29 adapted to fit over an enlargement on the side wall of the saddle 24.

Thus, the arm 16 is adapted to be pivoted between the position of FIGS. 1 and 2 with the gear means 21-23 selectively and automatically pivoting head 19 and attached trolling motor unit 1 relative to the arm 16 to positively establish the depending propulsion position and the horizontal transport position where it

is located immediately adjacent the deck 2a and generally within the boat 2.

More particularly, in the illustrated embodiment of the invention arm 16 is shown as a two-piece housing member having similar housing members 30 and 30a which are interconnected by suitable bolt means to essentially enclose the gear positioning means 21. The support head 19 is shown as a solid cast member projecting inwardly between a bifurcated end of the arm 16. The head 19 includes a tubular opening 31 through which the swivel tube 6 extends. The head 19 further includes a threaded tubular extension 32 projecting upwardly from the opening with the swivel tube 16 passing therethrough. A locking nut 33 encircles the swivel tube 6 and is releasably threaded onto the tube 32 causing the outer end, which has end slits, to collapse into clamping engagement about the swivel tube 6 and thereby selectively locking the swivel tube 6 within the head 19. This provides for selective dependent positioning of the pipe 5 and thus of the lower unit 4 with respect to the watercraft 2 for adjusting the depth of the lower unit 4 within the body of water, not shown.

The head 19 includes an inwardly projecting portion located between the side arms 34 of the bifurcated end of the arm 16. The arms 34 are formed by integral extension of the side and top wall of the housing section 30 and 30a. The upper walls are partially removed with an integral hub 35 of the head 19 projecting between the arms 34 and pivotally mounted therebetween by the pivot means 20. Thus, hub 35 is rotatably journaled on a bolt shaft 35 which extends through the arms 34 and threads into a threaded opening in the one arm to firmly and rotatably mount the head between arms 34.

The head 19 further includes an integrally cast gear sector 37 which may be integrally cast with or otherwise connected to one side of the hub 35 and with the outer face thereof bearing on an adjacent portion of the one side arm 34. The gear sector 37 is shown semicircular a bevel gear member with a mounting flange 38 encircling a reduced portion of the hub and secured by bolts 38a to the hub portion 35. The inner faces of the side arms are shaped to define inwardly projected cone-shaped portion 39 defining bearing surfaces against which the hub member abuts.

The bevel gear means 37 forms a part of gear means 22 and meshes with a bevel gear 40 which has a hub portion 41 rotatably mounted in a wall 42 of the arm 16 and in particular the housing sections 30 and 30a. The opening in the two-piece wall 42 is shown provided with a suitable radial and thrust bearing member for rotatably supporting of the bevel gear 40 in driving meshing engagement with the gear sector 37.

The bevel gear 40 is slidably interlocked with a torque tube 43 of gear train 21. Tube 43 extends rearwardly through the arm 16 and is interconnected at the opposite end to the gear means 23.

In the illustrated embodiment of the invention, the gear-tube interlock includes a locking pin 44 of locking means 26 which is secured within the corresponding end of the torque tube 43 and projects outwardly towards the hub 35. In the depending propulsion position, pin 44 is aligned with and moves into engagement with a locking opening or recess 45 in the periphery of hub 35 to the full line position shown in FIG. 4. A pin member 46 extends through the interlock pin 44 and the outer end of the torque tube 43 and extends outwardly therefrom into coupling slots 47 within the bevel gear 40 to

the opposite side of the torque tube 43. Thus the pin 46 drivingly interconnects the torque tube 43 to the bevel gear 40 such that rotation of the torque tube 43 is directly transmitted to the bevel gear 43 and therefrom to the gear sector 37 of head 19. The torque tube 43, as more fully developed hereinafter, is slidably mounted within the housing 16 and must be withdrawn to disengage the pin 44 from the hub locking recess 45 to permit the rotation of the trolling motor unit 1 as the arm 16 pivots. The interlocking pin and slot type connection provides a simple connecting means to permit engagement and disengagement of the locking means 26 while maintaining the driving engagement between the bevel gear 37 and 40.

The torque tube 43 is driven by the gear means 23 which includes a bevel gear 48 having a hub portion 49 rotatably mounted in a rear wall 50 of the arm 16 similar to the mounting of the bevel gear 40. The torque tube 43 is coupled to the bevel gear 48 by a diametrically extended coupling pin 51 mating with coupling slots 52 in the bevel gear 48 in the same manner as the coupling of the bevel gear 41. This permits the sliding movement of the torque tube 43 as previously described.

The bevel gear 48 meshes with a bevel gear 53 fixed to and pivoting with arm 16 as follows.

The bevel gear 53 includes a hub 54 journaled on a shaft 55 forming part of pivot support 18. The shaft 55 extends through the housing sections 30 and 30a and outwardly thereof into a pair of lateral arms 56 and 57 which project upwardly integrally from and as a part of bracket 17. The arms 56 and 57 include threaded openings 58 coaxial of the location of shaft 55 to receive similar clamping bolts 59 which have relatively large heads for manual operation. The inner end of the bolt members 59 include smooth pivot pins 60 extending inwardly into corresponding recesses in the ends of the shaft 55, such that the shaft 55 is free to pivot on the pins.

The hub 54 gear 53 projects outwardly with the shaft 55 into recess 61 in the bracket arm 56. At the opposite side the shaft 55 extends outwardly directly into a smaller recess 61a. The sides of the hub 54 are formed as flat surfaces 62 to provide interlocking with the flat sidewalls of the recess 61, as most clearly shown in FIG. 6. The bevel gear 53 is thus locked against rotation with the arm 56 and bevel gear 53 is locked against rotation. The shaft 55 however, is pivotally mounted within the hub 54 and within the slot 61a in the opposite arm 57 and thus is free to rotate.

In the illustrated embodiment of the invention, the shaft 55 includes an intermediate box section 63 immediately adjacent the inner face of the bevel gear 53 and defining an opening into which the torque tube 43 projects from the bevel gear 48, as shown in FIG. 4. The release mechanism 27 extends through the box section 64 and is interconnected to the adjacent end of the torque tube 43 for selective positioning thereof.

Thus with the bevel gear 53 locked against rotation, pivoting of the arm 16 results in the bevel gear 48 rolling across the fixed gear 53 and imparting rotation to gear 48 and correspondingly to torque tube 43. This rotation is transmitted through the opposite bevel gear 40 to the sector gear 37 with a corresponding positive rotation of the gear sector 37. The integrated head 19 is thereby also pivotal positioned along with the interconnected swivel tube 6 and therefore the interconnected trolling motor unit 1.

As previously noted, the transmission of the forces is positively prevented by the gear interlock means 26 with the unit in depending position, and must be released before pivoting of the arm to the release position. The release means 27 is coupled to the torque tube 43 to permit retraction and release of the means 26 and simultaneously of the arm interlock means 25, as follows.

The release means 27 includes a rod 65 extending into the torque tube with an inner head 66. The end of the tube is closed by a generally cup-shaped member 67 with the rod 65 extended through the base. A small coil spring 68 within the cup-shaped member 67 acts between the base thereof and the head 66 to continuously urge the rod 65 inwardly into the torque tube 43. The outer end of the rod 65 projects through arm 16 and outwardly through the end or back wall 69 of the housing arm 61 with a latch release handle 70 connected thereto as by a pin 71.

A relatively heavy coil spring 72 encircles the rod 65 between the interior of end wall and the adjacent end of the torque tube 43 and cup 67 and continuously urges the torque tube 43 forwardly to establish the locked position of gear lock means 26. The latch release handle 70 is located within a pocket formed within the housing arm 16 by an inset portion of the back wall 69. The handle 70 is generally a plate-like member with a relatively thick solid portion which is recessed and pinned to the rod 65 to define a pivot axis generally parallel to the pivot axis of the pivot means 18. The opposite end of the handle 70 thus is spaced from the inset wall 69 for convenient finger grasping and pivoting of the handle 70 on the pinned attachment 71. The opposite solid portion of the handle 70 defines a cam wall 73. Thus, when handle 70 is pivoted, the cam wall 73 moves into engagement with the recessed end wall 69, providing a camming action, drawing the rod 65 outwardly and thereby moving the head 66 into engagement with the cup-member and exerting a retraction force on the torque tube 43. With the handle 70 pivoted to the release position the locking or return force exerted by the spring 72 on rod 65 holds the cam end or wall 73 into bearing engagement with the end wall 69 of the recess and locks the release means 27 in the release position. The movement of the handle 70 from the locked position to the release position, establishes sufficient movement of the torque tube 43 to completely withdraw the pin 44 from the recess 45 and thereby release the gear lock means 26.

The release movement of the torque tube 43 to the release position simultaneously releases the arm lock means 25.

In the illustrated embodiment of the invention, the arm lock means 25 includes a hook- and eye-type interlock means including a loop element 75 secured to the torque tube 43 with a downwardly extended portion defining a locking opening or eye member with the arm 16. The bottom wall of arm 16 has an opening 74 aligned with the loop element 75 to receive a hook end 76 of a latch lever 77 which is pivotally mounted to the base portion of the bracket 17. In the locking position, the loop element 75 engages the hook end 76 of latch lever 77. The lever 77 is generally an L-shaped member having the hook end 76 on one arm and a spring loaded arm 79 extending beneath an upper wall of the bracket 17. A coil spring 80 urges the latch lever 77 to the latch position, as shown in FIG. 4.

When the torque tube 43 is retracted the loop element 75 is moved from the hook end 76, thereby releasing the arm 16 for pivotal rotation about the pivot means 20, as previously described.

The actual pivoting of the arm 16 with the release mechanism 27 latched in the release position causes the extended handle 70 to move into engagement with the bottom wall of the bracket 17. This positively pivots the handle 70, in a clockwise direction as viewed in FIG. 4, to return the handle to the release position. The bottom bracket includes a concave or curved portion 80a aligned with the support arm 56 and 57 which complements the outer surface of the end of arm 16 with handle 70 pivoted to the lock position.

By the time arm 16 has pivoted sufficiently for the handle 70 to engage the bracket 17, the hub 35 of the head 19 has been rotated by the gear train 21 to align its outer periphery with the retracted end of the pin 44. Consequently, when the handle 70 is released, the hub 35 holds the torque tube 43 in the retracted position. The inner small spring 68, however, will function to pull the rod 65 into the torque 43 and permit and in fact assist the return of the handle 70 to the reset position.

Thus, with motor unit 1 in the depending propulsion position, the gear system or train 21 is locked against possible movement and the arm 16 is positively held against pivotal rotation. It is significant with the gear drive system, that such drive system is released with the arm release means 25. This positively avoids the establishing of excessive forces on the gear teeth which might occur if the arm lock means 25 were released without a released gear system.

When the arm 16 is again pivoted to the propulsion position the recess 45 will again automatically align with the end of pin 44 allowing the torque tube under the action of spring 73 to extend or move laterally to engage the gear lock means 26 and simultaneously the arm lock means 25.

Further, bracket 17 has a stop edge 81 portion limiting the pivoting of the latch lever 77 upon retraction of the loop 75 within the access opening 74 and further holding the hook member 76 in alignment with the lower end of the loop 75 of the dropping arm 16. Further, the outer end of the hook 76 is provided with an upper inclined cam edge 81. When arm 16 moves downwardly, the hook end 75 will move through the opening 74 in the lower wall of the arm 16 and into engagement with the inclined cam wall 81 on the end of the hook 76. The arm will have sufficient force to pivot the lever 77 about its axis, compressing the spring 80, and moving the latch hook 76 to the right and allowing loop 75 to move down the end of the hook 76. The spring then of course returns, the lever to the latch position, as shown in FIG. 4.

In addition in the transport position, the motor is preferably laid to one side with the elongated head 7 extending laterally across the boat and with the lower unit 4 similarly oriented upon the upper wall of the U-shaped saddle 24. The handle on the upper head 7 permits rotation of the swivel 6 within the head 19 to the desired transport position. Although, the friction clamp which supports the trolling motor unit 1 in the desired vertical position bars allow forced rotation of the head to a transport position when required. Further, where a flexible handle is employed such as disclosed in the copending application of O. C. Russell entitled OPERATING HANDLE FOR PIVOTALLY

MOUNTED TROLLING MOTOR Ser. No. 610,308, filed Sept. 4, 1975 even if the motor is not rotated the handle can readily flex to accommodate the positioning in a vertical position.

The support pipe 5 is relatively freely pivotally mounted within the swivel tube 6. With the foot control released, the lower unit 4 can therefore readily turn with the pipe 5 within the swivel tube 6. In the illustrated embodiment of the invention the saddle 24 is generally a U-shaped member having upstanding side-walls 82 which in the transport position are located to the opposite sides of the arm 16. The sidewalls 82 include a forward curved end 83 along which the lower unit is guided to and from the depending position.

The present invention thus provides a rugged, reliable position operating mechanism for outboard trolling motors with protective means to provide a long operating life and to minimize hazards to the user. Further, the mechanism is protected against accidental damage.

Thus, the hold down or locking mechanism must positively be released to lift the mechanism to the transport position and is automatically reset in response to the pivoting of the trolling motor unit 1 to its propulsion position. Further, the gear system provides a very positive positioning of the trolling motor unit between the desired positions while maintaining essentially a total enclosure of the locking and positioning mechanism. The arm 16 protects the gear train and locking mechanism from adverse environmental conditions in which the trolling motor may be employed and significantly reduces creation of any hazardous condition to the user as a result of exposed linkages and the like.

The present invention thus provides an improved practical trolling motor pivot mount assembly which can be conveniently manufactured and used. Various modes of carrying out the invention are contemplated as being within the scope of the following claims, particularly pointing out and distinctly claiming the subject matter which is regarded as the invention.

I claim:

1. In an electric trolling motor apparatus for propulsion of a watercraft, a mounting bracket means adapted to be secured to the watercraft and having a pivotally mounted arm means, means mounting an electric motor unit to the arm means, a gear train means mounted on said arm means and establishing rotation of the arm means and said electric motor unit in response to the pivoting of the arm means between a lowered propulsion position and a raised transport position, a first releasable locking means secured between the arm means and the bracket means and holding the arm means in place relative to the bracket means, second releasable locking means secured between the bracket means and the gear train means and preventing movement of the gear train means independently of said first releasable locking means, and a common operator coupled to said first and second releasable locking means and operable to simultaneously release said first and second locking means.

2. The electric trolling motor apparatus of claim 1 wherein said arm means is a hollow housing member defining an essentially complete protective enclosure of said first and second locking means and said gear means.

3. The apparatus of claim 1 wherein said gear train means includes a driven gear means coupled to rotate the motor, a gear shaft slidably mounted relative to the gear means by an axial slot and pin connection, said driven gear means having a hub with a periphery aligned with the end of the shaft, said second releasable locking means including a slot and pin gear lock means between the end of the shaft and the aligned hub, a resilient means within the pivoted end of the arm and connected to continuously urge the shaft outwardly to engage said gear lock means, and said common operator being resiliently coupled to said shaft to move the shaft to disengage the end of the shaft from said hub.

4. The apparatus of claim 3 wherein said first locking means includes a pair of releasable engageable latch elements, one of said elements being secured to the shaft and the second to said bracket, said elements being released by retraction of the shaft, said elements being engaged by pivoting of the arm means to the lowered propulsion position.

5. The apparatus of claim 4 wherein said release means includes a handle member mounted to the exterior of the pivoted end of the arm and having a rod projecting inwardly, resilient means coupling the inner end of the rod to the shaft for retraction of the shaft.

6. In an electric trolling motor apparatus for propulsion of a watercraft, a mounting bracket means adapted to be secured to the watercraft and having a pivotally mounted arm means, means mounting an electric motor unit to the arm means, a gear train means mounted on said arm means and establishing rotation of the arm means and said electric motor unit in response to the pivoting of the arm means between a lowered propulsion position and a raised transport position, a first releasable locking means secured between the arm means and the bracket means and holding the arm means in place relative to the bracket means, second releasable locking means secured between the bracket means and the gear train means and preventing movement of the gear train means independently of said first releasable locking means, and release means for releasing of said first and second lockable means and constructed to prevent release of the first locking means prior to release of said second locking means.

7. The apparatus of claim 6 wherein said gear train means includes a driven gear means coupled to rotate the motor, a gear shaft coupled to and slidably mounted relative to the driven gear means for transmission of the drive movement, said second releasable locking means including interlocking members on the shaft and the aligned gear means operable to prevent transmission of said movement, a resilient means within the arm connected to continuously urge the interlocking members into locking engagement, and said release means being coupled to said shaft to move the shaft to disengage the interlocking members.

* * * * *