



US008116097B2

(12) **United States Patent**
Love et al.

(10) **Patent No.:** US 8,116,097 B2
(45) **Date of Patent:** Feb. 14, 2012

(54) **APPARATUS FOR ELECTRICALLY COUPLING A SEMICONDUCTOR PACKAGE TO A PRINTED CIRCUIT BOARD**

(75) Inventors: **David G. Love**, Pleasanton, CA (US);
Bidyut K. Sen, Milpitas, CA (US)

(73) Assignee: **Oracle America, Inc.**, Redwood City, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 929 days.

(21) Appl. No.: **11/934,340**

(22) Filed: **Nov. 2, 2007**

(65) **Prior Publication Data**

US 2009/0113698 A1 May 7, 2009

(51) **Int. Cl.**
H05K 1/11 (2006.01)

(52) **U.S. Cl.** **361/803; 361/760; 361/736; 361/794**

(58) **Field of Classification Search** 174/260;
439/70; 361/803

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,082,394 A * 4/1978 Gedney et al. 439/69
5,493,237 A * 2/1996 Volz et al. 324/756.05
5,574,630 A * 11/1996 Kresge et al. 361/792

5,712,768 A * 1/1998 Werther 361/767
6,046,911 A * 4/2000 Dranchak et al. 361/784
6,135,786 A * 10/2000 Johnson et al. 439/76.1
6,366,467 B1 * 4/2002 Patel et al. 361/760
6,471,525 B1 * 10/2002 Fan et al. 439/70
7,259,457 B2 8/2007 Zhang
7,268,067 B2 9/2007 Hall
7,276,920 B2 10/2007 Jones
2003/0230428 A1 * 12/2003 Liew et al. 174/261
2005/0207131 A1 * 9/2005 Prokofiev et al. 361/760
2006/0091538 A1 * 5/2006 Kabadi 257/737
2007/0279880 A1 * 12/2007 Weir et al. 361/794
2008/0239683 A1 * 10/2008 Brodsky et al. 361/760

* cited by examiner

Primary Examiner — Tuan T Dinh


Assistant Examiner — Steven Sawyer

(74) *Attorney, Agent, or Firm* — Meyertons, Hood, Kivlin, Kowert & Goetzel, P.C.; Erik A. Heter

(57) **ABSTRACT**

An apparatus for coupling an integrated circuit (IC) package to a printed circuit board. The apparatus includes an interposer having a plurality of connections suitable for surface mounting on corresponding pads of a printed circuit board (PCB). The plurality of connections is arranged in a grid array. The interposer further includes a plurality of plated through holes. The apparatus further includes a substrate having a plurality of pins. The substrate is coupled to the interposer by inserting each of the plurality of pins into a corresponding one of the plurality of plated through holes of the interposer. An IC package including an IC is mounted on the substrate.

18 Claims, 3 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3

1

APPARATUS FOR ELECTRICALLY COUPLING A SEMICONDUCTOR PACKAGE TO A PRINTED CIRCUIT BOARD

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to electronic systems, and more particularly, to the packaging and connecting of integrated circuits in electronic systems.

2. Description of the Related Art

Pin counts for integrated circuits are rising for many types of devices, particularly those that are more complex (e.g., processors). The larger pin counts in turn require larger body sizes for such devices which in turn necessitates larger body sizes for integrated circuit packaging. However, the larger sizes for integrated circuit packaging results in various problems when mounted to a printed circuit board (PCB).

One significant problem for integrated circuit packages mounted on a PCB is expansion of the integrated circuit package relative to expansion of the PCB. During operation of the electronic system that includes the PCB and integrated circuit within a package, heat is generated. The generated heat causes expansion of both the integrated circuit and the PCB. If the PCB and integrated circuit package expand at different rates, strain is placed on the connections (e.g., solder joints) coupling the two. If the strain is severe enough, it may cause cracked or broken connections, which can lead to operational failures.

Other problems arise relating to signal integrity and power distribution. An increased number of signals to be conveyed between the PCB and the integrated circuit results in an increase of electromagnetic noise. This may result in crosstalk between various signal pins, which can adversely affect signal integrity. Power distribution to the integrated circuit must have low inductance and capability to transmit increasing amounts of power. Inefficient power supply will lead to transients (e.g., "ground bounce", "simultaneous switching noise") on the power bus. Such transients can cause erroneous operation of circuits within the integrated circuit.

One additional problem that this invention addresses is ability to easily and reliably replace an integrated circuit "chip" in order to upgrade or repair the system within which the chip and PCB reside.

SUMMARY OF THE INVENTION

An apparatus for coupling an integrated circuit (IC) package to a printed circuit board is disclosed. In one embodiment, the apparatus includes an interposer having a plurality of connections suitable for surface mounting on corresponding pads of a printed circuit board (PCB). The plurality of connections is arranged in a grid array. The interposer further includes a plurality of plated through holes. The apparatus further includes a substrate having a plurality of pins. The substrate is coupled to the interposer by inserting each of the plurality of pins into a corresponding one of the plurality of plated through holes of the interposer. An IC package including an IC is mounted on the pin grid array substrate.

In one embodiment, an electronic assembly includes a PCB having a grid array including a plurality of mounting pads. The plurality of mounting pads are suitable for surface mounting a component corresponding to the grid array, which may be a ball grid array (BGA) or a land grid array (LGA). An interposer having a plurality of connections is mounted upon the PCB. The connections may be solder balls (for a BGA) or elastomeric or metallic connectors (for an LGA), and are each

2

mounted on a corresponding one of the mounting pads. The interposer also includes a plurality of plated through holes. A substrate is coupled to the interposer. The substrate includes a plurality of pins. Each of the pins is inserted into a corresponding one of the plated through holes to couple the substrate to the interposer. An IC package, including an IC, is mounted to the substrate. The IC is electrically coupled to the PCB through the substrate and the interposer.

In various embodiments, an axis of each of the plurality of pins coincides with an axis of a corresponding one of the connections. That is, the connections from the interposer to the PCB (e.g., solder balls) are co-axial with the pins of the substrate. In one embodiment, the pins have a least an 8:1 aspect ratio (i.e. length-width). The interposer and the PCB have approximately equal coefficients of thermal expansion (CTE).

BRIEF DESCRIPTION OF THE DRAWINGS

Other aspects of the invention will become apparent upon reading the following detailed description and upon reference to the accompanying drawings in which:

FIG. 1 is a side view of one embodiment of an electronic assembly according to the disclosure;

FIG. 2 is a top view of one embodiment of an interposer according to the disclosure; and

FIG. 3 is a top view of one embodiment of a printed circuit board suitable for mounting the apparatus shown in FIGS. 1 and 2.

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that the drawings and description thereto are not intended to limit the invention to the particular form disclosed, but, on the contrary, the invention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the present invention as defined by the appended claims.

DETAILED DESCRIPTION OF THE INVENTION

Turning now to FIG. 1, a side view of one embodiment of an electronic assembly according to the disclosure is shown. In the embodiment shown, electronic assembly **100** includes an integrated circuit (IC) package **102** that is flip-chip mounted to a substrate **104**. Interposer **106** is mounted to printed circuit board (PCB) **108**, while substrate **104** is mounted to interposer **106**. Thus, an IC within IC package **102** is electrically coupled to PCB **108** through substrate **104** and interposer **106**. Each of substrate **104**, interposer **106**, and PCB **108** may include a plurality of signal traces and power/ground planes on and within. While the signal traces and power/ground planes are not shown here for the sake of simplicity, their presence is nonetheless noted.

IC package **102** may be a chip or a chip-scale package housing one of many different types of IC's, or may be a multi-chip package as well. There may also be a plurality of these IC **102** packages so that substrate **104** may carry multiple chips in separate packages. In the embodiment shown, IC package **102** is a flip chip device, although other types of suitable IC packages are possible and contemplated. The specific type of IC packaging may depend both on the type of IC to be packaged within, the various operating parameters of the IC, and the type of package for which substrate **104** is configured to receive. In the embodiment utilizing a flip-chip, IC package **102** includes a plurality of solder bumps **103**

extending from the bottom side. These solder bumps are soldered to corresponding pads located on the top side of substrate **104**.

The IC (or IC's, in the case of multi-chip packages) may be of various types, including analog, digital, or mixed signal. Discrete devices such as capacitors, resistors, inductors may also be present on substrate **104** and/or within device **102**. In one embodiment, IC package **102** includes a processor within (e.g., a central processing unit of a computer system). In another embodiment, IC package **102** may include an application specific integrated circuit (ASIC). In general, the IC(s) within IC package **102** may be any type suitable for coupling to a PCB as shown in FIG. 1.

Substrate **104** in the embodiment shown is a multilayer substrate, and may include various layers for the routing of signal traces and power/ground planes that are electrically coupled to the connections of IC package **102**. On the bottom side of substrate **104** is a plurality of pins **115** that are configured for mounting within corresponding plated through holes on interposer **106**. The plurality of pins is arranged in a grid, and thus forms a pin grid array (PGA). In the embodiment shown, pins **115** have at least an 8:1 aspect ratio (i.e. height-width ratio). This allows the pin, made of a metal or alloy, to bend undergoing without plastic deformation during thermal and power cycling temperature excursions and the subsequent mismatch of thermal expansion rates. This also results in a separation between substrate **104** and interposer **106**. However, embodiments of substrate **104** having pins with different aspect ratios are also possible and contemplated.

Interposer **106** includes, on its top side, a plurality of plated through holes **116**. Substrate **104** is mounted to interposer **106** by positioning it such that each of the pins **115** is inserted into a corresponding one of the plated through holes **116**. In some embodiments, pins **115** may be soldered into plated through holes **116**. Other attachment methods are also possible, e.g. conductive adhesives.

The construction of interposer **106** can be determined by those skilled in the art of PCB fabrication. Ideally the plated through hole on the top surface is exactly aligned in the same vertical axis as its corresponding pad at the bottom of the interposer, as shown in FIG. 1. This allows tight pitch of the pins through avoidance of "dogbone" offsets. Examples of ways interposer **106** can be constructed would include back-drilling of the plated through hole, or tenting of a completely drilled through hole.

The bottom side of interposer **106** includes a plurality of connections **117** suitable for surface mounting to PCB **108**. The connections **117** are arranged in a grid array pattern. In one embodiment, connections **117** are solder balls, and thus form a ball grid array (BGA). In another embodiment, connections **117** are elastomeric connectors, and thus form a land grid array (LGA). In yet another possible embodiment, a socket mounted to the PCB could also accept this connection to the bottom or interposer **106**.

Interposer **106** is mounted upon PCB **108** by coupling connections **117** to corresponding surface mounting pads (e.g., by soldering the solder balls to corresponding surface mount pads). A top view of PCB **108** is shown in FIG. 3. In the embodiment shown, PCB **108** includes component footprints **118**, **128**, and **138**. Component footprints **128** and **138** may be suitable for mounting other types of IC packages, such as packages of the gull wing type. Although circuit traces are not explicitly shown here for the sake of simplicity, it is noted that IC's mounted to component footprints **128** and **138** may be electrically connected to an IC coupled to PCB **108** through an interposer mounted on component footprint **108**. It should

also be noted that PCB **108** shown here is an exemplary embodiment, and is thus one of a wide variety of PCB's that may be useful in the electronic assembly discussed herein. Similarly, the pattern of connections is also simply one example of many possibilities.

Component footprint **118** is a grid array of surface mount pads, and corresponds to the grid array of connections **117** of interposer **106**. Each of the pads of component footprint is arranged in order to couple a BGA or LGA of a corresponding component (e.g., interposer **106**) by soldering or coupling of elastomeric connectors. As previously noted, circuit traces and power/ground planes are not shown here for the sake of simplicity, although it is understood that circuit traces will be electrically and physically coupled to various ones of the pads of component footprint **118**. Pads of component footprint **118** may be power connections, ground connections, or signal connections. In some cases, various ones of the pads may have no electrical connection, but nonetheless provide a connection for coupling to interposer **106**, and may provide structural integrity for electronic assembly **100**.

Returning to FIG. 1, it is noted that each of the connections **117** is co-axial with its corresponding plated through hole **116** of interposer **106** (and thus is also co-axial with a corresponding pin **115** of substrate **104**). That is, the axis of both the connection **117** and its corresponding plated through hole **116** is the same. This arrangement may greatly simplify the design of interposer **106**, as it may minimize or altogether eliminate the need for routing signal traces horizontally. In various other embodiments, each of the connections **117** is ideally but not necessarily co-axial with its corresponding plated through hole.

In order to minimize strain on the connections **117** coupling interposer **106** to PCB **108**, their respective coefficients of thermal expansion (CTE) are matched as closely as possible. Thus, by making their respective coefficients of thermal expansion approximately equal, both PCB **108** and interposer **106** may expand under thermal stress by the same approximate amounts. This in turn may result in a reduction of the mechanical stresses that may be placed on the connections **117** that might otherwise result if interposer **106** and PCB **108** have a significant difference between them. In various embodiments, interposer **106** may be constructed of the same or similar material as PCB **108**. Interposer **106** may also be comprised of two or more layers.

Power and ground contacts may be provided between interposer **106** and substrate **104** through a plurality of bus bars **119**. In one embodiment, bus bars **119** are integral to the structure of interposer **106**, extending upward where they may be coupled to corresponding contacts on substrate **104**. However, other embodiments are possible and contemplated wherein the bus bars **119** are integral to the structure of substrate **104**, and attach to corresponding contacts on interposer **106**. Power is delivered from PCB **108** to IC package **102** through various ones of the connections **117**, one or more bus bars **119**, through substrate **104** and solder bumps **103**. Similarly, ground connections from PCB **108** are also provided to IC package **102** through corresponding ones of the connections **117**, a corresponding one or more bus bars **119**, through substrate **104** and solder bumps **103**.

Turning now to FIG. 2, a top view of one embodiment of an interposer according to the disclosure is shown. In the embodiment shown, interposer **106** includes a plurality of plated through holes **116**, which are arranged in a grid array. Plated through holes **116** are each configured to receive a corresponding pin of a pin grid array (PGA) associated with a substrate such as substrate **104** discussed above. In some embodiments, substrate **104** may be secured in place after

5

insertion of the pins into the corresponding plated through holes **116** by soldering. In such embodiments, the solder used may have a higher melting point than the solder of BGA solder balls that are located on the bottom side of interposer **106**. This may in turn enable interposer **106** to be de-soldered from a PCB in the event of the need for rework without having to remove substrate **104**. Other embodiments are possible and contemplated wherein pins of substrate **104** are secured into place within corresponding plated through holes **116** without soldering.

Interposer **106** includes a plurality of bus bars **119**. In the embodiment shown, bus bars **119-P** provide a path to convey power from interposer **106** to substrate **104**. Bus bars **119-G** provide a ground path between interposer **106** and substrate **104**. Bus bars **119** may be composed of an electrically conductive material such as copper or other material suitable for providing power and ground paths. In this embodiment, bus bars **119** are centrally located. Bus bars **119** may be attached to interposer **106** (as well as the corresponding substrate **104**) by soldering, brazing, or other suitable method. In various embodiments, bus bars **119-P** are used for providing core power to the IC(s) in the IC package mounted on substrate **104**. The pins of the PGA may be used to convey I/O signals (e.g., data signals, address signals, control signals, analog signals, and so forth) between interposer **106** and substrate **104**. Some pins of the PGA may also be used to convey I/O power (which may be separated from core power) to substrate **104** and subsequently to the IC(s) of IC package **102**. Similarly, some pins of the PGA may also be used to provide a ground path for I/O power from substrate **104** (and thus, from the IC(s) of IC package **102**).

A pair of chip capacitors **121** are also located near the bus bars **119**, which may provide decoupling and a low inductance path to provide clean power to the IC within IC package **102**. Additional chip capacitors **121** may be placed in other portions of the grid array, as shown in the drawing. The use of chip capacitors **121** on interposer **106** may result in a cleaner, less noisy power being supplied to the IC(s) within the IC package mounted on the substrate by providing a low inductance path between power and ground.

Although not specifically shown here, it is be noted that embodiments are also possible and contemplated wherein additional capacitors are placed on substrate **104**. Such capacitors may be placed on either side of substrate **104**. Some capacitors may even be placed within the area defined by the PGA by removing pins (similar to that shown in FIG. 2, where some plated through holes are replaced by a chip capacitor in the upper left hand portion). These additional capacitors within the PGA may be particularly useful for decoupling I/O power.

The use of a surface mounted interposer and a substrate with a pin grid array as disclosed herein may allow for higher pin count devices to be electrically coupled to a PCB. Attachment of high pin count devices directly to a PCB may be impractical and/or unreliable. In the case of direct attachment of surface mount devices, mismatches in coefficients of thermal expansion can result in different rates of expansion between the device and the PCB under thermal stress, while the type of solder (in a BGA) or elastomeric material (in an LGA) may be too weak to prevent metal fatigue, cracks, or breakages due to the mechanical stress that is induced by the thermal stress. Direct attachment of a PGA device to a PCB may be impractical due to the fanout and signal routing requirements. However, using the dual-level interconnect scheme as disclosed herein may result in the ability to electrically couple high pin count devices without the attendant

6

problems discussed above. Table 1 is an exemplary table with some possible pin counts based on body size and pitch:

TABLE 1

Body Size mm	1.27 mm pitch	1.12 mm pitch	1.00 mm pitch
50 mm	1489	1914	2401
60 mm	2158	2775	3481

While the present invention has been described with reference to particular embodiments, it will be understood that the embodiments are illustrative and that the invention scope is not so limited. Any variations, modifications, additions, and improvements to the embodiments described are possible. These variations, modifications, additions, and improvements may fall within the scope of the inventions as detailed within the following claims.

What is claimed is:

1. An apparatus for coupling an integrated circuit (IC) package to a printed circuit board, the apparatus comprising: an interposer having a plurality of connections suitable for surface mounting on corresponding pads of a printed circuit board (PCB), wherein the plurality of connections is arranged in a grid array, and wherein the interposer includes a plurality of plated through holes; and a substrate coupled to the interposer, wherein the substrate includes a plurality of pins, and wherein the substrate is coupled to the interposer by inserting each of the plurality of pins into a corresponding one of the plurality of plated through holes, and wherein the substrate is configured for mounting of an integrated circuit (IC) package thereon, wherein the substrate includes a plurality of layers including a first layer having a power plane, a second layer having a ground plane, and a third layer having a plurality of signal traces; wherein the interposer includes a plurality of bus bars which provide power and ground connections to the substrate when the substrate and the interposer are coupled together, wherein the bus bars are centrally located on the interposer and extend perpendicularly from the interposer to the substrate when the interposer and substrate are coupled together.
2. The apparatus as recited in claim 1, wherein plurality of pins and the plurality of plated through holes are arranged to form a pin grid array (PGA), and wherein each of the plated through holes is co-axial with a corresponding one of the plurality of connections.
3. The apparatus as recited in claim 1, wherein the interposer and the substrate are configured to electrically couple an integrated circuit contained within the integrated circuit package to a PCB when the interposer is mounted thereon, and wherein the plurality of connections include power connections, ground connections, and signal connections.
4. The apparatus as recited in claim 1, wherein a co-efficient of thermal expansion (CTE) of the interposer is approximately equal to a CTE of a PCB upon which the interposer is to be mounted.
5. The apparatus as recited in claim 1, wherein the grid array is a ball grid array, and wherein each of the plurality of connections is a solder ball.
6. The apparatus as recited in claim 1, wherein the grid array is a land grid array, and wherein each of the plurality of connections is an elastomeric connector.
7. The apparatus as recited in claim 1, wherein integrated circuit package is a flip-chip package.

7

- 8. The apparatus as recited in claim 1, wherein an aspect ratio of each of the plurality of pins is at least 8:1.
- 9. An electronic assembly comprising:
 - a printed circuit board (PCB) having a grid array, wherein the grid array includes a plurality of mounting pads;
 - an interposer having a plurality of connections, wherein each of the plurality of connections is surface mounted to a corresponding one of the plurality of mounting pads, and wherein the interposer includes a plurality of plated through holes;
 - a substrate coupled to the interposer, wherein the substrate includes a plurality of pins, and wherein the substrate is coupled to the interposer by inserting each of the plurality of pins into a corresponding one of the plurality of plated through holes, and wherein the substrate includes a plurality of layers including a first layer having a power plane, a second layer having a ground plane, and a third layer having a plurality of signal traces; and
 - an integrated circuit (IC) package mounted on the substrate;
 - wherein the interposer includes a plurality of bus bars which provide power and ground connections to the substrate when the substrate and the interposer are coupled together, wherein the bus bars are centrally located on the interposer and extend perpendicularly from the interposer to the substrate when the interposer and substrate are coupled together.
- 10. The electronic assembly as recited in claim 9, wherein plurality of pins and the plurality of plated through holes are arranged to form a pin grid array (PGA), and wherein each of the plated through holes is co-axial with a corresponding one of the plurality of connections.
- 11. The electronic assembly as recited in claim 9, wherein an integrated circuit contained within the integrated circuit package is electrically coupled to the PCB through the substrate and the interposer, and wherein the plurality of connections include power connections, ground connections, and signal connections.
- 12. The electronic assembly as recited in claim 9, wherein the PCB has a first co-efficient of thermal expansion (CTE) and the interposer has a second CTE, and wherein the first CTE and the second CTE are approximately the same.

8

- 13. The electronic assembly as recited in claim 9, wherein an aspect ratio of each of the plurality of pins is at least 8:1.
- 14. The electronic assembly as recited in claim 9, wherein the integrated circuit package is a flip-chip package.
- 15. An electronic assembly comprising: first means having a plurality of pads arranged in a grid array;
 - second means for mounting to said first means, said second means having a plurality of connections each arranged to correspond to one of the plurality of pads, wherein said second means further including a plurality of plated through holes;
 - third means for coupling to said second means, said third means having a plurality of pins each corresponding to one of the plurality of plate through holes, said third means further including a plurality of layers including a first layer having a power plane, a second layer having a ground plane, and a third layer having a plurality of signal traces; and an integrated circuit package mounted to said third means;
 - wherein said second means includes a plurality of bus bars that provide power and ground connections to said third means when said second means and said third means are coupled together, wherein the bus bars are centrally located on said second means and extend perpendicularly from said second means to said third means when said second means and said third means are coupled together.
- 16. The electronic assembly as recited in claim 15, wherein plurality of pins and the plurality of plated through holes are arranged to form a pin grid array (PGA), and wherein each of the plated through holes is co-axial with a corresponding one of the plurality of connections.
- 17. The electronic assembly as recited in claim 15, wherein the first means has a first co-efficient of thermal expansion (CTE) and the second means has a second CTE, and wherein the first CTE and the second CTE are approximately the same.
- 18. The electronic assembly as recited in claim 15, wherein an aspect ratio of each of the plurality of pins is at least 8:1.

* * * * *