

(12) **Patent Application Publication**  
**Bennett et al.**

(10) **Pub. No.: US 2016/0106072 A1**  
(43) **Pub. Date: Apr. 21, 2016**

*A01K 29/00* (2006.01)  
*A01K 39/012* (2006.01)

(52) **U.S. Cl.**  
CPC ..... ***A01K 39/04*** (2013.01); ***A01K 29/005***  
(2013.01); ***A01K 39/0206*** (2013.01); ***A01K***  
***39/012*** (2013.01); ***G05B 15/02*** (2013.01);  
***H04N 7/185*** (2013.01); ***G06F 3/165*** (2013.01)

(57) **ABSTRACT**

Animal sustenance-dispensing stations described herein may be capable of supplying food or water to animals, of controlling electrical loads that prevent liquid sustenance freeze-up or overheating and other loads that help sanitize the sustenance, that illuminate the station, or that generate sounds; of acquiring and processing data from a variety of sensors both internal and external to the station, and of reporting both raw and processed data. They may also be capable of wirelessly communicating with other stations, or with non-station devices over wireless communication networks to facilitate reporting of sensor and other data, and to support configuration of station controller operational and reporting behavior. Station configurations may facilitate monitoring of video and audio activity of nearby animals, tagged animals visiting the station, weather conditions in the station's vicinity, station food or water supply levels, and other parameters according to the sensors of a given embodiment.

### Related U.S. Application Data

(63) Continuation of application No. 14/517,913, filed on Oct. 19, 2014, now Pat. No. 9,247,719.

## Publication Classification

(51) **Int. Cl.**  
*A01K 39/04* (2006.01)  
*A01K 39/02* (2006.01)  
*G06F 3/16* (2006.01)  
*G05B 15/02* (2006.01)  
*H04N 7/18* (2006.01)






FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 3A

# Liquid Sustenance Dispensing Tray 305




FIG. 3B

### Solid Sustenance Dispensing Tray 304






FIG. 3C




Green Light = Power ON



Red Light = Heater/Cooler ON  
Flashing Red Light = Low Food

FIG. 3D








FIG. 4A

# Solid Sustenance Dispensing Tray 401




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6





FIG. 7A





**FIG. 7B**




FIG. 8

**900 STATION CONFIGURATION SETTINGS**

Alerts

☐ Food supply level < \_\_\_\_%  
☐ Temperature < \_\_\_\_°F or > \_\_\_\_°F  
☐ Food supply possibly unsafe

Prefs

☐ Email: \_\_\_\_\_  
☐ Text ph: \_\_\_\_\_  
 Date: Aug 8, 2010 Time: 3:46 pm

Comm

☐ WiFi Enable  
☐ Bluetooth Enable  
☐ Cellular Enable

Cntrlr

☐ Model 100  
☐ SW v 1.5.100408  
☐ Auto update

**Operational Settings**

☐ Cooling Temp: \_\_\_\_ °F  
☐ Heating Temp: \_\_\_\_ °F  
☐ UV Purifier  
☐ Ambient Lights ON:\_\_\_\_ OFF:\_\_\_\_  
☐ Status Lights Ena:\_\_\_\_ OFF:\_\_\_\_  
☐ Audio ON:\_\_\_\_ OFF:\_\_\_\_  
     Playlist: \_\_\_\_\_  
☐ Camera 1  
☐ Camera 2  
☐ RFID  
☐ Add Station  
☐ Order Accessories  
☐ Share Station Data

FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D

## FLYING ANIMAL FEEDER CONTROL, MONITORING, AND REPORTING SYSTEM

### CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. application Ser. No. 14/517,913, filed 19 Oct. 2014, entitled “Flying Animal Feeder Control, Monitoring, and Reporting System.”

### STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

[0002] Not Applicable

### REFERENCE TO SEQUENCE LISTING, A TABLE, OR A COMPUTER PROGRAM LISTING COMPACT DISK APPENDIX

[0003] Not Applicable

### BACKGROUND

[0004] People often place feeders in their backyards to attract hummingbirds, songbirds, and other flying animals (e.g., bats, moths, butterflies) to identify them, observe them in close proximity, and experience their presence when outdoors. These highly desirable animals most often migrate with the seasons and as such, are typically thought of as summer flyers but some species of birds (e.g., chickadee, sparrow) commonly overwinter in the higher latitudes where winter climates can include freezing temperatures and snow-fall. During periods of snow and freezing temperatures, the seeds, nuts, and insects upon which overwintering birds rely may become covered by snow or ice and drinking water sources may freeze over—leaving them with diminished availability of sustenance essential to their very survival. Of those who put out seed and water sustenance for flying animals, many neglect to check and refill their feeders and even those that do so regularly may find it burdensome or impossible to keep dry food accessible in the presence of snow, and maintain a constant supply of liquid water during freezing temperatures.

[0005] Though most hummingbird species are migratory, the Anna’s hummingbird can be found year-round along the Pacific coast as far north as British Columbia, Canada. Additionally, members of migrating hummingbird species may arrive early in the season to claim territory for attracting a mate, or stay late—being caught off guard by an early season storm. Younger birds may find themselves trapped in winter areas due to their inexperience with migration and hummingbirds of any age may be victims of storms or other factors that push them off course into winter’s path. When temperatures drop, hummingbirds are vulnerable to the scarce supply of insects and nectar that are so vital to their survival.

[0006] Backyard feeders can be life-savers for hummingbirds that find themselves in winter climates but the nectar (sugar water) in the feeders may freeze—depriving hummingbirds of a food source on which they rely. Though bird enthusiasts (birders) may take measures to keep nectar within their feeders from freezing (e.g., bringing them in at night, increasing sugar content, using elaborate lamps or heat tape), they may miss the fact that a feeder is empty or the nectar within frozen, and one day without this food supply may spell doom for the bird that is living in sub-freezing temperatures. Some birders may keep two feeders and exchange the freezing one with a warm one that has been kept indoors—some-

times several times a day, but this scheme is difficult to maintain for those at work or on vacation. During the summer months, flying animal enthusiasts may not be aware when high temperatures have spoiled the liquid sustenance within their feeders—possibly driving birds away from their feeders or even making them ill.

### SUMMARY

[0007] This summary is provided to introduce simplified concepts concerning flying animal sustenance control, monitoring, and reporting stations & systems, which are further described below in the Detailed Description. This summary is not intended to identify key or essential features of the claimed subject matter, nor is it intended for use in determining the scope of the claimed subject matter. Furthermore, the claimed subject matter is not limited to implementations that solve any or all disadvantages noted in any part of this disclosure.

[0008] Disclosed herein are embodiments of flying animal sustenance stations (commonly referred to as birdfeeders) that hold liquid sustenance for consumption by birds (commonly used for feeding hummingbirds and providing water to songbirds) and other flying animals (e.g., bats, moths), having control and monitoring systems that may heat the liquid food as necessary to prevent the food from freezing in cold weather; that may cool the liquid food as necessary to retard bacterial, fungal, and other growth within the food in warm weather; that may kill bacteria and other biological agents growing within the liquid sustenance; that may report power, function, and food status; that may predict when the sustenance supply is likely to be depleted; that may communicate live video and audio of activity surrounding the feeder; that may gather and report statistics of birds and food consumption; that may be configured to generate alarms when specified conditions are met; that may have feeder lighting configurable by the user to turn on and off when desired; that may read and store ID tag information attached to an animal and report the information and time it was present; that may drive electrical loads (e.g., lights, speakers) external to the station; that may receive data from sensors external to the station (e.g., temperature, humidity, barometric pressure, wind speed, wind direction) for reporting purposes; that may receive and that may bi-directionally communicate information wirelessly with other stations and devices as necessary for configuration by a user, and control, monitoring, and reporting information to a user.

[0009] The foregoing and other objects, features, and advantages of the inventions will become more apparent from the following detailed description, which proceeds with reference to the accompanying figures.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0010] To facilitate understanding of the advantages of the invention, a more complete description of the invention briefly described in the summary above, is given in the detailed description with reference to specific embodiments illustrated in the drawings listed below. These drawings depict embodiments of the invention and should not be considered as limiting in its scope. All sustenance stations depicted in drawings herein are illustrated in cylindrical form, but may be embodied in any sizes, shapes, and forms for aesthetic and/or functional purposes that suit the needs of other embodiments. The invention will be described and

explained in detail using specific references to elements depicted in the accompanying drawings.

[0011] The detailed description relies on reference to the accompanying figures. The left-most digit(s) of a figure reference number identifies the figure in which the reference number first appears. The use of the same reference numbers in different locations in the description and the figures may indicate similar or identical items.

[0012] FIG. 1A depicts a component schematic of a flying animal liquid-sustenance station control, monitoring, and reporting station.

[0013] FIG. 1B depicts an example of flying animal liquid-sustenance station electrical loads driven by auxiliary outputs from the controller.

[0014] FIG. 1C depicts an example of flying animal liquid-sustenance station external sensors connected to auxiliary inputs of the controller.

[0015] FIG. 2A illustrates a flying animal sustenance station control, monitoring, and reporting system block diagram.

[0016] FIG. 2B shows flying animal sustenance station alternative controller configurations.

[0017] FIG. 3A depicts component schematics of flying animal liquid- and solid-sustenance station control, monitoring, and reporting stations.

[0018] FIG. 3B illustrates a liquid-dispensing tray with controller and other components.

[0019] FIG. 3C illustrates a solid-dispensing tray with auxiliary components.

[0020] FIG. 3D depicts power, heating, and cooling state visual indicators.

[0021] FIG. 3E illustrates a wired communication link between multi-dispenser flying animal liquid-dispensing and solid-dispensing sustenance stations.

[0022] FIG. 4A shows a flying animal solid-sustenance dispensing station control, monitoring, and reporting system.

[0023] FIG. 4B depicts a solid-dispensing tray with controller and other components.

[0024] FIG. 5A illustrates controller communications between multiple flying animal liquid-dispensing and solid-dispensing sustenance stations.

[0025] FIG. 5B illustrates wireless controller communications between flying animal liquid-dispensing and solid-dispensing sustenance stations.

[0026] FIG. 5C illustrates wireless controller communications between multiple flying animal liquid-dispensing and solid-dispensing sustenance stations.

[0027] FIG. 6 depicts flying animal sustenance station wireless communication with devices.

[0028] FIG. 7A depicts an example of a hummingbird feeder status report.

[0029] FIG. 7B depicts an example of a hummingbird feeder status dashboard.

[0030] FIG. 8 depicts an example of a station status and bird activity statistics report.

[0031] FIG. 9 depicts an example of a system configuration user interface.

[0032] FIG. 10A depicts an example of solid-sustenance station power and signal routing for pole-mounting configuration.

[0033] FIG. 10B depicts an example of liquid-sustenance station power and signal routing for configuration where the station is suspended from a pole.

[0034] FIG. 10C depicts an example of liquid-sustenance station power and signal routing for a configuration where the station is suspended from an upper support.

[0035] FIG. 10D depicts another example of liquid-sustenance station power and signal routing for a configuration where the station is suspended from an upper support.

## DETAILED DESCRIPTION

[0036] Overview

[0037] Flying animal sustenance stations are used throughout the world in urban and suburban settings at private residences, office parks, zoological parks/gardens, in wildlife refuges, and in the wilderness at large. In all settings the invention disclosed herein helps prevent liquid sustenance freeze-up, overheating, and bacterial growth, while facilitating monitoring of sustenance station status, animal identification, animal activity near the station, and weather conditions over the internet or other wireless communication means. Remotely-located stations may connect to the internet via cellular radio and stations located in range of local area network (LAN) or wide area network (WAN) wireless access points (APs), may connect to the internet via compatible radios and protocols (e.g., 802.11, Bluetooth). Users may directly connect to stations within wireless communication range via a mobile device (e.g., smartphone, tablet, laptop) application, using 802.11, Bluetooth, or other short-range wireless radios and protocols.

[0038] Flying animal enthusiasts using the invention may be able to view & record live video & audio feeds of birds and other animal action around their sustenance stations, check the level of the sustenance supply, the sustenance and air temperatures, current weather conditions at the station, statistics of activities at the station over time, change alarm and other settings, see information from ID tags carried by animals near the station, etc. from their mobile device (e.g., smartphone, tablet, laptop) application, an online web application, or an application hosted on a local server or on the sustenance station controller itself. Ornithologists, chiropterologists, lepidopterologists, and zoologists may use the invention to collect data acquired from individual stations, or multiple stations locally networked together where one or more stations aggregate sensor data, and serve as monitoring, reporting, and configuration nodes for locally-networked stations, through the node's wireless internet (or other external network or device) connection. The audio, visual, ID tags, and other sensor data gathered can provide researchers with valuable information for studying flying animal populations, migrations, behavior and other aspects of their lives that may help guide efforts to protect threatened, endangered, and stressed species populations. Data acquired by amateur-operated stations may be shared with researchers to facilitate their investigations of flying animal populations by increasing the amount of data at their disposal for analysis.

## Example Implementations

[0039] FIG. 1A shows, in schematic form that is not drawn to scale, a non-exhaustive collection of components that may be incorporated into a flying-animal liquid sustenance station 100, a key apparatus of the control, monitoring, and reporting system. Typical flying-animal liquid sustenance stations may dispense water, sugar-water, or other liquid 104 sustenance, and comprise a storage vessel 101 for storing the liquid 104 and a feeding tray 102 into which liquid 104 from the storage

vessel **101** drains. The feeding tray **102** is removably attached to the storage vessel **101** (via e.g., threaded coupling, snap on & releasable fitting) to facilitate cleaning and liquid sustenance **104** replenishment, and has one or more openings **129** positioned around the top surface from which the animals access the sustenance for consumption.

**[0040]** Typically attached (fixedly or removably) to the top of the storage vessel **101** is a cap **136** with at least one attachment ring **128** fixedly or removably attached to the cap **136**, that enables the station **100** to be attached to a rope, hook, chain, cable or other means and suspended from an overhead support such as a porch ceiling, eave, tree branch, pole with support arm, etc. The cap **136** may have a hole **140** positioned in the area of the attachment ring **128**, through which electrical wiring carrying power and other electrical signals may be routed to and from the station **100** as may be required for specific embodiments or station mounting configurations. The cap **136** may also be fitted with electrical loads such as station **100** area illuminating lamps **137**, or other electrical loads such as, but not limited to, speakers **307**, or fitted with sensors such as, but not limited to, audio **112** and imaging **113** sensors depicted mounted to the cap **136** in FIG. 3A.

**[0041]** As further illustrated in FIG. 1A, the feeding tray **102** comprises two main chambers, upper and lower, divided substantially horizontally by a sealing barrier **103** that prevents the liquid **104** in the upper chamber from escaping into the lower chamber containing the station controller **105** and other electrical components and associated circuitry. The sealing barrier **103** may be flat, curved, or otherwise shaped to accommodate the attachment of sensors and electrical loads at various locations to optimize their respective functions. The electrical loads and sensors shown in the feeding tray **102** are positioned for illustrative purposes only and may be placed as appropriate for the size, geometries, and other requirements specific to different station embodiments. The types and quantities of sensors and electrical loads shown are for descriptive purposes only and not limiting in any way to the types and quantities of sensors and electrical loads used for other embodiments.

**[0042]** A temperature (T) sensor **107** (e.g., thermistor, infrared (IR)), a thermoelectric cooling and heating device (TEC) **108** (e.g., Peltier device), and an optional resistive (R) heater **139** are electrically coupled to a station controller **105** that attempts to maintain a specified liquid temperature or temperature range setting by determining the temperature of the liquid **104** based on input data received from T sensor **107**, and applying or removing power to the TEC **108** or resistive heater **139** as necessary. The T sensor **107** is located above the sealing barrier **103** and sensor types best suited to direct contact (e.g., thermistor) may be immersed in liquid **104** for optimum thermal coupling, or if a non-contact sensor (e.g., IR) it may be positioned above the surface of liquid **104** at some point (not shown) under the top surface of the feeding tray **102**. The TEC **108** is ideally located in the center of the sealing barrier **103**, with the top side thermally coupled to the liquid **104** either directly or with heat sink **109** thermally bonded to the top surface of the TEC **108** and immersed in liquid **104** to provide improved temperature transfer between TEC **108** and liquid **104**. Thermally bonded to the lower side of the TEC **108** is a thermally conductive material (e.g., aluminum) **110** that extends substantially to the edge of the feeding tray **102** where it is thermally bonded to a heat sink **111** that is substantially exposed to ambient air.

**[0043]** The controller **105** may operate the TEC **108** in a mode that moves heat from the upper surface to the lower surface (cooling mode), or in a mode that moves heat from the lower surface to the upper surface (heating mode), by reversing the polarity of the voltage output driving the TEC **108** electrical load. Although heat sink **109** is shown attached to the top surface of TEC **108** to increase the surface area for improved thermal transfer to and from liquid **104**, it may not be necessary for use in designs incorporating TECs with large surface areas. The ability of TECs to transfer heat from one surface to the other diminishes as the temperature difference between the two surfaces increases and as such, it may be beneficial to use an efficient thermal conductor **110** to optimize transfer of heat from the lower surface of TEC **108** to the heat sink **111** exposed to ambient air. Typical single-stage TECs (e.g., TEC1-12703) produce a maximum temperature difference of about 70° C. between their upper and lower surfaces and their ability to maintain the liquid **104** above freezing temperatures in extremely cold winter environments may be challenged. In embodiments where a station **100** may be used in such conditions, R heater **139** may be bonded to or otherwise immersed in liquid **104** and powered solely or together with the TEC **108** to provide sufficient heat to keep the liquid **104** from freezing. To further help keep the liquid **104** from freezing, insulation **115** may be applied to (e.g., a sleeve that slides over), or be an integral part of the storage vessel **101** and the underside of the cap **136** to reduce heat loss from the liquid **104**. Insulation **115** also serves to reduce heat transfer to the liquid **104** when the station is exposed to high-temperature environments. Insulation (e.g., compartments filled with air or insulating material) may also be incorporated into the outer perimeters of the feeding tray **102** and beneath the sealing barrier **103** to aid in temperature regulation of the liquid **104**. The use of transparent material for insulation (e.g., double pane glass or plastic) **115** around the storage vessel **101** may be preferred by a station owner but decorative opaque insulating materials may also find favor. Glass or plastic storage vessels **101** not covered with insulation **115** may be coated with a low emissivity (Low E) material to reduce solar radiative heating of the liquid **104**, but may have little effect on high ambient temperature environments.

**[0044]** It is not necessary to locate the TEC **108** and bonded heat sink **109** (if used) in the center of the sealing barrier **103** as shown, but doing so allows for optimal convection currents of the liquid **104** when the TEC **108** is operated in cooling mode, and also when operated in heating mode. When the TEC **108** top surface is cooler than the surrounding liquid **104**, a convection current in the liquid **104** forms as the liquid **104** above the TEC **108** cools and its increased density causes it to sink **133** and forces the warmer, less dense liquid **104** to rise along the outer areas of the storage vessel **101**, in the general cooling-mode circulation pattern **130** depicted. Conversely, when the TEC **108** top surface is warmer than the surrounding liquid **104**, the liquid warming above the TEC rises **132** forming a general warming-mode circulation pattern **131** as depicted.

**[0045]** A parallel conductive strip capacitive or resistive liquid level sensor **106** is shown immersed in the liquid **104** above the sealing barrier **103**, the capacitance or resistance of which is measured by the controller **105**. An alternative type of liquid level sensing comprises a float that floats on the surface of the liquid **104**, that is attached to a line that winds around a lightly spring-loaded spool attached to the sealing barrier **103** so that as the liquid level drops, the spool reels in

the line and a shaft position encoder (e.g., potentiometer, optical) provides a signal to the controller **105** that is proportional to the amount of line on the spool and correspondingly, the level of the liquid **104**. Another means of measuring the level of the liquid **104** uses a force transducer located at the station mounting point that is read by the controller **105** to determine the weight of the feeder. Other sensors or techniques may be employed for level sensing. The level sensed may be may span to the full capacity of the storage vessel **101**, to the capacity of the feeding tray **102**, or anywhere between. Other embodiments may implement level sensing with multiple sensors such as, but not limited to, an external capacitive sensor to detect fluid level in the storage vessel **101** and a float level switch in the feeding tray **102** to signal when the liquid drops below a predetermined level.

**[0046]** Flying-animal liquid sustenance stations **100** are typically visited for sustenance by numerous flying animals that may be from local or migrating populations. Flying animals carrying such as, but not limited to, bacterial infections that feed at the station may leave infectious agents transmitted through direct contact with the liquid **104** in the feeder as they draw sustenance through feeding station ports **129**, or by other means. To prevent or retard the growth of infectious agents in the liquid **104**, the station **100** may be equipped with one or more ultraviolet (UV) light emitters **138**, ideally light emitting diodes (LEDs), that emit UV light having a wavelength at or shorter than 290 nanometers (nm). Research by NASA and others show that UV light of these wavelengths has a germicidal effect and as such, the use of such UV lights may help prevent or reduce the spread of infectious agents among animals drawing sustenance from the station.

**[0047]** To avoid the possibility of potentially harmful UV exposure of a flying animal's proboscis, eyes, beak, or other body parts, the use of UV emitters **138** with wavelengths from 270 nm to 290 nm are preferred along with positioning the UV emitters **138** such that if they are powered when animals are using the station **100**, they are blocked from exposure to the UV light. This can be accomplished by locating the emitters **138** in a position that an animal's beak and proboscis are not exposed while drawing sustenance through ports **129** by, for example, using one or more UV-blocking barriers. Alternatively or additionally, data from sensors such as, but not limited to imaging **112**, audio **113**, or motion **114** sensors, may be processed by software executing in the controller **105** to determine the presence of an animal at the station and apply power to the UV emitters **138** only when no animals are present. Though FIG. 1A depicts two emitters **138**, any number (including 0) of emitters may be used to accommodate different sizes and geometries of stations **100** according to the configuration desired for other given embodiments.

**[0048]** To facilitate cleaning the feeding tray **102**, some embodiments may have a piezoelectric ultrasonic transducer **141** mounted inside the feeding tray **102**. When the feeding tray **102** requires cleaning, it may be detached from the storage vessel **101**, emptied of any remaining liquid **104**, filled with a cleaning solution, and by activation of a cleaning mode the ultrasonic transducer **141** creates pressure waves in the solution that dislodge biotic agents clinging to the interior surfaces of the feeding tray **102**. The ultrasonic transducer **141** may be driven by an electrical load output from the controller **105**, or by a separate circuit that is activated when external power is applied through a connector located on a component of the station **100**.

**[0049]** Any number (including 0) of imaging **112** or audio **113** sensors may be used in an embodiment, and may be located near feeding ports **129** as shown in FIG. 1A, or on the underside of the cap **136** as depicted in FIG. 3A, or anywhere as required to accommodate different sizes, geometries, or intended applications of stations **100** of other embodiments to optimize animal or station area viewing, listening, and recording objectives.

**[0050]** Station **100** and other embodiments may or may not include status lights **122** attached to the station **100** in a location that allows them to be viewed externally by users looking from a distance (e.g., when gardening, viewing through window). This serves to provide a visual indication of key station parameters without the need to view the station status page **700** or Dashboard **706** on a computing device. Multiple status lights **122** may be positioned around the periphery of the station to facilitate viewing from all angles. Two LED lights are illustrated as status lights **122** in FIG. 1A, FIG. 3B, FIG. 3C, and FIG. 3D with the intended function of indicating the state (on or off) of station **100** power, the state (on or off) of the TEC **108** or R heater **139**, and the liquid level LOW status. FIG. 3D shows one way that two LEDs, one green and one red, may be driven by the controller **105** to indicate the status described. Status lights **122** might also be implemented using a single, bi-color, green and red LED. Some embodiments may implement status indicators as LED or LCD displays capable of displaying alphanumeric characters to convey status information.

**[0051]** Located in the lower part of feeding tray **102** beneath the sealing barrier **103**, the station controller **105** receives input from sensors, and drives electrical loads, that are located both within (FIG. 1A) and external (FIG. 1B & FIG. 1C) to the station **100**. In the preferred embodiment, the controller **105** is capable of communicating wirelessly using one or more standard communication protocols such as, but not limited to, 802.11, Bluetooth, RFID, ZigBee, XBee, Cellular, et al. through the use of one or more antennas **125**. The controller **105** has additional sensory input capacity referred to as auxiliary inputs **134** to receive data from external sensors FIG. 1C, and additional output drive capacity referred to as auxiliary outputs **135** to drive external electrical loads FIG. 1B. External sensors FIG. 1C and electrical loads FIG. 1B may be physically attached to the station **100** or mounted elsewhere within communication range of the controller **105**. External sensors and loads may be communicatively coupled to the controller via wired connections or wirelessly.

**[0052]** FIG. 1B depicts an example of flying animal liquid-sustenance station electrical loads driven by auxiliary outputs **135** from the controller. Some examples of electrical loads that may be used in various embodiments are one or more lamps (e.g., LEDs) for area lighting **123** to shine on a broader area than those illuminating the station **137**, and one or more speakers **124** for creating sounds such as flowing water that might attract flying animals to a station dispensing drinking water. The loads used in various embodiments are not limited in number or variety. Some embodiments may use no auxiliary loads while other embodiments may use alternative or additional loads **126**.

**[0053]** FIG. 1C depicts an example of flying animal liquid-sustenance station external sensors connected to auxiliary inputs **134** of the controller. The RFID antenna **118** sensor is ideally located near where flying animals may hover or perch at the station so that software executing in the controller **105** can detect, interrogate, and read RFID tags that some animals



may carry. The other collection of sensors depicted are those typically used to provide data on weather conditions near the station. The weather condition sensors shown are temperature (T) sensor 117, relative humidity (H) sensor 116, barometric pressure (BP) sensor 119, rain (R) accumulation sensor 120, and wind (W) speed and direction sensor 121. Sensor information gathered by controller 105 may be communicated wirelessly to a computing device as depicted in FIG. 6, and viewed in the station status page 700 or Dashboard 706. Some embodiments may use no auxiliary sensors while other embodiments may use alternative types of sensors, or additional sensors 127. The sensors used in various embodiments described herein are not intended to be limiting in type, quantity, or variety of sensors that may be used in other embodiments.

**[0054]** FIG. 2A illustrates one embodiment of a flying animal sustenance station control, monitoring, and reporting station controller 105 block diagram. Controller 105 comprises a processor 200 for executing software instructions retrieved from memory 201, and retrieving and storing data in memory 201, accessible through memory data bus 209. The processor 200 may acquire data from sensors 218 directly through input data bus 206, or may selectively enable sensor input data 218 on a per-sensor basis, to be routed directly to memory through direct memory access (DMA) data bus 207. For illustrative purposes, FIG. 2A depicts the processor 200 as having a dedicated memory data bus 209 and a dedicated input data bus 206 while a separate DMA data bus 207 is dedicated for direct communication with the memory 201 by the input module 204 and the radio(s) 202, but other embodiments may contain architectures where communication buses are combined.

**[0055]** The processor 200 communicates with the output module 205 via output data bus 208 for driving electrical loads 219, and for receiving electrical load status information, if available, from output module 205. The processor 200 communicates with one or more radios 202 through data bus 210 to facilitate wireless communications 212 with external devices 213, through one or more antennas 125. The one or more radios 202 may be capable of communicating at frequencies and power settings chosen to conform with various wireless networking protocols such as IEEE 802.11, Bluetooth, Cellular, Zigbee, XBee, RFID, and any other wireless networking protocol that meets the wireless communication requirements for a given embodiment.

**[0056]** Electrical wiring for all sensors contained within the station 100 are routed to the input module 204 as depicted in internal 214 sensor connections, and connections from sensors external to station 100 are routed to the input module 204 as depicted in auxiliary 134 sensor connections. The input module 204 acquires and digitizes sensor input signals as directed by the processor 200, which under program control may set the acquisition rate on a per-sensor basis, may configure the input module 204 on a per-sensor basis to send acquired data directly to a specified buffer in memory 201 under DMA control, or directly to a specified buffer within one or more radios 202. The radio(s) 202 may support DMA transfers to or from memory 201 to, for example, transmit sensor data streams buffered in memory 201 over wireless communications link 212 to external devices 213, or load software or configuration data received over wireless communications link 212 from external devices 213 into memory 201. While DMA control is not a required for routing sensor data from input module 204 to memory 201 or radios 202, it

reduces the processing load of processor 200 for acquiring multimedia data streams such as video and audio from imaging 112 and audio 113 sensors, as well as any sensor data acquired periodically at a less frequent rate. The processor 200, may also read sensor input data from the input module 204 at any time by reading the most recently acquired data that has been stored in a register by the input module 204. Techniques described herein for acquiring, routing, storing, and reading sensor data from the input module 204 are for exemplary purposes and not intended to limit the scope of how embodiments acquire, route, store, and read sensor input data.

**[0057]** Under programmed control, the processor 200 controls the output module 205 to activate or deactivate power or to send signals such as digital audio (e.g., MP3 audio coding format file) stored in memory 210, to electrical loads 219 through internal load connections 215 for loads considered internal to the station 100, and through auxiliary loads 135 connections for loads considered external to the station 100. The output module 205 may be able to stream digital audio files from memory 201 via output module 205 DMA data bus 211 for conversion to analog signals that are input to amplifier circuitry within output module 205, which drives audio output loads such as speakers 124. The output module 205 may comprise volatile or non-volatile memory within to obviate the need for using a DMA data bus 211 to stream media files from memory 201 external to the output module 205. The output module 205 may detect the operational state of electrical loads 219 and report them through an electrical load status register that may be read by processor 200 via data bus 208. The preferred technique for detecting the state of electrical loads 219 is to sense the current flowing through the load when power is applied or removed, and store the measured current for each load in a status buffer that may be read by the processor 200 via data bus 208. Detection and reporting of load status may be accomplished through the use of simpler or more complex techniques in other embodiments depending upon their individual station system requirements.

**[0058]** The power management module 203 receives power through a connection to a generated 216 power source (e.g., transformed household line power, fuel cell, solar power, wind power) or through a connection to a stored 217 power source (e.g., battery, super capacitor), and conditions and transforms it to supply the voltages and currents required by the modules comprising the controller 105. With the variety of power management integrated circuits currently marketed (e.g., from Linear Technology Corp.) that can operate from input voltages ranging from 2.4 to 28 volts at currents from 2 to 12 amperes, the designer of a given embodiment may choose from a variety of power converters for supplying generated 216 power.

**[0059]** One example of a generated 216 power source converter is a 12 volt 60 watt module power supply that converts 120 volts AC to supply 12 volts DC at 5 amperes—sufficient power to drive a TEC (TEC1-12703) load at 36 watts, various LED loads, audio loads, and the electrical component modules within the controller 105. Other generated 216 power sources may be used such as solar panels, fuel cells, and wind generators. To ensure continuous operation of the station 100 when generated 216 power is interrupted due to a power outage, fuel cell fuel exhaustion, or lack of sufficient wind for wind generators or sun for solar panels, one or more power storage devices in the form of e.g., batteries, super capacitors, etc. may be coupled to the station through the stored 217

power input. The power management module **203** may operate to maintain the state of charge of the power storage device (s) while sufficient generated **216** power is available, and may automatically draw power from the stored **217** power source when generated **216** power is not available, or to augment the generated **216** power supply for a limited time should the electrical load **219** demand temporarily exceed the capacity of the generated **216** supply.

[0060] FIG. 2B depicts a simpler embodiment of a flying animal liquid sustenance station controller block diagram. The simpler controller **220** receives power **216** that is conditioned for use by electrical components within the controller **220**, and to provide power to electrical loads **219** as well as any station sensors **218** that may require power. Controller **220** comprises input circuitry **222**, control circuitry **221**, and output circuitry **225**. Input circuitry **222** receives input signals from sensors **218**, conditions them as required (e.g., impedance matching, signal buffering, amplification) and communicates the sensor data to control circuitry **221** via input data bus **223**. Control circuitry **221** uses data from input data bus **223** to control the activation and deactivation of electrical loads **219** through output data bus **224** and output circuitry **225** designed to drive the electrical loads **219**. Output data bus **224** may also convey the status of electrical loads (e.g., heater on/off state) that may be monitored and reported by electrical load drivers in output circuitry **225** module, to control circuitry **221**. Control circuitry **221** may comprise one or more analog, digital, or discrete components, a microcontroller, or any combination thereof to implement one or more functions such as, but not limited to those of the following list:

- [0061] a) Controlling a heating component to maintain the liquid sustenance approximately at or above a selected temperature threshold;
- [0062] b) Controlling a cooling component to maintain the liquid sustenance approximately at or below a selected temperature threshold;
- [0063] c) Determining the approximate level of liquid sustenance remaining in the station;
- [0064] d) Inhibiting power to the heating and cooling components when the liquid sustenance level is below a specified level;
- [0065] e) Controlling power to one or more ultraviolet (UV) light emitters **138** on a specified schedule, or based on the time of day as measured by a digital clock or a daylight detection sensor (e.g., photocell) or both.
- [0066] f) Controlling power to one or more station lights **137** on a specified schedule, or based on the time of day as measured by a digital clock or a daylight detection sensor (e.g., photocell) or both.
- [0067] g) Controlling power to one or more station status lights FIG. 3D: **122** to indicate the station power state, the state of one or more electrical loads (e.g., Heater/Cooler On/Off), the state of the sustenance supply (e.g., Low Food), and/or other specified information.
- [0068] h) Playing an audio file (e.g., MP3 audio coding format file) stored in memory within the control circuitry **221** module, by converting it to an analog signal, amplifying it, and sending it to a station audio output device (e.g., speaker **124**). An audio file may be played continuously, on a specified schedule, or based on the time of day as measured by a digital clock or a daylight detection sensor (e.g., photocell) or both.

- [0069] i) Activating an ultrasonic cleaning actuator **141** when commanded through a switch or by other means when the cleaning part or all of the station.

[0070] The functionality of the station controllers is not limited to that described herein, and may be performed by one or more types of analog and digital discrete and integrated hardware components singly, multiply, or in any combination. Examples of types of hardware that may be used are, but not limited to: microcontrollers, field-programmable gate arrays (FPGAs), complex programmable logic devices (CPLDs), application-specific integrated circuits (ASICs), application-specific standard products (ASSPs), system-on-a-chip (SOC) ICs, comparators, operational amplifiers (Op Amps), power management (PM) ICs, transistors, relays, etc. Station controllers need not be packaged together on a single controller circuit card, but modules and components may be located apart from, but still communicatively coupled to others to accommodate the packaging or other requirements of station embodiments.

[0071] FIG. 3A depicts an example of an embodiment of a flying animal combined liquid-, and solid-sustenance control, monitoring, and reporting station. This particular combination has the benefit of providing solid sustenance (e.g., seeds, nuts) with liquid sustenance (e.g., water) in a communicatively-coupled configuration with a common controller, or with individual controllers that communicate with each other for control, monitoring, and reporting functions. The combined stations may be physically separate as depicted, or may be physically joined and may or may not be separable so that they can be independently removed for servicing (e.g., refilling, cleaning), and replaced. Further, station combinations are not limited to one of each type, but may comprise any combination of single or multiple liquid and solid sustenance stations. Individual stations within a combined station are all communicatively coupled in a way that enables control, monitoring, and reporting of the combination of stations.

[0072] The individual stations shown in the combined station depicted in FIG. 3A are solid-sustenance station **300** and liquid-sustenance station **301**. They are each depicted as having features in common, many of which have been previously described herein, but this is only for illustrative purposes and is not intended to be limiting in any way with respect to type, quantity, combination, or placement of features, sensors, electrical loads, components, etc. that may be used for individual stations within a combined station.

[0073] Stations **300** and **301** are depicted with storage vessel **101** having a cap **136** with an attachment ring **128** mounted to the cap **136**, providing the ability to suspend stations **300** and **301** from an overhead support such as a porch ceiling, eave, tree branch, pole with support arm, etc. The caps **136** may have a hole **140** positioned near the attachment ring **128**, through which electrical wiring carrying power and other electrical signals may be routed to and from the stations **300** and **301** as may be required for specific embodiments or combined station mounting configurations. Individual station caps **136** may also be fitted with electrical loads such as station **300** & **301** area illuminating lamps **137**, or other electrical loads such as, but not limited to, speakers **306** and **307**, or fitted with sensors such as, but not limited to, audio **112** and imaging **113** sensors as depicted mounted to the caps **136**. The storage vessel **101** of station **300** stores solid sustenance **302** (e.g., seeds, nuts) and attached to the bottom of storage vessel is the feeding tray **304** into which solid sustenance **302** from the storage vessel **101** is dispensed.

The feeding tray **304** is removably attached to the storage vessel **101** (via e.g., threaded coupling, snap on & releasable fitting) to facilitate cleaning and solid sustenance **302** replenishment, and has one or more openings **308** positioned around the top surface from which the animals access the sustenance **302** for consumption.

**[0074]** The storage vessel **101** of station **301** stores liquid sustenance **303** (e.g., water) and attached to the bottom of storage vessel is the feeding tray **305** into which liquid sustenance **303** from the storage vessel **101** is dispensed. The feeding tray **305** is removably attached to the storage vessel **101** (via e.g., threaded coupling, snap on & releasable fitting) to facilitate cleaning and liquid sustenance **303** replenishment, and has one or more openings **309** positioned around the top surface from which the animals access the sustenance for consumption. To facilitate access to the liquid sustenance by larger animals, the openings are typically larger than those that would be designed for a tray targeted only for small flying animals (e.g., hummingbirds, moths, bats). The liquid-sustenance station **301** may have an insulating or other type of material **115** wrapped around or otherwise fixed to the outer surface of the storage vessel **101** for facilitating temperature regulation of the liquid sustenance **303**.

**[0075]** The liquid sustenance (typically water in combined station embodiments) dispensing tray **305** depicted in FIG. 3B is shown in a schematic representation of the tray used by flying animals (e.g., song birds) to consume the liquid sustenance, with the controller **105** connected with the sensors, electrical loads, antenna(s) **125** and auxiliary inputs **134** and outputs **135**. The sensors, electrical loads, and other components of the tray **305** shown in FIG. 3B are substantially the same as those depicted in FIG. 1A and function as described in the paragraphs related to FIG. 1A. The types and number of sensors, electrical loads, and other components used in the tray **305** are not limited in any way and other embodiments may use more or less of any sensor, load, or other component as appropriate to the needs of the particular embodiment design.

**[0076]** In this particular embodiment of a flying animal combined liquid-, and solid-sustenance control, monitoring, and reporting station, the dispensing tray **304** of the solid-sustenance station **300** contains sensors and electrical loads that are connected by wiring to the controller **105** within the liquid sustenance dispensing tray **305**. FIG. 3C illustrates a solid-dispensing tray **304** with a solid sustenance **302** level-sensing component comprising a light emitter array **311** whose light emissions are sensed by a light sensor array **312**. The level-sensing component depicted extends above the tray **304** into the storage vessel **101** for measuring the amount of solid sustenance **302** remaining in the station **300**. Other means of measuring solid sustenance **302** level may be used such as, but not limited to acoustic (e.g., ultrasonic), station weight sensing, float level, etc. and other embodiments may have no solid sustenance **302** level measurement sensor.

**[0077]** The dispensing tray **304** has a sealing barrier **308** to prevent solid sustenance **302** in the space above the sealing barrier **308** from entering the space below it. The space below the sealing barrier **308** houses sensors wired to the auxiliary inputs **134**, and electrical loads wired to the auxiliary outputs **135** of the controller **105** within the liquid-sustenance dispensing tray **305**. Under control of the controller **105**, the low-temperature heating element **309** warms the sealing barrier **308** that is thermally conductive so that it, in turn, warms the solid sustenance **302** to help evaporate moisture that may

accumulate in the solid sustenance **302**. The temperature sensor **107** is thermally bonded to the heating element **309** and provides feedback to the controller **105** indicating the temperature of the heating element **309**.

**[0078]** The motion sensor **114** senses motion of the solid-sustenance station **300** due to animals contacting the station, as well as forces of weather such as wind, rain, etc., and provides output indicating station motion to the controller **105**. When the controller **105**, based on a predetermined signature of motion sensing input, determines that an undesired large animal (e.g., rat, squirrel, raccoon) has landed on the station, the controller **105** may activate the noise-making solenoid **310** one or more times in succession to surprise the undesired animal to discourage their presence. The solenoid **310** is affixed to the tray in a manner so that the solenoid rod strikes a surface that produces both a loud noise and vibration that can be heard and felt by animals at the station. Actuation of the solenoid **310** may be augmented by surprising sounds sent through electrical load outputs by the controller **105** to the solid-sustenance station loudspeaker **306**, to further discourage the presence of animals not desired at the station. The controller ceases activation of noise-making electrical loads when it has determined, based on a predetermined signature of motion sensing input, that the undesired animals are no longer present. The use of motion sensing by the controller **105** for detection of the presence or absence of undesired animals at the sustenance station, may be augmented by the output of algorithms processing sound and images received via inputs from audio **112** and imaging **113** sensors. Such algorithms may help determine the cause of unexpected motion by recognizing characteristic sounds that are made by undesirable animals, and recognition of animal features such as size, shape, body characteristics, etc. from images.

**[0079]** As discussed previously, multiple status lights **122** may be positioned around the periphery of the station to facilitate viewing from all angles. Two LED lights are illustrated as status lights **122** with the intended function of indicating the state (on or off) of station power, the state (on or off) of the heating element **309**, and the solid-sustenance level LOW status. FIG. 3D shows one way that two LEDs, one green and one red, may be driven by the controller **105** to indicate the status described.

**[0080]** FIG. 3E illustrates a wired power and communications link between liquid-dispensing and solid-dispensing sustenance stations of a combined liquid-, and solid-sustenance control, monitoring, and reporting station. Wiring bundle **314** is routed from station **301** to station **300** along the station support member **313** or by some other means determined by the installation, and into each station through opening **140** or by other means (e.g., a weather-sealed connector). Stations **300** and **301** may be located any distance from each other provided the power and communications cables are appropriately sized so that power loss and signal degradation are within design constraints. The number and size of wires carried in wiring bundle **314** may be reduced in some embodiments with the addition of a data acquisition, communication, and driver (DACD) module (e.g., microcontroller, PLD, ASIC, FPGA) to the solid-sustenance station that can communicate with the controller **105** over one or more serial links (e.g., I<sup>2</sup>C, CAN, Ethernet) to send digitized sensor data and receive electrical load actuation commands. In this embodiment, the DACD module would comprise electrical load driver circuitry to eliminate the need for wires large enough to handle electrical load drive current—thereby reducing the

wiring bundle 314 size to a minimum number of wires carrying power, return, and communication link wires. Other embodiments may forego the use of a wired communications link in favor of wireless communications (e.g., Bluetooth, 802.11, Zigbee, Xbee) from the DACD module in station 300 to the controller 105 in station 301—thereby reducing the wiring bundle 314 in size to accommodate only power and return wires.

[0081] The flying animal solid-sustenance dispensing station 400 control, monitoring, and reporting system depicted in FIG. 4A is, except for the dispensing tray 401, the same as the solid-sustenance dispensing station 300 described in FIG. 3A. Similarly, the cap 136 may have a hole 140 positioned near the attachment ring 128, through which electrical wiring carrying power and other electrical signals may be routed to and from the station 300 as may be required for specific embodiments. The station cap 136 may also be fitted with electrical loads such as station 400 area illuminating lamps 137, or other electrical loads such as, but not limited to, speaker 306, or fitted with sensors such as, but not limited to, one or more audio 112 and imaging 113 sensors as depicted. The storage vessel 101 of station 400 stores solid sustenance 302 (e.g., seeds, nuts) and attached to the bottom of storage vessel 101 is the sustenance dispensing tray 401 into which solid sustenance 302 from the storage vessel 101 is dispensed. The feeding tray 401 is removably attached to the storage vessel 101 (via e.g., threaded coupling, snap on & releasable fitting) to facilitate cleaning and solid sustenance 302 replenishment, and has one or more openings 308 positioned around the top surface from which the animals access the sustenance 302 for consumption.

[0082] FIG. 4B depicts the solid-sustenance dispensing tray 401 that attaches to the station 400. It comprises the controller 105 discussed in the description of FIG. 2C, and the same sensors and electrical loads discussed in the description of FIG. 3C, and reproduced schematically in FIG. 4B for convenient reference. As in the liquid-sustenance stations 100 and 301 embodiments, the controller 105 in the solid-sustenance dispensing station 400 can drive external electrical loads (e.g., like those in FIG. 1B) via auxiliary outputs 135, and receive inputs from external sensors (e.g., like those in FIG. 1C) via auxiliary inputs 134.

[0083] FIG. 5A illustrates one combined sustenance station 500 (depicted in FIGS. 3A-3E) communicating wirelessly with another combined sustenance station 501 in a local area network (LAN) configuration. The station 500 communicates using one or more protocols such as (but not limited to) 802.11, Bluetooth, RFID, ZigBee, Xbee, et al. through the use of antenna 125, via wireless communications 502 with station 501. In addition to communicating with station 500, station 501 can wirelessly communicate with a host of other external devices 213 such as (but not limited to) those depicted in FIG. 6 and described in subsequent paragraphs. Station 501 also functions as a wireless access point (AP) for station 500, thereby providing a conduit for it to communicate with the wider network of external devices as well. While FIG. 5A depicts two combined stations, this architecture may be scaled to any number combined stations that the networking architecture, power constraints, and controller designs allow.

[0084] Multiple individual sustenance stations may be networked similarly to that illustrated in FIG. 5A for combined stations. FIG. 5B depicts two networked stations—one solid-dispensing sustenance station 400 and one liquid-dispensing

sustenance station 301—wirelessly coupled and operating in the same manner as detailed in the text describing FIG. 5A. In this example, station 301 can wirelessly communicate with other external devices 213, and functions as a wireless access point (AP) for station 400, thereby providing a conduit for it to also communicate with the wider network of external devices. FIG. 5C depicts four individual stations of types 400 and 301 networked together and communicating with other external devices 213 through the AP service provided by one liquid-sustenance station 301 on the right side of the figure. This architecture may be scaled to any number combined stations that the networking architecture, power constraints, and controller designs allow. This networked station concept is not limited to the specific architectures illustrated herein, but the same concept may be implemented using different networking or other communication architectures (e.g., mesh net) or topologies that may, for example, have multiple stations providing AP services to other stations for communicating with other external devices 213.

[0085] FIG. 6 depicts flying animal sustenance stations 400 and 301 in wireless communication with one or more non-sustenance-station external devices 213 using one or more antennas 125. In addition to being stations capable of communicating wirelessly with a given sustenance station, external devices 213 may also be wireless routers 600, mobile devices (e.g., smart phones 601, tablets 602, laptop/notebook computers 603), desktop computers 604, Cellular networks 605, Cloud computing servers 606, and other wireless-enabled devices supporting protocols compatible with those used by the sustenance station controllers and/or the networks to which they are connected.

[0086] The wireless router 600 may be in direct wireless communication with one or more sustenance stations (e.g., station 400, station 301), or may be in direct communication with a cellular communication network 605 that is in communication one or more sustenance stations. The wireless router 600 may serve as an AP through which mobile devices (e.g., smart phones 601, tablets 602, laptop/notebook computers 603), desktop computers 604, Cellular networks 605, Cloud computing servers 606 may communicate with connected networked sustenance stations. Wireless-enabled devices (e.g., mobile devices, desktops) supporting protocols (e.g., WiFi, Bluetooth) compatible with those used by the sustenance station controllers may communicate directly with one or more wirelessly-enabled sustenance stations without routing through an AP as illustrated in FIG. 6, devices 601, 602, and 603. Cellular networks 605 and cloud servers 606 may communicate with the AP 600 via internet protocol, or other networking protocols that may be deemed suitable for a given embodiment.

[0087] Users may interact with sustenance stations (e.g., 400, 301) through a client application executing on one or more devices (e.g., 601, 602, 603, and 604), or through a web application hosted on a cloud server 606 or local server in communication with one or more sustenance stations. FIGS. 7 through 9 depict examples of how sustenance station sensor and load status information may be presented to a user, or how an application may provide a user interface (UI) for viewing and modifying sustenance station configuration settings (e.g., user preferences, alerts, communication, software update, operational). There are a plethora of ways to organize and present the sensor data, load status, statistical data, and UI for setup and configuration of one or more sustenance stations. The screens depicted in FIGS. 7 through 9 are exemplary only

and not intended to be limiting in the type or amount of data, status, setup & configuration options, statistics, or any other information that may be presented to a user through a sustenance station application.

[0088] FIG. 7A depicts an example of a hummingbird feeder status page 700, illustrating one way station status may be presented to a viewer. The station select widget 709 allows the user to select the station (if multiple stations have been configured) from which the application pages receive and send data. Live video and audio sensor feeds 703 may be presented through image panes such as those shown as camera 1 (CAM 1) 701 and camera 2 (CAM 2) 702, with audio being routed through the user device audio system. Sustenance station reservoir level (shown full) may be reported in graphical format 704, along with an estimate of the number of days remaining until the next refill may be required (e.g., 7 days). One way this may be computed is by dividing the volume of sustenance in the reservoir by the daily sustenance depletion rate averaged over some number of recent days. An alert icon 705 may be displayed to notify the user that the station will require service (e.g., refill, cleaning) within a specified time period (e.g., 7 days) to ensure an uninterrupted supply of sustenance to the flying animals. The “Purchase” hyperlink button 710 provides a convenient way for users to replenish their supply of sustenance, by opening a page through which they may order sustenance, station accessories, and related products and services. Sustenance station sensor data 707 and electrical load status 708 may be viewed by using a device’s input means (e.g., mouse, stylus, finger) to select an individual sensor or load from the presented list (e.g., Feeder Temp, Wind Speed) for viewing its data or status. This example depicts a dashboard hyperlink 706 through which the user may navigate to a Dashboard 720 page (FIG. 7B) displaying real-time sensor data and load status, a Statistics hyperlink 711 to a Station Statistics 800 page (FIG. 8), and a Setup/Configuration hyperlink 712 to a Station Configuration Settings 900 page (FIG. 9). The status page 700 depicted in FIG. 7A is merely one example of how station status may be presented and not intended in any way to be limiting in the type, order, organization, layout, or amount of information presented. The information presented in the status page 700 is largely produced from data and status outputs of the sensors and loads that an embodiment comprises, as well as whatever information that may be further derived from them.

[0089] FIG. 7B depicts an example of a sustenance station sensor data and load status dashboard 720. The Dashboard 720 page is intended to present data from sustenance station sensors in an easy-to-view format. For example, the air and sustenance temperature may be viewed together for comparison in the “TEMPERATURE” 721 window; the current barometric pressure and trend indication in the “PRESSURE” 722 window; the relative humidity and trend indication in the “HUMIDITY” 723 window; the present rain accumulation and cumulative amounts in the “RAINFALL” 724 window; the wind speed and direction in the “WIND” 725 graphic; the recent history of motion of the sustenance station over a selectable period of time in the “FEEDER MOTION” 726 window; the current date and time in the “TODAY” 727 window; the most recent RFID tag identification along with the time-stamp of the acquisition in the “RFID” 728 window; and the status of electrical loads as shown in the “LOADS” 729 window. In other embodiments of client or web applications, the Dashboard 720 page might be presented as the

home page with more or less information displayed, and hyperlinks from which the other pages may be launched for user viewing and interaction.

[0090] FIG. 8 depicts an example of a Station Statistics page 800 presenting station status and bird activity statistical information. Information illustrated in this figure present the “TODAY” 801 window with today’s date and time; the “BIRD VISITS” 802 window with counts of bird visits to the feeder for today, the past week, and the past 4 weeks; the “FOOD CONSUMPTION” 803 window with the percent of sustenance consumed today and the average daily consumption; and the “BIRDS VISIT HISTORY” 804 graph showing the number of birds that have visited the station daily over a period of time chosen through the “Select” widget 805. FIG. 8 presents but a small sampling of the wide variety of statistics that may be compiled for casual, amateur, and academic interest in flying animal behavioral and migration monitoring. Gathering and reporting statistics associated with visits by flying animals carrying RFID tags may be of particular value to scientists monitoring specific animal populations that may be at risk. Statistical data compiled and presented by sustenance station applications is expected to vary widely and may be user-selectable and configurable according to the dictates of individual or academic interests.

[0091] FIG. 9 depicts an example of a system configuration UI under the page entitled “Station Configuration Settings” 900. In this example, a user may configure the settings for alerts 901, preferences 902, communications 903, and the station controller 904, as well as operational settings 905. The example of alerts 901 settings shown allow a user to configure the station to enable an alert to be generated when the food supply drops below a user-specified level, when the sustenance temperature is below or above separately specified temperatures, or when computing software determines that the sustenance supply may be nearing the point where it may be unsafe for consumption. The software determining the safety of the sustenance may be running on the station controller or on an external device, that tracks parameters related to the sustenance safety such as, for example: the time since the sustenance was last filled, the time the station was last cleaned, the temperature ranges to which the sustenance has been subjected, the use of UV purification, and other factors that affect the growth of harmful biological agents known to grow in the sustenance.

[0092] The preferences 902 configuration box shows an example of preferences a user might configure. These include an email address, a mobile phone number for text (SMS) message communication, and the current date and time setting. The communications 903 box shows an example of communication settings a user might configure to enable/disable radio communication using WiFi (IEEE 802.11), Bluetooth, or Cellular (e.g., CDMA LTE, GSM). Selecting a communication option (e.g., WiFi) opens up a configuration window (not shown) through which the user may configure specific settings (e.g., AP SSID), required and optional, that may be used by the controller to facilitate communication. The Controller 904 box shows an example of information about the station controller that may be displayed (e.g., model, software version), as well as a setting for enabling the automatic over-the-air (OTA) update of controller software. Other/additional information about the controller may be displayed and other/additional controller settings may be configured in other embodiments.

**[0093]** The operational settings **905** configuration box provides a UI through which sustenance station electrical loads may be enabled and configured, stations may be communicatively linked, and station data sharing may be configured. Embodiments of client and web applications may offer station owners the option to participate in scientific research on flying animals by allowing data collected by their station(s) to be shared with researchers. Operational settings **905** that may be enabled or configured in the example depicted are:

**[0094]** a) Cooling temperature—cool sustenance when temperature rises above specified setting.

**[0095]** b) Heating temperature—heat sustenance when temperature drops below specified setting.

**[0096]** c) Ultraviolet purifier—enable purifier operation.

**[0097]** d) Ambient lights—set ‘on’ and ‘off’ times.

**[0098]** e) Status lights—enable time and inhibit time.

**[0099]** f) Audio output—set ‘on’ and ‘off’ times; select playlist (e.g., water flowing sounds).

**[0100]** g) Camera **1**—enable.

**[0101]** h) Camera **2**—enable.

**[0102]** i) RFID—enable.

**[0103]** j) Configure communication with other station(s).

**[0104]** k) Order station parts & accessories—opens webpage catalog.

**[0105]** l) Station data sharing—configure data format and destination address for sending station data.

**[0106]** The number and type of configuration items depicted in boxes **901-905** in FIG. **9** are for descriptive purposes only and this, as well as other embodiments may support configuring more or fewer items than those listed in the each box, as well as more or fewer configuration settings boxes (categories) than those shown. Though not depicted for the sake of brevity, additional required or optional settings that may be associated with any entry within configuration item boxes (e.g., the WiFi settings of the communications **903** box discussed above) can be accommodated through a separate settings window associated with the entry, which opens via a hyperlink or pop-up when the entry is selected (for example).

**[0107]** FIG. **10A** depicts an example of solid-sustenance station **400** power and signal routing for pole-mounting configuration. Power **1000** supplied from an external source is conducted through power wiring **1001** that is routed through a hole near the lower end of the station support pole **1003** upon which the solid sustenance station **400** is mounted. The power wiring **1001** is connected to the controller electronics within the feeding tray **401**. Wiring conduit **1002** provides a protected means of routing power and signal wiring to electrical loads mounted on or integrated into the cap **136**.

**[0108]** FIG. **10B** depicts an example of liquid-sustenance station **301** power and signal routing for configuration where station is suspended from pole. Power **1000** supplied from an external source is conducted through power wiring **1001** that is routed through a hole near the lower end of the station support pole **1004** from which the liquid sustenance station **301** is suspended. The power wiring **1001** is routed through a hole in the station cap **136** where it is connected to a power distribution and conditioning module supplying power to the controller electronics within the feeding tray **102** via wiring conduit **1002**, which also provides a protected means of routing power and signal wiring to electrical loads mounted on or integrated into the cap **136**.

**[0109]** FIG. **10C** depicts an example of liquid-sustenance station **301** power and signal routing for configurations where

the station is suspended from an upper support **1006** by some attachment means **1005** (e.g., cable, rope, hook, rod). Power **1000** supplied from an external source is conducted through power wiring **1001** that is routed through a hole in the station cap **136** where it is connected to a power distribution and conditioning module supplying power to the controller electronics within the feeding tray **102** via wiring conduit **1002**, which also provides a protected means of routing power and signal wiring to electrical loads mounted on or integrated into the cap **136**. FIG. **10D** depicts another example of liquid-sustenance station **301** power and signal routing for configurations where the station is suspended from an upper support **1006** by some attachment means **1005** (e.g., cable, rope, hook, rod). In this example a bow-shaped conduit **1007** provides the protected means of routing power to the feeding tray **102**, as well as power and signal wiring to electrical loads mounted on or integrated into the cap **136**.

**[0110]** The different mounting configurations and station power connection designs shown are not intended to be limiting in how stations are mounted and power supplied to them. These are illustrative examples of how it can be accomplished but anyone skilled in the art would recognize many other ways of mounting and supplying power to sustenance stations.

**[0111]** The disclosed methods, apparatus, and systems should not be construed as limiting in any way. Instead, the present disclosure is directed toward all novel and nonobvious features and aspects of the various disclosed embodiments, alone and in various combinations and sub-combinations with one another. The disclosed methods, apparatus, and systems are not limited to any specific aspect or feature or combination thereof, nor do the disclosed embodiments require that any one or more specific advantages be present or problems be solved.

**[0112]** In view of the many possible embodiments to which the principles disclosed herein may be applied, it should be recognized that the illustrated embodiments are only preferred examples and should not be taken as limiting the scope of the disclosure. Rather, the scope of the disclosure is defined by the following claims. We therefore claim all that comes within the scope of these claims.

What is claimed is:

**1.** A method performed by a computing device, the method comprising:

receiving from an animal sustenance dispensing apparatus, operational status or sensor data;

determining an action to perform related to the animal sustenance dispensing apparatus, based on the received data or based on user input to the computing device; and sending data to perform the action.

**2.** The method of claim **1** wherein the method further comprises presenting at least some of the received data to a user of the computing device via an output component of the computing device.

**3.** The method of claim **1** wherein the action to perform is updating software in the animal sustenance dispensing apparatus based at least on determining that a newer version of the software is available than that indicated in the received data.

**4.** The method of claim **1** wherein the action to perform is changing one or more configuration settings of the animal sustenance dispensing apparatus.

**5.** The method of claim **1** wherein the action to perform causes camera images or live video from the animal suste-

nance dispensing apparatus to be presented to a user of the computing device via a display.

6. The method of claim 1 wherein the action to perform causes audio data from a file or from the user of the computing device to be sent to the animal sustenance dispensing apparatus.

7. The method of claim 1 wherein the action to perform causes multiple sets of data from the animal sustenance dispensing apparatus to be sent to the computing device.

8. The method of claim 1 wherein the action to perform is communicating with an auxiliary animal sustenance dispensing apparatus that is networked with said animal sustenance dispensing apparatus, and performing actions related to the auxiliary animal sustenance dispensing apparatus.

9. The method of claim 1 wherein the received data comprises data multiple sets of data from the animal sustenance dispensing apparatus related to animal visits to the sustenance dispensing apparatus.

10. An animal sustenance dispensing apparatus comprising:

a dispensing vessel operatively coupled to a storage vessel that stores liquid sustenance,

the dispensing vessel having a capacity to hold some amount of the liquid sustenance, and automatically receives additional liquid sustenance from the storage vessel to maintain the dispensing vessel's liquid sustenance level to the capacity;

a thermoelectric cooler (TEC) heat-exchangeably coupled to the liquid sustenance and operatively coupled to a controller that applies power to the TEC to cool the liquid sustenance when the liquid sustenance is substantially at or above a predetermined temperature.

11. The apparatus of claim 1 wherein the controller applies power to the TEC to heat the liquid sustenance when the liquid sustenance is substantially at or below a second predetermined temperature.

12. The apparatus of claim 1 further comprising one or more ultraviolet (UV) light sources configured to illuminate the liquid sustenance, wherein the controller applies power continuously or intermittently to the UV light sources.

13. The apparatus of claim 1 further comprising a level sensor configured for measuring one or more levels of the liquid sustenance contained in the storage vessel or the dispensing vessel.

14. The apparatus of claim 1 further comprising a resistive element heat-exchangeably coupled to the liquid sustenance, wherein the controller applies power to the TEC or the resistive element to heat the liquid sustenance when the liquid sustenance is substantially at or below a second predetermined temperature.

15. The apparatus of claim 1 further comprising a second dispensing vessel attached to a second storage vessel that stores solid sustenance;

the second dispensing vessel having a second capacity to hold some amount of the solid sustenance, and automatically receives additional solid sustenance from the second storage vessel to maintain the second dispensing vessel's solid sustenance level to the second capacity.

16. An animal sustenance dispensing apparatus comprising:

a dispensing vessel operatively coupled to a storage vessel that stores sustenance,

the dispensing vessel having a capacity to hold some amount of the sustenance, and automatically receives

additional sustenance from the storage vessel to maintain the dispensing vessel's sustenance level to the capacity;

a level sensor configured to measure one or more levels of the sustenance contained in the storage vessel or the dispensing vessel;

a controller configured for executing programmed instructions, and operatively coupled to a bidirectional wireless communications component;

wherein the controller is able to receive command, configuration, or update data, and to send status data over the bidirectional wireless communications component; and

wherein the controller controls the state of electrical loads responsive to sensory input data, configuration data, or from information received over the bidirectional wireless communications component.

17. The apparatus of claim 7 further comprising a visual indicator to which the controller applies power when the sustenance is at or below one or more specified levels.

18. The apparatus of claim 7 further comprising a resistive element configured to heat the sustenance; and wherein the controller applies power to the resistive element to heat the sustenance when the sustenance is substantially at or below a predetermined temperature.

19. The apparatus of claim 9 wherein the sustenance is liquid sustenance and further comprising a thermoelectric cooler (TEC) heat-exchangeably coupled to the liquid sustenance, whereby the controller applies power to the TEC to cool the liquid sustenance when the liquid sustenance is substantially at or above a predetermined temperature.

20. The apparatus of claim 10 wherein the controller applies power to the TEC to heat the liquid sustenance in response to sensing that the liquid sustenance is substantially at or below a second predetermined temperature.

21. The apparatus of claim 9 further comprising one or more ultraviolet (UV) light sources configured to illuminate the liquid sustenance, wherein the controller applies power continuously or intermittently to the UV light sources.

22. The apparatus of claim 7 further comprising one or more of the following:

an image sensor configured to capture still or moving images;

an audio sensor configured to receive sounds;

a motion sensor configured for measuring motion of the apparatus;

an RFID reader configured for reading RFID tags or chips;

a air temperature sensor;

a barometric pressure sensor;

a wind velocity sensor;

a moisture sensor configured for measuring air humidity;

a rain accumulation sensor configured for measuring rainfall; and

wherein each sensor is operatively coupled to the controller.

23. The apparatus of claim 7 further comprising one or more of the following actuators:

a vibration generator vibrationally coupled to the apparatus;

a solenoid actuator configured to strike a surface of the apparatus when actuated;

a loudspeaker for reproducing amplified audio signals; and wherein each actuator is operatively coupled to the controller.

**24.** The apparatus of claim **7** wherein the controller wirelessly transmits data related to one or more controller inputs or outputs continuously, at scheduled intervals, or when the controller wirelessly receives a command to send controller input or output data.

**25.** The apparatus of claim **7** further comprising:

a power management component that when receiving power from at least one power source, supplies charging power to a rechargeable electrical power storage component, and supplies power to the apparatus; and

when not receiving power from at least one power source, the power management component draws power from the rechargeable electrical power storage component to operate the apparatus.

**26.** The apparatus of claim **7** wherein the sustenance is solid sustenance, and the apparatus further comprising:

a liquid dispensing vessel removably attached to a liquid storage vessel,

the liquid dispensing vessel having a liquid capacity to hold some amount of the liquid, and automatically receives additional liquid from the liquid storage vessel to maintain the dispensing vessel's liquid level to its capacity; and

a thermoelectric cooler (TEC) heat-exchangeably coupled to the liquid, whereby the controller applies power to the TEC to cool the liquid when the liquid is substantially at or above a predetermined temperature.

**27.** The apparatus of claim **17** wherein the controller applies power to the TEC to heat the liquid when the liquid is substantially at or below a second predetermined temperature.

**28.** The apparatus of claim **18** further comprising a resistive element heat-configured to heat the liquid and whereby the controller applies power to the TEC or the resistive element to heat the liquid when the liquid is substantially at or below a second predetermined temperature.

\* \* \* \* \*