



(19) **United States**

(12) **Patent Application Publication**  
Spaur et al.

(10) **Pub. No.: US 2004/0185842 A1**

(43) **Pub. Date: Sep. 23, 2004**

(54) **SECURE TELEMATICS**

**Publication Classification**

(76) Inventors: **Charles W. Spaur**, Aurora, CO (US);  
**Patrick J. Kennedy**, Boulder, CO (US);  
**Michael F. Braitberg**, Boulder, CO (US);  
**Axel Fuchs**, Park Ridge, IL (US);  
**Nate Klingenstein**, Boulder, CO (US);  
**Lane Lee**, Boulder, CO (US)

(51) **Int. Cl.7** ..... **H04M 3/00**

(52) **U.S. Cl.** ..... **455/420; 455/410**

(57) **ABSTRACT**

A telematics system that includes a security controller is provided. The security controller is responsible for ensuring secure access to and controlled use of resources in the vehicle. The security measures relied on by the security controller can be based on digital certificates that grant rights to certificate holders, e.g., application developers. In the case in which applications are to be used with vehicle resources, procedures are implemented to make sure that certified applications do not jeopardize vehicle resource security and vehicle users' safety. Relationships among interested entities are established to promote and support secure vehicle resource access and usage. The entities can include vehicle makers, communication service providers, communication apparatus vendors, vehicle subsystem suppliers, application developers, as well as vehicle owners/users. At least some of the entities can be members of a federation established to enhance and facilitate secure access and usage of vehicle resources.


Correspondence Address:  
**SHERIDAN ROSS PC**  
**1560 BROADWAY**  
**SUITE 1200**  
**DENVER, CO 80202**


(21) Appl. No.: **10/767,548**

(22) Filed: **Jan. 28, 2004**

**Related U.S. Application Data**


(60) Provisional application No. 60/443,505, filed on Jan. 28, 2003.





MOST, IDB1394, I TTP, CAN,  
 FlexRay, LIN, SAE J1708/1587, SAE J1939,  
 SAE J1850, ISO9141

Fig. 1



KDC-Modeled Security Controller




Fig. 3

Flows between the Origin and Target may need to be encrypted to protect against "man-in-the-middle" attacks

The Origin Application may remain anonymous to the Target Service throughout the transaction.

The assertion check in step 8 could be done against the Security Controller's PKC, eliminating the need for Target Service to Security Controller communication.




Fig. 4

Anonymous Toll Payment - Airport Shuttle





Fig. 5

Anonymous, Secure Cab Fare Payment



Secure Vehicle Location Access





Fig. 7

Secure Access to Vehicle Bus by Consumer Device



## SECURE TELEMATICS

### FIELD OF THE INVENTION

[0001] The present invention relates to telematics and in particular to securing communications involving uses of proprietary resources in a vehicle.

### BACKGROUND OF THE INVENTION

[0002] Technologies have been devised or advanced that contribute to expanding the use of commercial and personal vehicles from merely a form of transportation to acting as communication hubs. The vehicle is able to communicate wirelessly with remote systems in order to serve or facilitate a number of objectives including related to safety, navigation, information gathering, entertainment and education. Communications in and with the vehicle typically involve a cellular phone or other communication source/device that is able to send and receive communications from outside the vehicle.

[0003] Although significant efforts have been directed to improving vehicle communications, substantial barriers remain to fulfill the vast potential of the telematics field. Vehicle communications can require a number of systems and devices that can include hardware and/or software resident in the vehicle. These can be proprietary to certain entities, such as owners or lessees. There is great reluctance on the part of vehicle makers and others to allowing use of proprietary systems by third parties. In the context of the car manufacturer, it may have numerous proprietary rights in vehicle interfaces, storage memories, vehicle buses, and vehicle devices. There are concerns with the safety and integrity of such systems if third parties were allowed unauthorized or uncontrolled access. There must also be sufficient economic and financial reasons to permit access and use by third parties. Consequently, it is important not only to provide a physical infrastructure that facilitates communications involving the vehicle, but also economic incentives and acceptable returns on investment.

[0004] Unleashing the potential of telematics requires cooperation among various entities, including car makers, manufacturers of communication devices including cellular telephones, developers of applications and communication service providers. One or more of these entities has proprietary technologies or interests that must be taken into account and safeguarded. For example, handset manufacturers interface to the handset and vehicle manufacturers interface to vehicle devices. Until there are compelling applications that make use of proprietary vehicle systems and technologies in place to protect proprietary rights, telematics development will be inhibited. Furthermore, vehicles themselves are complex systems where reliability is critical for human safety. Any modifications to the tested and deployed vehicle systems introduces new risk. On the other hand, if proprietary systems can be rendered secure and shared by the various entities, the issue of security is no longer a draw-back and overall costs associated with vehicle communications can be reduced. Additionally, a rich set of applications can be developed once acceptable access to proprietary systems in the vehicle are made available.

[0005] It would be advantageous therefore to provide a framework for protecting the proprietary systems and the interests of multiple parties, including the end user, who are

involved with numerous and diverse vehicle communications. The interests of the end user is can include in at least certain applications protection of the user's privacy. Privacy of the end user might be safeguarded when utilizing resources in the vehicle to conduct financial transactions. In addition to appropriate security and/or privacy protection, it would also be appropriate to establish relationships among the various parties that provide incentive for providing open access to resources associated with vehicles including acceptable remuneration.

### SUMMARY OF THE INVENTION

[0006] In accordance with the present invention, system and method are provided for utilizing resources, including proprietary resources in a vehicle. Such utilization requires establishing relationships between and/or among entities having interests, proprietary and otherwise, in resources that are found in the vehicle or can be located in the vehicle. Establishment of relationships includes defining compensation provisions between or among various entities, together with approving resources to be used with proprietary and/or non-proprietary resources found in the vehicle and ensuring that only approved resources are used.

[0007] The proprietary resources can include one or more of the following: vehicle buses, vehicle devices, interfaces, subsystems, storage memory in the vehicle, applications executed in the vehicle, connectivity hardware/software and communication devices. Digital buses in the vehicle might include: MOST, IDB 1394, TTP, CAN, FlexRay, LIN, SAE J1939, SAE J1708/1587, SAE J1850, ISO9141, as well as a common bus to which numerous proprietary and non-proprietary resources communicate. The common bus can be based on one or more of the above-noted bus technologies. The common bus could also be implemented using wireless technologies. Proprietary subsystems and/or vehicle devices might include various electronic control units (ECUs) a navigational global positioning system (GPS), an inflator subsystem or device, a personal digital assistant (PDA), a laptop computer, a vehicle monitoring system (VMS) and an accident and emergency notification alarm (AENA). Interfaces might include numerous and diverse application programming interfaces (APIs). Communication subsystems might include portable or cellular telephones and subsystems that communicate with wireless technology networks using licensed and unlicensed communication channels. Proprietary and/or non-proprietary applications might include applications related to entertainment delivered to the vehicle, data gathering from the vehicle, educational information supplied to the vehicle, information sent to the vehicle for use by one or more subsystems and/or vehicle devices in the vehicle. Such applications can be in a variety of fields or areas including related to security services, multi-user services, vehicle-to-vehicle communication services, geographical services, regulatory services, communication services and commerce services.

[0008] The entities with whom relationships can be built based on mutually acceptable conditions include the vehicle makers as the primary entity and other entities including application developers/providers, governmental entities, communication, financial, business and consumer service providers, providers of products and proprietary subsystems and/or device suppliers, as well as vehicle owners/users. The conditions under which two or more of these entities are to

cooperate can be based on one or more fixed payments, use payments to be made by at least one entity to at least another entity, geographic requirements, resource usage limitations, and remedies for non-compliance. A key factor related to establishing the necessary relationships includes certifying resources for use with each other, while taking into account the safety of those involved with such resources and the security of the resources. At least some of the entities can be members of a federation that is implemented by a federated security architecture in which member entities accept security requirements and protocols as part of interacting with each other.

**[0009]** The resources of the system include one or more communication subsystems that enable wireless communications relative to the vehicle. These communication subsystems might include cellular telephones together with their associated interfaces, and other apparatuses for enabling communications with one or more appropriate wireless technologies, such as a wireless LAN (Local Area Network). The system can also include a vehicle gateway that allows access to information obtained from vehicle devices that are connected to vehicle buses. In a preferred embodiment, the vehicle gateway communicates with the common bus to which a number of proprietary and/or non-proprietary resources can also communicate.

**[0010]** The system also includes a security controller that is connected to the common bus. The security controller can act as a hub through which all information passes in connection with achieving desired security, especially controlling usage of resources by more than one entity. The security controller is involved with security authentication of entities and/or resources, facilitates secure channel establishment between or among entities and/or resources and provides bus and bandwidth arbitration services. The security controller essentially acts as a switch in the system and can act as a proxy for other resources or services. All traffic between or among entities and/or resources is routed by or initiation is mediated by the security controller. After a secure session has been established, the security controller need only be involved as necessary to monitor traffic. Monitoring can relate to verifying that the traffic conforms to the predetermined profile, for example, of one or more particular applications. In one embodiment, the security controller is not integrated into the common bus as a hub or switch, but communicates with the common bus and monitors activities related to security in order to effect its control in connection with assuring that conditions associated with the established relationships are met.

**[0011]** In a preferred embodiment, the system further includes a number of interface modules for which the security controller could provide authentication services. These can be identified as a communication services module, a human/machine interface services module and vehicle services module. The communication services module protects and arbitrates access to resources related to communication. The human interface services module arbitrates access to resources related to display and operator intervention or involvement. The vehicle services module controls access to vehicle gateway services including assistance related to accessing information obtained from vehicle devices that are connected to one or more vehicle buses. In one embodiment, these interface modules may be incorporated in the security controller.

**[0012]** With regard to steps, operations and/or procedures implementing or involving the system, entities accept conditions that establish their relationships. The conditions can be the same for three or more entities or they can be different. For example, establishing relationships might involve a vehicle maker and an application owner or another having a proprietary interest in an application that is used or is executable with a proprietary vehicle device. Another relationship might be established between this same car maker and a proprietary subsystems supplier, such as an after market vehicle device or an add-on vehicle device. The conditions accepted by the car maker and subsystem supplier may be different from those that establish the relationship between the car maker and the application developer or other application providing entity. Relatedly, such an application entity might establish a relationship with the subsystem supplier that includes conditions that are the same or different from those that establish the relationship between the car maker and the subsystem supplier. These conditions can relate to compensation and resource usage.

**[0013]** The establishment of relationships can also involve empowering a certificate authority, who can issue assertions, credentials or certificates that are to be used by the system. The certificate authority is fundamentally responsible for issuing certificates in a secure manner to approved resources for use in the vehicle. Such resources may be proprietary or non-proprietary. These resources can include applications that utilize other resources. A certificate authority can be one of the entities that is included in the group that establishes relationships, such as a vehicle maker, or the certificate authority could be an independent third party. There can be more than one certificate authority and a certificate authority could reside with the vehicle that issues credentials to resources within the vehicular security domain. The security controller itself could act as a certificate authority and issue certificates to vehicle subsystems or other vehicle resources. In addition to issuing certificates for approved applications and/or subsystems, the certificate authority could also be involved with certifying one or more entities themselves.

**[0014]** In one embodiment, the certification process has the certificate authority being initialized with one or more signature keys associated with supporting desired security. The certificate authority could create a public key and a private key pair. The public key is delivered to the security controller and can be used to verify or authenticate one or more certificate signatures that are submitted to it. The certificate authority could also issue keys to an application developer that allows one or more applications to make certificate requests. For example, the certificate authority could create at least a certificate request private key that it sends to the application developer. The application developer uses that private key to generate an application certificate request that is sent to the certificate authority. The certificate authority determines whether or not to grant the certificate request. In connection with that determination, certain procedures can be implemented. These procedures can be implemented by the certificate authority or, alternatively, another entity such as an application verification authority. Such an authority can perform steps related to auditing the application developer's security practices and testing the application in a number of system environments for behavioral and safety considerations. When there is approval, the certificate authority can issue the certificate. The certificate can include certain properties and/or rights,

such as: a unique identifier for the certificate owner, a priority level assigned to the application, duration of the certificate, geographic or other location where the certificate is deemed valid, the identification or description of other resources and/or entities with which the application must communicate to function properly, and APIs that the application is allowed to use.

[0015] The certification process may also be associated with other aspects of the relationships that have been established, such as being correlated with compensation affinity credits or royalties that might be paid as part of one or more conditions accepted by the involved entities. A certificate may also be revoked for an application that has been compromised. The security controller is provided with revocation information so that during its authentication process it can determine whether or not the certificate for a particular application has been revoked.

[0016] After the certificate is granted for an application, access and use according to the contents of the certificate are allowed. As part of its functions, the security controller can monitor the access sought by such an application. After authorization by the security controller, the application can work with one or more resources in the vehicle based on the properties and/or rights set out in the certificate. As previously noted, the application can take many forms in numerous and diverse fields for a large number of uses or functions.

[0017] Based on the foregoing summary, a number of advantages of the present invention are readily understood. The present invention expands telematics usage in a vehicle by providing architecture and methodology so that desired incentives and security are met. Development of numerous and diverse applications for vehicle communications are encouraged and supported. Vehicle resource usage can be enhanced by the framework of the present invention. Passenger safety and convenience are fostered by facilitating more and different ways to communicate with the vehicle and its passengers. Sharing of resources should lead to more services for the vehicle user and concomitant reductions in cost. More specifically, the present invention protects the integrity of vehicle resources. Privacy of user and vehicle information is benefitted. Telematics applications are able to more safely access and utilize resources in the vehicle. Standards and procedures are provided related to achieving desired security at the application level. Selective and secure enabling of functions associated with the vehicle is advanced. Opportunities are promoted for additional revenue streams, such as pay for use applications and subscriptions. Secure remote diagnostic capabilities and secure upgrades of vehicle software are included. New business or market models are facilitated including mobile advertising and customer affinity programs. Multiple vehicle buses can be rendered more robust and adaptable in communicating with other vehicle resources. The intelligent and secure selection of communication paths are also provided. Security measures can be implemented using a federated security framework that protects user privacy when accessing resources involved with providing of services and/or products for consumers and/or businesses.

[0018] Additional advantages of the present invention will become readily apparent from the following discussion, particularly when taken together with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0019] FIG. 1 is a block diagram of an embodiment of the system of the present invention in which the security controller acts as a central hub or switch;

[0020] FIG. 2 is a block diagram of another embodiment of the system in which the security controller implements security functions for the system but is not a central hub or switch;

[0021] FIG. 3 is a diagram that illustrates steps and communications for authorizing/authenticating use of a target service by an origin application;

[0022] FIG. 4 is a diagram that illustrates steps and communications for securely purchasing a product (e.g., quick food purchase application) in a federated security framework;

[0023] FIG. 5 is a diagram that illustrates steps and communications for securely making a toll payment in a federated security framework;

[0024] FIG. 6 is a diagram that illustrates steps and communications for securely making a transportation payment in a federated security framework;

[0025] FIG. 7 is a diagram that illustrates steps and communications for securely obtaining vehicle location access information in a federated security framework; and

[0026] FIG. 8 is a diagram that illustrates steps and communications for securely allowing access to a vehicle bus by a consumer device in a federated security framework.

#### DETAILED DESCRIPTION

[0027] Referring to FIG. 1, a telematics secure system 20 is illustrated that can be located with a vehicle. The system 20 includes apparatuses or subsystems for providing communications to and from the vehicle. Although one or more of a number of apparatuses could be employed including an embedded cellular transceiver and later developed apparatuses, certain apparatuses are noted. A cellular phone 24 can be held in the vehicle for transmitting/receiving digital and/or analog information, such as voice and digital commands and digital data. The cellular phone 24 permits wireless communications outside the vehicle including to/from remote sources that wish to communicate with vehicle resources. The cellular phone 24 can be physically held and electronically adapted to vehicle communication paths using a docking/interfaces subsystem 28. This subsystem 28 facilitates communications for the vehicle user (driver and/or passenger), particularly where the cellular phone 24 is being operated in a hands-free mode. Like the cellular phone 24 that can be selected from various makes and models of cellular telephones, the docking/interfaces subsystem 28 can be one or more different apparatuses that are compatible with the particular cellular phone 24 that is selected and utilized. Implementations of certain docking/interfaces subsystems are disclosed in patents assigned to the same assignee as the owner of the present application including U.S. Pat. No. 5,333,177 issued Jul. 26, 1994; U.S. Pat. No. 5,535,274 issued Jul. 9, 1996; U.S. Pat. No. 6,377,825 issued Apr. 23, 2002; and U.S. Pat. No. 6,341,218 issued Jan. 22, 2002.

[0028] In one embodiment, the docking/interfaces subsystem 28 communicates or is associated with a communi-

cation services module **32**. The module **32** can be software comprised of executable program code that protects and arbitrates access to communication resources in or involved with the vehicle. Fundamental functions that can be associated with the communications services module **32** include: supporting communication paths to the Internet for other resources associated with the vehicle; contributing to secure communications on one or more buses found in the vehicle; outputting fault notifications; monitoring and logging usage of communications-related resources; enforcing usage rules for communication resources and managing tools involved with security control, including authentication and authorization related to usage of links and/or resources associated with the vehicle. The communications services module **32** could also be used to support automatic or intelligent selection of communication links, as described in U.S. Pat. No. 6,122,514 issued Sep. 19, 2000 and which is also assigned to the assignee of the present application. Other wireless communication subsystems that can be included with the vehicle include a wireless LAN **36** and a wireless PAN **38**. Like the cellular phone **24**, the wireless LAN **36** and wireless PAN **38** subsystems can communicate with a compatible interface (e.g. docking/interfaces **28**) for providing transmissions to the vehicle and sending transmissions from the vehicle, which are properly arbitrated and protected using the communication services module **32**.

[0029] In addition to communication resources, the system **20** can include human interface **40** to permit operator or human interaction or control and can also provide information to the vehicle user by means of visual displays and/or audio outputs. The human interface **40** may have a number of input/output mechanisms or devices. These can include a tactile and/or biometric input subsystem(s) **44** that are implemented using appropriate technologies for receiving certain sensory inputs, such as those produced by touch or contact. The tactile devices can include programmable input elements, such as buttons, switches, touch points/ screens, that enable the user to input desired control information or to modify existing settings. Inputs related to visual or scanned information can also be supplied using one or more of these subsystems **44**. One or more voice/audio inputs or subsystems **48** can also be part of the human interface **40**. These subsystems or technologies enable voice inputs to be received for desired control/command objectives useful in initiating or otherwise controlling voice-recognition functions. The audio outputs from such subsystem(s) **48** can be provided for any number of purposes, including entertainment, education, pre-recorded voice prompts, and other information desirable objectives, including providing responses and directions (text-to-speech outputs) based on voice inputs. One or more displays **52** can be part of the human interface **40**. The display or one of the displays **52** can be for navigation purposes to present location-related information. The display or displays **52** can also be used to depict requested vehicle device information. The media input **56** can include one or more subsystems that enable desired media to be seen and/or heard within the vehicle, such as a hard disk as a storage medium, DVD and CD-ROM machines and a map database. Generally, the human interface **40** is part of the vehicle and has one or more components and/or subsystems that are proprietary to the vehicle maker.

[0030] Like the communication resources, the human interface **40** has a human/machine interface services module

**64** that is similar in many respects to the communication services module **32**. The human/machine interface services module **64** functions to support secure communications on one or more of the vehicle buses, provides fault notification related to the human interface **40**, can monitor and log resource usage associated with operator subsystems and components, polices usage rules associated with the human interface **40** and can also be involved with overseeing and managing tools involved with verifying proper usage of component/subsystems of the human interface **40**.

[0031] A number of other subsystems can also be incorporated, either permanently or removably, as part of the telematics secure system **20**. The subsystems can be provided as part of the original vehicle equipment or included later as vehicle add-ons. They can be proprietary or non-proprietary resources. Proprietary interest(s) in such subsystems can reside in the vehicle makers themselves or in other parties having authorized access to the vehicle. The subsystems can include a global positioning system (GPS) **70** that provides geographic or locational information associated with the vehicle, one or more computers **74**, and storage memory **76**. The computer or computers **74** can be portable and removable from the vehicle or embedded with the vehicle for use by vehicle passengers. The computer(s) **74** can include a personal digital assistant (PDA) a laptop or any other intelligent and/or processing unit. The computer(s) **74** can be used to send and receive communications relative to the other resources of the system **20**, as well as communications externally of the vehicle. The storage memory **76** can contain proprietary data and/or program code that involves use of other resources located within and/or outside of the vehicle. The storage memory **76** can also encompass one or more hard disks and/or removable memory, such as CD-ROMs.

[0032] The subsystems can also include an assertion repository **78** which functions to store and retrieve signed or unsigned information that may be generated by devices **88** within the vehicle or may be generated by entities involved with or supporting security measures within the vehicle or any other authorized third party. Such information can comprise assertions that include information or statements related to characteristics associated with an entity involved with the communication, transaction and/or other activity being conducted, or sought to be conducted, using one or more vehicle resources. The content of the assertion can be varied in other ways to provide enough information to grant desired access and/or use, while preserving privacy of one or more users or involved parties. Relatedly, based on the content of a particular assertion, rights, obligations and/or abilities associated with the communication, transaction and/or other can be defined or described.

[0033] The assertion repository **78** may include a policy decision engine **82** and a database **90**. The policy decision engine **82** is responsible for deciding which information of a plurality of stored information is to be released to a particular request. The factors that might be relied upon by the decision engine **82** in making its determinations can include the identity of the requester, the information being requested and the existence of an appropriate user's consent. One or more decisions may also be based on information or results from communications with third parties. Third parties may also be utilized to obtain additional information for release. The decision engine **82** can also be configured to

handle requests to store additional information in the database **90** and make decisions on whether or not to accept such additional information. The signed or unsigned information can be applicable to granting or denying authorization to use a particular service or product provider, i.e. target provider. The database **90** can store any number of signed or unsigned assertions related to allowing access in connection with obtaining a particular service or product, or information. These assertions are available for request by the policy decision engine **82**, and the database **90** is configured to release this information only to or with the authorization of the decision engine **82**. The database can be implemented using any number of data storage techniques such as relational and/or object databases and including LDAP, XML, and SQL. Appropriate applications for the assertion repository **78** will be described later herein in the context of discussions about uses of the secure telematics system **20**.

[0034] Additional resources found in the vehicle can include a vehicle gateway **80**. The vehicle gateway **80** conventionally communicates with one or more vehicle buses **84** to which one or more vehicle devices **88** are connected or communicate with using electronic control units (ECUs) **86**. Each ECU **86** interfaces one or more of the digital buses **84** with a particular vehicle device **88** and each such ECU can be individually designated as **86a**, **86b**, **86c**. . . . The ECU **86** can include one more of a number of different control subsystems such as a body control, a chassis control, an engine control, a transmission control and a telematics control. The body control typically controls all interior equipment such as seats, HVAC, instrument cluster, power windows, power doors and other vehicle devices. The vehicle devices **88** can be separately identified as **88a**, **88b**, **88c**. . . . The vehicle buses **84** can be one or more digital buses and can include known buses identified as MOST, IDB 1394, TTP, CAN, FlexRay, LIN, SAE J1708/1587, SAE J1939, SAE J1850, ISO9141. The vehicle devices **88** can include an engine monitor, an engine temperature sensor, a pressure sensor, an inflator system for activating air bags and/or vehicular tension-producing devices (e.g., for tensioning seat belts). The vehicle gateway **80** controls access to and use of the vehicle buses **84**. Relatedly, by means of the vehicle gateway **80**, commands can be sent on one or more buses **84** to one or more selected devices **88** that are connected to the particular bus or buses **84**. The vehicle gateway **80** can also have wireless communication interfaces, as well as directly receive remote wireless input(s) by means of an antenna or the like. Such input(s) could be used to supply control signals to vehicle devices **88** including those used in supporting the locking/unlocking of vehicle doors and remote vehicle engine starting.

[0035] In communication with the vehicle gateway **80** is a vehicle services module **92**. Similar to the communication services module **32** and the human/machine interface services module **64**, communications relative to the vehicle gateway **80** pass through the vehicle services module **92** in order to control access to vehicle gateway controlled vehicle buses **84** and vehicle devices **88**. The functions of the vehicle services module **92** include supporting secure communications on one or more vehicle or telematics buses **84**, contributing to the enablement of intra-vehicle wireless communications (e.g. PAN, such as Bluetooth), arbitrating vehicle bus access for outgoing requests, providing fault notification related to vehicle gateway operations, monitoring and logging usage of the vehicle gateway **80**, vehicle

buses **84** and/or vehicle devices **88**, enforcing rules related to uses of such resources that communicate with the vehicle gateway **80**, and managing tools related to providing security, such as access keys and certificates approving access.

[0036] With regard to enabling communications in a secure manner, the system **20** preferably includes a common bus **96** with which a number of, if not all, communicable resources in the vehicle communicate. In this embodiment, the common bus **96** can link these resources to a security controller **100**, which acts as a hub or switch through which communications pass relative to the communicable resources. Although represented in **FIG. 1** as separate lines or connections to the security controller **100**, it should be appreciated that all such lines when linked together represent a common bus. The common bus **96** can be based on one of a number of available bus technologies including those that provide or implement the vehicle or digital buses **84**. The common bus **96** could also be implemented using wireless technologies.

[0037] The common bus **96** can be defined to include a physical layer and a logical layer. The physical communication layer of the common bus **96** connects the different resources of the system **20** together. Vehicle manufacturers would typically control the characteristics of such buses. The common bus **96** should have at least the following capabilities: sufficient bandwidth to support applications, an open architecture, standardized features, be widely supported, be multiplexed and have peer-to-peer functionality available. The logical layer provides the manner by which resources on the common bus **96** communicate with each other. The logical layer is configured so that different resources from different manufacturers can be properly linked to and communicate with the bus. The logical layer can be comprised of several different protocols to enable communication between or among devices, services and application program interfaces (APIs) that facilitate requests for certain services. Services may define their own APIs for communication with other devices. APIs that may be defined include: the security controller **100** to establish secure connections between resources or between a resource and a hub; a communication services API enabling Internet and wireless communications for resources on the common bus **96**; a vehicle gateway services API enabling status retrieval and control services for the vehicle; an API for the GPS **70** to enable transmissions of position information; a display API for displaying information using the operator unit **40**; registration related APIs to register resource capabilities; and broadcast related APIs for general dispersal of information. Some APIs are already available, for example, AMI-C (Automotive Multi-Media Interface Collaboration) has a defined set of protocols for communication with the vehicle gateway **80**. Security protocols associated with the system **20** are to be compatible with AMI-C, as well as other existing protocols.

[0038] The successful growth of telematics requires safeguards against unauthorized requests to vehicle resources so as not to allow adverse impacts on vehicle operations. Vehicle communications may be classified from those that entail essentially no risk to those having high risks, with different risk levels in between, such as low risk and medium risk. The degree of risk can be based on a number of factors including sensitivity of information, privacy of information, and extent of detrimental effects that can occur when there

is an unauthorized communication. A risk can be assessed based on key factors that include the resource or resources involved with the sending function and the resource or resources involved with the receiving function. A key risk factor relates to the particular application involved with a transmission. Applications can include changing configurations of vehicle devices or equipment; displaying vehicle status, upgrading firmware in the vehicle, conducting vehicle diagnostics, downloading one or more applications, downloading media information, downloading advertising, obtaining position information and updating or checking security assertions.

[0039] In one embodiment, the security controller **100** can include one or more secure processors and a GPS receiver that is embedded or integral with the secure processor. This combination can effect appropriate secure operations, especially when it is desired to accurately associate GPS information with one or more particular security controller operations. Preferably, the security controller **100** is configured in the system **20** as a central hub or switch through which all traffic involving resources passes. After a secure session has been established, the security controller **100** need only be involved as necessary to monitor data or other information including one or more applications. The security controller **100** can be implemented as a single chip. Representative responsibilities and functions of the security controller **100** are:

[0040] User authentication—the security controller **100** may be involved with storing a number of log-ins and can acquire authentication information in connection with conducting the log-ins. The security controller **100** may trust an authentication service, entity or other resource that can maintain a set of credentials for each log-in and inform the security controller **100** regarding the identity of each log-in. In such a way, the security controller **100** manages identities. For example, the log-in might be performed when the ignition of the vehicle is activated and the authentication services are provided by the owner of a taxi fleet. As another example, a smart card might perform the log-in using a central hospital as an authentication service, which is trusted by the security controller **100**. The security controller **100** may store user identification information in one or more of a number of forms including a personal identification number (PIN) smart card, password or by means of biometric information. This information can be passed to the security controller **100** through one or more apparatuses or devices communicating with the communication services module **32**, such as the cellular phone **24**, W-LAN subsystem **36** and/or the W-PAN subsystem **38** or, alternatively, through the human/machine interface services module **64** that can receive vehicle user identification information from the human interface **40**.

[0041] Secure location and time—either as an integral unit or as a stand-alone device with which it communicates, the security controller **100** can communicate with a GPS receiver (e.g., GPS **70**). This receiver provides a secure source of location and time information. The GPS receiver is configured to eliminate or minimize tampering with the information that it provides. This trusted time and location information can be used to check against any location restrictions that might apply to certain resources in the vehicle.

[0042] Security monitoring—the security controller **100** monitors common bus **96** activity and vehicle bus **84** activity between or among resources to ensure that the security conditions established during configuration or authentication continue to be met over time. For example, if there were a time condition related to bus activity, the security controller **100** could dynamically discontinue the secure channel connection after a predetermined time event.

[0043] Bus arbitration—the security controller **100** can provide arbitration between high priority and low priority activity on one or more buses located in the vehicle. For example, when there is an emergency, the security controller **100** might halt all low priority activity, such as digital audio or video.

[0044] Application authentication (public key infrastructure)—the security controller **100** contains a registry of digital credential information associated with registered resources. When an application requires secure access to the common bus **96**, it presents its credential, or certificate indicative of such credential(s), to the security controller **100**. Generally, access to the common bus **96** is denied unless all traffic on the bus **96** is encrypted. The security controller **100** is responsible for ensuring security on the bus **96**, while applications listen to encrypted traffic. The security controller **100** may reject an application requesting access to the common bus **96** on a number of grounds, such as an invalid certificate authority signature, invalid or unknown properties, time expiration or revocation of the certificate. If the certificate is deemed authentic, the security controller **100** requests that the application prove that it is the principal of the credential by presenting valid access information, such as performing a cryptographic operation using the associated private key. Upon successful response, the security controller **100** can open a secure channel with the application for future transactions or transmissions. In the case of Internet applications, laptop usage, PDA usage, or consumer applications, each individual application is required to authenticate with the security controller **100**. A more detailed description of digital certificates will follow herein. A related embodiment for application authentication involving a federated architecture will also be described.

[0045] Multiple keys—the security controller **100** can also require more than one key or other security tool to be able to access one or more functions. More than one factor or requirement may be necessary to authenticate an application or a particular entity/user. For example, configuring the settings for a vehicle may require the physical presence of a particular phone (first factor) as well as a particular PIN or password entered through the human interface **40** (second factor). Additional factors may include time, location information, biometric information from the operator or user (fingerprint, voice print, facial print and the like) or third-party information, such as may be required over the Internet, before authentication of a user.

[0046] Multiple resources—the security controller **100** can enable multiple resources to participate or be associated with one application. For example, executing a navigation application might require authentication of software running on a display of the operator unit **40**, the vehicle gateway **80** and the GPS **70**. Many other examples are feasible including using an application that requires GPS location and GPS time.

[0047] Multiple public key protocols and algorithms—the security controller **100** may utilize or be aware of several public key infrastructure (PKI) protocols while a particular resource may have information about only one such protocol. This allows application providers to select from a number of protocols and algorithms as are appropriate for their communications. However, a single algorithm can be chosen so that there are proper communications once a secured channel has been established.

[0048] Carry-in device firewall—to support any interface to a computer **74** that can be used in the vehicle, security firewall functions can be built into the security controller **100**. The firewall protects resources in the vehicle from invalid, unwanted or malformed requests. Applications running on such carry-in computers that require access to services and information provided by the system **20** require certification. The security controller **100** handles authentication and key exchange with such applications. If a particular application is not certified, the security controller **100** can allow certain, predetermined vehicle services to be made available to non-certified applications.

[0049] With reference to **FIG. 2**, another embodiment of a telematic secure system **20-1** is illustrated. The security controller **100-1** is included in the system **20-1** as another apparatus or resource on the common bus **96-1**. According to this architecture, the security controller **100-1** performs all the security functions that are available in the embodiment of **FIG. 1**. However, the security controller **100-1** does not serve as a switch on the common bus **96-1**, unlike the **FIG. 1** embodiment. This can be a drawback to the effectiveness of the security controller **100-1** since its ability to isolate segments of the common bus **96-1** does not exist inasmuch as it is no longer a switch or central hub through which all communications pass between and among resources on the common bus **96-1**. However, multiple key authentication, location-based authentication and certificate management can still be performed by the security controller **100-1**. In another embodiment, the security controller **100** may also be merged with any one of the services modules, for example, the communication services module **32**, the human/machine interface services module **64** and/or the vehicle services module **92**. This configuration has the advantage of improving the authentication with the resource that it is merged with since no authentication is required as they constitute the same resource. On the other hand, like the embodiment of **FIG. 2**, the ability to isolate the common bus **96** is lost.

[0050] Main functions performed by the security controller **100** relate to authorization for access to and use of the telematics secure system **20**. To perform these functions, the security controller **100** can rely on certain tools involving previously granted digital certificates or other digital security assertions or credentials. A certificate evidences a grant of properties or rights for accessing and using the system **20**. A certificate may apply to a resource, such as an application that is to run in the vehicle using one or more other resources or a proprietary subsystem that is included with the vehicle and which may or may not be removable, e.g., a subsystem that is an add-on to the vehicle by an entity different from the manufacturer of the vehicle. A certificate may also be made available that applies to an entity who has generally established itself as meeting all requirements, including safety and security requirements, for access to and use of resources with the vehicle. In the case of an entity being certified, the

resources from this entity may be deemed acceptable for use with the vehicle in the case in which the entity has a proven record of meeting requirements for resources available from it.

[0051] Generally, a digital certificate is presented to the security controller **100**. The certificate can apply to a resource such as an application. The security controller **100** determines whether the presenter (e.g., owner or licensed user of the application) of the particular certificate has the rights associated with the certificate. Once this verification or authentication scheme is satisfied, a secure channel of communication may be established for the application. The secure channel can include use of adequate encryption.

[0052] The certification process involves a number of procedures and tools. An important part is establishing or identifying a certificate authority (CA) that provide certificates for use in the secure telematics system **20**. The CA is responsible for issuing certificates to approved resources for use in the vehicle and/or entities that provide such resources. The CA can revoke the rights of previously authorized resources and/or entities when certain violations or breaches are determined. The CA is involved with the following, at least some of which will be the subject of later explanation: the security of certificate authority private signature keys; the security of a public key list; the ability to verify that a certificate presenter possesses the associated private key; the ability to assign reasonable properties with each certificate; the ability to automate responses to requests in order to satisfy a large number of certificate requests; and the ability to designate another or secondary CA that is authorized to provide certificate authority functionality instead of the primary CA and which ability can be used to lower bandwidth requirements on the primary CA. The CA can include one or more of a number of entities including one or more vehicle manufacturers, application developers, service providers and representatives thereof, as well as one or more third parties that are independent of vehicle manufacturers and vehicle resource suppliers and/or developers.

[0053] Procedures and processes associated with certification are next discussed, particularly in the context of a certificate or other security credentials or assertions being provided for one or more applications that are intended to be executed within the secure telematics system **20**, although it should be appreciated that such processes and procedures can be adapted to apply to other resources and entities associated with such resources. The main certification processes include: the CA being initialized with one or more CA signature keys; the CA issuing a set of keys to an application developer that allows such applications to make certificate requests; creating a certificate request by the application and delivering it to the CA; and the CA granting the certificate request and returning it to the application.

[0054] With regard to the CA signature key(s) creation process, the CA has a signature key or set of signature keys that are used to sign certificates. The CA signature key generation process is performed once and the key or keys are stored in a physically secure manner. The signature key creation can include the CA creating a CA signature public key (CASPK) and CA signature private key (CASRK) key pair. After its creation, the CA stores the CASRK in a secure manner. The CASPK is delivered by the CA to the security controller **100** where it can be used to verify signatures of

certificates that are submitted to it. Multiple CA signature key pairs can be generated which allow a diversity of signatures on certificates. In such a case, a list public keys is embedded with the security controller **100** for verification and a CA signature key index is added to the certificate.

[**0055**] Next regarding enablement of the generation of certificate requests, certain security tools or information are provided to the developer of the application that is to be a resource for the vehicle. However, before providing such access tools or other information to the developer, the particular application is first approved. In one embodiment, the approval procedures are conducted by an entity different from the CA. This different entity may be termed an application verification authority (AVA). Alternatively, the CA is also responsible for application verification or approval. Regardless of the identity of the entity or entities, it is authorized and responsible for ensuring that applications entering into the system **20** are safe, secure and operate within predetermined guidelines. The approval of the AVA, whether it is the CA or another entity(ies), is obtained before the CA can issue a certificate for the application. Approval from this authorized authority can require the following main processes: submission of the application to the AVA by the application developer; auditing of the application developer security practices by the AVA; testing the application by the AVA in a number of environments involving the system **20** for behavioral and safety determinations; providing written notification to the application developer by the AVA when corrections are required before approval can be granted; and upon passing AVA verification, **25** the CA is notified of application approval, in the case in which the AVA is different from the CA.

[**0056**] With respect to the application submittal process, an application developer is required to request that its application be allowed to enter the secure telematics system **20**. The request requires submittal of the application accompanied with written documentation that can comprise the following: a mutual non-disclosure agreement, a copy of the application, a complete description of the application, one or more reasons for the application to be part of the system **20**, the set of properties and/or rights that the application requires to perform its function(s) and a description of the security infrastructure used to protect one or more private keys.

[**0057**] Regarding the application approval process, the AVA performs a security audit before granting the application developer the ability to enter the system **20** and which audit can include: visiting the application development site by the AVA to make sure that proper security precautions and procedures are in place including to ensure that the protection of keys at the development site and/or at the manufacturing site is sufficient; reviewing the security firmware or other software by the AVA that is related to the protection of one or more keys; and testing of the application in a number of secure telematics system environments to make sure that the application does not jeopardize safety within the vehicle and that the application is sufficiently behaved within the system **20**.

[**0058**] Also with respect to approval, certain relevant factors are considered and/or noted. First, approval of one version of an application does not automatically grant approval to one or more later versions. Secondly, any

application that has received a certificate may be subject to tampering. Members of the hacker community may try to modify the application to make it perform in unexpected or undesirable ways. One or more members of the developer community may modify their own applications after obtaining a valid certificate.

[**0059**] The modification may take the application outside the original specifications or result in security flaws that expose the application to unwanted hacking or attacks. To enforce compliance, the AVA can compute a secure hash of portions of the application and provide that hash to the CA for incorporation into the certificate. Once deployed in the field, the application is required to submit the same portions of itself to the security controller **100**. As part of authentication, the security controller **100** computes the same secure hash and verifies that it matches the value or properties within the certificate.

[**0060**] The application approval process can also entail adherence to guidelines for application developers and guidelines for applications, together with implementation considerations. In that regard, developers of applications may be required to provide for the physical security of keys within their development facilities and manufacturing facilities. For example, gaining physical access to such keys might require a minimum of two persons present at all times. Application developers are to be cognizant of the kinds of attacks that the application may be subjected including communication channel tapping, entity spoofing, denial of service attacks (e.g., network overloading), software or firmware emulation and diagnostic back doors. Application developers may be required to partition the application into modules that fall within the jurisdiction of the verification authority and those that fall outside the jurisdiction of the verification authority. A clear partitioning allows the developer more abilities to revise modules that fall outside the jurisdiction of the verification authority version control mechanisms. Developers of applications can be required to implement a secure download procedure for field updates since a secured download procedure prevents unwanted applications from entering into the secure telematics system

[**0061**] Guidelines for applications can include being sensitive to or highly compatible with the vehicle environment. For example, an application may only be appropriate when the car is not moving and be inappropriate when the car is moving as there may be some distraction to the driver. Each application is required to protect its key or keys such as by means of hardware protection, key obfuscation and encryption techniques. Each application may be required to be aware of priority schema within the system **20**. Some applications may be considered low priority and can be terminated by high priority applications.

[**0062**] Regarding application implementation factors, the verification authority can be responsible for behavioral auditing, security auditing and safety auditing. The verification authority might rely on software and hardware tools to conduct verification or auditing procedures intended to meet these objectives.

[**0063**] Once the developer is determined to have met the requirements of the verification authority, the process related to generating one or more certificate requests can continue. In particular, the CA creates a certificate request public key (CRPK) and a certificate request private key (CRRK) pair.

Concomitantly the CA assigns the key pair a certificate request identifier (CRID). After generation of the key pair and the identifier, the CA delivers the CRID and the CRRK to the developer through secure procedures, paths or means. Such security may involve delivery in person, or through a separate secure channel established during an on-site visit. The CA also creates a new entry in a local database that can be labeled certificate request public key list (CRPKL). The new entry is linked to the developer's CRID for future access capability. The unique identifier may be the next available index to the CRPKL or it may be a globally unique identifier (GUID) or any other unique value that may be used to look up the associated CRPK. The new entry can include the following information:

[0064] (a) the CRPK associated with the application;

[0065] (b) the properties of the certificate to be granted. A property range may be entered which limits the range of requested property values, rights and/or obligations that may be issued by the CA. These properties become part of the certificate when a certificate is granted for the particular application; and/or

[0066] (c) any additional rules associated with the granting of the certificate(s) for the application. These can include a maximum number of certificates to be granted, a limited time period in which to grant certificates and a requirement that a financial transaction be confirmed (e.g., compensation or fee to be paid) prior to issuing the certificate.

[0067] Such information can also include a secure hash of the application. The secure hash involves the reduction of a large amount of data to a small number of bits in such a way that it is mathematically extremely burdensome to revert to the large amount of data without authorization. A secure hash value may be encrypted using a secure session key in order to create a "message authentication code."

[0068] As previously noted, the certificate to be granted has a number of properties or rights. The properties in a certificate may include any amount of information: a unique identifier for the owner of the certificate; the priority level assigned to the application where a higher priority application receives bandwidth allocation before a lower priority application; expiration date and time of the certificate; geographic location where the certificate is valid; wireless LAN "hot spot" identifier where the certificate is valid; other resources that are part of the system 20 that the application needs to communicate with to function correctly (the security controller 100 uses this information to open a common secure channel with all resources required for an application to run correctly); APIs that the application is allowed to use whereby restricting access to certain APIs reduces the security risk of some certificates, e.g., a certificate that only grants access to commands that read the state of vehicle information involves a lower risk than a certificate that grants access to commands that control vehicle services to perform one or more functions; and/or additional authentication that may take the form of user confirmation procedure, or external third-party authentication procedures.

[0069] Once an application developer has been granted the right to utilize the system 20 by means, for example, of receiving a CRRK, it may obtain a certificate by issuing an

application certificate request to the CA. The certificate request process varies depending on the type of application that is receiving the certificate, where the application receives its certificate and how the application is distributed. Applications may request certificates that involve the following:

[0070] an application embedded within an electronics subsystem may request a certificate from the CA during its manufacturing process so that the application ships in a state that is acceptable for use within the secure telematics system 20.

[0071] an application that is to be distributed through a hard medium (e.g. CD-ROM or DVD) undergoes a single certificate request process that is managed by the application developer. As part of its distribution, the certificate and one or more keys are embedded into the application.

[0072] an application may be distributed through a WAN, LAN, or PAN network. The application developer can choose to obtain certificates for the application dynamically at download or perform a one-time certificate request similar to a hard medium distributed application.

[0073] an application may request a new certificate while running in the end-user environment. The application may require a new or updated certificate to gain access to the system 20. This ability allows an application to be enabled by the user in the field by obtaining a new or updated certificate, which may include payment of a fee.

[0074] Regardless of whether the application or the application developer is requesting a certificate, fundamental steps can be implemented that are applicable for virtually all applications including those just identified and which include the application creating a certificate public key (CPK) and a certificate private key (CRK) key pair; the application securely storing the CRK into non-volatile memory; the application creating a certificate request that includes the following components: the CRID that identifies the requestor to the CA, the CPK that is the application's public key, other certificate properties that are required, and a certificate request signature (CRS) that is created by digitally signing all the above-noted information using the CRRK as the key, with the CRS being used to authenticate the requestor to the CA; and the application delivering the request to the CA and which request does not necessarily require a secure channel for transmission.

[0075] With respect to the certificate creation, the CA retrieves the CRPK properties, rules and secure hash from the database using the supplied CRID as a lookup parameter. The CA also validates the CRS using the CRPK. The CA verifies that none of the rules associated with the CRID have failed. For example, the CA verifies that the time period in which the CA grants certificates has not expired. Further, the CA verifies that the requested properties are within the scope of the properties agreed upon during the request to enter into the secure telematics system 20. An application may be unable to ask for a certificate over a certain expiration time. The CA creates the certificate including the properties in secure hash, as well as digitally signing it with a CA signature private key (CASRK). After the foregoing are

implemented, the CA returns the completed certificate to the requester, which return may be conducted across an insecure channel. After receipt, the application is expected to verify that the public key in the certificate matches the CPK that was originally part of the certificate request and verify the authenticity of the certificate by verifying the CA signature.

[0076] With receipt of the certificate, the application can gain access to the secure telematics system **20**. Generally, this includes interaction with the security controller **100**. In particular, the certified application sends a service request with the certificate to the secure controller **100**. The secure controller **100** can return a challenge request to the application that includes a random number encrypted with a public key. The application decrypts the random number using its local private key. The application sends back to the controller **100** a random number response. If the random number received by the controller **100** in response from the application matches the number encrypted for challenge then the service request is granted. Once granted, the controller **100** sends an indication of a service or session to be initiated to the application.

[0077] Certificates usually last until the expiration date. However, there can be predetermined conditions under which a certificate is revoked. By way of example, an application that has been compromised, such as where its private key has been exposed, may be required to be revoked. The CA can maintain a certificate revocation list (CRL) that can be embedded within the security controller **100**. The security controller **100** consults the CRL during its authentication process to ensure that the application has not been revoked. Updating the CRL may be supported by including a requirement for additional third-party authentication within the certificate itself.

[0078] Certificate creation might utilize currently available tool kits that provide security code that can be required for the application developer. These tool kits can include RSA's Cert-C and Certicom's TrustPoint.

[0079] Generated certificates can have other uses including the tracking of fees, payments, royalties or other compensation requirements. In cases where proprietary resources are to be accessed within the system **20**, the issuance of the digital certificates may be used to indicate that such a proprietary resource is to be accessed and/or used. Each time a certificate is created for an application, an entry is made into the certificate database. The database may be queried to retrieve the number of certificates issued that allow access to proprietary resources and a previously determined fee or royalty may be levied in conjunction with such access or use.

[0080] The secure telematics system **20** enables secure applications to be used in a safe manner with one or more other resources associated with the vehicle. Additionally, incentives are provided to owners or others who have proprietary interest in resources to make available their proprietary resources to control the access in use. The proprietary resources, in contrast to non-proprietary resources, are resources in which one or more entities has a legally protectable proprietary interest in the resource. The legally protectable proprietary interest can be based on one or more legally recognized intellectual properties including patents, trade secrets, copyrights and contract-based rights. Resource usage and expansion thereof, particularly use of

proprietary resources, is fostered by establishment of relationships with entities that can be involved with the telematics secure system **20**. These entities can include vehicle makers, communication device vendors, communication services providers, proprietary subsystem suppliers, application developers and vehicle users. Establishment of relationships can include the definition and acceptance of conditions by the entities. Conditions, such as rights and obligations, can be different for different entities or groups of entities. These conditions might include sufficient descriptions or identifications of the resources that can be used; compensation-related factors associated with usage; duration of use; specific definitions or limits of use that can be made of proprietary resources; geographic limitations that define locations within which use can be made; remedies for non-compliance with one or more conditions; and other relevant requirements including obtaining certification as previously discussed including approval of proprietary resources, such as applications, by a designated authority.

[0081] With the proper establishment of relationships in place, together with acceptable security, various uses and/or applications of the telematics secure system **20** can be identified and advanced. For example, a vendor of after market audio equipment may desire access to proprietary and/or non-proprietary resources in the vehicle in order to interface the vehicle radio to controls and displays associated with the operator or head unit **40**. The add-in radio maker may also desire access to the vehicle audio system and hands-free features, such as hands-free cellular telephone usage, that are already contained in or embedded with the vehicle, including voice recognition. Further, access to a vehicle PDA interface may be desirable to allow upload and/or download of personal or other desired data. Such resources can be made available to the after market supplier based on approval of the radio application and obtaining a digital certificate that works with the security controller **100**. In this case, the vehicle maker, as an entity having one or more proprietary interests in one or more proprietary resources associated with the vehicle, can establish a relationship with such a vendor utilizing appropriate conditions including conditions that provide incentives to the vehicle maker, e.g., revenue to be received for such access and use that might be in the form of a one-time fixed payment, by subscription and/or when the vehicle is resold.

[0082] Numerous other applications can be identified or described that might involve applicable resources to be used with other resources associated with the vehicle. There can be many general application areas including related to security, multi-user, geographical, regulatory, communication and commerce. One or more applications may fall into more than one of these groups or categories and other applications may not be clearly delineated into one or more of them. Some representative applications are next described.

[0083] Vehicle configuration—the cellular phone **24** is available to send configuration information into the vehicle. This configuration information may include driver identification, seat position, mirror positions, radio station pre-sets and use of other subsystems or devices located in the vehicle. Upon receiving the information, these can be adjusted under commands from the telematics control unit **80** or other vehicle-resident computing devices. Such an application may require the following steps:

[0084] 1) The cellular telephone **24** is placed in a cradle with power on.

[0085] 2) Operator identification is entered, such as a "PIN", biometric, smart card, voice command and the like.

[0086] 3) The cellular telephone **24** receives this information and the vehicle configuration application is initiated.

[0087] 4) The security controller **100** authenticates the configuration application using, for example, appropriate key exchanges.

[0088] 5) After successful authentication, the security controller enables or authenticates a communication channel with the gateway to the appropriate bus, vehicle bus or buses **84**, which can be the vehicle gateway **80**, if a secure session is not already in progress.

[0089] 6) The security controller **100** chooses a common encrypted session key and distributes it to the cellular phone **24** and the vehicle gateway **80**.

[0090] 7) The vehicle configuration commands are sent from the cellular phone **24** to the vehicle gateway **80** via the secure, encrypted channel.

[0091] 8) The vehicle gateway **80** may verify, when desirable or appropriate, that configuration adjustments are to be performed only when the vehicle is stationary.

[0092] 9) As part of the overall access and use involving the configuration application, a user acknowledgment might be required before any such adjustments are implemented.

[0093] Another representative example of an application can involve the activation of an inflator system, such as an air bag in the vehicle, which triggers a notification that is sent to a designated entity or authority. Relevant steps for this application include:

[0094] 1) During system initialization, a secure alarm channel is established involving the GPS **70**, the vehicle gateway **80**, the security controller **100**, and the communication services module **32** for use during an emergency.

[0095] 2) When a sufficient vehicle impact is detected, an air bag of the inflator system is activated or deployed.

[0096] 3) The vehicle gateway **80** receives one or more air bag related alarms from this vehicle device, which may occur across an embedded vehicle bus **84** when the inflator system is connected thereto.

[0097] 4) The security controller **100** receives the alarm by way of a secure connection.

[0098] 5) The security controller **100** obtains GPS information from the GPS **70** and delivers it to the communication services module **32**. The communication services module **32** initiates communications to notify the remote designated entity or authority of the vehicle using the cellular telephone **24** or other communications subsystems, such as the W-LAN and W-PAN subsystems **36, 38**.

[0099] A navigation application involving a subscription service can also be implemented. By way of example, a vehicle can be sold with a GPS and a navigation application built into the human interface **40**. For the application to continue to work, the subscription must be renewed. A real time certificate is obtained from the certificate authority by creating a certificate request that is validated based on a

verifiable financial transaction. Certain steps are next described related to this application:

[0100] 1) The vehicle user is notified that the navigation subscription is about to expire and is offered the opportunity to continue the service for another term, such as one year of service.

[0101] 2) The user accepts the offer by entering electronic payment information, such as a credit card number. Secondary user authentication may be required to ensure that the user is allowed to make the transaction, i.e., the user is the owner of the vehicle.

[0102] 3) The application requests a secure channel with the financial institution through the communications services module **32**. The security controller **100** enables this transaction by opening a common secure channel between the application and with the financial institution through the communication services module **32**.

[0103] 4) The application and financial service communicate through the secure channel to charge the user's account.

[0104] 5) The financial service responds with a confirmation number for the charge.

[0105] 6) The application creates a certificate request to the certificate authority including the confirmation number of the charge as a receipt of the financial transaction.

[0106] 7) The application sends the certificate request to the CA, which does not require a secure channel.

[0107] 8) The CA receives the request, verifies with the financial institution that the charge occurred and issues a one year certificate for the application.

[0108] 9) The application presents the new certificate to the security controller **100** to enable access by the application to the GPS **70**.

[0109] 10) The CA distributes the subscription notification to the vehicle maker and application developer for possible fees that might be due including royalties.

[0110] The secure telematics system is also involved with certificate-related procedures including assertion repository updates and certificate revocation lists that may involve the following:

[0111] 1) The system **20** receives notification that an update to a certificate is available. This notification can be received via a wireless link or wired connection such as involving a vehicle or digital bus.

[0112] 2) The vehicle user can be notified that the update is available and may acknowledge and/or approve the upload of the update.

[0113] 3) The source of the software or the certificate is authenticated by the security controller **100**.

[0114] 4) The upload might be constrained by location such that it occurs only when the vehicle is located within a certain geographic region. In such a case, the certificate presented for the application to be uploaded contains the identification of the required geographic region.

[0115] 5) The upload can also be constrained by time whereby uploads are only allowed within a certain period of time.

[0116] 6) A secure session involving an encrypted communication is set up between the certificate source and the security controller **100**.

[0117] 7) The update is loaded into the security controller, which may be a new certificate and/or a certificate revocation list.

[0118] 8) The security controller **100** authenticates the certificate and/or CRL by means of a digital signature.

[0119] 9) Optionally, a third party might be consulted to verify authenticity.

[0120] 10) The security controller **100** stores the new certificate and/or CRL in its non-volatile memory.

[0121] Similar procedures or steps can be utilized for an application update. Updates may also be requested by the security controller **100** for expired certificates. Certificates may expire after a predetermined date, which can be useful for subscription-based services. In such cases, a secure time source is necessary, such as the embedded GPS **70**. Wireless communication network clock verifications at local hot spots might also be utilized.

[0122] Further applications are next described according to groups or categories. The following relate to security applications:

[0123] Secure VIN for warranty and quality control—the vehicle maker uses the security controller **100** to ensure that the integrity of stored information related to warranty and quality assurance has not been compromised. An activation log could be included that documents automatic collision notification being sent to a designated entity or authority. The secure VIN certificate/key can be loaded at the vehicle maker's plant.

[0124] Access to car information for vehicle user application—the car maker can use the security controller to grant access to vehicle information, driver information and vehicle control only to the authorized owner. Essentially this can be the secure key to the vehicle for the owner or other authorized user. One example might be to unlock vehicle doors using a cell phone or PDA.

[0125] Secure access for diagnostic tools—the vehicle maker can use the security controller **100** to grant access to diagnostics information and vehicle configuration only to authorized dealers with authorized tools.

[0126] Access for service provider applications—the vehicle maker can use the security controller **100** to grant access to vehicle information, driver information and vehicle control to authorized service providers with authorized tools.

[0127] Access to user interface resources—the vehicle maker can use the security controller **100** to grant access to the vehicle user interfaces only to authorized applications and devices. The vehicle maker may limit the risk for accidents due to driver distraction, e.g., allowing a cell phone to be controlled by steering wheel buttons or built in voice recognition.

[0128] Secure fleet vehicle status—a fleet operator can use the security controller **100** to control access to each vehicle and load status data for its fleet. This information can be securely stored in the vehicle memory **76** and only accessed by authorized entities.

[0129] Secure position data for fleet management—the fleet operator can use the security controller **100** to control access to position data of its fleet. The position information can be securely stored in the vehicle memory **76** and only accessed by authorized entities.

[0130] Protection of position data—the car owner or other authorized user can use the security controller **100** to control access to position data of the owners vehicle. The position information can be securely stored in the vehicle memory and only accessed by authorized entities.

[0131] Vehicle tracking and security—internal GPS assets, vehicle bus access and vehicle telecommunications can offer many levels of vehicle safety and security such as being aware of the current location of hazardous materials being transported by trucking companies.

[0132] The telematics secure system **20** is adaptable for multi-user applications including:

[0133] A number of authorized vehicle users—resources associated with the system **20** can be specially and uniquely configured for each authorized user of the same vehicle, for example, in providing communication options such as: filtering of “hot spots” for each user based on the particular user's special interests; limiting or presetting vehicle controls for each family member, valet or authorized vehicle operator; and subscriptions associated with particular user authentication.

[0134] Rental car customization—the rental vehicle user can interact with the rented vehicle in order to use a personal cell phone and/or upload a personal directory for radio station preferences.

[0135] The telematics secure system **20** can be accessed for geographical and/or regulatory applications which might include:

[0136] Traffic information subscription-various levels of traffic maps, warnings and special routings can be displayed using a navigation display screen that might be part of the operator **20** unit **40**.

[0137] Vehicle pollution control—the system **20** might be accessed to modify or adjust controls in the vehicle in order to reduce emissions or switch the vehicle to electric power.

[0138] Current road conditions—advanced warning of upcoming road construction or major accidents can be provided using a wireless link warning station that can broadcast the relevant information at a distance from the construction or accident. The vehicle user or driver can be warned using a display or audio information by means of the human interface **40**.

[0139] Weather conditions—advanced warning of weather hazards, such as fog, ice and/or snow can be provided using the system **20** so that the vehicle driver has sufficient time to take appropriate action including the possibility of changing to a different route.

[0140] Border crossing and inspection—governmental entities may use the security controller **100** to control access to vehicle data related to border crossings and weight inspection. Such information can be securely stored in the vehicle memory **76** and only accessed by authorized entities.

[0141] Smog testing—governmental entities may use the security controller **100** to control access to vehicle data related to smog tests. Such information can be securely stored in the vehicle memory and only accessed by authorized entities.

[0142] Another category of applications generally relates to communications where the vehicle can be considered a client that receives desired or requested information using wireless LAN network technologies or other protocols. Information to be communicated by downloads to the vehicle might include: music (such as MP-3 or WMA formats); address book entries; navigation system updates and personal navigation maps; document synchronization and updates; synchronization with the car PDA; updating online game status; updating and modifying vehicle permissions for authorized users; firewall permissions to control e-commerce applications for a particular user; driver validations and supporting group chats. A more specific example of a music download might involve an association with a particular geographic region. For example, based on location awareness of a vehicle entering Yellowstone Park, a special offer might be downloaded to the driver and passengers of the vehicle in the form of music that was compiled to enjoy as they travel through the park. Such a special music offering could be made using the secure telematics system **20** via a wireless communication network broadband link or the like to the vehicle occupants. After acceptance of the offering related to the special music, a fee associated with acceptance can be paid using the digital funds resource **78**. After this occurs, the music is downloaded in an acceptable format to the operator unit **40** for subsequent playing.

[0143] Some e-commerce applications of the telematics secure system **20** are next described.

[0144] Vehicle as a service provider—with the vehicle having an assertion repository **78** that can be securely accessed by authorized entities, the vehicle can be a source of services that are paid for by transactions using the assertion repository **78**. Such services might include those related to leasing, financing, repair and/or maintaining the vehicle. Such services may be basic navigation services and/or premiums for such services. The vehicle maker may be able to exercise appropriate controls over the vehicle when proper payments are not made (e.g., discontinue services, regulate vehicle usage). Additionally, the vehicle might have configured devices, subsystems and components that have activatable features provided that certain conditions including payments are met. These features might include making available extra engine horsepower for a certain period of time. Relatedly, vehicles that have the assertion repository **78** may require further validation related to entities or individuals that can use the assertion repository **78**. Various biometric devices, such as a retina scanner, fingerprint verification or the like might be used to validate access to this resource.

[0145] Control access to consumer electronics devices—the maker of such device uses the security controller **100** to grant access only to authorized users. This may be a secure key to unlock premium features of a cellular phone or a PDA when located in the vehicle.

[0146] Toll payments—governmental entities may use the security controller **100** to control access to the assertion repository **78** for use in making toll and parking payments.

Public and private transportation companies can also take advantage of the system **20**. A WiFi link to an outside toll gate might communicate with the fare meter of a cab in determining the combination of trip distance fare as well as trip related toll costs. Additionally, the system might send an electronic receipt to the cab passenger's PDA having WiFi capability.

[0147] Third-party services and promotions—the vehicle driver and any passenger can receive communications related to products and services that might be available including from business establishments that are within a predetermined distance or range of the vehicle. These subscription services and promotions can relate to digital coupons for gas station purchases, hot spot Internet privileges, menus of restaurants and their promotions, and communication offerings, such as free voice over IP long distance.

[0148] Multi-media downloads—music and video can be downloaded by subscription that is based on individual subscriber identification, which can be correlated with the driver and one or more passengers in the vehicle.

[0149] It should be understood that many other applications are possible and the foregoing applications are intended to be representative thereof. The telematics secure system **20** establishes the environment for numerous and diverse applications that might only be limited by the relationships that can be established and the resources that can be identified or devised for use with or for executing one or more of such applications.

[0150] The security controller **100** can also be configured as part of a federated architecture in which access to and use of resources is also based on one or more assertions or credentials, and/or set(s) thereof, provided by federation members. In this embodiment, the security controller **100** acts as a proxy or trust arbiter in authorizing and authenticating access requests to vehicle resources. In connection with authorizing and authenticating access requests, the security controller **100** can evaluate complex sets of assertions or security credentials that are provided by an entity or requestor. Based on the credentials, the security controller **100** can determine whether access should be granted or denied. An assertion is a signed bundle of information that is asserted to be true by a trusted principal. An assertion may only have meaning or be relevant to certain parties. Assertions can be categorized according to different levels or classes that are associated with concomitant rights, privileges and/or obligations. For example, the assertions can include identifiers or other information that associate the requesting entity with a particular class of service providers, such as vehicle maintenance members, transportation providers, vehicle fuel providers, and highway toll entities.

[0151] The security controller **100** can also be involved with assertions or security credentials on its own behalf or on behalf of other resources in the vehicle. Certain examples can include providing credentials that authorize release of vehicle location information and which need not include releasing the user or vehicle identity. The security controller **100** as part of a vehicle can operate in a federated security environment in which the member entities of the federation agree on the format and content of an assertion, such as security credentials or attributes. They also accept the protocol for exchanging these credentials. The security controller **100** can implement the protocols on its own behalf and on behalf of vehicle resources under its domain.

[0152] More specifically, the security controller 100 is able to issue certificates to resources in the vehicle using a signing certificate issued by a broadly recognized root CA. At the same time, the security controller 100 is able to understand embedded assertions about authentication and authorization in connected resources. The PKI model is still supported, as the PKC's issued to those resources are considered a subclass of the types of assertions that may be utilized by the security controller 100.

[0153] In one embodiment, when a new resource (e.g. device) is connected, it contacts the security controller 100, or vice versa, and a new certificate is requested. The decision whether or not to issue the certificate to that resource in that name is made by the security controller 100. This decision is based on the location of the resource (e.g. connected to one or more vehicle buses), input from the user (e.g. which would be asked, "Is the resource you just connected Radio 407b built by Acme Co.?", and could later be asked what to allow the radio to do), pre-embedded assertions in the resource that the security controller 100 can verify with the issuers, as well as other appropriate information. Using all these inputs, an intelligent decision with the maximum available information is made whether to grant the certificate.

[0154] Identity certificates should always be issued, but that authorization privilege associated with these certificates should be carefully partitioned. This is where the control and the business model can be elaborated. The security controller 100 decides based on certain information whether or not to grant certain permissions for unintelligent applications. For intelligent applications, it can act as the domain controller, allowing those clever resources to potentially decide authorization on their own in whatever fashion desired. Either way, the security controller 100 is a necessary component and there are several hooks in the allocation of permissions to various resources to utilize other resources where billing systems can be attached.

[0155] Making the security controller 100 able to issue its own certificates to resources in the vehicle greatly lessens the exposure of all the resources involved since new certificates can be easily and locally issued. If the issuer of the security controller's certificate is compromised, new certificates only have to be issued for the security controller(s) it signed for. Additionally, permissions and identities can be handled in a federated way: the radio manufacturer can bundle authorization assertions inside the radio which the security controller 100 can verify with the manufacturer and decide whether to trust.

[0156] With reference to FIG. 3, a general description is next provided related to an application and operations in which the vehicle, under control of the security controller 100, is part of such a federation. The security controller 100 communicates with an origin or requesting application and a target provider, which can be a target service provider, a target product provider or other provider. Generally, the requesting application seeks to utilize the target provider for a particular function or activity. In connection with determining whether access by the origin application is to be granted, certain procedures are followed to ascertain whether or not the origin application is authenticated and has the authority to execute its application. Major steps for these procedures include:

[0157] 1. The origin application contacts the target provider requesting some product, service, resource or other information.

[0158] 2. The target provider sends the origin application a signed assertion with the name of the target provider and the information needed to allow access by the origin application.

[0159] 3. The origin application contacts the security controller 100 to request a new assertion related to authorization by the origin application to use the target provider.

[0160] 4. The security controller 100 and the origin application mutually authenticate using an established protocol, e.g. a secure sockets layer (SSL) for IP networking.

[0161] 5. The origin application presents the assertion that it receives from the target provider to the security controller 100.

[0162] 6. The security controller utilizes the assertion that it receives from the origin application to generate a new assertion for the origin application. This new assertion may include information about the origin application. Alternatively, the information may simply be related to an approval with reference to the original target provider assertion in order to maintain a high level of privacy related to the identity of one or more parties involved with executing the origin application.

[0163] 7. The origin application presents this temporary assertion to the target provider, which may include an accompanying handle or other identifier.

[0164] 8. The target provider verifies the temporary assertion by using information and checking it against the public key of the security controller 100. Alternatively or additionally, the target provider could check directly with the security controller 100 in connection with performing this verification. As part of this direct communication, additional information could be given to the target provider by the security controller 100.

[0165] 9. Based on the information in the temporary assertion that it receives, the target provider grants or denies access to the origin application, which may involve one or more resources under the control of the target provider and/or services/products available through the target provider.

[0166] Referring to FIG. 4, a more specific use of a federated architecture, particularly related to maintaining desired privacy, is described. According to this example, vehicle resources are used to pay for a product purchased by the vehicle user and, more particularly, to pay for food from a fast or quick food vendor. Entities that are part of the federation to provide a secure transaction involving this product purchase include a vendor, a financial institution (e.g., bank) and the vehicle itself through the security controller 100 and the assertion repository 78, together with the vehicle user who is involved with authorizing the payment. This transaction example includes the following steps:

[0167] 1. The vehicle user or consumer places an order with the vendor, who requests payment.

[0168] 2. The security controller 100 receives the payment request and can query the policy decision engine 82 related

to payment information. The decision engine **82** can access the database **90** or other appropriate assertion or credential repository **94** in order to receive necessary verified or signed assertions based on the queries submitted by the security controller **100**.

[**0169**] 3. The decision engine **82** may provide the vehicle user with the payment amount and choices for making the payment, for example, using the human interface **40**. Since no trust relationship exists between the vendor and the security controller **100**, the payment amount and recipient are unsecured and untrusted. To establish the security and trust, the financial institution or bank is employed.

[**0170**] 4. The decision engine **82** selects a bank account to debit for the purchase based on the user input.

[**0171**] 5. Next, the decision engine **82** finds the bank account and connection information in the credential repository **94**. Although the credential repository **94** is indicated as being part of the assertion repository **78**, it can be located remotely of the vehicle and an authentication and authorization process would be required to obtain the necessary information from any such remote repository.

[**0172**] 6. In one embodiment or optionally, security and anonymity can be enhanced by the decision engine **82**, with the assistance and control of the security controller **100**, communicating with the bank and obtain a temporary pseudonym to identify the transaction rather than utilizing a pre-established, persistent identifier.

[**0173**] 7. Regardless of its location, the credential repository **94** returns to the decision engine **82** the name of the bank and the identifier associated with the transaction. In the case in which the credential repository **94** is remote relative to the vehicle, the decision engine **82** might access it using a wireless session by means of the security controller **100**.

[**0174**] 8. Next, the decision engine **82** provides the security controller **100** with the payment credentials that can include the bank name and the transaction identifier.

[**0175**] 9. After obtaining them, the security controller **100** sends the payment credentials to the vendor.

[**0176**] 10. The vendor authenticates and authorizes with the bank.

[**0177**] 11. The vendor sends the bank payment credentials.

[**0178**] 12. The bank authenticates and authorizes with the security controller **100**.

[**0179**] 13. The bank presents a payment request to the security controller **100**.

[**0180**] 14. The security controller **100** presents the payment request to the vehicle user.

[**0181**] 15. The vehicle user accepts the payment request.

[**0182**] 16. The security controller **100** indicates authorization of payment and sends it to the bank.

[**0183**] 17. The bank acknowledges that the payment was made to the vendor.

[**0184**] Referring to **FIG. 5**, another federated security transaction is described. In this example, a toll can be paid by the vehicle user in an anonymous manner. The members of the federation include a toll entity, a shuttle company

associated with a directory and being involved with transportation, and the vehicle having the security controller **100**, together with the decision engine **82** of the assertion repository **78**. The steps and communications associated with this transaction example include:

[**0185**] 1. The toll booth entity initiates an authenticated SSL connection with the security controller **100** utilizing mutually recognized certificate authorities.

[**0186**] 2. The toll booth entity presents payment demand.

[**0187**] 3. The security controller **100** queries the decision engine **82** for appropriate payment source.

[**0188**] 4. The decision engine **82** initiates and establishes an authenticated secure connection with a directory that is remote from the vehicle.

[**0189**] 5. The decision engine **82** presents the authorized assertion to the directory.

[**0190**] 6. The directory generates credentials containing appropriate payment information signed or authorized by the shuttle company.

[**0191**] 7. The decision engine **82** returns the credentials to the security controller **100**.

[**0192**] 8. The security controller **100** presents the credentials to the toll booth entity.

[**0193**] In one embodiment, additional validation can be made with the shuttle company itself before access is granted. Payment could then occur or transactions could be aggregated by the toll booth entity and present them to the shuttle company later based on their established relationship. In a related embodiment, instead of security credentials from the remote directory, persistent, cached assertions could be relied on that are immediately accessible by the security controller.

[**0194**] Another anonymous transaction example is illustrated in **FIG. 6**. According to this scenario, a cab for hire is paid anonymously and the cab user or passenger receives a digitally signed receipt. The federation members include a financial institution, such as a credit card company and a public transportation or taxi company, as well as the vehicle resources including the security controller **100** and a vehicle user device that can contain an assertion repository **78**. Due to the federation relationship between the credit card company and the taxi company, the cab driver does not need to know the identity of the cab user or credit card number and there need not be a trust relationship between the vehicle user and the taxi company. The steps and communications in this transaction include:

[**0195**] 1. The security controller **100** in the cab is alerted that it will be the source for paying the cab fare using, for example, a laptop, a cell phone or other consumer device that contains the assertion repository **78** for the cab user.

[**0196**] 2. Once the trip is completed, the fare amount is read from the cab meter by the security controller **100**.

[**0197**] 3. The security controller **100** establishes a secure authenticated connection with the cab company, which could be a pre-existing connection.

[**0198**] 4. The fare amount, together with identifier for the cab, is sent to the cab company.

[0199] 5. The cab company generates a signed or authorized fare assertion or reply.

[0200] 6. The security controller **100** passes the assigned fare to the consumer device of the cab user.

[0201] 7. The consumer device itself authenticates directly to the credit card company which authorizes payment or provides its indication that it has responsibility for paying the fare amount. It is preferable that this communication be SSL protected and, alternatively or optionally, the communication could be encrypted at the Internet protocol (IP) layer. This provides protection in the form of not permitting the taxi cab and any other passenger from getting information about the bank with whom the fare paying cab user is communicating.

[0202] 8. The consumer device transmits the signed fare assertion to the credit card company.

[0203] 9. The credit card company authenticates with the taxi company and makes payment based on the signed fare information.

[0204] 10. The taxi company then sends an acknowledgment of payment to the security controller **100** in the cab.

[0205] 11. The security controller **100** can then send payment acknowledgment to the consumer device.

[0206] In one embodiment, the fare assertion is an attribute assertion containing transaction information, the fare amount, the cab identifier and could also include other information such as the origin and destination of travel, with all such information being asserted or authorized by the cab company.

[0207] In another example of a federated environment that need not involve a payment as part of the user application, steps and communications are described to permit checking of the current location of a package or other item being shipped. With reference to **FIG. 7**, the company receiving the item and the delivery company have entered into mutually accepted conditions. These procedures or steps for this example include:

[0208] 1. The shipping manager of the receiving company logs on to the company computer.

[0209] 2. The shipping manager queries the delivery company for location of the shipment.

[0210] 3. Information about the shipping manager is securely transferred to target web services that is to make the determination and provide the authorization to enable the shipping manager to obtain the location information. The transferred information about the shipping manager can include the identity of the receiving company, the role of the shipping manager at the shipping company and the item tracking number. With regard to transferring the information about the shipping manager, in one embodiment, a middleware software system or module could be employed identified as the Shibboleth architecture. The Shibboleth architecture is a known architecture that supports sharing of resources which are subject to access controls.

[0211] 4. A signed or authorized assertion is generated by the target web services to which the information was directed. This signed assertion includes the security controller address of the vehicle containing the item, one or more

credentials trusted by the security controller **100** that specify GPS access privileges and a unique session identifier or handle that links the shipping manager to the request in order to prevent unauthorized additional uses and/or other potential misuse.

[0212] 5. Based on the address of the security controller **100** in the vehicle, a SSL session is established directly between the shipping manager and the security controller **100**.

[0213] 6. The credential(s) is (are) presented to the security controller **100**, which performs relevant validity checks.

[0214] 7. In one variation, the security controller **100** might contact the delivery company to verify the validity of the credential(s) and may request additional information about the vehicle location transaction. In such a case, the credential(s) need not include authentication and authorization information since these would be furnished by the delivery company.

[0215] 8. The security controller **100** then requests the vehicle GPS coordinates.

[0216] 9. These coordinates are returned to the security controller **100** in the vehicle from which location information is requested.

[0217] 10. The GPS coordinates are sent to the shipping manager.

[0218] In a more significant variation of this example, the site of the receiving company might act as a front end portal for all interactions between it and the security controller **100**.

[0219] Alternatively as well, an estimated time of arrival could be provided to the shipping manager instead of the actual GPS location of the vehicle.

[0220] In still another example of a federation implementation, maintenance of a vehicle using a particular software diagnostic tool is described in conjunction with **FIG. 8**. In order to execute the vehicle diagnostic software tool, secure access to the bus of the vehicle is granted. The federation members include a vehicle dealer or maker and entities involved with vehicle maintenance, as well as the vehicle itself having the security controller **100**. In one embodiment, the credentials for allowing use of this diagnostic software are generated by the vehicle dealer. The credentials might be specific for the particular vehicle and/or for a period of time. The sequence associated with this application includes:

[0221] 1. The credentials associated with use of the software and concomitant access to the vehicle bus are loaded on a computer, such as a laptop, of the vehicle diagnostics entity in order to enable the software.

[0222] 2. The diagnostic application on the computer establishes a secure session with the security controller **100** of the vehicle.

[0223] 3. The diagnostic application presents the credentials to the security controller **100**.

[0224] 4. The security controller **100** establishes a secure connection with the dealer.

[0225] 5. The security controller **100** presents the credentials contained in the software to the dealer for validation.

[0226] 6. The dealer validates the credentials.

[0227] 7. The security controller **100** might seek the vehicle owner's permission if access to the vehicle bus is granted by the vehicle dealer.

[0228] 8. The vehicle owner grants access to the vehicle engine bus.

[0229] 9. The security controller **100** accesses the vehicle engine bus and requests information.

[0230] 10. The security controller **100** reads information from the engine bus.

[0231] 11. The security controller **100** then transmits this information to the computer.

[0232] The process of obtaining information from the vehicle engine bus could be repeated numerous times after the credentials are validated. The credentials might allow the engine bus to be accessed for a defined period of time and/or a limited number of times. The credentials are preferably generated specific to each individual computer or other diagnostic device and not to the diagnostic software itself.

[0233] The foregoing discussion of the invention has been presented for purposes of illustration and description. Further, the description is not intended to limit the invention to the form disclosed herein. Consequently, variations and modifications commensurate with the above teachings, within the skill and knowledge of the relevant art, are within the scope of the present invention. The embodiments described hereinabove are further intended to explain the best modes presently known of practicing the invention and to enable others skilled in the art to utilize the invention in such, or in other embodiments, and with the various modifications required by their particular application or uses. It is intended that the appended claims be construed to include alternative embodiments to the extent permitted by the prior art.

What is claimed is:

1. A method for controlling use of proprietary resources associated with a vehicle, comprising:

providing resources including proprietary resources associated with a vehicle including a plurality of the following: a first bus, a first interface, a first display, a first vehicle device, a first subsystem, a first application, and a second application;

establishing a plurality of relationships involving at least three entities, wherein first and second entities of said at least three entities has proprietary rights in at least first and second proprietary resources, respectively, and each of said three entities accepts a plurality of conditions related to use of said at least first proprietary resource; and

performing at least a first function after said establishing while making use of at least said first and second proprietary resources.

2. A method of claim 1 wherein said first vehicle device communicates with said first bus and said first application executes in association with said first vehicle device and in which said first entity has proprietary rights in said first vehicle device, but not in said first application and said second entity has proprietary rights in said first application, but not in said first vehicle device.

3. A method of claim 1 wherein said first application relates to at least one of the following: regulating said first vehicle device using commands; changing a certificate related to granting use of at least one of said proprietary resources; accessing an assertion repository associated with a security controller; providing weather and road conditions information; monitoring vehicle location; toll and transportation payments; servicing a navigation subscription for the vehicle; executing vehicle diagnostics; exercising control over said first subsystem related to use thereof.

4. A method of claim 1 wherein said first vehicle device includes at least one of: an engine monitor, an oil pressure sensor, a temperature sensor and an inflator device.

5. A method of claim 1 wherein said first subsystem includes at least one of the following: a body control, a chassis control, an engine control, a transmission control, telematics control, a global positioning system (GPS), storage memory located in the vehicle, a personal digital assistant (PDA), a laptop computer, a CD-ROM, a vehicle monitoring system (VMS), a printer, and an accident and emergency notification alarm (AENA).

6. A method of claim 1, wherein:

said providing includes providing a security controller in communication with at least some of said plurality of resources and being used in controlling at least one of the following: monitoring stored information related to vehicle warranty and quality assurance; arbitrating priority; granting access to diagnostic information and vehicle configuration information; granting access to vehicle information, driver information and vehicle control to authorized service providers; granting access to vehicle information, driver information and vehicle control to an authorized user of the vehicle; granting access to enable or change control of vehicle devices; granting access to one or more features of said first subsystem when made available for communication in the vehicle; granting access to services authorized for a user; granting access to authorized credit and debit entities to using an assertion repository; granting access to vehicle positioning data; granting access to vehicle data related to border crossing and weight inspection; granting access to vehicle data related to a smog test; and granting access to an assertion repository related to public or private transportation, toll and parking payments.

7. A method of claim 1, wherein at least one condition of said plurality of conditions is different for at least one of said three entities.

8. A method of claim 1 wherein said establishing includes describing said plurality of conditions that said three entities accept including at least some of: compensation for using at least said first proprietary resource, time within which said at least first proprietary resource can be used, an identity of said at least first proprietary resource, use to which said first proprietary resource can be made and at least one remedy that is available when one or more of said conditions is not met.

9. A method of claim 1 wherein said establishing includes certifying at least one of said first application and said first subsystem for use in the vehicle using a first certificate.

10. A method of claim 9 wherein said certifying includes producing a plurality of keys related to allowing use of at least said first proprietary resource by a third entity of said three entities.

11. A method of claim 9 wherein said certifying includes providing a number of properties as part of a first certificate granted to a third entity of said three entities, said properties including at least one of the following: an identifier that identifies uniquely said third entity; a priority level; a geographic area where said first certificate is valid; an expiration date of said first certificate; one or more proprietary resources with which communications are to be made using said first application; one or more application programming interfaces (APIs) available for use; and one or more authentication procedures required to enable use of one or more of said plurality of resources.

12. A method of claim 9 wherein said certifying includes generating a first certificate request by a third entity of said three entities and providing said first certificate request to a certificate authority.

13. A method of claim 9 wherein said certifying includes associating a signature key from a certificate authority with said first certificate.

14. A method of claim 13 wherein said certifying includes associating a signature key of a requester of said first certificate with said first application.

15. A method of claim 9, wherein said certifying includes approving said first application by at least a first authority.

16. A method of claim 9 wherein said certifying includes enabling generation of a certificate request by a certificate authority.

17. A method of claim 9 wherein said certifying includes issuing said first certificate by a certificate authority and checking accuracy of said first certificate by a requester of said first certificate.

18. A method of claim 9 wherein said certifying includes granting a certificate request related to said first certificate to a certificate requester by a certificate authority.

19. A method of claim 9 further including utilizing information related to said first certificate to ascertain compensation to be made by a first certificate requester.

20. A method of claim 9 further including revoking said first certificate by a certificate authority based on at least a first predetermined condition.

21. A method of claim 9 further including authenticating said first certificate by a security controller in the vehicle.

22. A method of claim 1 in which said establishing includes establishing a federation in which at least some of said entities have predetermined credentials to enable access and use of at least one of the said resources and in which said resources further include an assertion repository.

23. A system for controlling use of proprietary resources in a vehicle, comprising:

resources including proprietary resources for use in the vehicle including a plurality of the following: a first bus, a first vehicle device, a first subsystem, a first display, a first application, a second application and a first interface; and

a security controller communicating with at least a first of said proprietary resources wherein said security controller controls use of at least said first proprietary resource utilizing certificate information that includes stored certificate information accessible by said security controller that relates to approval of use of said at least first proprietary resource by a first certificate holder of a first certificate, wherein said approval

involves at least a first entity having proprietary rights associated with said at least first proprietary resource.

24. A system of claim 23 wherein said stored certificate information includes a certificate authority public key used to authenticate a first certificate of said first certificate holder.

25. A system of claim 23 wherein said security controller is involved with performing at least one of the following: authenticating said first application using said stored certificate information; authenticating a user associated with said first application using stored identification information; verifying use of said at least first proprietary resource utilizing at least one of location and time; relying on at least a first key in determining whether to allow execution of said first application; enabling a number of applications including said first application and said second application to execute simultaneously using a plurality of said proprietary resources; enabling access to at least non-proprietary resources of said resources; arbitrating use of said first bus; and monitoring activity on said first bus.

26. A system of claim 23 further including at least one of: a communication services module in communication with at least said first proprietary resource that is involved with communications, said communication services module for use in protecting and arbitrating access to said first proprietary resource and performing at least some of the following functions: managing at least said first certificate and at least a first key; enforcing one or more usage rules for said first proprietary resource; monitoring and logging usage associated with said first proprietary resource; providing fault notification; supporting communications outside the vehicle, including over the Internet; and supporting communication on said first bus.

27. A system of claim 23 further including a human/machine interface services module in communication with said security controller that protects and arbitrates access to said first display and performs at least some of the following functions: managing, responding to, handling or otherwise being involved with: (a) tactile inputs such as steering wheel controls, buttons, switches, (b) audio and voice recognition, text-to-speech and/or voice prompts; (c) multiple displays including said first display; managing said first certificate and at least a first key related to use of said first display; enforcing one or more usage rules associated with said first display; monitoring and logging usage information related to said first display; providing fault notification related to said first display and supporting communication on said first bus.

28. A system of claim 23 further including a vehicle gateway and a vehicle services module, wherein said first bus includes one or more vehicle buses including a first vehicle bus communicating with said vehicle gateway that allows access to information obtained from vehicle devices in communication with said vehicle bus, said vehicle services module involved with at least one of the following functions: managing said first certificate and at least a first key related to use of one or more vehicle devices including said first vehicle device communicating with said first vehicle bus; enforcing one or more usage rules associated with said first vehicle bus and said vehicle devices; monitoring and logging usage related to said first vehicle bus and said vehicle devices; providing fault notification related to said first vehicle bus and said vehicle devices; upgrading said first vehicle bus access for outgoing requests; and supporting security on said first vehicle bus.

29. A system of claim 23 wherein said proprietary resources include at least some of the following: sensors of vehicle devices, diagnostic messages and alarms, a global positioning system (GPS) receiver, a storage memory located in the vehicle, a compact disc read only memory (CD-ROM), a cellular telephone, a vehicle monitoring system (VMS), an inflator system, a printer, a personal digital assistant (PDA), a laptop computer, and an accident and emergency notification alarm (AENA).

30. A system of claim 23 wherein said first application relates to at least one of the following: determining access to vehicle devices and controlling vehicle functions; contributing to alarm notification sent to at least one predetermined authority; a subscription service for navigation; performing vehicle diagnostics; upgrading firmware; conducting a configuration upgrade for the vehicle; accessing and using an assertion repository; providing vehicle, road and weather conditions; and determining that said first proprietary resource can be used.

31. A method for securely controlling access and use related to a target provider involving a vehicle having a security controller, comprising:

- providing a security system that includes a security controller in a vehicle;
- requesting a target provider;
- obtaining first information using said security controller related to authorizing use of said target provider by a requesting application; and

determining use related to said target provider based on said first information.

32. A method of claim 31 wherein said requesting is conducted using said requesting application and said determining is made using said target provider.

33. A method of claim 31 wherein said requesting is initiated by said requesting application.

34. A method of claim 31 wherein said first information relates to a plurality of information available from said security system and said security system includes a database for storing said plurality of information and a decision engine in communication therewith.

35. A method of claim 34 wherein said decision engine determines to provide said first information based on at least one factor that includes: an identity related to said requesting application, information being requested and consent from an entity involved with authorizing use of said target provider.

36. A method of claim 31 wherein said first information maintains privacy of an identity associated with at least one of said requesting application, said security controller and an entity whose consent is required to implement said requesting application.

37. A method of claim 31 wherein said security controller issues credentials related to at least a first resource located in the vehicle.

\* \* \* \* \*