



(12) **United States Patent**
Dacosta et al.

(10) **Patent No.:** **US 11,696,767 B2**
(45) **Date of Patent:** ***Jul. 11, 2023**

(54) **ALIGNMENT GUIDES, CUT GUIDES, SYSTEMS AND METHODS OF USE AND ASSEMBLY**

(71) Applicant: **Paragon 28, Inc.**, Englewood, CO (US)

(72) Inventors: **Albert Dacosta**, Lone Tree, CO (US);
Laura Zagrocki Brinker, Lone Tree, CO (US); **Randy Allard**, Golden, CO (US)

(73) Assignee: **Paragon 28, Inc.**, Englewood, CO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 282 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/115,442**

(22) Filed: **Dec. 8, 2020**

(65) **Prior Publication Data**

US 2021/0085338 A1 Mar. 25, 2021

Related U.S. Application Data

(63) Continuation of application No. 16/516,857, filed on Jul. 19, 2019, now Pat. No. 10,856,886, which is a (Continued)

(51) **Int. Cl.**

A61B 17/15 (2006.01)

A61B 17/16 (2006.01)

A61B 17/17 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 17/15** (2013.01); **A61B 17/1682** (2013.01); **A61B 17/1775** (2016.11)

(58) **Field of Classification Search**

CPC A61B 17/15; A61B 17/151; A61B 17/152; A61B 17/1682; A61B 17/17; A61B 17/1739; A61B 17/1775

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,425,574 B2 4/2013 Huebner
9,936,994 B2* 4/2018 Smith A61B 17/1739
(Continued)

FOREIGN PATENT DOCUMENTS

WO 2017011656 1/2017
WO 2017031000 2/2017
WO 2017031020 2/2017

OTHER PUBLICATIONS

Extended European Search Report for European Patent Application No. 18886100.9, dated Jul. 15, 2021, 12 pages.

(Continued)

Primary Examiner — Eric S Gibson


(74) *Attorney, Agent, or Firm* — Heslin Rothenberg Farley & Mesiti PC; Jacquelyn A. Graff, Esq.

(57) **ABSTRACT**


Guides, systems, and methods for maintaining, correcting and/or fusing joint deformities are disclosed. The guide system including a cut guide, an alignment guide, and at least one directional wire. The cut guide including a base portion, an extension member extending away from a bottom surface of the base portion, and at least one arm extending away from an end of the base portion. The alignment guide, including a base portion, a first extension member extending away from a bottom surface of the base portion in a first direction, and a second extension member extending away from the bottom surface of the base portion in a second direction. Methods of using a guide system for maintaining, correcting and/or fusing joint deformities are also disclosed.

17 Claims, 61 Drawing Sheets

100



100



Related U.S. Application Data

continuation of application No. PCT/US2018/064368, filed on Dec. 7, 2018.

(60) Provisional application No. 62/595,155, filed on Dec. 6, 2017.

References Cited

U.S. PATENT DOCUMENTS

10,335,220	B2 *	7/2019	Smith	A61B 17/1728
10,342,590	B2 *	7/2019	Bays	A61B 17/1728
10,575,862	B2 *	3/2020	Bays	A61B 17/1682
10,856,886	B2 *	12/2020	Dacosta	A61B 17/1682
2007/0265634	A1	11/2007	Weinstein		
2015/0223852	A1	8/2015	Lietz et al.		
2016/0192950	A1 *	7/2016	Dayton	A61B 17/15 606/87
2016/0235414	A1 *	8/2016	Hatch	A61B 17/151
2016/0242791	A1 *	8/2016	Fallin	A61B 17/151

2017/0042598	A1 *	2/2017	Santroek	A61B 17/1775
2017/0056031	A1 *	3/2017	Awtrey	A61B 6/485
2017/0079669	A1 *	3/2017	Bays	A61B 17/562
2017/0172638	A1 *	6/2017	Santroek	A61B 17/1739
2018/0317992	A1 *	11/2018	Santroek	A61B 17/1775
2019/0274745	A1 *	9/2019	Smith	A61B 17/1682
2019/0328435	A1 *	10/2019	Bays	A61B 17/1775
2019/0328436	A1 *	10/2019	Bays	A61B 17/1728
2019/0336140	A1 *	11/2019	Dacosta	A61B 17/15
2021/0085338	A1 *	3/2021	Dacosta	A61B 17/15

OTHER PUBLICATIONS

Paragon 28 “Surgical Technique Guide: Lapidus Cut Guide System,” <http://www.paragon28.com/products/lapidus-cut-guide-system/>, Feb. 26, 2019.
International Search Report and Written Opinion of the International Searching Authority for PCT/US2018/064368, dated Mar. 29, 2019, 13 pages.

* cited by examiner

100




FIG. 1

100




FIG. 2

100




FIG. 3

100




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16

200




FIG. 17

200




FIG. 18

250




FIG. 19

250




FIG. 20




FIG. 21




FIG. 22

250




FIG. 23

250




FIG. 24

250




FIG. 25

250




FIG. 26

300




FIG. 27

300




FIG. 28

300




FIG. 29

300




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34

350




FIG. 35

350




FIG. 36




FIG. 37




FIG. 38

400




FIG. 39

400




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44

500




FIG. 45

500




FIG. 46

510




FIG. 47

510




FIG. 48

510




FIG. 49

510




FIG. 50

510




FIG. 51

510




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 64

550




FIG. 65






FIG. 66






FIG. 69




FIG. 70







FIG. 71



418

FIG. 72




FIG. 73




FIG. 74

700




FIG. 75

700




FIG. 76




FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81




FIG. 82

750




FIG. 83

750




FIG. 84

800




FIG. 85

800




FIG. 86




FIG. 87




FIG. 88




FIG. 89




FIG. 90




FIG. 91




FIG. 92




FIG. 93




FIG. 94




FIG. 95




FIG. 96




FIG. 97




FIG. 98




FIG. 99




FIG. 100




FIG. 101




FIG. 102




FIG. 105




FIG. 106

1000




FIG. 107

1000




FIG. 108




FIG. 109




FIG. 110

1000




FIG. 111

1000




FIG. 112




FIG. 113




FIG. 114

**ALIGNMENT GUIDES, CUT GUIDES,
SYSTEMS AND METHODS OF USE AND
ASSEMBLY**

CROSS REFERENCE TO RELATED
APPLICATION

This application is a continuation of U.S. patent application Ser. No. 16/516,857 filed on Jul. 19, 2019 and entitled Alignment Guides, Cut Guides, Systems and Methods of Use and Assembly and which will issue as U.S. Pat. No. 10,856,886 on Dec. 8, 2020, which is a continuation of PCT/US2018/064368 filed on Dec. 7, 2018 and entitled Alignment Guides, Cut Guides, Systems and Methods of Use and Assembly, which claims priority benefit under 35 U.S.C. § 119(e) of U.S. provisional application No. 62/595,155, filed Dec. 6, 2017 and entitled Alignment Guides, Cut Guides, Systems and Methods of Use and Assembly, which are incorporated herein by reference in their entireties.

TECHNICAL FIELD

The present disclosure relates generally to general, podiatric, and orthopaedic surgery related to joint deformities. More specifically, but not exclusively, the present disclosure relates to devices, systems, and methods for maintaining, correcting and/or fusing joint deformities.

BACKGROUND OF THE INVENTION

The Lapidus procedure is commonly used to correct a hallux valgus deformity, which is a lateral deviation of the great toe, with subsequent hypermobility (or laxity). The Lapidus procedure is also commonly used to repair failed surgeries. Typically, a wedge of bone is removed in a biplanar direction at the distal end of the cuneiform, which will provide correction of the deformity and typically results in shortening of the first ray. The result of this shortening is a shift in weight distribution to the second ray, which can result in metatarsalgia. When the first ray is shortened, the function of the patient's sesamoids may also be affected because of the change in weight distribution on the sesamoids. Currently, to avoid shortening of the first ray when doing a Lapidus procedure, the accepted practice is for surgeons to make a straight transverse cut on the metatarsal, then cut only the cartilage or a minimal wedge resection of the cuneiform to obtain realignment of the transverse plane intermetatarsal angle as determined by the surgeon. If shortening beyond an acceptable amount occurs, a bone graft can be used to restore first ray length. Blood supply complications and anatomical height and weight bearing through the joint are all concerns for post-operative healing from a Lapidus procedure.

Accordingly, it is an object of the present invention to overcome one or more of the above-described drawbacks and/or disadvantages of the currently used procedures. For example, in view of the deficiencies of the current implants and methods of performing the Lapidus procedure and fusion of the first tarso-metatarsal joint, and similar implants and surgical methods for other areas of the body where multiple bone structures exist including, but not limited to, the hand, wrist and spine, it would be desirable to develop devices, systems, instrumentation, and methods for maintaining, correcting and/or fusing joint deformities to overcome the above-noted deficiencies of the currently available solutions for addressing joint deformities.

SUMMARY OF THE INVENTION

The present disclosure is directed toward devices, systems and methods for use in maintaining, correcting and/or fusing joint deformities.

In one aspect of the present disclosure provided herein, is a guide system. The guide system including a cut guide, an alignment guide coupled to the cut guide, and a directional wire engaging a portion of the alignment guide.

In another aspect of the present disclosure provided herein, is a cut guide. The cut guide including a base portion, an extension member extending away from a bottom surface of the base portion, and at least one arm extending away from an end of the base portion.

In yet another aspect of the present disclosure provided herein, is an alignment guide. The alignment guide, including a base portion, a first extension member extending away from a bottom surface of the base portion in a first direction, and a second extension member extending away from the bottom surface of the base portion in a second direction.

In a further aspect of the present disclosure provided herein, is a method for using the guide system. The method includes obtaining a cut guide, in which the cut guide includes a base portion, an extension member extending away from a bottom surface of the base portion, and at least one arm extending away from an end of the base portion. The method also includes inserting the extension member into a joint space and coupling the alignment guide to the cut guide. The method further includes inserting a directional wire into at least one opening in the alignment guide and inserting a k-wire into a dorsal hole in the cut guide and checking the orientation of the cut guide. In addition, the method includes inserting at least two wires through the at least one arm of the cut guide and into at least one bone and removing the alignment guide and k-wire. Next, the method includes cutting a first bone and a second bone using at least one slot of the cut guide and removing at least one lateral wire from the at least one bone and the cut guide. Then, the method includes moving the first and second bones to the desired correctional position.

These and other objects, features and advantages of this disclosure will become apparent from the following detailed description of the various aspects of the disclosure taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the disclosure and together with the detailed description herein, serve to explain the principles of the disclosure. It is emphasized that, in accordance with the standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion. The drawings are only for purposes of illustrating preferred embodiments and are not to be construed as limiting the disclosure.

FIG. 1 is a top perspective view of one embodiment of a cut guide, in accordance with an aspect of the present disclosure;

FIG. 2 is a bottom perspective view of the cut guide of FIG. 1, in accordance with an aspect of the present disclosure;

FIG. 3 is a side view of the cut guide of FIG. 1, in accordance with an aspect of the present disclosure;

5

FIG. 60 is a side view of FIGS. 57-59 after removal of the directional wire, the alignment guide, and the lateral guide wire, in accordance with an aspect of the present disclosure;

FIG. 61 is a first end, perspective view of FIG. 60, in accordance with an aspect of the present disclosure;

FIG. 62 is a perspective, side view of the foot, cut guide and guide wires of FIGS. 60 and 61 with a saw blade inserted into a first slot of the cut guide, in accordance with an aspect of the present disclosure;

FIG. 63 is a side, perspective view of the foot, cut guide, and guide wires of FIG. 62 with the saw blade inserted into a second slot of the cut guide, in accordance with an aspect of the present disclosure;

FIG. 64 is a partially exploded, side perspective view of the foot and two guide wires of FIG. 63 with a position rotation device being inserted onto at least one of the guide wires, in accordance with an aspect of the present disclosure;

FIG. 65 is a front perspective view of the position rotation device, in accordance with an aspect of the present disclosure;

FIG. 66 is a top perspective view of an embodiment of a cut guide system including a transparent cut guide and insertion handle, in accordance with an aspect of the present disclosure;

FIG. 67 is a side view of the cut guide system of FIG. 66, in accordance with an aspect of the present disclosure;

FIG. 68 is a top view of the cut guide system of FIG. 66, in accordance with an aspect of the present disclosure;

FIG. 69 is an exploded, first end perspective view of the cut guide system of FIG. 66 with a solid cut guide, in accordance with an aspect of the present disclosure;

FIG. 70 is an exploded, second end perspective view of the cut guide system of FIG. 69, in accordance with an aspect of the present disclosure;

FIG. 71 is an exploded first end view of the cut guide system of FIG. 69, in accordance with an aspect of the present disclosure;

FIG. 72 is an exploded second end view of the cut guide system of FIG. 69, in accordance with an aspect of the present disclosure;

FIG. 73 is a side view of the insertion handle of FIG. 66, in accordance with an aspect of the present disclosure;

FIG. 74 is a top view of the insertion handle of FIG. 66, in accordance with an aspect of the present disclosure;

FIG. 75 is a top perspective view of an embodiment of a cut guide, in accordance with an aspect of the present disclosure;

FIG. 76 is a bottom perspective view of the cut guide of FIG. 75, in accordance with an aspect of the present disclosure;

FIG. 77 is a side view of the cut guide of FIG. 75, in accordance with an aspect of the present disclosure;

FIG. 78 is another side view of the cut guide of FIG. 75, in accordance with an aspect of the present disclosure;

FIG. 79 is an end view of the cut guide of FIG. 75, in accordance with an aspect of the present disclosure;

FIG. 80 is another end view of the cut guide of FIG. 75, in accordance with an aspect of the present disclosure;

FIG. 81 is a top view of the cut guide of FIG. 75, in accordance with an aspect of the present disclosure;

FIG. 82 is a bottom view of the cut guide of FIG. 75, in accordance with an aspect of the present disclosure;

FIG. 83 is a top perspective view of an embodiment of a cut guide, in accordance with an aspect of the present disclosure;

6

FIG. 84 is a bottom perspective view of the cut guide of FIG. 83, in accordance with an aspect of the present disclosure;

FIG. 85 is a top perspective view of an embodiment of a cut guide, in accordance with an aspect of the present disclosure;

FIG. 86 is a bottom perspective view of the cut guide of FIG. 85, in accordance with an aspect of the present disclosure;

FIG. 87 is a side view of the cut guide of FIG. 85, in accordance with an aspect of the present disclosure;

FIG. 88 is another side view of the cut guide of FIG. 85, in accordance with an aspect of the present disclosure;

FIG. 89 is an end view of the cut guide of FIG. 85, in accordance with an aspect of the present disclosure;

FIG. 90 is another end view of the cut guide of FIG. 85, in accordance with an aspect of the present disclosure;

FIG. 91 is a top view of the cut guide of FIG. 85, in accordance with an aspect of the present disclosure;

FIG. 92 is a bottom view of the cut guide of FIG. 85, in accordance with an aspect of the present disclosure;

FIG. 93 is a top perspective view of an embodiment of a cut guide, in accordance with an aspect of the present disclosure;

FIG. 94 is a bottom perspective view of the cut guide of FIG. 93, in accordance with an aspect of the present disclosure;

FIG. 95 is a top perspective view of an embodiment of a cut guide, in accordance with an aspect of the present disclosure;

FIG. 96 is a bottom perspective view of the cut guide of FIG. 95, in accordance with an aspect of the present disclosure;

FIG. 97 is a side view of the cut guide of FIG. 95, in accordance with an aspect of the present disclosure;

FIG. 98 is another side view of the cut guide of FIG. 95, in accordance with an aspect of the present disclosure;

FIG. 99 is an end view of the cut guide of FIG. 95, in accordance with an aspect of the present disclosure;

FIG. 100 is another end view of the cut guide of FIG. 95, in accordance with an aspect of the present disclosure;

FIG. 101 is a top view of the cut guide of FIG. 95, in accordance with an aspect of the present disclosure;

FIG. 102 is a bottom view of the cut guide of FIG. 95, in accordance with an aspect of the present disclosure;

FIG. 103 is a top perspective view of an embodiment of a cut guide, in accordance with an aspect of the present disclosure;

FIG. 104 is a bottom perspective view of the cut guide of FIG. 103, in accordance with an aspect of the present disclosure;

FIG. 105 is a top perspective view of an embodiment of a cut guide, in accordance with an aspect of the present disclosure;

FIG. 106 is a bottom perspective view of the cut guide of FIG. 105, in accordance with an aspect of the present disclosure;

FIG. 107 is a side view of the cut guide of FIG. 105, in accordance with an aspect of the present disclosure;

FIG. 108 is another side view of the cut guide of FIG. 105, in accordance with an aspect of the present disclosure;

FIG. 109 is an end view of the cut guide of FIG. 105, in accordance with an aspect of the present disclosure;

FIG. 110 is another end view of the cut guide of FIG. 105, in accordance with an aspect of the present disclosure;

FIG. 111 is a top view of the cut guide of FIG. 105, in accordance with an aspect of the present disclosure;

FIG. 112 is a bottom view of the cut guide of FIG. 105, in accordance with an aspect of the present disclosure;

FIG. 113 is a top perspective view of an embodiment of a cut guide, in accordance with an aspect of the present disclosure; and

FIG. 114 is a bottom perspective view of the cut guide of FIG. 113, in accordance with an aspect of the present disclosure.

DETAILED DESCRIPTION FOR CARRYING OUT THE INVENTION

Generally stated, disclosed herein are devices, systems, and methods for maintaining, correcting and/or fusing joint deformities. Further, methods for using the devices and systems for maintaining, correcting and/or fusing joint deformities are discussed.

In this detailed description and the following claims, the words proximal, distal, anterior or plantar, posterior or dorsal, medial, lateral, superior and inferior are defined by their standard usage for indicating a particular part or portion of a bone or implant according to the relative disposition of the natural bone or directional terms of reference. For example, “proximal” means the portion of a device or implant nearest the torso, while “distal” indicates the portion of the device or implant farthest from the torso. As for directional terms, “anterior” is a direction towards the front side of the body, “posterior” means a direction towards the back side of the body, “medial” means towards the midline of the body, “lateral” is a direction towards the sides or away from the midline of the body, “superior” means a direction above and “inferior” means a direction below another object or structure. Further, specifically in regards to the foot, the term “dorsal” refers to the top of the foot and the term “plantar” refers the bottom of the foot.

Similarly, positions or directions may be used herein with reference to anatomical structures or surfaces. For example, as the current devices, systems, instrumentation and methods are described herein with reference to use with the bones of the foot, the bones of the foot, ankle and lower leg may be used to describe the surfaces, positions, directions or orientations of the devices, systems, instrumentation and methods. Further, the devices, systems, instrumentation and methods, and the aspects, components, features and the like thereof, disclosed herein are described with respect to one side of the body for brevity purposes. However, as the human body is relatively symmetrical or mirrored about a line of symmetry (midline), it is hereby expressly contemplated that the devices, systems, instrumentation and methods, and the aspects, components, features and the like thereof, described and/or illustrated herein may be changed, varied, modified, reconfigured or otherwise altered for use or association with another side of the body for a same or similar purpose without departing from the spirit and scope of the disclosure. For example, the devices, systems, instrumentation and methods, and the aspects, components, features and the like thereof, described herein with respect to the right foot may be mirrored so that they likewise function with the left foot. Further, the devices, systems, instrumentation and methods, and the aspects, components, features and the like thereof, disclosed herein are described with respect to the foot for brevity purposes, but it should be understood that the devices, systems, instrumentation and methods may be used with other bones of the body having similar structures.

Referring to the drawings, wherein like reference numerals are used to indicate like or analogous components

throughout the several views, and with particular reference to FIGS. 1-8, there is illustrated a cut guide 100. The cut guide 100 includes a top surface 102, a bottom surface 104, a first or proximal end 106, a second or distal end 108, a first or medial side 110, and a second or lateral side 112. The cut guide 100 also includes a base portion 114 and a paddle, fin or extension member 128 extending away from the bottom surface 104 of the base portion 114. The cut guide 100 further includes a first or proximal arm 130 extending away from the base portion 114 on a first end 106 and a second or distal arm 140 extending away from the base portion 114 on a second end 108. The cut guide 100 may be, for example, a right foot cut guide.

As shown in FIGS. 1, 5 and 6, the top surface 102 of the base portion 114 may be, for example, curved or arced between the first side 110 and the second side 112. In one embodiment, the top surface 102 of the base portion 114 may include, for example, a flat or planar portion positioned between a first curvature or arc extending from the first side 110 to the flat portion and a second curvature or arc extending from a second side 112 to the flat portion. The base portion 114 also includes at least one slot 116, 118, 120, 122, as shown in FIGS. 1-4, 7 and 8. In the depicted embodiment, the base portion 114 includes a first slot 116 adjacent to a second slot 118 and a third slot 120 adjacent to a fourth slot 122. The first and second slots 116, 118 may be, for example, positioned on the second end 108 of the base portion 114 and the third and fourth slots 120, 122 may be, for example, positioned on the first end 106 of the base portion 114.

With continued reference to FIGS. 1-4 and 7, the slots 116, 118, 120, 122 may extend, for example, linearly through the base portion 114 from the top surface 102 to the bottom surface 104 of the cut guide 100. Alternatively, the slots 116, 118, 120, 122 may also be, for example, angled as the slots 116, 118, 120, 122 extend from the top surface 102 to the bottom surface 104. The slots 116, 118, 120, 122 may be angled, for example, approximately 1° to 4° and more specifically, approximately 2°, as they extend between the top surface 102 and the bottom surface 104. It is also contemplated that some of slots 116, 118, 120, 122 may be angled and other slots 116, 118, 120, 122 may be linear as they extend through the base portion 114 from the top surface 102 to the bottom surface 104.

In addition, the slots 116, 118, 120, 122 may be angled as they extend between the first side 110 and the second side 112, for example, the slots may be angled approximately 0° to 30° as the slots 116, 118, 120, 122 extend between the first and second sides 110, 112. As shown, slots 116, 118, 120, 122 have an angle of 0° as the slots 116, 118, 120, 122 extend between the first and second sides 110, 112. Although not shown with respect to cut guide 100, it is also contemplated that a first set of slots 116, 118 may be angled as they extend between the first and second sides 110, 112 and the second set of slots 120, 122 may be straight, and vice versa. As shown, the slots 120, 122 are positioned to extend between the first and second sides 110, 112 parallel to the first metatarsal, as discussed in greater detail below with respect to the method of using the cut guide 100. The slots 116, 118, 120, 122 may be configured or sized and shaped to receive a saw blade and may have a width of, for example, approximately 0.58 mm to 0.92 mm. The slots 116, 118, 120, 122 may be positioned, for example, to allow for removal of the articular cartilage layer of the two bones. To prevent resecting more bone than absolutely necessary, the slots 116, 118, 120, 122 may be positioned, for example, such that the medial portion of the slots 116, 118, 120, 122 are aligned

with the intersection of the cartilage and bone. In one embodiment, the slots **116**, **118** are positioned a first distance from the extension member **128**, the slots **120**, **122** are positioned a second distance from the extension member **128**, and the first distance is smaller than the second distance. The first distance may be measured from the extension member **128** to an inner surface of the slots **116**, **118** and the second distance may be measured from the extension member **128** to an inner surface of the slots **120**, **122**.

The base portion **114** may also include a hole or dorsal hole **124**, as shown in at least FIGS. **4**, **7** and **8**. The hole **124** is positioned between the second slot **118** and the third slot **120** near the second side **112** of the base portion **114**. The hole **124** may extend, for example, into the base portion **114** from the top surface **102** of the cut guide **100** and to a point within the extension member **128**. As shown in FIGS. **2** and **8**, as the hole **124** extends into the extension member **128**, the hole **124** forms a through hole in a proximal-distal direction through the extension member **128**. The hole **124** may, for example, extend into the cut guide **100** parallel to the angled portion of the extension member **128**, as shown in FIG. **2**. The hole **124** may be sized and shaped or configured, for example, to receive a wire, alignment wire, k-wire, guide wire or the like to provide information on the position of the cut guide **100** in a joint. For example, the wire inserted into hole **124** should align approximately with the long axis of the tibia to provide the proper orientation of the cut guide **100** in the joint, which may be, for example, approximately 45° from dorsal and 45° from medial.

Referring now to FIGS. **1-4** and **8**, the base portion **114** also includes a recessed region **126** positioned on the bottom surface **104**. The recessed region **126** extends from the first side **110** to the second side **112** and into the base portion **114** a first distance from the bottom surface **104** toward the top surface **102**. The extension member **128** is coupled to the recessed region **126** of the base portion **114** and extends away from the recessed region **126** of the base portion **114**. In addition, the extension member **128** is positioned between the second slot **118** and the third slot **120** and also extends from the second side **112** toward the first side **110**, as shown in FIGS. **5**, **6** and **8**. The extension member **128** may be shaped, for example, to fit within the joint space between two bones, such as, a first metatarsal and cuneiform, as well as to make contact with the adjoining articular joint surfaces. The extension member **128** may include a perpendicular portion near the first side **110** that extends perpendicularly away from the bottom surface **104**. The perpendicular portion of the extension member **128** may be, for example, angled when the cut guide **100** is inserted into a patient's joint and the angle that the perpendicular portion is positioned at may correspond to the angle of the first tarsometatarsal joint medially. The extension member **128** may also include an angled portion extending from the second side **112** to the end of the extension member **128**. The angled portion of the extension member **128** may, for example, allow for the extension member **128** to fit within a variety of anatomic presentations. The angled portion of the extension member **128** may, for example, be oriented laterally and should align with the long axis of the tibia, as well as fit within the joint to rest against the relatively straight surface of the adjacent bone, for example, the second metatarsal. When the angled portion of the extension member **128** is oriented against the second metatarsal, the cut guide **100** will be positioned at a 45° angle in the frontal plane.

As shown in FIGS. **1**, **2**, **7** and **8**, the first or proximal arm **130** may extend away from an end of the base portion **114** and may be, for example, tapered from the base portion **114**

to the first end **106** of the cut guide **100**. The first arm **130** includes at least one opening **132**, **134**. In the depicted embodiment, the first arm **130** includes a first opening **132** and a second opening **134** positioned near the first end **106**. The first opening **132** may be spaced apart from the second opening **134**. The openings **132**, **134** may extend from a top surface **102** to a bottom surface **104** of the cut guide **100**. The openings **132**, **134** may extend through the first arm **130**, for example, parallel to the extension member **128**, angled as they extend from the top surface **102** toward the bottom surface **104**, or a combination of parallel and angled. In one embodiment, the first opening **132** may extend, for example, parallel to the extension member **128** and the second opening **134** may be, for example, angled with respect to the extension member **128** to permit the inserted wires, guide wires, k-wires and the like to cross above the cut guide **100** without intersecting. By positioning the openings **132**, **134** such that inserted wires cross above the openings **132**, **134** allows for a smaller surgical incision and less interaction or interference with other instruments during the procedure. The openings **132**, **134** positioning the wires to cross also allows for the cut guide **100** to be, for example, suspended above and/or proximate to the bone surfaces being cut. The ability to suspend the cut guide **100** above the bone surfaces prevents the cut guide **100** from being tilted because of varying patient anatomy and this avoids moving the slots **116**, **118**, **120**, **122** which would affect the proposed cut angles. Alternative combinations of orientations of the openings **132**, **134** are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The first arm **130** may be shaped to provide a bone contacting surface **136** that corresponds to the shape of the bone that it will engage. The first arm **130** may be, for example, curved or arced as it extends between the first side **110** and the second side **112**.

As shown in FIGS. **1**, **2**, **7** and **8**, the second or distal arm **140** may extend away from an end of the base portion **114** and may be, for example, tapered from the base portion **114** to the second end **108** of the cut guide **100**. The second arm **140** includes at least one opening **142**, **144**. In the depicted embodiment, the second arm **140** includes a third opening **142** and a fourth opening **144** positioned near the second end **108**. The third opening **142** may be spaced apart from the fourth opening **144** and extend from a top surface **102** to a bottom surface **104** of the cut guide **100**. The openings **142**, **144** may extend through the second arm **140**, for example, parallel to the extension member **128**, angled as they extend from the top surface **102** toward the bottom surface **104**, or a combination of parallel and angled. In one embodiment, the third opening **142** may extend, for example, parallel to the extension member **128** and the fourth opening **144** may be, for example, angled with respect to the extension member **128** to permit inserted wires, guide wires, k-wires, and the like to cross above the cut guide **100** without intersecting. By positioning the openings **142**, **144** such that the inserted wires cross above the openings **142**, **144** allows for a smaller surgical incision and less interaction or interference with other instruments during the procedure. The openings **142**, **144** being positioned for the wires to cross, also allows for the cut guide **100** to be, for example, suspended above and/or mated with the bone surfaces being cut. Suspending the cut guide **100** above the bone surfaces prevents the cut guide **100** from being angled because of varying patient anatomy which results in not having to move the slots **116**, **118**, **120**, **122** which would affect the proposed cut angles. In one embodiment, the openings **132**, **142** may be, for example, positioned such that they are parallel to one

11

another as they extend between the top and bottom surfaces **102, 104**. By positioning the openings **132, 142** parallel to each other, the cut guide **100** may be, for example, removed from guide wires inserted through openings **132, 142** without removing the guide wires. In addition, parallel openings **132, 142** allow for the relative rotation between the two guide wires to be measured or calculated after the bones are cut using cut guide **100**. Further, the openings **132, 142** may be, for example, spaced apart from the extension member **128** a standard or set distance to allow for interchangeability with alternative cut guides **200, 250, 300, 400**, if a different or additional resection is needed. Alternative, combinations of orientations of the openings **142, 144** are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The second arm **140** may be shaped to provide a bone contacting surface **146** that corresponds to the shape of the bone that it will engage. The second arm **140** may be, for example, curved or arced as it extends between the first side **110** and the second side **112**. The second arm **140** may have, for example, a larger length and width than the first arm **130**.

Referring now to FIGS. 9 and 10, another cut guide **150** is shown. The cut guide **150** is a mirror image of the cut guide **100** in a medial-lateral direction, which will not be described again in full detail for brevity purposes. For example, the hole **124** is positioned on a left side of the cut guide **100** when in an insertion position and the hole **174** is positioned on a right side of the cut guide **150** when in an insertion position. The cut guide **150** may be, for example, for a left foot. The cut guide **150** may include a top surface **152**, a bottom surface **154**, a first or proximal end **156**, a second or distal end **158**, a first or medial side **160**, and a second or lateral side **162**, which may be of the type described above with respect to the top surface **102**, the bottom surface **104**, the first or proximal end **106**, the second or distal end **108**, the first or medial side **110**, and the second or lateral side **112**, respectively. The cut guide **150** may also include a base portion **164** which may be the mirror image of the base portion **114**, as described above. The slots **166, 168, 170, 172**, the hole **174**, and the recessed region **176** may be similar to the slots **116, 118, 120, 122**, hole **124**, and recessed region **126**, as described in greater detail above. Further, the cut guide **150** may include a fin, paddle or extension member **178**, a first or proximal arm **180**, and a second or distal arm **190**, which may be as described above with respect to the extension member **128**, the first arm **130**, and the second arm **140**, respectively. The openings **182, 184** and the bone contacting surface **186** may be as described above with reference to openings **132, 134** and bone contacting surface **136** and the openings **192, 194** and the bone contacting surface **196** may be as described above with reference to openings **142, 144** and the bone contacting surface **146**, which will not be described again here for brevity purposes.

Another cut guide **200** is shown in FIGS. 11-18. The cut guide **200** includes a top surface **202**, a bottom surface **204**, a first or proximal end **206**, a second or distal end **208**, a first or medial side **210**, and a second or lateral side **212**. The top surface **202** may be, for example, wider than the top surface **102** of cut guide **100** providing for larger angular corrections. The cut guide **200** also includes a base portion **214**, a paddle, fin or extension member **228** extending away from the bottom surface **204** of the base portion **214**, a first or proximal arm **230** extending away from the base portion **214** on the first end **206**, and a second or distal arm **240** extending away from the base portion **214** on the second end **208**. The cut guide **200** may be, for example, a right foot cut

12

guide. A mirror image of the cut guide **200** for, for example, a left foot is also contemplated. The cut guide **200** may provide, for example, for transverse plane correction angles of approximately 16°, 18° and 20°, although alternative angles of correction are also contemplated.

As shown in FIGS. 11, 15 and 16, the top surface **202** of the base portion **214** may be, for example, curved or arced between the first side **210** and the second side **212**. In one embodiment, the top surface **202** of the base portion **214** may include, for example, a flat or planar portion positioned between a first curvature or arc extending from the first side **210** to the flat portion and a second curvature or arc extending from a second side **212** to the flat portion. The end of the base portion **214** near the first end **206** of the cut guide **200** may be, for example, angled from the second side **212** to the first side **210**, as shown in FIG. 17. The end of the base portion **214** near the second end **208** of the cut guide **200** may extend, for example, perpendicularly between the first side **210** and the second side **212**, as shown in FIG. 17.

The base portion **214** also includes at least one slot **216, 218, 220, 222**, as shown in FIGS. 11-14, 17 and 18. In the depicted embodiment, the base portion **214** includes a first slot **216** adjacent to a second slot **218** and a third slot **220** adjacent to a fourth slot **222**. The first and second slots **216, 218** are positioned on the base portion **214** near the second end **208** of the cut guide **200** and the third and fourth slots **220, 222** are positioned on the base portion **214** near the first end **206** of the cut guide **200**. The slots **216, 218, 220, 222** may extend, for example, linearly or angled through the base portion **214** from the top surface **202** to the bottom surface **204** of the cut guide **200**. The slots **216, 218, 220, 222** may be, for example, angled approximately 1° to 4° and more specifically, approximately 2°, as the slots **216, 218, 220, 222** extend between the top and bottom surfaces **202, 204**. It is also contemplated that some of slots **216, 218, 220, 222** may be angled and other slots **216, 218, 220, 222** may be linear as they extend through the base portion **214** from the top surface **202** to the bottom surface **204**.

In addition, the slots **216, 218** may be oriented, for example, relatively perpendicular to the first side **210** and the second side **212** as the slots **216, 218** extend from the first side **210** to the second side **212**, as shown in FIGS. 11-14, 17 and 18. The slots **220, 222** may be, for example, angled as the slots **220, 222** extend between the second side **212** and the first side **210**. The slots **220, 222** may also be, for example, angled toward the slots **216, 218**, as the slots **220, 222** extend from the second side **212** to the first side **210**. The slots **220, 222** may also be positioned to extend parallel to the end of the base portion **214** near the second end **208** of the cut guide **200**. The slots **220, 222** may be, for example, angled between approximately 2° and 30°, and more specifically between approximately 8° and 22° as the slots **220, 222** extend from the second side **212** to the first side **210** providing for an angulation correction of 8° to 22° in the transverse plane. The slots **216, 218, 220, 222** may be configured or sized and shaped to receive a saw blade and may have a width of, for example, approximately 0.58 mm to 0.92 mm. The slots **216, 218, 220, 222** may be positioned, for example, to allow for removal of the articular cartilage layer at the ends of the two bones. To prevent resecting more tissue than absolutely necessary, the slots **216, 218, 220, 222** may be positioned, for example, such that the medial portion of the slots **216, 218, 220, 222** are aligned with the intersection of the cartilage and bone.

The base portion **214** may also include a hole or dorsal hole **224**, as shown in at least FIGS. 12, 13, 17 and 18. The hole **224** is positioned between the second slot **218** and the

third slot 220 near the second side 212 of the base portion 214. The hole 224 may extend, for example, into the base portion 214 from the top surface 202 of the cut guide 200 and to a point within the extension member 228. As shown in FIGS. 12, 15, 16 and 18, as the hole 224 extends into the extension member 228, the hole 224 forms an opening in a proximal-distal direction through the extension member 228. The hole 224 may, for example, extend into the cut guide 200 parallel to the angled portion of the extension member 228, as shown in FIG. 12. The hole 224 may be sized and shaped or configured, for example, to receive a wire, alignment wire, k-wire, guide wire or the like to provide information on the position of the cut guide 200 in a joint. For example, a wire inserted into hole 224 should align approximately with the long axis of the patient's tibia to provide the proper orientation of the cut guide 200 in the joint, which may be, for example, approximately 45° from dorsal and 45° from medial in the frontal plane.

Referring now to FIGS. 11-14 and 18, the base portion 214 also includes a recessed region 226 positioned on the bottom surface 204. The recessed region 226 extends from the first side 210 to the second side 212 and into the base portion 214 from the bottom surface 204 toward the top surface 202. The recessed region 226 extends to engage the bone contacting surface 236 of the first arm 230 at the first side 210 of the base portion 214. The extension member 228 is coupled to the recessed region 226 of the base portion 214 and extends away from the recessed region 226 of the base portion 214. In addition, the extension member 228 is positioned between the second slot 218 and the third slot 220. The extension member 228 also extends from the second side 212 toward the first side 210, as shown in FIGS. 12, 15, 16 and 18. The extension member 228 may include a perpendicular portion near the first side 210 that extends perpendicularly away from the bottom surface 204. The perpendicular portion of the extension member 228 may be, for example, angled when the cut guide 200 is inserted into a patient's joint and the angle that the perpendicular portion is positioned at may correspond to the angle of the first tarso-metatarsal joint medially. The extension member 228 may also include an angled portion extending from the second side 212 to the end of the extension member 228. The extension member 228 may be shaped, for example, to fit within the joint space between two bones, such as, a first metatarsal and cuneiform, as well as to mate with the articular joints. The angled portion of the extension member 228 may, for example, be oriented laterally and should align with the long axis of the tibia, as well as fit within the joint to rest against the relatively straight surface of the adjacent bone, for example, the second metatarsal. When the angled portion of the extension member 228 is oriented against the second metatarsal, the cut guide 200 will be positioned at a 45° angle in the frontal plane.

As shown in FIGS. 11, 12, 17 and 18, the first or proximal arm 230 may extend away from an end of the base portion 214 and may be, for example, tapered from the base portion 214 to the first end 206 of the cut guide 200. The side of the first arm 230 on the first side 210 of the cut guide 200 may be, for example, longer than the side of the first arm 230 on the second side 212 of the cut guide 200. The first arm 230 includes at least one opening 232, 234. In the depicted embodiment, the first arm 230 includes a first opening 232 and a second opening 234 positioned near the first end 206. The first opening 232 may be spaced apart from the second opening 234. The openings 232, 234 may extend from a top surface 202 to a bottom surface 204 of the cut guide 200. The openings 232, 234 may extend through the first arm 230,

for example, parallel to the extension member 228, angled as they extend from the top surface 202 toward the bottom surface 204, or a combination of parallel and angled. In one embodiment, the first opening 232 may extend, for example, parallel to the extension member 228 and the second opening 234 may be, for example, angled with respect to the extension member 228. Alternative combinations of the orientations of the openings 232, 234 are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The first arm 230 may be shaped to provide a bone contacting surface 236 that corresponds to the shape or surface of the bone that it will engage. The first arm 230 may be, for example, curved or arced as it extends between the first side 210 and the second side 212 of the cut guide 200.

As shown in FIGS. 11, 12, 17 and 18, the second or distal arm 240 may extend away from an end of the base portion 214 and may be, for example, tapered from the base portion 214 to the second end 208 of the cut guide 200. The second arm 240 also includes at least one opening 242, 244. In the depicted embodiment, the second arm 240 includes a third opening 242 and a fourth opening 244 positioned near the second end 208. The third opening 242 may be spaced apart from the fourth opening 244. The openings 242, 244 may extend from a top surface 202 to a bottom surface 204 of the cut guide 200. The openings 242, 244 may extend through the second arm 240, for example, parallel to the extension member 228, angled as they pass from the top surface 202 to the bottom surface 204, or a combination of parallel and angled. In one embodiment, the third opening 242 may extend, for example, parallel to the extension member 228 and the fourth opening 244 may be, for example, angled with respect to the extension member 228. Alternative combinations of the openings 242, 244 orientations are also contemplated, as would be understood by one of ordinary skill in the art from the above description. In one embodiment, the holes 232, 242 may be, for example, positioned such that they are parallel to one another as they extend between the top and bottom surfaces 202, 204. By positioning the holes 232, 242 parallel to each other, the cut guide 200 may be, for example, removed from guide wires inserted through holes 232, 242 without removing the guide wires. In addition, parallel holes 232, 242 allow for the relative rotation between the two guide wires to be measured or calculated after the bones are cut using cut guide 200. Further, the holes 232, 242 may be, for example, spaced apart from the extension member 228 a standard or set distance to allow for interchangeability with alternative cut guides 100, 250, 300, 400, if a different or additional resection is needed. The second arm 240 may be shaped to provide a bone contacting surface 246 that corresponds to the surface or shape of the bone that it will engage. The second arm 240 may be, for example, curved or arced as it extends between the first side 210 and the second side 212. The second arm 240 may have, for example, a larger length and width than the first arm 230.

The openings 232, 234, 242, 244 may be positioned such that wires inserted into the first and second openings 232, 234 cross above the cut guide 200 and wires inserted into the third and fourth openings 242, 244 cross above the cut guide 200. By positioning the openings 232, 234 and openings 242, 244 such that inserted wires cross above the openings 232, 234 and openings 242, 244, respectively, the surgeon may make a smaller surgical incision and reduce the interaction or interference with other instruments during the procedure. The openings 232, 234, 242, 244 being positioned to allow the wires to cross also allows for the cut guide 200 to be, for example, suspended above and/or in

contact with the bone surfaces being cut. Suspending the cut guide 200 above the bone surfaces prevents the cut guide 200 from being angled or tilted on the irregular bone surface and avoids moving the slots 216, 218, 220, 222, which would affect the proposed cut angles.

Referring now to FIGS. 19-26, yet another cut guide 250 is shown. The cut guide 250 includes a top surface 252, a bottom surface 254, a first or proximal end 256, a second or distal end 258, a first or medial side 260, and a second or lateral side 262. The top surface 252 may be, for example, narrower than the top surface 202 of cut guide 200 to provide for smaller angular corrections. The cut guide 250 also includes a base portion 264, a paddle, fin or extension member 278 extending away from the bottom surface 254 of the base portion 264, a first or proximal arm 280 extending away from the base portion 264 on a first end 256, and a second or distal arm 290 extending away from the base portion 264 on a second end 258. The cut guide 250 may be, for example, a right foot cut guide. A mirror image of the cut guide 250 for, for example, a left foot is also contemplated. The cut guide 250 may provide, for example, for transverse plane correction angles of approximately 2°, 4°, 6°, 8°, 10°, 12° and 14°, although alternative angles are also contemplated.

As shown in FIGS. 19, 23 and 24, the top surface 252 of the base portion 264 may be, for example, curved or arced between the first side 260 and the second side 262. The top surface 252 of the base portion 264 may include, for example, a flat or planar portion positioned between a first curvature or arc extending from the first side 260 to the flat portion and a second curvature or arc extending from the second side 262 to the flat portion, as shown in FIGS. 23 and 24. The end of the base portion 264 near the first end 256 of the cut guide 250 may be, for example, angled from the second side 262 to the first side 260, as shown in FIG. 25. The end of the base portion 264 near the second end 258 of the cut guide 250 may extend, for example, perpendicularly between the first side 260 and the second side 262, as shown in FIG. 25.

The base portion 264 also includes at least one slot 266, 268, 270, 272, as shown in FIGS. 19-22, 25 and 26. In the depicted embodiment, the base portion 264 includes a first slot 266 adjacent to a second slot 268 and a third slot 270 adjacent to a fourth slot 272. The first and second slots 266, 268 are positioned on the base portion 264 near the second end 258 of the cut guide 250 and the third and fourth slots 270, 272 are positioned on the base portion 264 near the first end 256 of the cut guide 250. The slots 266, 268, 270, 272 may extend, for example, linearly through the base portion 264 from the top surface 252 to the bottom surface 254. The slots 266, 268, 270, 272 may also be, for example, angled as the slots 266, 268, 270, 272 extend from the top surface 252 to the bottom surface 254. The slots 266, 268, 270, 272 may be angled, for example, approximately 1° to 4° or more specifically, approximately 2°, as the slots 266, 268, 270, 272 extend from the top surface 252 to the bottom surface 254. It is also contemplated that some of the slots 256, 258, 230, 232 may be angled and other slots 256, 258, 260, 262 may be linear as they extend through the base portion 254 from the top surface 252 to the bottom surface 254.

The slots 266, 268 may also extend, for example, relatively perpendicular to the first side 260 and the second side 262 as the slots 266, 268 extend from the first side 260 to the second side 262, as shown in FIGS. 19-22, 25 and 26. The slots 270, 272 may be, for example, angled as the slots 270, 272 extend between the second side 262 and the first side 260. The slots 270, 272 may also be, for example, angled

toward the slots 266, 268 as the slots 270, 272 extend from the second side 262 to the first side 260. The slots 270, 272 may be positioned to extend parallel to the end of the base portion 264 near the first end 256 of the cut guide 250. The slots 270, 272 may be, for example, angled at approximately 10°, 12°, 14°, and 16° as they extend between the first side 260 and the second side 262 providing for angulation corrections of 8°, 10°, 12°, and 14°, respectively. The slots 266, 268, 270, 272 may be configured or sized and shaped to receive a saw blade and may have a width of, for example, approximately 0.58 mm to 0.92 mm. The slots 266, 268, 270, 272 may be positioned, for example, to allow for removal of the articular cartilage. To prevent resecting more tissue than absolutely necessary, the slots 266, 268, 270, 272 may be positioned, for example, such that the medial portion of the slots 266, 268, 270, 272 are aligned with the intersection of the cartilage and bone or the cartilage-bone line.

The base portion 264 may also include a hole or dorsal hole 274, as shown in at least FIGS. 19-21 and 23-26. The hole 274 is positioned between the second slot 268 and the third slot 270 near the second side 262 of the base portion 264. The hole 274 may extend, for example, through the base portion 264 from the top surface 252 of the cut guide 250 and to an intersection point within the extension member 278. As shown in FIGS. 23, 24 and 26, as the hole 274 extends into the extension member 278, the hole 274 forms an opening in a proximal-distal direction through the extension member 278. The hole 274 may, for example, extend into the cut guide 250 parallel to the angled portion of the extension member 278, as shown in FIGS. 20, 23 and 24. The hole 274 may also be sized and shaped or configured, for example, to receive a wire, alignment wire, k-wire, guide wire or the like to provide information on the position of the cut guide 250 in a joint. For example, the wire inserted into hole 274 should align approximately with the long axis of the tibia to provide the proper orientation of the cut guide 250 relative to the joint, which may be, for example, approximately 45° from dorsal and 45° from medial in the frontal plane.

Referring now to FIGS. 19-22 and 26, the base portion 264 may also include a recessed region 276 positioned on the bottom surface 254. The recessed region 276 extends from the first side 260 to the second side 262 and into the base portion 264 from the bottom surface 254 toward the top surface 252. The extension member 278 is coupled to the recessed region 276 of the base portion 264 and extends away from the recessed region 276. In addition, the extension member 278 is positioned between the second slot 268 and the third slot 270 and extends from the second side 262 toward the first side 260, as shown in FIGS. 20, 23, 24 and 26. The extension member 278 may include a perpendicular portion near the first side 260 that extends perpendicularly away from the bottom surface 254. The perpendicular portion of the extension member 278 may be, for example, angled when the cut guide 250 is inserted into a patient's joint and the angle that the perpendicular portion is positioned at may correspond to the angle of the first tarsometatarsal joint medially. The extension member 278 may also include an angled portion extending from the second side 262 to the end of the extension member 278. The extension member 278 may be shaped, for example, to fit within the joint space between two adjacent bones, such as, a first metatarsal and cuneiform, as well as to make contact with the two side of an articular joint. The angled portion of the extension member 278 may, for example, be oriented laterally and should align with the long axis of the tibia, as well as fit within the joint to rest against the relatively

straight surface of the adjacent bone, for example, the second metatarsal. When the angled portion of the extension member **228** is oriented against the second metatarsal, the cut guide **250** will be positioned at a 45° angle in the frontal plane.

As shown in FIGS. **19, 20, 25** and **26**, the first or proximal arm **280** may extend away from an end of the base portion **264** and may be, for example, tapered from the base portion **264** to the first end **256** of the cut guide **250**. The side of the first arm **280** on the first side **260** of the cut guide **250** may be, for example, longer than the side of the first arm **280** on the second side **262** of the cut guide **250**. The first arm **280** includes at least one opening **282, 284**. In the depicted embodiment, the first arm **280** includes a first opening **282** and a second opening **284** positioned near the first end **256**. The first opening **282** may be spaced apart from the second opening **284**. The openings **282, 284** may extend from a top surface **252** to a bottom surface **254** of the cut guide **250**. The openings **282, 284** may extend through the first arm **280**, for example, parallel to the extension member **278**, angled as they extend from the top surface **252** toward the bottom surface **254**, or a combination of parallel and angled orientations. In one embodiment, the first opening **282** may extend, for example, parallel to the extension member **278** and the second opening **284** may be, for example, angled with respect to the extension member **278**. Alternative, combinations of orientations of the openings **282, 284** are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The first arm **280** may be shaped to provide a bone contacting surface **236** that corresponds to the shape of the bone that it will engage. The first arm **280** may be, for example, curved or arced as it extends between the first side **260** and the second side **262** of the cut guide **250**.

As shown in FIGS. **19, 20, 25** and **26**, the second or distal arm **290** may extend away from an end of the base portion **264** and may be, for example, tapered from the base portion **264** to the second end **258** of the cut guide **250**. The second arm **290** includes at least one opening **292, 294**. In the depicted embodiment, the second arm **290** includes a third opening **292** and a fourth opening **294** positioned near the second end **258**. The third opening **292** may be spaced apart from the fourth opening **294**. The openings **292, 294** may extend from the top surface **252** to the bottom surface **254** of the cut guide **250**. The openings **292, 294** may extend through the second arm **290**, for example, parallel to the extension member **278**, angled as they extend from the top surface **252** toward the bottom surface **254**, or a combination of parallel and angled. In one embodiment, the third opening **292** may extend, for example, parallel to the extension member **278** and the fourth opening **294** may be, for example, angled with respect to the extension member **278**. Alternative combinations of the orientations of the openings **292, 294** are also contemplated, as would be understood by one of ordinary skill in the art from the above description. In one embodiment, the openings **282, 292** may be, for example, positioned such that they are parallel to one another as they extend between the top and bottom surfaces **252, 254**. By positioning the openings **282, 292** parallel to each other, the cut guide **250** may be, for example, removed from guide wires inserted through openings **282, 292** without removing the guide wires. In addition, parallel openings **282, 292** allow for the relative rotation between the two guide wires to be measured or calculated after the bones are cut using cut guide **250**. Further the openings **282, 292** may be, for example, spaced apart from the extension member **278** a standard or set distance to allow for interchangeability

with alternative cut guides **100, 200, 300, 400**, if a different or additional resection is needed. The second arm **290** may be shaped to provide a bone contacting surface **296** that corresponds to the shape of the bone surface that it will engage. The second arm **290** may be, for example, curved or arced as it extends between the first side **260** and the second side **262**. The second arm **290** may have, for example, a larger length and width than the first arm **280**.

The openings **282, 284, 292, 294** may be positioned such that wires inserted into the first and second openings **282, 284** and wires inserted into the third and fourth openings **292, 294** all cross above the cut guide **250**. By positioning the openings **282, 284** and openings **292, 294** such that inserted wires cross above the openings **282, 284** and openings **292, 294**, respectively, the surgeon can make a smaller surgical incision and reduce the interaction or interference with other instruments during the procedure. The openings **282, 284, 292, 294** being positioned to allow wires to cross also allows for the cut guide **250** to be, for example, suspended above and/or in contact with the bone surfaces being cut. Suspending the cut guide **250** above the bone surfaces prevents the cut guide **250** from being tilted on the irregular bone surface and therefore avoids moving the slots **282, 284, 292, 294**, which would affect the proposed cut angles.

Another cut guide **300** is shown in FIGS. **27-34**. The cut guide **300** includes a top surface **302**, a bottom surface **304**, a first end **306**, a second end **308**, a first side **310**, and a second side **312**. The first end **306** may be, for example, a proximal end, and the second end **308** may be, for example, a distal end, or vice versa. The first side **310** may be, for example, a medial side, and the second side **312** may be, for example, a lateral side, or vice versa. The cut guide **300** also includes a base portion **314**, a paddle, fin or extension member **322** extending away from the bottom surface **304** of the base portion **314**, and an arm **330** extending away from the base portion **314** on the second end **308**. As shown in FIGS. **27-34**, the cut guide **300** may be, for example, a right foot cut guide. The cut guide **300** may provide, for example, a 4° angulation from dorsal to plantar on the metatarsal.

Cut guide **300** may be used, for example, when a surgeon decides that correction of the first metatarsal in plantarflexion is not sufficient enough and needs to take off more of the metatarsal from the dorsal to plantar direction. Alternatively, cut guide **300** may be used, for example, when a surgeon knows from pre-operative radiographs that the first ray is dorsiflexed in order to cut more bone of the metatarsal plantarly to correct the dorsiflexion. For example, when guide **300** is used, it will be inserted into the patient's joint, the surgeon will use cut guide **300** to cut the first metatarsal, then cut guide **300** will be removed and replaced with another cut guide, such as, cut guide **100, 200, 250**, to cut the cuneiform. The second guide **100, 200, 250** will be selected based on the size and desired angular correction of the cuneiform. The cut guide **300** may be removed from the patient's bones, for example, by sliding the guide **300** off a guide wire inserted through the opening **332** and inserting the second cut guide **100, 200, 250** onto the guide wire to properly align the second cut guide **100, 200, 250** on the patient's bones with respect to the first cut made to the metatarsal.

As shown in FIGS. **27, 31** and **32**, the top surface **302** of the base portion **314** may be, for example, curved or arced between the first side **310** and the second side **312**. In an embodiment, the top surface **302** of the base portion **314** may include, for example, a flat or planar portion positioned between a first curvature or arc extending from the first side

310 to the flat portion and a second curvature or arc extending from the second side 312 to the flat portion. The base portion 314 also includes at least one slot 316, 318, as shown in FIGS. 27-30, 33 and 34. In the depicted embodiment, the first slot 316 is positioned adjacent to a second slot 318. The slots 316, 318 may extend, for example, through the base portion 314 from the top surface 302 to the bottom surface 304 of the cut guide 300. The slots 316, 318 may be, for example, angled as the slots 316, 318 extend from the top surface 302 to the bottom surface 304. The slots 316, 318 may be angled, for example, approximately 1° to 4° and more specifically, approximately 2°, as the slots 316, 318 extend between the top surface 302 and the bottom surface 304. It is also contemplated that the interior slot 316 may be angled while the exterior slot 318 may be linear as they extend between the top and bottom surfaces 302, 304.

In addition, the slots 316, 318 may be angled as they extend across the base portion 314 from the first side 310 to the second side 312, as shown in FIGS. 33 and 34. The slots 316, 318 may be, for example, angled at approximately 6° as they extend between the first and second sides 310, 312 providing for an angulation correction of 4°. The slots 316, 318 may be configured or sized and shaped to receive a saw blade and may have a width of, for example, approximately 0.58 mm to 0.92 mm. As shown in FIG. 33, the slots 316, 318 may be angled from a distal-medial position to a proximal-lateral position of the cut guide 300. The slots 316, 318 may be positioned, for example, to allow for removal of the articular cartilage only. To prevent resecting too much tissue, the slots 316, 318 may be positioned, for example, such that the medial portion of the slots 316, 318 are aligned with the cartilage and bone boundary.

The base portion 314 also includes a hole or dorsal hole 320, as shown in at least FIGS. 27-29, 33 and 34. The hole 320 is positioned between the second slot 318 and the arm 330. The hole 320 may extend, for example, through the base portion 314 from the top surface 302 to the bottom surface 304. The hole 320 may, for example, extend through the base portion 314 of the cut guide 300 parallel to the angled portion of the extension member 322, as shown in FIG. 27. The hole 320 may be sized and shaped or configured, for example, to receive a wire, alignment wire, k-wire, guide wire, directional wire or the like to provide information on the position of the cut guide 300 in a joint. For example, the wire inserted into hole 320 should align approximately with the long axis of the tibia to provide the proper orientation of the cut guide 300 in the joint, which may be, for example, approximately 45° from dorsal and 45° from medial in the frontal plane.

Referring now to FIGS. 28-32 and 34, the extension member 322 is attached to a bottom surface 304 of the base portion 314. The extension member 322 also extends away from the base portion 314 and is positioned on the first end 306 of the cut guide 300. In addition, the extension member 322 extends from the second side 312 toward the first side 310, as shown in at least FIGS. 28, 31 and 32. The extension member 322 may include a portion near the first side 310 that extends perpendicularly away from the bottom surface 304. The perpendicular portion of the extension member 322 may be, for example, angled when the cut guide 300 is inserted into a patient's joint and the angle that the perpendicular portion is positioned at may correspond to the angle of the first tarso-metatarsal joint medially. The extension member 322 may also include an angled portion extending from the second side 312 to the end of the extension member 322. The extension member 322 may be shaped, for example, to fit within the joint space between the two bones,

such as, a first metatarsal and cuneiform, as well as to mate with the two sides of an articular joint. The angled portion of the extension member 322 may, for example, be oriented laterally and should align with the long axis of the tibia, as well as fit within the joint to rest against the relatively straight surface of the adjacent bone, for example, the second metatarsal. When the angled portion of the extension member 322 is oriented against the second metatarsal, the cut guide 300 will be positioned at a 45° angle in the frontal plane.

As shown in FIGS. 27-30 and 32-34, the arm 330 may extend away from an end of the base portion 314 and may be, for example, tapered from the base portion 314 to the second end 308 of the cut guide 300. The arm 330 may be, for example, a distal arm. The arm 330 may include at least one opening 332, 334. In the depicted embodiment, the arm 330 includes a first opening 332 and a second opening 334 positioned near the second end 308. The first opening 332 may be spaced apart from the second opening 334. The openings 332, 334 may extend from a top surface 302 to a bottom surface 304 of the cut guide 300. The openings 332, 334 may extend through the arm 330, for example, parallel to the extension member 322, be angled as the openings 332, 334 extend from the top surface 302 toward the bottom surface 304, or a combination of being parallel and angled. In one embodiment, the first opening 332 may extend, for example, parallel to the extension member 322 and the second opening 334 may be, for example, angled with respect to the extension member 322 resulting in the inserted wires, guide wires, k-wires and the like to cross above the cut guide 300. By positioning the openings 332, 334 such that the inserted wires cross above the openings 332, 334, the surgeon may make a smaller surgical incision and there will be less interaction or interference with other instruments during the procedure. Alternative combinations of the orientations of the openings 332, 334 are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The arm 330 may be shaped, for example, to provide a bone contacting surface 336 that corresponds to the surface or shape of the bone that the arm 330 will engage. The arm 330 may be, for example, curved or arced as it extends between the first side 310 and the second side 312.

Referring now to FIGS. 35 and 36, another cut guide 350 is shown. As shown, the cut guide 350 may be a mirror image of the cut guide 300 in a medial-lateral direction, therefore, the cut guide 350 will not be described in full detail for brevity purposes. Therefore, the cut guide 350 may be, for example, for a left foot. The cut guide 350 may include a top surface 352, a bottom surface 354, a first or proximal end 356, a second or distal end 358, a first or medial side 360, and a second or lateral side 362, which may be as described above with respect to the top surface 302, the bottom surface 304, the first or proximal end 306, the second or distal end 308, the first or medial side 310, and the second or lateral side 312, respectively, which will not be described again here for brevity sake. As the cut guide 350 is a mirror image of the cut guide 300, the cut guide 350 may also include a base portion 364 which may be the mirror image of the base portion 314 as described above. In addition, the hole 320 is positioned on a left side of the cut guide 300 when in an insertion position and the hole 370 is positioned on the right side of the cut guide 350 when in an insertion position. The slots 366, 368 and the hole 370 may be similar to the slots 316, 318 and hole 320, as described in greater detail above. Specifically, as the cut guide 350 is a mirror image of the cut guide 300, the slots 366, 368 may be angled

from a distal-lateral position to a proximal-medial position of the cut guide 350 resulting in 4° of cumulative dorsal to plantar cutting, as described in greater detail above with reference to cut guide 300. Further, the cut guide 350 may include a fin, paddle or extension member 372 and an arm 380, which may be as described above with respect to the fin, paddle or extension member 322 and the arm 330, respectively. The openings 382, 384 and bone contacting surface 386 may be as described above with reference to the openings 332, 334 and bone contacting surface 336, which will not be described again here for brevity purposes.

Another cut guide 400 is shown in FIGS. 37-44. The cut guide 400 includes a top surface 402, a bottom surface 404, a first end 406, a second end 408, a first side 410, and a second side 412. The first end 406 may be, for example, a proximal end, and the second end 408 may be, for example, a distal end, or vice versa. The first side 410 may be, for example, a medial side, and the second side 412 may be, for example, a lateral side, or vice versa. The cut guide 400 also includes a base portion 414, a paddle, fin or extension member 418 extending away from the bottom surface 404 of the base portion 414, and an arm 420 extending away from the base portion 414 on the second end 408. The cut guide 400 may be, for example, used on a right foot or a left foot.

The cut guide 400 may be, for example, used after any one of cut guides 100, 150, 200, 250, 300, 350 to take off additional tissue or bone when the original cut does not take off enough tissue or bone. The cut guide 400 may be positioned so that the extension member 418 is against and parallel to a previous cut in the joint, to cut away additional tissue or bone without changing the angulation of the prior cut.

As shown in FIGS. 41 and 42, the top surface 402 of the base portion 414 may be, for example, curved or arced between the first side 410 and the second side 412. In an embodiment, the top surface 402 of the base portion 414 may include, for example, a flat or planar portion positioned between a first curvature or arc extending from the first side 410 to the flat portion and a second curvature or arc extending from a second side 412 to the flat portion. The base portion 414 also includes at least one slot 416, as shown in FIGS. 37-40, 43 and 44. In the depicted embodiment, the slot 416 is positioned near a center or longitudinal axis of the base portion 414. The slot 416 may extend, for example, linearly through the base portion 414 from the top surface 402 to the bottom surface 404 of the cut guide 400. The slot 416 may also be, for example, positioned parallel with the extension member 418, as the slot 416 extends from between the top surface 402 and the bottom surface 404. The slot 416 may be positioned, for example, to allow for removal of the articular cartilage layer of the bones. To prevent resecting more bone than absolutely necessary, the slot 416 may be positioned, for example, such that the medial portion of the slot 416 is aligned with the cartilage-bone border. The slot 416 may be positioned, for example, a first distance from the extension member 418. The slot 416 may be configured or sized and shaped to receive a saw blade and may have a width of, for example, approximately 0.58 mm to 0.92 mm.

Referring now to FIGS. 37-42 and 44, the extension member 418 is coupled to a bottom surface 404 of the base portion 414. The extension member 418 also extends away from the base portion 414 and is positioned on the first end 406 of the cut guide 400. In addition, the extension member 418 extends from the second side 412 to the first side 410, as shown in at least FIGS. 38, 41 and 42. The extension member 418 may be tapered and include a first angled portion extending from the first side 410 to the end of the

extension member 418 and a second angled portion extending from the second side 412 to the end of the extension member 418. As the cut guide 400 may be used on either a right or left foot, extension member 418 is angled on both the first and second sides 410, 412 to allow for an angled portion to mate with the lateral side of the joint. Further, the angled portion may rest against the relatively straight surface of the adjacent bone, for example, the second metatarsal. When an angled portion of the extension member 418 is oriented against the second metatarsal, the cut guide 400 will be positioned at a 45° angle medial in the frontal plane. The extension member 418 may be shaped, for example, to fit within the joint space between two bones, such as, a first metatarsal and cuneiform, as well as to mate with the surface of an articular joint.

As shown in FIGS. 37-40 and 42-44, the arm 420 may extend away from an end of the base portion 414 and may be, for example, tapered from the base portion 414 to the second end 408 of the cut guide 400. The portion of the arm 420 at the second end 408 of the cut guide 400 may be, for example, angled as the arm 420 extends from the second side 412 to the first side 410. The arm 420 may be, for example, a distal arm. The arm 420 may include at least one opening 422, 424. In the depicted embodiment, the arm 420 includes a first opening 422 and a second opening 424 positioned near the second end 408. The first opening 422 may be spaced apart from the second opening 424. The openings 422, 424 may extend from the top surface 402 through the bottom surface 404. The openings 422, 424 may extend through the arm 420, for example, parallel to the extension member 418, angled with respect to the top surface 402 and the bottom surface 404, or a combination of being parallel and angled. In one embodiment, the first opening 422 may extend, for example, parallel to the extension member 418 and the second opening 424 may be, for example, angled with respect to the extension member 418 to cause the inserted wires, guide wires, k-wires and the like to cross above the cut guide 400. By positioning the openings 422, 424 such that inserted wires cross above the openings 422, 424, a smaller surgical incision may be made and less interaction or interference with other instruments will be experienced during the procedure. The openings 422, 424 positioning the wires to cross also allows for the cut guide 400 to be, for example, suspended above and/or against the bone surfaces being cut. The ability to suspend the cut guide 400 above the bone surfaces prevents the cut guide 400 from being angled or tilted because of the inconsistent bone surface which avoids moving the slot 416 and prevents the proposed cut angles from being moved. Alternative combinations of the orientations of the openings 422, 424 are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The arm 420 may be shaped, for example, to provide a bone contacting surface 426 that corresponds to the shape of the bone surface that the arm 420 will engage. The arm 420 may be, for example, curved or arced as it extends between the first side 410 and the second side 412.

With continued reference to the cut guide 400 of FIGS. 37-44, an alternative embodiment cut guide 430 and insertion handle 450 are shown in FIGS. 66-74. The cut guide 430 includes a top surface 402, a bottom surface 404, a first end 406, a second end 408, a first side 410, and a second side 412, as described in greater detail above with reference to cut guide 400 and which will not be described again here for brevity sake. The cut guide 430 also includes a base portion 414, a paddle, fin or extension member 418 extending away from the bottom surface 404 of the base portion 414, and an

arm 420 extending away from the base portion 414 on the second end 408, as described in greater detail above with reference to cut guide 400 and which will not be described again here for brevity sake. The base portion 414 also includes at least one slot 416, as also described in greater detail above with reference to cut guide 400 and which will not be described again here for brevity sake. The arm 420 may include at least one opening 422, 424, as described in greater detail above with reference to cut guide 400 and which will not be described again here for brevity sake. The arm 420 may be shaped, for example, to provide a bone contacting surface 426 that corresponds to the shape of the bone surface that the arm 420 will engage, as described in greater detail above with reference to cut guide 400 and which will not be described again here for brevity sake. The cut guide 430 may be, for example, used on a right foot or a left foot.

As shown in FIGS. 66-69 and 71, the cut guide 430 may also include a recess or opening 432 inset into the surface of the base portion 414 on the first end 406. The recess 432 may have, for example, an oval, round, or a polygonal shaped recess for receiving a correspondingly shaped protrusion 460 on an insertion handle 450. The insertion handle 450 allows for a surgeon to apply pressure against a patient's joint to achieve maximum contact between the cut guide 430 and the previously cut bone. As shown in FIGS. 66-74, the insertion handle 450 includes a handle portion 452 with a stem portion 454 extending away from a distal end of the handle portion 452. The stem portion 454 includes a tip 456 at the distal end of the stem portion 454. The tip 456 includes an end surface 458 which may be, for example, angled with respect to the proximal end of the handle portion 452. The end surface 458 may be, for example, angled to provide the desired angle for insertion of the cut guide 430. The insertion handle 450 may further include an engagement member or protrusion 460 extending away from the end surface 458. The engagement member 460 may be, for example, shaped to correspond to the recess 432 in the cut guide 430. The engagement member 460 may have, for example, an oval, round or polygonal shape.

Referring now to FIGS. 45 and 46, a guide system 500 is shown. The guide system 500 includes a cut guide 100, 150, 200, 250, 300, 350 and an alignment guide 510. The guide system 500 may also include the cut guide or revision cut guide 400. The guide system 500 may also include a position rotation device 550, as shown in FIG. 64. Further, the guide system 500 may include at least one directional wire 606 and at least two wires, guide wires, k-wires, or the like 608, 610, 612, 614, 616, as shown in FIGS. 57-59. In the depicted embodiment of FIGS. 45 and 46, the guide system 500 includes the cut guide 100 and the alignment guide 510. Although not shown, it is also contemplated that cut guides 150, 200, 250, 300, 350 may be interchangeable with cut guide 100 in the below described method or alternatively, used in conjunction with the cut guide 100 as described in greater detail below. The various embodiments of the cut guides 100, 150, 200, 250, 300, 350 are described in greater detail above and will not be described again here for brevity sake. As shown in FIGS. 45 and 46, the alignment guide 510 removably engages the cut guide 100. The alignment guide 510 may, for example, couple to at least one slot 116, 118, 120, 122 of the cut guide 100. In one embodiment, the alignment guide 510 couples to two slots 116, 118, 120, 122 and, for example, it is preferable that the alignment guide 510 couple to the two proximal slots 120, 122.

As shown in FIGS. 45-52, the alignment guide 510 includes a base portion 512 with a top surface 514, a bottom

surface 516, a first end 518, a second end 520, a first side 522, and a second side 524. The a first end 518 may be, for example, a proximal end, a second end 520 may be, for example, a distal end, a first side 522 may be, for example, a medial side, and a second side 524 may be, for example, a lateral side. The base portion 512 may also include at least one opening 526, 528, 530 extending between the first end 518 and the second end 520. In the depicted embodiment, the base portion 512 includes a first opening 526 positioned near the first side 522, a third opening 530 positioned near the second side 524, and a second opening 528 positioned between the first opening 526 and the third opening 530, as shown in FIGS. 45-48 and 50. The openings 526, 528, 530 may be, for example, sized and shaped to receive a wire, guide wire, k-wire, directional wire, or the like, as shown in FIGS. 55-59.

The alignment guide 510 may also include a first extension member or leg member 532 extending away from a bottom surface 516 of the base portion 512, as shown in FIGS. 45, 47-49, 51, and 52. The first extension member 532 may include a first portion 534, a second portion 536 and a first engagement member 538. The first portion 534 may be coupled to the bottom surface 516 of the base portion 512 at a first end, extend away from a position near a center of the base portion 512 in the direction of the first end 518 at an angle, and be coupled to the second portion 536 at a second end. The first end of the second portion 536 may extend from the second end of the first portion 534 in a direction toward the second end 520 of the base portion 512 and be coupled to the first engagement member 538 at a second end. The first engagement member 538 may be coupled to the second portion 536 at a first end and extend in a plantar direction away from the second portion 536 to a second end. The second end of the first engagement member 538 may be shaped to engage the slots in a cut guide, for example, the slots 116, 118, 120, 122 of cut guide 100, as shown in FIGS. 45 and 46. The second end of the second engagement member 546 may also engage the slots of alternative cut guides, such as, cut guides 150, 200, 250, 300, 350.

The alignment guide 510 may also include a second extension member or leg member 540 extending away from a bottom surface 516 of the base portion 512, as shown in FIGS. 45, 47-49, 51, and 52. The second extension member 540 may include a third portion 542, a fourth portion 544 and a second engagement member 546. The third portion 542 may be coupled to the bottom surface 516 of the base portion 512 at a first end, extend away from a position near a center of the base portion 512 in the direction of the second end 520 at an angle, and be coupled to the fourth portion 544 at a second end. The first end of the second extension member 540 may also couple to or engage the first end of the first extension member 532. The first end of the fourth portion 544 may extend from the second end of the third portion 542 in a direction toward the first end 518 of the base portion 512 and be coupled to the second engagement member 546 at a second end. The second engagement member 546 may be coupled to the fourth portion 544 at a first end and extend in a plantar direction away from the fourth portion 544 to a second end. The second end of the second engagement member 546 may be shaped to engage slots in a cut guide, for example, the slots 116, 118, 120, 122 of cut guide 100, as shown in FIGS. 45 and 46. The second end of the second engagement member 546 may also engage the slots of alternative cut guides, such as, cut guides 150, 200, 250, 300, 350.

Referring now to FIGS. 45, 47-49, and 52, the first extension member 532 and second extension member 540

may be, for example, mirror images of each other as the members **532, 540** extend away from the bottom surface **516** of the base portion **512**. The extension members **532, 540** may be shaped, for example, to form a triangular shape with the first portion **534** forming a first side, the third portion **542** forming a second side, and the second portion **536** and the fourth portion **544** together forming a third side. The shape of the extension members **532, 540** allows for the alignment guide **510** to be positioned with respect to a cut guide **100, 150, 200, 250, 300, 350** to create a visual depiction of the angle of deformity correction in both the dorsal and lateral planes. The first engagement member **538** may extend away from the second portion **536**, for example, generally parallel to the second engagement member **546** as the second engagement member **546** extends away from the fourth portion **544**. The engagement members **538, 546** may extend away from the second and fourth portions **536, 544**, respectively, for example, generally perpendicular to the top surface **514** of the base portion **512**. Alternatively, it is also contemplated that the engagement members **538, 546** may extend, for example, away from the second and fourth portions **536, 544**, respectively, at an angle with respect to the top surface **514** of the base portion **512**. The extension members **532, 540** may act to create, for example, a spring like mechanism in the engagement members **538, 546** to allow the engagement members **538, 546** to couple to the cut guides **100, 150, 200, 250, 300, 350**.

The position rotation device **550** is shown in FIGS. **64** and **65**. The rotation device includes a base **552** with a top surface **554** opposite a bottom surface **556**. The base **552** also includes a first end **558** opposite a second end **560**. The base **552** may be, for example, curved to form a semi-circle or arc as the base **552** extends from the first end **558** to the second end **560**. The base **552** may also optionally include a center alignment groove **562**. The alignment groove **562** may be inset into a front side of the base **552** and may extend from the top surface **554** through the base **552** to the bottom surface **556**.

With continued reference to FIGS. **64** and **65**, the base **552** further includes a first or zero opening **564** positioned, for example, centered between the first end **558** and the second end **560** of the base **552**. The zero opening **564** may be positioned adjacent to the first end **582** of the shaft **580**. The zero opening **564** may also be positioned, for example, near a back side of the base **552**. The zero opening **564** may have, for example, an insertion angle for a guide wire, k-wire or the like of 0° as the opening **564** extends from the top surface **554** to the bottom surface **556**. The zero opening **564** may be used for positioning and aligning the position rotation device **550** on a patient. The zero opening **564** may be, for example, sized and shaped or configured to receive a guide wire, k-wire or the like, for aligning the rotation device **550** on a patient's bone.

As shown in FIGS. **64** and **65**, the base **552** may also include a first set of overlapping openings **566**. The openings **566** may be positioned along the front side of the rotation device **550** between the groove **562** and the first end **558**. The base **552** may also include a second set of overlapping openings **568**. The openings **568** may be positioned along the front side of the rotation device **550** between the groove **562** and the second end **560**. The base **552** may also include a third opening **570** positioned along the front side of the rotation device **550** between the first set of openings **566** and the first end **558**. The base **552** may also include a fourth opening **572** positioned along the front side of the rotation device **550** between the second set of openings **568** and the second end **560**. The openings **566, 568, 570, 572** may be,

for example, angled as they extend from the top surface **554** to the bottom surface **556**. The first set of overlapping openings **566** and the second set of overlapping openings **568** may each include, for example, three openings. The three overlapping openings **566, 568** may each have an angle of rotation relative to the zero opening **564**, for example, the openings **566, 568** closest to the groove **562** may have a rotation angle of approximately 10° to 19° . The next openings **566, 568** may have a rotation angle of, for example, approximately 20° to 29° and the outer most opening **566, 568** from the groove **562** may have a rotation angle of, for example, approximately 30° to 39° . Finally, the third and fourth openings **570, 572** may have rotation angles relative to the zero opening **564** of, for example, approximately 40° to 50° . In one embodiment, the rotation angles may be, for example, $15^\circ, 25^\circ, 35^\circ,$ and 45° . In yet another embodiment, the rotation angles may be, for example, $15^\circ, 22^\circ, 30^\circ,$ and 45° . The openings **566, 568, 570, 572** may be positioned linearly along the base **552** as it curves from the first end **558** to the second end **560** and offset from the zero opening **564**. Alternatively, each of the openings **566, 568, 570, 572** may be, for example, offset from each other and the zero opening **564**.

Referring now to FIGS. **53-64**, a method of using the guide system **500** is shown. As shown in FIGS. **53-63**, the guide system **500** may include the cut guide **100**, the alignment guide **510**, the position rotation device **550**, at least one directional wire **606**, and multiple guide wires **608, 610, 612, 614, 616**. Although FIGS. **53-63** show the method using the cut guide **100**, it is also contemplated that the method may include using any one of cut guides **100, 150, 200, 250, 700, 750, 800, 850, 900, 950**. Alternatively, the method may include using a combination of one of cut guides **300, 350, 1000, 1050** on the first metatarsal and then any one of cut guides **100, 150, 200, 250, 700, 750, 800, 850, 900, 950** on the cuneiform.

The method may include inserting the extension member **128** of the cut guide **100** into the joint space between a first bone or first metatarsal **602** and a second bone or medial cuneiform **604**, as shown in FIGS. **53** and **54**. The extension member **128** fits between the first bone **602** and second bone **604** to align the slots **116, 118, 120, 122** of the base portion **114** to produce the desired angled cut. The slots **116, 118, 120, 122** may be angled relative to the extension member **128** to account for the extension member **128** shifting during resection of the bone. The extension member **128** may be inserted so that the first arm **130** is positioned on the second bone **604** and the second arm **140** is positioned on the first bone **602**.

Next, the alignment guide **510** may be coupled to the cut guide **100**, as shown in FIGS. **55** and **56**. The first engagement member **538** may be, for example, inserted into a first slot **120, 122** and the second engagement member **546** may be, for example, inserted into a second slot **120, 122**. For example, as shown in FIGS. **55** and **56**, the first engagement member **538** may be inserted in the slot **120** and the second engagement member **546** may be inserted into the slot **122**. The method may also include inserting at least one directional wire **606** into at least one opening **526, 528, 530** in the alignment guide **510**. As further shown in FIGS. **55** and **56**, a directional wire **606** is inserted into the opening **530** in the alignment guide **510**. The directional wire **606** inserted into the alignment guide **510** depicts the exact angle of deformity correction in both the dorsal and lateral planes. The mating of the engagement members **538, 546** and the slots **120, 122** produces the resulting angle of correction and illustrates the correction angle during surgery.

After inserting a direction wire **606** into the alignment guide **510**, the method may optionally include changing the cut guide **100** to a cut guide with a different angular size. For example, if the alignment guide **510** shows an over-correction or under-correction of the hallux valgus deformity, then the surgeon may go down or up an angular size of cut guide, respectively. Each of the cut guides **100, 150, 200, 250, 300, 350, 700, 750, 800, 850, 900, 950, 1000, 1050** may have different angular sizes and/or be for a right or left foot. If the alignment guide **510** shows an over-correction or under-correction, then the cut guide **100** may be removed from the foot **600** and replaced with an alternative size cut guide **150, 200, 250, 300, 350**. If the cut guide **700, 750** is used, then the cut guide **700, 750** may be removed from the foot **600** and replaced with an alternative size cut guide **800, 850, 900, 950, 1000, 1050**. Once the new cut guide is inserted into the foot **600**, the surgeon may re-check the correction by inserting the alignment guide **510** into the new cut guide and the directional wire **606** into the alignment guide **510**, as described in greater detail above, to determine whether the new cut guide provides the desired correction.

Once the cut guide **100, 150, 200, 250, 300, 350, 700, 750, 800, 850, 900, 950, 1000, 1050** with the desired correction is inserted into the patient's joint space, then a k-wire, guide wire or dorsal wire **608** may be inserted into the dorsal hole **124** of the cut guide **100** between the slot **118** and the slot **120**, as shown in FIGS. **57-59**. The guide wire **608** may be used to check the orientation of the cut guide **100** by checking that the wire **608** is parallel to a patient's tibia and perpendicular to the weight-bearing surface. After the desired orientation is achieved, k-wires, guide wires, wires **610, 612, 614, 616** may be inserted through the holes **132, 134, 142, 144** in the cut guide **100** and into the bones **602, 604**, to secure the cut guide **100** to the bones **602, 604**, as shown in FIGS. **57-59**. For example, a distal-medial wire, k-wire, guide wire **610** may be inserted into the fourth opening **144** in the cut guide **100**, a proximal-medial wire, k-wire, guide wire **612** may be inserted into the second opening **134**, a distal-lateral wire, k-wire, guide wire **614** may be inserted into the third opening **142**, and a proximal-lateral wire, k-wire, guide wire **616** may be inserted into the first opening **132**, as shown in FIGS. **57-59**.

Next, the dorsal k-wire **608** and the alignment guide **510** may be removed from the cut guide **100**, as shown in FIGS. **60** and **61**. After the cut guide **100** is coupled to the bones **602, 604** and the alignment guide **510** and dorsal k-wire **608** are removed from the cut guide **100**, the bones **602, 604** may be cut using the desired slots **116, 118, 120, 122**, as shown in FIGS. **62** and **63**. For example, a saw blade **620** of saw **618** may be inserted through the first slot **116** to cut the first bone **602**, as shown in FIG. **62**, then the saw blade **620** may be removed and inserted through the third slot **120** to cut the second bone **604**, as shown in FIG. **63**. After the bones **602, 604** are cut, the lateral k-wires **614, 616** and the cut guide **100** may be removed from the bones **602, 604** and the medial k-wires **610, 612** may be left in the bones **602, 604**, as shown in FIGS. **64**. The medial k-wires **610, 612** may be positioned, for example, parallel to each other. If the angle of correction is not accurate the surgeon may insert another cut guide **200, 250, 300** over the medial k-wires **610, 612** and perform additional cutting to achieve the desired angle of correction. Alternatively or additionally, if more tissue or bone needs to be removed from the patient's bones, then the cut guide **400** may be inserted over one of the medial k-wires **610, 612**. The cut guide **400** may then be positioned to align the extension member **418** against the cut surface of the bone to remove additional tissue or bone parallel to the original

cut. Once the desired amount of tissue and/or bone is removed and the desired angle of correction achieved, a position rotation device **550** may be slid over the medial k-wires **610, 612**. The cartilage and bone that was resected using the cut guide **100** may also be removed from the joint, as shown in FIG. **64**.

After the bones **602, 604** have been cut and the resected bone and cartilage removed, the rotation device **550** may be inserted over the distal-medial wire **610**, as shown in FIG. **64**. The wire **610** may be inserted into the first opening **564** of the rotation device **550**. Then, a second k-wire (not shown) may be inserted into one of the openings **566, 568, 570, 572** corresponding to the desired angulation correction. After the second k-wire (not shown) is inserted through the selected opening **566, 568, 570, 572**, the distal-medial wire **610** may be removed from the bone **602** and the rotation device **550**. Next, the rotation device **550** may be removed from the foot **600**. Then, the method may include rotating the bones **602, 604** to the desired correction where the second k-wire (not shown) in the first metatarsal **602** is positioned parallel to the k-wire **612** in the medial cuneiform **604** and temporarily securing the bones **602, 604** in the rotated position. Finally, the bones **602, 604** may be secured in the rotated position using a plate (not shown) and screws (not shown). Finally, the surgical procedure may include performing incision closure or concomitant procedures.

Referring now to FIGS. **75-82**, another cut guide **700** is shown. The cut guide **700** includes a top surface **702**, a bottom surface **704**, a first or proximal end **706**, a second or distal end **708**, a first or medial side **710**, and a second or lateral side **712**. The cut guide **700** also includes a base portion **714** and a paddle, fin or extension member **728** extending away from the bottom surface **704** of the base portion **714**. The cut guide **700** further includes a first or proximal arm **730** extending away from the base portion **714** on a first end **706** and a second or distal arm **740** extending away from the base portion **714** on a second end **708**. The cut guide **700** may be, for example, a right foot cut guide.

As shown in FIGS. **75, 79** and **80**, the top surface **702** of the base portion **714** may be, for example, curved or arced between the first side **710** and the second side **712**. In one embodiment, the top surface **702** of the base portion **714** may include, for example, a flat or planar portion positioned between a first curvature or arc extending from the first side **710** to the flat portion and a second curvature or arc extending from a second side **712** to the flat portion. The end of the base portion **714** near the first end **706** of the cut guide **800** may be, for example, angled from the second side **712** to the first side **710**, as shown in FIG. **81**. The end of the base portion **714** near the second end **708** of the cut guide **700** may extend, for example, perpendicularly between the first side **710** and the second side **712**, as shown in FIG. **81**. The base portion **714** also includes at least one slot **716, 718, 720, 722**, as shown in FIGS. **75-78, 81** and **82**. In the depicted embodiment, the base portion **714** includes a first slot **716** adjacent to a second slot **718** and a third slot **720** adjacent to a fourth slot **722**. The first and second slots **716, 718** may be, for example, positioned on the second end **708** of the base portion **714** and the third and fourth slots **720, 722** may be, for example, positioned on the first end **706** of the base portion **714**.

With continued reference to FIGS. **75-78** and **81**, the slots **716, 718, 720, 722** may extend, for example, linearly through the base portion **714** from the top surface **702** to the bottom surface **704** of the cut guide **700**. Alternatively, the slots **716, 718, 720, 722** may also be, for example, angled as the slots **716, 718, 720, 722** extend from the top surface **702**

to the bottom surface **704**. The slots **716**, **718**, **720**, **722** may be angled, for example, approximately 1° to 4° and more specifically, approximately 2° , as they extend between the top surface **702** and the bottom surface **704**. It is also contemplated that some of slots **716**, **718**, **720**, **722** may be angled and other slots **716**, **718**, **720**, **722** may be linear as they extend through the base portion **714** from the top surface **702** to the bottom surface **704**.

In addition, the slots **716**, **718**, **720**, **722** may be angled as they extend between the first side **710** and the second side **712**, for example, the slots may be angled approximately 0° to 30° as the slots **716**, **718**, **720**, **722** extend between the first and second sides **710**, **712**. As shown, slots **716**, **718** have an angle of 0° as the slots **716**, **718** extend between the first and second sides **710**, **712** and slots **720**, **722** have an angle of 8° as the slots **720**, **722** extend between the first and second sides **710**, **712**. Although not shown with respect to cut guide **700**, it is also contemplated that both the first set of slots **716**, **718** and the second set of slots **720**, **722** may be straight as the slots **716**, **718**, **720**, **722** extend between the first and second sides **710**, **712**. As shown, the slots **720**, **722** are positioned to extend between the first and second sides **710**, **712** parallel to the first metatarsal, as discussed in greater detail above with respect to the method of using the cut guide **700**. The slots **716**, **718**, **720**, **722** may be configured or sized and shaped to receive a saw blade and may have a width of, for example, approximately 0.58 mm to 0.92 mm. The slots **716**, **718**, **720**, **722** may be positioned, for example, to allow for removal of the articular cartilage layer of the two bones. To prevent resecting more bone than absolutely necessary, the slots **716**, **718**, **720**, **722** may be positioned, for example, such that the medial portion of the slots **716**, **718**, **720**, **722** are aligned with the intersection of the cartilage and bone. In one embodiment, the slots **716**, **718** are positioned a first distance from the extension member **728**, the slots **720**, **722** are positioned a second distance from the extension member **728**. The first distance may be measured from the extension member **728** to an inner surface of the slots **716**, **718** and the second distance may be measured from the extension member **728** to an inner surface of the slots **720**, **722**.

The base portion **714** may also include a hole or dorsal hole **724**, as shown in at least FIGS. **78**, **81** and **82**. The hole **724** may be of the type described above with reference to hole **124**, which will not be described again here for brevity sake. As shown in FIGS. **75-78** and **82**, the base portion **714** also includes a recessed region **726** positioned on the bottom surface **704**. The recessed region **726** extends from the first side **710** to the second side **712** and into the base portion **714** a first distance from the bottom surface **704** toward the top surface **702**. The extension member **728** is coupled to the recessed region **726** of the base portion **714** and extends away from the recessed region **726** of the base portion **714**. In addition, the extension member **728** is positioned between the second slot **718** and the third slot **720** and also extends from the second side **712** toward the first side **710**, as shown in FIGS. **79**, **80** and **82**. The extension member **728** may be shaped, for example, to fit within the joint space between two bones, such as, a first metatarsal and cuneiform, as well as to make contact with the adjoining articular joint surfaces. The extension member **728** may include a perpendicular portion near the first side **710** that extends perpendicularly away from the bottom surface **704**. The perpendicular portion of the extension member **728** may be, for example, angled when the cut guide **700** is inserted into a patient's joint and the angle that the perpendicular portion is positioned at may correspond to the angle of the first tarso-

metatarsal joint medially. The extension member **728** may also include an angled portion extending from the second side **712** to the end of the extension member **728**. The angled portion of the extension member **728** may, for example, allow for the extension member **728** to fit within a variety of anatomic presentations. The angled portion of the extension member **728** may, for example, be oriented laterally and should align with the long axis of the tibia, as well as fit within the joint to rest against the relatively straight surface of the adjacent bone, for example, the second metatarsal. When the angled portion of the extension member **728** is oriented against the second metatarsal, the cut guide **700** will be positioned at a 45° angle in the frontal plane.

As shown in FIGS. **75**, **76**, **81** and **82**, the first or proximal arm **730** may extend away from an end of the base portion **714** and may have, for example, a first portion extending from the base portion **714** to a coupling portion **738** positioned at the first end **706** of the cut guide **700**. The coupling portion **738** may have a width larger than the width of the first portion of the first arm **730**. The coupling portion **738** of the first arm **730** includes at least one opening **732**, **734**. In the depicted embodiment, the first arm **730** includes a first opening **732** and a second opening **734** positioned near the first end **706**. The first opening **732** may be spaced apart from the second opening **734**. The openings **732**, **734** may extend from a top surface **702** to a bottom surface **704** of the coupling portion **738** of the cut guide **700**. The openings **732**, **734** may extend through the coupling portion **738** of the first arm **730**, for example, parallel to the extension member **728**, angled as they extend from the top surface **702** toward the bottom surface **704**, or a combination of parallel and angled. In one embodiment, the first opening **732** may extend, for example, parallel to the extension member **728** and the second opening **734** may be, for example, angled with respect to the extension member **728** to permit the inserted wires, guide wires, k-wires and the like to cross above the cut guide **700** without intersecting. By positioning the openings **732**, **734** such that inserted wires cross above the openings **732**, **734** allows for a smaller surgical incision and less interaction or interference with other instruments during the procedure. The openings **732**, **734** positioning the wires to cross also allows for the cut guide **700** to be, for example, suspended above and/or proximate to the bone surfaces being cut. The ability to suspend the cut guide **700** above the bone surfaces prevents the cut guide **700** from being tilted because of varying patient anatomy and this avoids moving the slots **716**, **718**, **720**, **722** which would affect the proposed cut angles. Alternative combinations of orientations of the openings **732**, **734** are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The first arm **730** may be shaped to provide a bone contacting surface **736** that corresponds to the shape of the bone that it will engage. The first arm **730** may be, for example, curved or arced as it extends between the first side **710** and the second side **712**.

As shown in FIGS. **75**, **76**, **81** and **82**, the second or distal arm **740** may extend away from an end of the base portion **714** and may have, for example, a first portion extending from the base portion **714** to a coupling portion **748** positioned at the second end **708** of the cut guide **700**. The coupling portion **748** may have a width larger than the width of the first portion of the second arm **740**. The coupling portion **748** of the second arm **740** includes at least one opening **742**, **744**. In the depicted embodiment, the second arm **740** includes a third opening **742** and a fourth opening **744** positioned near the second end **708**. The third opening **742** may be spaced apart from the fourth opening **744** and

extend from a top surface 702 to a bottom surface 704 of the cut guide 700. The openings 742, 744 may extend through the second arm 740, for example, parallel to the extension member 728, angled as they extend from the top surface 702 toward the bottom surface 704, or a combination of parallel and angled. In one embodiment, the third opening 742 may extend, for example, parallel to the extension member 728 and the fourth opening 744 may be, for example, angled with respect to the extension member 728 to permit inserted wires, guide wires, k-wires, and the like to cross above the cut guide 700 without intersecting. By positioning the openings 742, 744 such that the inserted wires cross above the openings 742, 744 allows for a smaller surgical incision and less interaction or interference with other instruments during the procedure. The openings 742, 744 being positioned for the wires to cross, also allows for the cut guide 700 to be, for example, suspended above and/or mated with the bone surfaces being cut. Suspending the cut guide 700 above the bone surfaces prevents the cut guide 700 from being angled because of varying patient anatomy which results in not having to move the slots 716, 718, 720, 722 which would affect the proposed cut angles. In one embodiment, the openings 732, 742 may be, for example, positioned such that they are parallel to one another as they extend between the top and bottom surfaces 702, 704. By positioning the openings 732, 742 parallel to each other, the cut guide 700 may be, for example, removed from guide wires inserted through openings 732, 742 without removing the guide wires. In addition, parallel openings 732, 742 allow for the relative rotation between the two guide wires to be measured or calculated after the bones are cut using cut guide 700. Further, the openings 732, 742 may be, for example, spaced apart from the extension member 728 a standard or set distance to allow for interchangeability with alternative cut guides 800, 900, 1000, if a different or additional resection is needed. Alternative, combinations of orientations of the openings 742, 744 are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The second arm 740 may be shaped to provide a bone contacting surface 746 that corresponds to the shape of the bone that it will engage. The second arm 740 may be, for example, curved or arced as it extends between the first side 710 and the second side 712. The second arm 740 may have, for example, a larger length than the first arm 730.

Referring now to FIGS. 83 and 84, another cut guide 750 is shown. The cut guide 750 is a mirror image of the cut guide 700 in a medial-lateral direction, which will not be described again in full detail for brevity purposes. For example, the hole 724 is positioned on a left side of the cut guide 700 when in an insertion position and the hole 774 is positioned on a right side of the cut guide 750 when in an insertion position. The cut guide 750 may be, for example, for a left foot. The cut guide 750 may include a top surface 752, a bottom surface 754, a first or proximal end 756, a second or distal end 758, a first or medial side 760, and a second or lateral side 762, which may be of the type described above with respect to the top surface 702, the bottom surface 704, the first or proximal end 706, the second or distal end 708, the first or medial side 710, and the second or lateral side 712, respectively. The cut guide 750 may also include a base portion 764 which may be the mirror image of the base portion 714, as described above. The slots 766, 768, 770, 772, the hole 774, and the recessed region 776 may be the same or similar to the slots 716, 718, 720, 722, the hole 724, and the recessed region 726, as described in greater detail above. Further, the cut guide 750 may include a fin, paddle or extension member 778, a first or proximal

arm 780, and a second or distal arm 790, which may be as described above with respect to the extension member 728, the first arm 730, and the second arm 740, respectively. The coupling portion 788, the openings 782, 784 and the bone contacting surface 786 may be as described above with reference to the coupling portion 738, the openings 732, 734 and the bone contacting surface 736 and the coupling portion 798, the openings 792, 794 and the bone contacting surface 796 may be as described above with reference to the coupling portion 748, the openings 742, 744 and the bone contacting surface 746, which will not be described again here for brevity purposes.

Referring now to FIGS. 85-92, another cut guide 800 is shown. The cut guide 800 includes a top surface 802, a bottom surface 804, a first or proximal end 806, a second or distal end 808, a first or medial side 810, and a second or lateral side 812. The cut guide 800 also includes a base portion 814, a paddle, fin or extension member 828 extending away from the bottom surface 804 of the base portion 814, a first or proximal arm 830 extending away from the base portion 814 on the first end 806, and a second or distal arm 840 extending away from the base portion 814 on the second end 808. The cut guide 800 may be, for example, a right foot cut guide.

As shown in FIGS. 85, 89 and 90, the top surface 802 of the base portion 814 may be, for example, curved or arced between the first side 810 and the second side 812. In one embodiment, the top surface 802 of the base portion 814 may include, for example, a flat or planar portion positioned between a first curvature or arc extending from the first side 810 to the flat portion and a second curvature or arc extending from a second side 812 to the flat portion. The end of the base portion 814 near the first end 806 of the cut guide 800 may be, for example, angled from the first side 810 to the second side 812, as shown in FIG. 91. The end of the base portion 814 near the second end 808 of the cut guide 800 may extend, for example, perpendicularly between the first side 810 and the second side 812, as shown in FIG. 91.

The base portion 814 also includes at least one slot 816, 818, 820, 822, as shown in FIGS. 85-88, 91 and 92. In the depicted embodiment, the base portion 814 includes a first slot 816 adjacent to a second slot 818 and a third slot 820 adjacent to a fourth slot 822. The first and second slots 816, 818 are positioned on the base portion 814 near the second end 808 of the cut guide 800 and the third and fourth slots 820, 822 are positioned on the base portion 814 near the first end 806 of the cut guide 800. The slots 816, 818, 820, 822 may extend, for example, linearly or angled through the base portion 814 from the top surface 802 to the bottom surface 804 of the cut guide 800. The slots 816, 818, 820, 822 may be, for example, angled approximately 1° to 4° and more specifically, approximately 2°, as the slots 816, 818, 820, 822 extend between the top and bottom surfaces 802, 804. It is also contemplated that some of slots 816, 818, 820, 822 may be angled and other slots 816, 818, 820, 822 may be linear as they extend through the base portion 814 from the top surface 802 to the bottom surface 804.

In addition, the slots 816, 818 may be oriented, for example, relatively perpendicular to the first side 810 and the second side 812 as the slots 816, 818 extend from the first side 810 to the second side 812, as shown in FIGS. 85-88, 91 and 92. The slots 820, 822 may be, for example, angled as the slots 820, 822 extend between the first side 810 to the second side 812. The slots 820, 822 may also be, for example, angled toward the slots 816, 818, as the slots 820, 822 extend from the first side 810 to the second side 812. The slots 820, 822 may also be positioned to extend parallel

to the end of the base portion **814** near the first end **806** of the cut guide **800**. The slots **820**, **822** may be, for example, angled between approximately 8° and 22° as the slots **820**, **822** extend from the second side **812** to the first side **810** providing for an angulation correction of 8° to 20° . The slots **816**, **818**, **820**, **822** may be configured or sized and shaped to receive a saw blade and may have a width of, for example, approximately 0.58 mm to 0.92 mm. The slots **816**, **818**, **820**, **822** may be positioned, for example, to allow for removal of the articular cartilage layer at the ends of the two bones. To prevent resecting more tissue than absolutely necessary, the slots **816**, **818**, **820**, **822** may be positioned, for example, such that the medial portion of the slots **816**, **818**, **820**, **822** are aligned with the intersection of the cartilage and bone.

The base portion **814** may also include a hole or dorsal hole **824**, as shown in at least FIGS. **85**, **86**, and **88-91**. The hole **824** is positioned between the second slot **818** and the third slot **820** near the second side **812** of the base portion **814**. The hole **824** may extend, for example, into the base portion **814** from the top surface **802** of the cut guide **800** and to a point within the extension member **828**. As shown in FIGS. **86**, **89**, **90** and **92**, as the hole **824** extends into the extension member **828**, the hole **824** forms an opening in a proximal-distal direction through the extension member **828**. The hole **824** may, for example, extend into the cut guide **800** parallel to the angled portion of the extension member **828**, as shown in FIG. **86**. The hole **824** may be sized and shaped or configured, for example, to receive a wire, alignment wire, k-wire, guide wire or the like to provide information on the position of the cut guide **800** in a joint. For example, a wire inserted into hole **824** should align approximately with the long axis of the patient's tibia to provide the proper orientation of the cut guide **800** in the joint, which may be, for example, approximately 45° from dorsal and 45° from medial in the frontal plane.

Referring now to FIGS. **86-88** and **92**, the base portion **814** also includes a recessed region **826** positioned on the bottom surface **804**. The recessed region **826** extends from the first side **810** to the second side **812** and into the base portion **814** from the bottom surface **804** toward the top surface **802**. The recessed region **826** extends to engage the bone contacting surface **836** of the first arm **830** at the first side **810** of the base portion **814**. The extension member **828** is coupled to the recessed region **826** of the base portion **814** and extends away from the recessed region **826** of the base portion **814**. In addition, the extension member **828** is positioned between the second slot **818** and the third slot **820**. The extension member **828** also extends from the second side **812** toward the first side **810**, as shown in FIGS. **86**, **89**, **90** and **92**. The extension member **828** may include a perpendicular portion near the first side **810** that extends perpendicularly away from the bottom surface **804**. The perpendicular portion of the extension member **828** may be, for example, angled when the cut guide **800** is inserted into a patient's joint and the angle that the perpendicular portion is positioned at may correspond to the angle of the first tarso-metatarsal joint medially. The extension member **828** may also include an angled portion extending from the second side **812** to the end or distal end of the extension member **828**. The extension member **828** may be shaped, for example, to fit within the joint space between two bones, such as, a first metatarsal and cuneiform, as well as to mate with the articular joints. The angled portion of the extension member **828** may, for example, be oriented laterally and should align with the long axis of the tibia, as well as fit within the joint to rest against the relatively straight surface

of the adjacent bone, for example, the second metatarsal. When the angled portion of the extension member **828** is oriented against the second metatarsal, the cut guide **800** will be positioned at a 45° angle in the frontal plane.

As shown in FIGS. **85**, **86**, **91** and **92**, the first or proximal arm **830** may extend away from an end of the base portion **814** and may have, for example, a first portion extending from the base portion **814** to a coupling portion **838** positioned at the first end **806** of the cut guide **800**. The coupling portion **838** may have a width larger than the width of the first portion of the first arm **830**. The coupling portion **838** of the first arm **830** includes at least one opening **832**, **834**. In the depicted embodiment, the first arm **830** includes a first opening **832** and a second opening **834** positioned near the first end **806**. The first opening **832** may be spaced apart from the second opening **834**. The openings **832**, **834** may extend from a top surface **802** to a bottom surface **804** of the coupling portion **838** of the cut guide **800**. The openings **832**, **834** may extend through the coupling portion **838** of the first arm **830**, for example, parallel to the extension member **828**, angled as they extend from the top surface **802** toward the bottom surface **804**, or a combination of parallel and angled. In one embodiment, the first opening **832** may extend, for example, parallel to the extension member **828** and the second opening **834** may be, for example, angled with respect to the extension member **828** to permit the inserted wires, guide wires, k-wires and the like to cross above the cut guide **800** without intersecting. By positioning the openings **832**, **834** such that inserted wires cross above the openings **832**, **834** allows for a smaller surgical incision and less interaction or interference with other instruments during the procedure. The openings **832**, **834** positioning the wires to cross also allows for the cut guide **800** to be, for example, suspended above and/or proximate to the bone surfaces being cut. The ability to suspend the cut guide **800** above the bone surfaces prevents the cut guide **800** from being tilted because of varying patient anatomy and this avoids moving the slots **816**, **818**, **820**, **822** which would affect the proposed cut angles. Alternative combinations of orientations of the openings **832**, **834** are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The first arm **830** may be shaped to provide a bone contacting surface **836** that corresponds to the shape of the bone that it will engage. The first arm **830** may be, for example, curved or arced as it extends between the first side **810** and the second side **812**.

As shown in FIGS. **85**, **86**, **91** and **92**, the second or distal arm **840** may extend away from an end of the base portion **814** and may have, for example, a first portion extending from the base portion **814** to a coupling portion **848** positioned at the second end **808** of the cut guide **800**. The coupling portion **848** may have a width larger than the width of the first portion of the second arm **840**. The coupling portion **848** of the second arm **840** includes at least one opening **842**, **844**. In the depicted embodiment, the second arm **840** includes a third opening **842** and a fourth opening **844** positioned near the second end **808**. The third opening **842** may be spaced apart from the fourth opening **844** and extend from a top surface **802** to a bottom surface **804** of the cut guide **800**. The openings **842**, **844** may extend through the second arm **840**, for example, parallel to the extension member **828**, angled as they extend from the top surface **802** toward the bottom surface **804**, or a combination of parallel and angled. In one embodiment, the third opening **842** may extend, for example, parallel to the extension member **828** and the fourth opening **844** may be, for example, angled with respect to the extension member **828** to permit inserted

wires, guide wires, k-wires, and the like to cross above the cut guide **800** without intersecting. By positioning the openings **842**, **844** such that the inserted wires cross above the openings **842**, **844** allows for a smaller surgical incision and less interaction or interference with other instruments during the procedure. The openings **842**, **844** being positioned for the wires to cross, also allows for the cut guide **800** to be, for example, suspended above and/or mated with the bone surfaces being cut. Suspending the cut guide **800** above the bone surfaces prevents the cut guide **800** from being angled because of varying patient anatomy which results in not having to move the slots **816**, **818**, **820**, **822** which would affect the proposed cut angles. In one embodiment, the openings **832**, **842** may be, for example, positioned such that they are parallel to one another as they extend between the top and bottom surfaces **802**, **804**. By positioning the openings **832**, **842** parallel to each other, the cut guide **800** may be, for example, removed from guide wires inserted through openings **832**, **842** without removing the guide wires. In addition, parallel openings **832**, **842** allow for the relative rotation between the two guide wires to be measured or calculated after the bones are cut using cut guide **800**. Further, the openings **832**, **842** may be, for example, spaced apart from the extension member **828** a standard or set distance to allow for interchangeability with alternative cut guides **700**, **900**, **1000**, if a different or additional resection is needed. Alternative, combinations of orientations of the openings **842**, **844** are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The second arm **840** may be shaped to provide a bone contacting surface **846** that corresponds to the shape of the bone that it will engage. The second arm **840** may be, for example, curved or arced as it extends between the first side **810** and the second side **812**. The second arm **840** may have, for example, a larger length than the first arm **830**.

Another cut guide **850** is shown in FIGS. **93** and **94**. The cut guide **850** is a mirror image of the cut guide **800** in a medial-lateral direction, which will not be described again in full detail for brevity purposes. For example, the hole **824** is positioned on a left side of the cut guide **800** when in an insertion position and the hole **874** is positioned on a right side of the cut guide **850** when in an insertion position. The cut guide **850** may be, for example, for a left foot. The cut guide **850** may include a top surface **852**, a bottom surface **854**, a first or proximal end **856**, a second or distal end **858**, a first or medial side **860**, and a second or lateral side **862**, which may be of the type described above with respect to the top surface **802**, the bottom surface **804**, the first or proximal end **806**, the second or distal end **808**, the first or medial side **810**, and the second or lateral side **812**, respectively. The cut guide **850** may also include a base portion **864** which may be the mirror image of the base portion **814**, as described above. The slots **866**, **868**, **870**, **872**, the hole **874**, and the recessed region **876** may be the same or similar to the slots **816**, **818**, **820**, **822**, the hole **824**, and the recessed region **826**, as described in greater detail above. Further, the cut guide **850** may include a fin, paddle or extension member **878**, a first or proximal arm **880**, and a second or distal arm **890**, which may be as described above with respect to the extension member **828**, the first arm **830**, and the second arm **840**, respectively. The coupling portion **888**, the openings **882**, **884** and the bone contacting surface **886** may be as described above with reference to the coupling portion **838**, the openings **832**, **834** and the bone contacting surface **836** and the coupling portion **898**, the openings **892**, **894** and the bone contacting surface **896** may be as described above with reference to the coupling portion **848**, the openings **842**, **844**

and the bone contacting surface **846**, which will not be described again here for brevity purposes.

Referring now to FIGS. **95-102**, a cut guide **900** is shown. The cut guide **900** includes a top surface **902**, a bottom surface **904**, a first or proximal end **906**, a second or distal end **908**, a first or medial side **910**, and a second or lateral side **912**. The cut guide **900** also includes a base portion **914**, a paddle, fin or extension member **928** extending away from the bottom surface **904** of the base portion **914**, a first or proximal arm **930** extending away from the base portion **914** on the first end **906**, and a second or distal arm **940** extending away from the base portion **914** on the second end **908**. The cut guide **900** may be, for example, a right foot cut guide.

As shown in FIGS. **95**, **99** and **100**, the top surface **902** of the base portion **914** may be, for example, curved or arced between the first side **910** and the second side **912**. In one embodiment, the top surface **902** of the base portion **914** may include, for example, a flat or planar portion positioned between a first curvature or arc extending from the first side **910** to the flat portion and a second curvature or arc extending from a second side **912** to the flat portion. The end of the base portion **914** near the first end **906** of the cut guide **900** may extend, for example, perpendicularly between the first side **910** to the second side **912**, as shown in FIG. **101**. The end of the base portion **914** near the second end **908** of the cut guide **900** may extend, for example, perpendicularly between the first side **910** and the second side **912**, as shown in FIG. **101**.

The base portion **914** also includes at least one slot **916**, **918**, **920**, **922**, as shown in FIGS. **89-98**, **101** and **102**. In the depicted embodiment, the base portion **914** includes a first slot **916** adjacent to a second slot **918** and a third slot **920** adjacent to a fourth slot **922**. The first and second slots **916**, **918** are positioned on the base portion **914** near the second end **908** of the cut guide **900** and the third and fourth slots **920**, **922** are positioned on the base portion **914** near the first end **906** of the cut guide **900**. The slots **916**, **918**, **920**, **922** may extend, for example, linearly or angled through the base portion **914** from the top surface **902** to the bottom surface **904** of the cut guide **900**. The slots **916**, **918**, **920**, **922** may be, for example, angled approximately 1° to 4° and more specifically, approximately 2° , as the slots **916**, **918**, **920**, **922** extend between the top and bottom surfaces **902**, **904**. It is also contemplated that some of slots **916**, **918**, **920**, **922** may be angled and other slots **916**, **918**, **920**, **922** may be linear as they extend through the base portion **914** from the top surface **902** to the bottom surface **904**.

In addition, the slots **916**, **918** may be oriented, for example, relatively perpendicular to the first side **910** and the second side **912** as the slots **916**, **918** extend from the first side **910** to the second side **912**, as shown in FIGS. **95-98**, **101** and **102**. The slots **916**, **918** may also be positioned to extend parallel to the end of the base portion **914** near the second end **908** of the cut guide **900**. The slots **920**, **922** may also be oriented, for example, relatively perpendicular to the first side **910** and the second side **912** as the slots **920**, **922** extend from the first side **910** to the second side **912**. The slots **920**, **922** may also be positioned to extend parallel to the end of the base portion **914** near the first end **906** of the cut guide **900**. The slots **916**, **918**, **920**, **922** may be, for example, angled approximately 0° to 30° as the slots **916**, **918**, **920**, **922** extend from the second side **912** to the first side **910** providing for an angulation correction of 4° to 20° . The slots **916**, **918**, **920**, **922** may be configured or sized and shaped to receive a saw blade and may have a width of, for example, approximately 0.58 mm to 0.92 mm.

The slots **916**, **918**, **920**, **922** may be positioned, for example, to allow for removal of the articular cartilage layer at the ends of the two bones. To prevent resecting more tissue than absolutely necessary, the slots **916**, **918**, **920**, **922** may be positioned, for example, such that the medial portion of the slots **916**, **918**, **920**, **922** are aligned with the intersection of the cartilage and bone.

The base portion **914** may also include a hole or dorsal hole **924**, as shown in at least FIGS. **95**, **96**, and **98-101**. The hole **924** is positioned between the second slot **918** and the third slot **920** near the second side **912** of the base portion **914**. The hole **924** may extend, for example, into the base portion **914** from the top surface **902** of the cut guide **900** and to a point within the extension member **928**. As shown in FIGS. **96**, **99**, **100** and **102**, as the hole **924** extends into the extension member **928**, the hole **924** forms an opening in a proximal-distal direction through the extension member **928**. The hole **924** may, for example, extend into the cut guide **900** parallel to the angled portion of the extension member **928**, as shown in FIG. **96**. The hole **924** may be sized and shaped or configured, for example, to receive a wire, alignment wire, k-wire, guide wire or the like to provide information on the position of the cut guide **900** in a joint. For example, a wire inserted into hole **924** should align approximately with the long axis of the patient's tibia to provide the proper orientation of the cut guide **900** in the joint, which may be, for example, approximately 45° from dorsal and 45° from medial in the frontal plane.

Referring now to FIGS. **96-98** and **102**, the base portion **914** also includes a recessed region **926** positioned on the bottom surface **904**. The recessed region **926** extends from the first side **910** to the second side **912** and into the base portion **914** from the bottom surface **904** toward the top surface **902**. The recessed region **926** extends to engage the bone contacting surface **936** of the first arm **930** at the first side **910** of the base portion **914**. The extension member **928** is coupled to the recessed region **926** of the base portion **914** and extends away from the recessed region **926** of the base portion **914**. In addition, the extension member **928** is positioned between the second slot **918** and the third slot **920**. The extension member **928** also extends from the second side **912** toward the first side **910**, as shown in FIGS. **96**, **99**, **100** and **102**. The extension member **928** may include a perpendicular portion near the first side **910** that extends perpendicularly away from the bottom surface **904**. The perpendicular portion of the extension member **928** may be, for example, angled when the cut guide **900** is inserted into a patient's joint and the angle that the perpendicular portion is positioned at may correspond to the angle of the first tarso-metatarsal joint medially. The extension member **928** may also include an angled portion extending from the second side **912** to the end or distal end of the extension member **928**. The extension member **928** may be shaped, for example, to fit within the joint space between two bones, such as, a first metatarsal and cuneiform, as well as to mate with the articular joints. The angled portion of the extension member **928** may, for example, be oriented laterally and should align with the long axis of the tibia, as well as fit within the joint to rest against the relatively straight surface of the adjacent bone, for example, the second metatarsal. When the angled portion of the extension member **928** is oriented against the second metatarsal, the cut guide **900** will be positioned at a 45° angle in the frontal plane.

As shown in FIGS. **95**, **96**, **101** and **102**, the first or proximal arm **930** may extend away from an end of the base portion **914** and may have, for example, a first portion extending from the base portion **914** to a coupling portion

938 positioned at the first end **906** of the cut guide **900**. The coupling portion **938** may have a width larger than the width of the first portion of the first arm **930**. The coupling portion **938** of the first arm **930** includes at least one opening **932**, **934**. In the depicted embodiment, the first arm **930** includes a first opening **932** and a second opening **934** positioned near the first end **906**. The first opening **932** may be spaced apart from the second opening **934**. The openings **932**, **934** may extend from a top surface **902** to a bottom surface **904** of the coupling portion **938** of the cut guide **900**. The openings **932**, **934** may extend through the coupling portion **938** of the first arm **930**, for example, parallel to the extension member **928**, angled as they extend from the top surface **902** toward the bottom surface **904**, or a combination of parallel and angled. In one embodiment, the first opening **932** may extend, for example, parallel to the extension member **928** and the second opening **934** may be, for example, angled with respect to the extension member **928** to permit the inserted wires, guide wires, k-wires and the like to cross above the cut guide **900** without intersecting. By positioning the openings **932**, **934** such that inserted wires cross above the openings **932**, **934** allows for a smaller surgical incision and less interaction or interference with other instruments during the procedure. The openings **932**, **934** positioning the wires to cross also allows for the cut guide **900** to be, for example, suspended above and/or proximate to the bone surfaces being cut. The ability to suspend the cut guide **900** above the bone surfaces prevents the cut guide **900** from being tilted because of varying patient anatomy and this avoids moving the slots **916**, **918**, **920**, **922** which would affect the proposed cut angles. Alternative combinations of orientations of the openings **932**, **934** are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The first arm **930** may be shaped to provide a bone contacting surface **936** that corresponds to the shape of the bone that it will engage. The first arm **930** may be, for example, curved or arced as it extends between the first side **910** and the second side **912**.

As shown in FIGS. **95**, **96**, **101** and **102**, the second or distal arm **940** may extend away from an end of the base portion **914** and may have, for example, a first portion extending from the base portion **914** to a coupling portion **948** positioned at the second end **908** of the cut guide **900**. The coupling portion **948** may have a width larger than the width of the first portion of the second arm **940**. The coupling portion **948** of the second arm **940** includes at least one opening **942**, **944**. In the depicted embodiment, the second arm **940** includes a third opening **942** and a fourth opening **944** positioned near the second end **908**. The third opening **942** may be spaced apart from the fourth opening **944** and extend from a top surface **902** to a bottom surface **904** of the cut guide **900**. The openings **942**, **944** may extend through the second arm **940**, for example, parallel to the extension member **928**, angled as they extend from the top surface **902** toward the bottom surface **904**, or a combination of parallel and angled. In one embodiment, the third opening **942** may extend, for example, parallel to the extension member **928** and the fourth opening **944** may be, for example, angled with respect to the extension member **928** to permit inserted wires, guide wires, k-wires, and the like to cross above the cut guide **900** without intersecting. By positioning the openings **942**, **944** such that the inserted wires cross above the openings **942**, **944** allows for a smaller surgical incision and less interaction or interference with other instruments during the procedure. The openings **942**, **944** being positioned for the wires to cross, also allows for the cut guide **900** to be, for example, suspended above

and/or mated with the bone surfaces being cut. Suspending the cut guide 900 above the bone surfaces prevents the cut guide 900 from being angled because of varying patient anatomy which results in not having to move the slots 916, 918, 920, 922 which would affect the proposed cut angles. In one embodiment, the openings 932, 942 may be, for example, positioned such that they are parallel to one another as they extend between the top and bottom surfaces 902, 904. By positioning the openings 932, 942 parallel to each other, the cut guide 900 may be, for example, removed from guide wires inserted through openings 932, 942 without removing the guide wires. In addition, parallel openings 932, 942 allow for the relative rotation between the two guide wires to be measured or calculated after the bones are cut using cut guide 900. Further, the openings 932, 942 may be, for example, spaced apart from the extension member 928 a standard or set distance to allow for interchangeability with alternative cut guides 700, 800, 1000, if a different or additional resection is needed. Alternative, combinations of orientations of the openings 942, 944 are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The second arm 940 may be shaped to provide a bone contacting surface 946 that corresponds to the shape of the bone that it will engage. The second arm 940 may be, for example, curved or arced as it extends between the first side 910 and the second side 912. The second arm 940 may have, for example, a larger length than the first arm 930.

FIGS. 103 and 104 show another cut guide 950. Another cut guide 950 is shown in FIGS. 103 and 104. The cut guide 950 is a mirror image of the cut guide 900 in a medial-lateral direction, which will not be described again in full detail for brevity purposes. For example, the hole 924 is positioned on a left side of the cut guide 900 when in an insertion position and the hole 974 is positioned on a right side of the cut guide 950 when in an insertion position. The cut guide 950 may be, for example, for a left foot. The cut guide 950 may include a top surface 952, a bottom surface 954, a first or proximal end 956, a second or distal end 958, a first or medial side 960, and a second or lateral side 962, which may be of the type described above with respect to the top surface 902, the bottom surface 904, the first or proximal end 906, the second or distal end 908, the first or medial side 910, and the second or lateral side 912, respectively. The cut guide 950 may also include a base portion 964 which may be the mirror image of the base portion 914, as described above. The slots 966, 968, 970, 972, the hole 974, and the recessed region 976 may be the same or similar to the slots 916, 918, 920, 922, the hole 924, and the recessed region 926, as described in greater detail above. Further, the cut guide 950 may include a fin, paddle or extension member 978, a first or proximal arm 980, and a second or distal arm 990, which may be as described above with respect to the extension member 928, the first arm 930, and the second arm 940, respectively. The coupling portion 988, the openings 982, 984 and the bone contacting surface 986 may be as described above with reference to the coupling portion 938, the openings 932, 934 and the bone contacting surface 936 and the coupling portion 998, the openings 992, 994 and the bone contacting surface 996 may be as described above with reference to the coupling portion 948, the openings 942, 944 and the bone contacting surface 946, which will not be described again here for brevity purposes.

Referring now to FIGS. 105-112, a cut guide 1000 is shown. The cut guide 1000 includes a top surface 1002, a bottom surface 1004, a first end 1006, a second end 1008, a first side 1010, and a second side 1012. The first end 1006

may be, for example, a proximal end, and the second end 1008 may be, for example, a distal end, or vice versa. The first side 1010 may be, for example, a medial side, and the second side 1012 may be, for example, a lateral side, or vice versa. The cut guide 1000 also includes a base portion 1014, a paddle, fin or extension member 1022 extending away from the bottom surface 1004 of the base portion 1014, and an arm 1030 extending away from the base portion 1014 on the second end 1008. As shown in FIGS. 105-112, the cut guide 1000 may be, for example, a right foot cut guide. The cut guide 1000 may provide, for example, a 4° angulation from dorsal to plantar on the metatarsal.

Cut guide 1000 may be used, for example, when a surgeon decides that correction of the first metatarsal in plantarflexion is not sufficient enough and needs to take off more of the metatarsal from the dorsal to plantar direction. Alternatively, cut guide 1000 may be used, for example, when a surgeon knows from pre-operative radiographs that the first ray is dorsiflexed in order to cut more bone of the metatarsal plantarily to correct the dorsiflexion. For example, when guide 1000 is used, it will be inserted into the patient's joint, the surgeon will use cut guide 1000 to cut the first metatarsal, then cut guide 1000 will be removed and replaced with another cut guide, such as, cut guide 700, 800, 900, to cut the cuneiform. The second guide 700, 800, 900 will be selected based on the size and desired angular correction of the cuneiform. The cut guide 1000 may be removed from the patient's bones, for example, by sliding the guide 1000 off a guide wire inserted through the opening 1032 and inserting the second cut guide 700, 800, 900 onto the guide wire to properly align the second cut guide 700, 800, 900 on the patient's bones with respect to the first cut made to the metatarsal.

As shown in FIGS. 105, 109 and 110, the top surface 1002 of the base portion 1014 may be, for example, curved or arced between the first side 1010 and the second side 1012. In an embodiment, the top surface 1002 of the base portion 1014 may include, for example, a flat or planar portion positioned between a first curvature or arc extending from the first side 1010 to the flat portion and a second curvature or arc extending from the second side 1012 to the flat portion. The base portion 1014 also includes at least one slot 1016, 1018, as shown in FIGS. 105-108, 111 and 112. In the depicted embodiment, the first slot 1016 is positioned adjacent to a second slot 1018. The slots 1016, 1018 may extend, for example, through the base portion 1014 from the top surface 1002 to the bottom surface 1004 of the cut guide 1000. The slots 1016, 1018 may be, for example, angled as the slots 1016, 1018 extend from the top surface 1002 to the bottom surface 1004. The slots 1016, 1018 may be angled, for example, approximately 1° to 4° and more specifically, approximately 2°, as the slots 1016, 1018 extend between the top surface 1002 and the bottom surface 1004. It is also contemplated that the interior slot 1016 may be angled while the exterior slot 1018 may be linear as they extend between the top and bottom surfaces 1002, 1004.

In addition, the slots 1016, 1018 may be angled as they extend across the base portion 1014 from the first side 1010 to the second side 1012, as shown in FIGS. 111 and 112. The slots 1016, 1018 may be, for example, angled at approximately 6° as they extend between the first and second sides 1010, 1012 providing for an angulation correction of 4°. The slots 1016, 1018 may be configured or sized and shaped to receive a saw blade and may have a width of, for example, approximately 0.58 mm to 0.92 mm. As shown in FIG. 111, the slots 1016, 1018 may be angled from a distal-medial position to a proximal-lateral position of the cut guide 1000.

The slots **1016**, **1018** may be positioned, for example, to allow for removal of the articular cartilage only. To prevent resecting too much tissue, the slots **1016**, **1018** may be positioned, for example, such that the medial portion of the slots **1016**, **1018** are aligned with the cartilage and bone boundary.

The base portion **1014** also includes a hole or dorsal hole **1020**, as shown in at least FIGS. **105-107**, **111** and **112**. The hole **1020** is positioned between the second slot **1018** and the arm **1030**. The hole **1020** may extend, for example, through the base portion **1014** from the top surface **1002** to the bottom surface **1004**. The hole **1020** may, for example, extend through the base portion **1014** of the cut guide **1000** parallel to the angled portion of the extension member **1022**, as shown in FIG. **105**. The hole **1020** may be sized and shaped or configured, for example, to receive a wire, alignment wire, k-wire, guide wire, directional wire or the like to provide information on the position of the cut guide **1000** in a joint. For example, the wire inserted into hole **1020** should align approximately with the long axis of the tibia to provide the proper orientation of the cut guide **1000** in the joint, which may be, for example, approximately 45° from dorsal and 45° from medial in the frontal plane.

Referring now to FIGS. **106-110** and **112**, the extension member **1022** is attached to a bottom surface **1004** of the base portion **1014**. The extension member **1022** also extends away from the base portion **1014** and is positioned on the first end **1006** of the cut guide **1000**. In addition, the extension member **1022** extends from the second side **1012** toward the first side **1010**, as shown in at least FIGS. **106**, **109** and **110**. The extension member **1022** may include a portion near the first side **1010** that extends perpendicularly away from the bottom surface **1004**. The perpendicular portion of the extension member **1022** may be, for example, angled when the cut guide **1000** is inserted into a patient's joint and the angle that the perpendicular portion is positioned at may correspond to the angle of the first tarsometatarsal joint medially. The extension member **1022** may also include an angled portion extending from the second side **1012** to the end of the extension member **1022**. The extension member **1022** may be shaped, for example, to fit within the joint space between the two bones, such as, a first metatarsal and cuneiform, as well as to mate with the two sides of an articular joint. The angled portion of the extension member **1022** may, for example, be oriented laterally and should align with the long axis of the tibia, as well as fit within the joint to rest against the relatively straight surface of the adjacent bone, for example, the second metatarsal. When the angled portion of the extension member **1022** is oriented against the second metatarsal, the cut guide **1000** will be positioned at a 45° angle in the frontal plane.

As shown in FIGS. **105-108** and **110-112**, the arm **1030** may extend away from an end of the base portion **1014** and may have, for example, a first portion extending from the base portion **1014** to a coupling portion **1038** positioned at the first end **1006** of the cut guide **1000**. The coupling portion **1038** may have a width larger than the width of the first portion of the arm **1030**. The coupling portion **1038** of the arm **1030** includes at least one opening **1032**, **1034**. In the depicted embodiment, the arm **1030** includes a first opening **1032** and a second opening **1034** positioned near the first end **1006**. The first opening **1032** may be spaced apart from the second opening **1034**. The openings **1032**, **1034** may extend from a top surface **1002** to a bottom surface **1004** of the coupling portion **1038** of the cut guide **1000**. The openings **1032**, **1034** may extend through the coupling portion **1038** of the arm **1030**, for example, parallel

to the extension member **1028**, angled as they extend from the top surface **1002** toward the bottom surface **1004**, or a combination of parallel and angled. In one embodiment, the first opening **1032** may extend, for example, parallel to the extension member **1028** and the second opening **1034** may be, for example, angled with respect to the extension member **1028** to permit the inserted wires, guide wires, k-wires and the like to cross above the cut guide **1000** without intersecting. By positioning the openings **1032**, **1034** such that inserted wires cross above the openings **1032**, **1034** allows for a smaller surgical incision and less interaction or interference with other instruments during the procedure. The openings **1032**, **1034** positioning the wires to cross also allows for the cut guide **1000** to be, for example, suspended above and/or proximate to the bone surfaces being cut. The ability to suspend the cut guide **1000** above the bone surfaces prevents the cut guide **1000** from being tilted because of varying patient anatomy and this avoids moving the slots **1016**, **1018** which would affect the proposed cut angles. Alternative combinations of orientations of the openings **1032**, **1034** are also contemplated, as would be understood by one of ordinary skill in the art from the above description. The arm **1030** may be shaped to provide a bone contacting surface **1036** that corresponds to the shape of the bone that it will engage. The arm **1030** may be, for example, curved or arced as it extends between the first side **1010** and the second side **1012**.

With reference to FIGS. **113** and **114** another cut guide **1050** is shown. As shown, the cut guide **1050** may be a mirror image of the cut guide **1000** in a medial-lateral direction, therefore, the cut guide **1050** will not be described in full detail for brevity purposes. Therefore, the cut guide **1050** may be, for example, for a left foot. The cut guide **1050** may include a top surface **1052**, a bottom surface **1054**, a first or proximal end **1056**, a second or distal end **1058**, a first or medial side **1060**, and a second or lateral side **1062**, which may be as described above with respect to the top surface **1002**, the bottom surface **1004**, the first or proximal end **1006**, the second or distal end **1008**, the first or medial side **1010**, and the second or lateral side **1012**, respectively, which will not be described again here for brevity sake. As the cut guide **1050** is a mirror image of the cut guide **1000**, the cut guide **1050** may also include a base portion **1064** which may be the mirror image of the base portion **1014** as described above. In addition, the hole **1020** is positioned on a left side of the cut guide **1000** when in an insertion position and the hole **1070** is positioned on the right side of the cut guide **1050** when in an insertion position. The slots **1066**, **1068** and the hole **1070** may be similar to the slots **1016**, **1018** and hole **1020**, as described in greater detail above. Specifically, as the cut guide **1050** is a mirror image of the cut guide **1000**, the slots **1066**, **1068** may be angled from a distal-lateral position to a proximal-medial position of the cut guide **1050** resulting in 4° of cumulative dorsal to plantar cutting, as described in greater detail above with reference to cut guide **1000**. Further, the cut guide **1050** may include a fin, paddle or extension member **1072** and an arm **1080**, which may be as described above with respect to the fin, paddle or extension member **1022** and the arm **1030**, respectively. The openings **1082**, **1084** and bone contacting surface **1086** may be as described above with reference to the openings **1032**, **1034** and bone contacting surface **1036**, which will not be described again here for brevity purposes.

As may be recognized by those of ordinary skill in the art based on the teachings herein, numerous changes and modifications may be made to the above-described and other embodiments of the present disclosure without departing

from the scope of the disclosure. The components of the guides and/or systems as disclosed in the specification, including the accompanying abstract and drawings, may be replaced by alternative component(s) or feature(s), such as those disclosed in another embodiment, which serve the same, equivalent or similar purpose as known by those skilled in the art to achieve the same, equivalent or similar results by such alternative component(s) or feature(s) to provide a similar function for the intended purpose. In addition, the guides and systems may include more or fewer components or features than the embodiments as described and illustrated herein. For example, the components and features of FIGS. 1-8, FIGS. 9-10, FIGS. 11-18, FIGS. 19-26, FIGS. 27-34, FIGS. 35-36, and FIGS. 37-44, FIGS. 66-74, FIGS. 75-82, FIGS. 83-84, FIGS. 85-92, FIGS. 93-94, FIGS. 95-102, FIGS. 103-104, FIGS. 105-112 and FIGS. 113-114 may be used interchangeably and in alternative combinations as would be modified or altered by one of skill in the art. Accordingly, this detailed description of the currently-preferred embodiments is to be taken in an illustrative, as opposed to limiting of the disclosure.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the disclosure. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprise" (and any form of comprise, such as "comprises" and "comprising"), "have" (and any form of have, such as "has", and "having"), "include" (and any form of include, such as "includes" and "including"), and "contain" (and any form of contain, such as "contains" and "containing") are open-ended linking verbs. As a result, a method or device that "comprises," "has," "includes," or "contains" one or more steps or elements possesses those one or more steps or elements, but is not limited to possessing only those one or more steps or elements. Likewise, a step of a method or an element of a device that "comprises," "has," "includes," or "contains" one or more features possesses those one or more features, but is not limited to possessing only those one or more features. Furthermore, a device or structure that is configured in a certain way is configured in at least that way, but may also be configured in ways that are not listed.

The disclosure has been described with reference to the preferred embodiments. It will be understood that the architectural and operational embodiments described herein are exemplary of a plurality of possible arrangements to provide the same general features, characteristics, and general system operation. Modifications and alterations will occur to others upon a reading and understanding of the preceding detailed description. It is intended that the disclosure be construed as including all such modifications and alterations.

Having thus described the preferred embodiments, the invention is now claimed to be:

1. A guide system, comprising:

a cut guide, wherein the cut guide comprises:

a base portion, wherein the base portion further comprises:

a hole extending into the base portion from a top surface;

an extension member extending away from a bottom surface of the base portion, wherein the hole extends into the extension member; and

at least one arm extending away from an end of the base portion; and

an alignment guide configured to releasably engage with the cut guide.

2. The guide system of claim **1**, wherein the base portion of the cut guide comprises at least one slot positioned on or between a first end of the base portion and a second end of the base portion and extending between a first side of the base portion and a second side of the base portion.

3. The guide system of claim **2**, wherein the alignment guide is configured to removably engage with the at least one slot such that the alignment guide is releasably coupled with the cut guide.

4. The guide system of claim **2**, wherein the at least one slot is two slots.

5. The guide system of claim **2**, wherein the at least one slot is four slots.

6. The guide system of claim **2**, wherein the at least one slot is angled as it extends from the second side to the first side of the base portion.

7. The guide system of claim **2**, wherein the at least one slot is angled as it extends from a top surface through the bottom surface of the base portion.

8. The guide system of claim **1**, wherein the at least one arm comprises:

a first arm extending away from a first end of the base portion; and

a second arm extending away from a second end of the base portion.

9. The guide system of claim **8**, wherein the first arm comprises:

a first tapered body with a first end coupled to the first end of the base portion and a second end;

a first opening positioned near the second end of the first tapered body; and

a second opening positioned near the second end of the first tapered body and spaced apart from the first opening.

10. The guide system of claim **9**, wherein the first opening extends through the first arm from a top surface through a bottom surface of the first arm and the first opening extends parallel to the extension member; and

wherein the second opening extends through the first arm from the top surface through the bottom surface and the second opening is angled relative to the extension member.

11. The guide system of claim **8**, wherein the second arm comprises:

a second tapered body with a first end coupled to the second end of the base portion and a second end;

a third opening positioned near the second end of the second tapered body; and

a fourth opening positioned near the second end of the second tapered body and spaced apart from the first opening.

12. The guide system of claim **11**, wherein the third opening extends through the second arm from a top surface through a bottom surface of the second arm and the second opening extends parallel to the extension member; and

wherein the fourth opening extends through the second arm from the top surface through the bottom surface and the fourth opening is angled relative to the extension member.

13. The guide system of claim **1**, wherein the base portion further comprises:

a recessed region extending into the base portion from the bottom surface toward a top surface of the base portion.

14. The guide system of claim **1**, further comprising:

a position rotation device.

45

- 15. A cut guide, comprising:
 - a base portion comprising:
 - at least one slot disposed between a first end and a second end of the base portion and extending between a first side and a second side of the base portion, wherein the at least one slot is angled as it extends from a top surface through to a bottom surface of the base portion; and
 - a hole extending into the base portion from the top surface;
 - an extension member extending away from the bottom surface of the base portion, wherein the hole extends into the extension member;
 - at least one arm extending away from an end of the base portion; and
 - a recessed region extending into the base portion from the bottom surface and toward the top surface of the base portion.
- 16. The cut guide of claim 15, wherein the at least one arm further comprises:
 - a first arm extending away from a first end of the base portion, comprising:
 - a first tapered body with a first end coupled to the first end of the base portion and a second end opposite the first end;

46

- a first opening positioned near the second end of the first tapered body; and
- a second opening positioned near the second end of the first tapered body and spaced apart from the first opening;
- a second arm extending away from a second end of the base portion, comprising:
 - a second tapered body with a first end coupled to the second end of the base portion and a second end;
 - a third opening positioned near the second end of the second tapered body; and
 - a fourth opening positioned near the second end of the second tapered body and spaced apart from the first opening.
- 17. A cut guide, comprising:
 - a base portion, wherein the base portion further comprises:
 - a hole extending into the base portion from a top surface;
 - an extension member extending away from a bottom surface of the base portion;
 - wherein the hole extends into the extension member;
 - at least one arm extending away from a bottom surface of the base portion; and
 - at least one slot disposed on the base portion configured to removably engage with an alignment guide.

* * * * *