



(19) **United States**

(12) **Patent Application Publication**
Shaheen

(10) **Pub. No.: US 2006/0025133 A1**

(43) **Pub. Date: Feb. 2, 2006**

(54) **WIRELESS COMMUNICATION METHOD
AND SYSTEM FOR ESTABLISHING A
MULTIMEDIA MESSAGE SERVICE OVER A
WLAN**

Publication Classification

(51) **Int. Cl.**
H04Q 7/20 (2006.01)
(52) **U.S. Cl.** **455/433; 455/466**

(75) **Inventor: Kamel M. Shaheen, King of Prussia,
PA (US)**

(57) **ABSTRACT**

A wireless communication system for supporting multimedia services (MMS) provided to a user of a wireless transmit/receive unit (WTRU) which communicates with the wireless communication system. The wireless communication system includes a third generation partnership program (3GPP) universal mobile telecommunications system (UMTS), a wireless local area network (WLAN) and an MMS server. The MMS server stores at least one MMS message for the WTRU in a memory until the WTRU retrieves the message. The 3GPP UMTS includes an internet protocol short message gateway (IP-SM-GW) having a short message service (SMS) proxy. The WTRU is registered with the SMS proxy to establish SMS connectivity, and is also registered with the MMS server to establish MMS connectivity. The WTRU is notified when the MMS server receives an MMS message for the WTRU. The WTRU then retrieves the MMS message from the memory of the MMS server.

Correspondence Address:
VOLPE AND KOENIG, P.C.
DEPT. ICC
UNITED PLAZA, SUITE 1600
30 SOUTH 17TH STREET
PHILADELPHIA, PA 19103 (US)


(73) **Assignee: InterDigital Technology Corporation,
Wilmington, DE (US)**

(21) **Appl. No.: 11/153,207**

(22) **Filed: Jun. 15, 2005**

Related U.S. Application Data

(60) **Provisional application No. 60/592,856, filed on Jul.
30, 2004.**






FIG. 1




FIG. 2






FIG. 3




FIG. 4

WIRELESS COMMUNICATION METHOD AND SYSTEM FOR ESTABLISHING A MULTIMEDIA MESSAGE SERVICE OVER A WLAN

CROSS REFERENCE TO RELATED APPLICATION(S)

[0001] This application claims the benefit of U.S. Provisional Application No. 60/592,856, filed Jul. 30, 2004, which is incorporated by reference as if fully set forth herein.

FIELD OF INVENTION

[0002] The present invention is related to a wireless communication system including at least one wireless transmit/receive unit (WTRU), a Third Generation Partnership Project (3GPP) universal mobile telecommunications system (UMTS), a multimedia service (MMS) server and a wireless local area network (WLAN). More particularly, the present invention enables the WTRU to register with the 3GPP UMTS and the MMS server such that the WTRU may retrieve MMS messages from the MMS server over the WLAN.

BACKGROUND

[0003] The implementation of WLANs in wireless communication systems has expanded dramatically to replace wired computer networks. Using a WLAN, an end user may gain benefits such as flexibility and freedom of movement. The WLANs provide faster bit rates and are cheaper because they operate on an unlicensed band. Additionally, the current WLAN architecture lacks the ability and mechanisms to page the WTRU to ensure its presence for the delivery of Internet-based services.

[0004] Existing 3GPP UMTS systems provide WTRU users with access to Internet-based services such as MMS. MMS is a store-and-forward method of transmitting graphics, video clips, sound files and short text messages, (i.e., emails), over wireless networks. It is desirable to implement a wireless communication system which provides 3GPP-based services using a WLAN interworking with a 3GPP system.

SUMMARY

[0005] The present invention is implemented in a wireless communication system for supporting MMS over a 3GPP UMTS interworking with a WLAN. The 3GPP UMTS includes a short message service—service center (SMS-SC), an SMS-gateway mobile switching center (SMS-GMSC)/SMS-interworking mobile switching center (MSC) (SMS-IWMSC), a home location register (HLR)/home subscriber server (HSS), an authentication, authorization, and accounting (AAA) server, an IP short message gateway (IP-SM-GW) having an SMS proxy and access to an IP address database, and a packet data gateway (PDG). The 3GPP UMTS and WLAN access an MMS server via the Internet.

[0006] A WTRU establishes an SMS tunnel connection between the 3GPP UMTS and the WLAN via the IP-SM-GW and the packet data gateway (PDG). The SMS tunnel connection is established to support MMS over the WLAN. The WTRU registers with the SMS Proxy within the IP-SM-GW to establish SMS connectivity. The WTRU also registers with the MMS server and provides its mobile station

international ISDN number (MSISDN), (i.e., telephone number). When an MMS message is received by the MMS server, the MMS server sends an SMS message to the WTRU via the WLAN using its MSISDN. The MMS server stores the MMS message in a memory until the WTRU retrieves it. The SMS message informs the user of the WTRU that an MMS message has been received. The user of the WTRU accesses an associated MMS account and retrieves the MMS message.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] A more detailed understanding of the invention may be had from the following description of a preferred embodiment, given by way of example, and to be understood in conjunction with the accompanying drawings, wherein:

[0008] **FIG. 1** is a block diagram of a wireless communication system including a 3GPP UMTS interworking with a WLAN in accordance with the present invention;

[0009] **FIG. 2** is a detailed block diagram of the wireless communication system of **FIG. 1**;

[0010] **FIG. 3** is a flow diagram of a method for establishing MMS over a WLAN by providing a WTRU user's telephone number when registering with a MMS server in accordance with one embodiment of the present invention; and

[0011] **FIG. 4** is a flow diagram of a method for establishing MMS over a WLAN by providing a WTRU user's IP address when registering with an MMS server in accordance with another embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0012] Hereafter, the terminology "WTRU" includes but is not limited to a user equipment (UE), a mobile station, a fixed or mobile subscriber unit, a pager, or any other type of device capable of operating in a wireless environment.

[0013] The present invention is implemented in a wireless communication system **100** for supporting MMS, as shown in **FIG. 1**. The wireless communication system **100** includes a 3GPP UMTS **105**, a WLAN **110** and at least one WTRU **115** which establishes MMS connectivity by registering with an MMS server **125** over the Internet **120** in accordance with the present invention. The MMS server **125** includes a memory **130** for storing MMS messages accessible by the WTRU **115**.

[0014] **FIG. 2** is a block diagram of a wireless communication system **200** which supports MMS in accordance with the present invention. The system **200** includes a 3GPP UMTS **105** including an SMS-SC **210** which provides multimedia services via the Internet **120**, an SMS-GMSC/SMS-IWMSC **215**, an HLR/HSS **220**, an AAA server **225**, an IP-SM-GW **230** having an SMS proxy platform **232** and access to an IP address database **235**, and a PDG **240**.

[0015] The SMS-GMSC/SMS-IWMSC **215** has two functions: an SMS-GMSC function and an SMS-IWMSC function. The SMS-GMSC function receives a short message and interrogates the HLR/HSS **220** for routing information. The SMS-IWMSC function forwards short messages received

from the WTRU 115 to the SMS-SC 210 and the MMS server 125 via the Internet 120.

[0016] The WLAN 110 provides MMS to at least one WTRU 115. The HSS/HLR 220 communicates with the AAA server 225 which stores information relating to which WTRUs can access the WLAN 110, what services the WTRUs 115 are permitted to use, and accounting records for each WTRU 115. Further details of HSS/HLR/AAA operation may be found in co-pending application Ser. No. 11/112,503 entitled "REPORTING TERMINAL CAPABILITIES FOR SUPPORTING SHORT MESSAGE SERVICE," which was filed on Apr. 22, 2005, and is incorporated by reference as if fully set forth herein.

[0017] FIG. 3 is a flow diagram of a process including method steps for establishing MMS over a WLAN 110 by a user providing the telephone number of the WTRU 115 when registering with the MMS server 125 in accordance with one embodiment of the present invention. In step 305, an SMS tunnel connection is established through the WTRU 115, the WLAN 110 and the PDG 240. In step 310, the records of the HLR 220 are updated. The HLR 220 has access to information needed to locate the WTRU 115 and how to route the incoming MMS service. When the WTRU 115 is registered to receive its SMS and MMS services via the WLAN 110, the HLR 220 returns the IP-SW-GW address in response to receiving a query regarding the location of the WTRU 115 specified by the MSISDN included in the SMS message.

[0018] In step 315, the WTRU 115 is registered with the SMS proxy 232 to establish SMS connectivity. In step 320, the WTRU is registered with the MMS server 125 to establish MMS connectivity. The user of the WTRU 115 may provide a telephone number, (i.e., MSISDN), associated with the WTRU 115 to the MMS server 125. When a new MMS message arrives at the MMS server 125, the MMS server 125 sends an SMS message to the WTRU 115 alerting the user of the WTRU 115 that there is an MMS message awaiting retrieval at the MMS server 125 (steps 325 and 340). The SMS message is routed by retrieving routing information, (i.e., the PDG/SMS server address associated with the WTRU 115), from the HLR/HHS 220 and/or the AAA server 225 (steps 330, 335). In step 345, the WTRU 115 retrieves the MMS message from the memory 130 of the MMS server 125.

[0019] FIG. 4 is a flow diagram of an IP process including method steps for establishing MMS over a WLAN 110 by providing a WTRU user's IP address when registering with the MMS server 125 in accordance with another embodiment of the present invention. In step 405, an MMS tunnel connection is established between the WTRU 115 and the WLAN 110. In step 410, the records of the HLR 220 are updated in a similar fashion as described with respect to step 315. In step 415, the WTRU 115 is registered with the MMS server 125 using an IP address associated with the WTRU 115. In step 420, a new MMS service is established and the user of the WTRU 115 is alerted that there is an MMS message awaiting retrieval at the MMS server 125 (step 420). In step 425, the WTRU 115 retrieves the MMS message from the memory 130 of the MMS server 125.

[0020] If the WTRU 115 remains idle for an extended period of time, the connection established between the WTRU 115 and the WLAN 110 may be terminated.

[0021] The WTRU 115 periodically registers with the SMS proxy 232 and/or the MMS server 125 to maintain the connection between the WLAN 110 and the MMS server 125.

[0022] The user of the WTRU 115 may initiate a service termination request to terminate any pending activities over the WLAN 110.

[0023] Although the features and elements of the present invention are described in the preferred embodiments in particular combinations, each feature or element can be used alone (without the other features and elements of the preferred embodiments) or in various combinations with or without other features and elements of the present invention.

What is claimed is:

1. In a wireless communication system including a third generation partnership program (3GPP) universal mobile telecommunications system (UMTS) including an internet protocol short message gateway (IP-SM-GW) having a short message service (SMS) proxy, a multimedia service (MMS) server and a wireless local area network (WLAN), a method for supporting MMS provided to a user of a wireless transmit/receive unit (WTRU) which communicates with the wireless communication system, the method comprising:

- (a) registering the WTRU with the SMS proxy to establish SMS connectivity;
- (b) registering the WTRU with the MMS server to establish MMS connectivity;
- (c) notifying the WTRU when the MMS server receives a MMS message for the WTRU; and
- (d) the WTRU retrieving the MMS message from the MMS server.

2. The method of claim 1 wherein step (a) further comprises establishing an SMS tunnel connection between the WTRU and the WLAN.

3. The method of claim 1 wherein step (b) further comprises providing a user telephone number associated with the WTRU to the MMS server.

4. The method of claim 1 wherein step (c) further comprises the MMS server sending an SMS message to the WTRU notifying the user that there is an MMS message waiting to be retrieved from the MMS server.

5. The method of claim 1 further comprising:

- (e) establishing an MMS tunnel connection between the WTRU and the WLAN.

6. The method of claim 1 wherein step (b) further comprises providing an internet protocol (IP) address associated with the WTRU to the MMS server via the Internet.

7. A wireless communication system for supporting multimedia services (MMS) provided to a user of a wireless transmit/receive unit (WTRU) which communicates with the wireless communication system, the system comprising:

- (a) a third generation partnership program (3GPP) universal mobile telecommunications system (UMTS), the 3GPP UMTS having an internet protocol short message gateway (IP-SM-GW) including a short message service (SMS) proxy;

- (b) a wireless local area network (WLAN);

- (c) an MMS server in communication with the 3GPP UMTS and the WLAN;

- (d) means for registering the WTRU with the SMS proxy to establish SMS connectivity; and
 - (e) means for registering the WTRU with the MMS server to establish MMS connectivity, wherein the MMS server notifies the WTRU when the MMS server receives a MMS message for the WTRU, and the WTRU retrieves the MMS message from the MMS server.
- 8.** The wireless communication system of claim 7 further comprising:
- (f) means for establishing an SMS tunnel connection between the WTRU and the WLAN.
- 9.** The wireless communication system of claim 7 wherein the user of the WTRU provides a user telephone number associated with the WTRU to the MMS server to register the WTRU with the MMS server.

- 10.** The wireless communication system of claim 7 wherein the MMS server comprises:
- (i) a memory for storing MMS messages; and
 - (ii) means for sending an SMS message to the WTRU notifying the user that there is an MMS message waiting to be retrieved from the memory.
- 11.** The wireless communication system of claim 7 further comprising:
- (f) means for establishing an MMS tunnel connection between the WTRU and the WLAN.
- 12.** The wireless communication system of claim 7 wherein the user of the WTRU provides an internet protocol (IP) address associated with the WTRU to register the WTRU with the MMS server via the Internet.

* * * * *